



FEATURES

- "F-Connect" design for heatsink and optics.
- Fit in most of MR16 LED downlight converters.
- Flicker-free external driver.
- 5-year guarantee.

Technical Data

Input Voltage/Hz	DC35V
Output Voltage/Current	/
Power	/
Rated Input Current	0.3A
THD	<20%
PF value	1
Ingress Protection	IP40
Operating Temperature	-10—40°C
Dimmability	Wireless or DALI DT8 control

Optical Data

LED Brand	Bridgelux COB LED
CRI	Ra> 90
Beam Angle	15°/24°/36°/60°
Colour temperatures	2700K-6500K
System luminous efficacy up to	111lm/W

Packaging

Box Dimensions	L70 x W70 x H96 mm
Box Net Weight	0.140Kg
Box Gross Weight	0.162Kg
Carton Dimensions	L365 x W365 x H405 mm/100 PCS
Carton Net Weight	14.0Kg
Carton Gross Weight	16.2Kg



Model	CCT		Beam Angle	Lumen	Efficacy
MD10-13-TW-01	2700K	CRI 90+	15°	958lm	92lm/W
			24°	947lm	90lm/W
			36°	978lm	94lm/W
			60°	949lm	91lm/W
MD10-13-TW-01	6500K		15°	1140lm	109lm/W
			24°	1134lm	108lm/W
			36°	1166lm	111lm/W
			60°	1122lm	107lm/W

ECLIPSE CONSEIL

Siège : +33 (1) 79 30 48 19- Showroom Paris : +33 (1) 78 95 50 14 - Mob : +33 (6) 87 82 12 04
Siège social : 7 rue Prudent Neel 92500 Rueil-Malmaison - Showroom : 1 rue Dulong 75017 PARIS