



FEATURES

- "F-Connect" design for heatsink and optics.
- Fit in most of MR16 LED downlight converters.
- External driver with DALI dimming.
- 5-year guarantee.

Technical Data

Input Voltage/Hz	AC200-240V 50/60Hz
Output Voltage/Current	DC35V/300mA
Power	13W
Rated Input Current	0.065A
THD	<13%
PF value	>0.95
Ingress Protection	IP20
Operating Temperature	-10-40°C
Dimmability	ACTEC DALI

Optical Data

LED Brand	Bridgelux COB LED
CRI	Ra> 90
Beam Angle	15°/24°/36°/60°
Colour temperatures	2700K-6500K
System luminous efficacy up to	88lm/W

Packaging

Box Dimensions	L201 x W70 x H106 mm
Box Net Weight	0.316Kg
Box Gross Weight	0.360Kg
Carton Dimensions	L422 x W375 x H445 mm/40 PCS
Carton Net Weight	12.64Kg
Carton Gross Weight	15.27Kg



CCT		Beam Angle	Lumen	Efficacy
2700K	CRI 90+	15°	930lm	71.5lm/W
		24°	933lm	71.7lm/W
		36°	1009lm	78.3lm/W
		60°	975lm	75.7lm/W
6500K		15°	1154lm	88lm/W
		24°	1121lm	86.3lm/W
		36°	1128lm	86.4lm/W
		60°	1080lm	83.1lm/W

ECLIPSE CONSEIL

Siège : +33 (1) 79 30 48 19- Showroom Paris : +33 (1) 78 95 50 14 - Mob : +33 (6) 87 82 12 04
Siège social : 7 rue Prudent Neel 92500 Rueil-Malmaison - Showroom : 1 rue Dulong 75017 PARIS