


FEATURES

- "F-Connect" design for heatsink and optics.
- Fit in most of MR16 LED downlight converters.
- External driver with DALI dimming.
- 5-year guarantee.



Technical Data

Input Voltage/Hz	AC200-240V 50/60Hz
Output Voltage/Current	DC34V/300mA
Power	13W
Rated Input Current	0.065A
THD	<20%
PF value	>0.95
Ingress Protection	IP40
Operating Temperature	-10—40°C
Dimmability	ACTEC DALI

Optical Data

LED Brand	Bridgelux COB LED
CRI	Ra> 80,Ra> 90
Beam Angle	15°/24°/36°/60°
Colour temperatures	2700K/3000K/4000K
System luminous efficacy up to	111.5lm/W

Packaging

Box Dimensions	L195 x W70 x H96 mm
Box Net Weight	0.358Kg
Box Gross Weight	0.414Kg
Carton Dimensions	L410 x W375 x H405 mm/40 PCS
Carton Net Weight	14.32Kg
Carton Gross Weight	18.82Kg



CCT		Beam Angle	Lumen	Efficacy		Beam Angle	Lumen	Efficacy
2700K	CRI 80+	15°	1182lm	92.3lm/W	CRI 90+	15°	1125lm	89.1lm/W
		24°	1178lm	92.4lm/W		24°	1134lm	89.4lm/W
		36°	1229lm	95.8lm/W		36°	1110lm	87.5lm/W
		60°	1210lm	94.3lm/W		60°	1104lm	87.2lm/W
3000K		15°	1399lm	106.5lm/W		15°	1056lm	83lm/W
		24°	1387lm	107lm/W		24°	1157lm	90.7lm/W
		36°	1345lm	103.5lm/W		36°	1110lm	87.4lm/W
		60°	1390lm	107.1lm/W		60°	1097lm	86.4lm/W
4000K		15°	1337lm	103.1lm/W		15°	1238lm	97.3lm/W
		24°	1440lm	111.5lm/W		24°	1230lm	97.3lm/W
		36°	1364lm	106.2lm/W		36°	1185lm	94lm/W
		60°	1351lm	105.2lm/W		60°	1270lm	95.3lm/W

ECLIPSE CONSEIL

Siège : +33 (1) 79 30 48 19- Showroom Paris : +33 (1) 78 95 50 14 - Mob : +33 (6) 87 82 12 04
Siège social : 7 rue Prudent Neel 92500 Rueil-Malmaison - Showroom : 1 rue Dulong 75017 PARIS