



FEATURES

- "F-Connect" design for heatsink and optics.
- Fit in most of MR16 LED downlight converters.
- Flicker-free external driver.
- Compatible with leading and trailing edge phase cut dimmers.
- 5-year guarantee.

Technical Data

Input Voltage/Hz	AC200-240V 50/60Hz
Output Voltage/Current	DC34V/300mA
Power	13W
Rated Input Current	0.065A
THD	<20%
Ingress Protection	IP40
Operating Temperature	-10—40°C
Dimmability	Triac dimmable with DIMMATE driver

Optical Data

LED Brand	Bridgelux COB LED
CRI	Ra> 80,Ra> 90
Beam Angle	15°/24°/36°/60°
Colour temperatures	2700K/3000K/4000K
System luminous efficacy up to	129lm/W

Packaging

Box Dimensions	L195 x W70 x H96 mm
Box Net Weight	0.298Kg
Box Gross Weight	0.354Kg
Carton Dimensions	L410 x W375 x H405 mm/40 PCS
Carton Net Weight	11.9Kg
Carton Gross Weight	14.16Kg



CCT		Beam Angle	Lumen	Efficacy			Beam Angle	Lumen	Efficacy
2700K	CRI 80+	15°	1270lm	102lm/W	CRI 90+	15°	1021lm	82lm/W	
		24°	1297lm	104lm/W		24°	1038lm	84lm/W	
		36°	1262lm	100lm/W		36°	1084lm	86lm/W	
		60°	1243lm	98lm/W		60°	1030lm	83lm/W	
3000K		15°	1514lm	120lm/W		15°	1216lm	97lm/W	
		24°	1545lm	124lm/W		24°	1167lm	93lm/W	
		36°	1516lm	121lm/W		36°	1222lm	97lm/W	
		60°	1447lm	116lm/W		60°	1192lm	94lm/W	
4000K		15°	1567lm	125lm/W		15°	1315lm	105lm/W	
		24°	1527lm	129lm/W		24°	1266lm	102lm/W	
		36°	1523lm	122lm/W		36°	1323lm	106lm/W	
		60°	1495lm	119lm/W		60°	1280lm	103lm/W	

ECLIPSE CONSEIL

Siège : +33 (1) 79 30 48 19- Showroom Paris : +33 (1) 78 95 50 14 - Mob : +33 (6) 87 82 12 04
Siège social : 7 rue Prudent Neel 92500 Rueil-Malmaison - Showroom : 1 rue Dulong 75017 PARIS