


## FEATURES

- "F-Connect" design for heatsink and optics.
- Fit in most of MR16 LED downlight converters.
- Flicker-free external driver.
- Compatible with leading and trailing edge phase cut dimmers.
- 5-year guarantee.



## Technical Data

Input Voltage/Hz	AC200-240V 50/60Hz
Output Voltage/Current	DC34V/300mA
Power	13W
Rated Input Current	0.065A
THD	<20%
PF value	>0.9
Ingress Protection	IP40
Operating Temperature	-10—40°C
Dimmability	Triac dimmable with <b>DIMMATE</b> driver

## Optical Data

LED Brand	Bridgelux COB LED
CRI	Ra>80, Ra>90
Beam Angle	18°/24°/38°/50°
Colour temperatures	2700K/3000K/4000K
System luminous efficacy up to	111lm/W

## Packaging

Box Dimensions	L195 x W70 x H96 mm
Box Net Weight	0.310Kg
Box Gross Weight	0.367Kg
Carton Dimensions	L410 x W375 x H405 mm/40 PCS
Carton Net Weight	12.4Kg
Carton Gross Weight	15.88Kg



CCT		Beam Angle	Lumen	Efficacy		Beam Angle	Lumen	Efficacy
2700K	CRI 80+	18°	1138lm	91lm/W	CRI 90+	18°	1067lm	82lm/W
		24°	1165lm	94lm/W		24°	1093lm	84lm/W
		38°	1168lm	94lm/W		38°	1095lm	84lm/W
		50°	1107lm	89lm/W		50°	1041lm	80lm/W
3000K		18°	1347lm	107lm/W		18°	1082lm	84lm/W
		24°	1381lm	110lm/W		24°	1105lm	86lm/W
		38°	1389lm	110lm/W		38°	1124lm	87lm/W
		50°	1322lm	105lm/W		50°	1064lm	83lm/W
4000K		18°	1362lm	108lm/W		18°	1193lm	92lm/W
		24°	1395lm	110lm/W		24°	1219lm	94lm/W
		38°	1399lm	111lm/W		38°	1222lm	94lm/W
		50°	1336lm	105lm/W		50°	1164lm	89lm/W

## ECLIPSE CONSEIL

Siège : +33 (1) 79 30 48 19- Showroom Paris : +33 (1) 78 95 50 14 - Mob : +33 (6) 87 82 12 04  
Siège social : 7 rue Prudent Neel 92500 Rueil-Malmaison - Showroom : 1 rue Dulong 75017 PARIS