



Indoor Luminaire Photometric Data

Description Information

Luminary Name: MD10-18-XX-01 2700K RA90 60D	Lum. Catalog:	Test ID: 01
Lamp Name:	Lamp Catalog: LED	Test Date: 2019/12/30
Manufacture: Shenzhen Norming Lighting Co., Ltd	Shld.Ang(°):	Test Machine:GON-2000
Test Lab: QUality peatment	Frequency (Hz):	Lamp CCT(K): Ra:
Lum. Size (W*L*H):0.550m*0.550m*0.850m	Lum. Area (m2):0.770	Lum. W(kg): 0.000
Test System: C, γ	Test Step: C=90.0 γ=1.0	Temp. (°C): 25
		Humidity(%):


Character Parameter

Lamp Speciality Parameter	Luminaire Speciality Parameter	
Rated Flux(lm): 1460.420	Luminary Flux(lm): 1460.415	Field Angle(10%Imax): 91.8(°)
Rated Power(W):	Luminary Efficiency: 100.00%	Down Lumens&Percent: 1422.060lm 97.37%
Rated Voltage(V):	Luminary EER(lm/W): 87.293	Up Lumens&Percent: 38.356lm 2.63%
Tested Power(W): 16.730	Max. Candela(cd): 1426.928	S/MH: C0_a180=0.918 C90_270=0.920
Lamps' Inside: 1	Max Cand@Ang. (°): C=0.0 γ=1.0	CIE Type: Semi-Direct
Tested Electrics (V, A, pf):240.2, 0.071	Beam Angle(50%Imax): 58.9(°)	ErP ϕ use(90°): 1261.362lm
Lamp Size (W*L*H):0.550m*0.550m*0.850m	Left=-28.3°, Right=30.6°	IRF(%): 216.707



2D Plane Light Intensity Distribution Curve

Lum. Name: MD10-18-XX-01 2700K RA90 60D	Lum. Catalog:	Test ID: 01
Lamp Name:	Lamp Catalog: LED	Test Lab: Quality peatment
Manufacture: Shenzhen Norming Lighting Co., Ltd	Test Machine:GON-2000	Test Date: 2019/12/30




IES Indoor Report

Photometric Filename:MD10-18-XX-01 2700K RA90 60D.IES

3D Light Intensity Distribution Modal

Lum. Name: MD10-18-XX-01 2700K RA90 60D	Lum. Catalog:	Test ID: 01
Lamp Name:	Lamp Catalog: LED	Test Lab: Quality peatment
Manufacture: Shenzhen Norming Lighting Co., Ltd	Test Machine:GON-2000	Test Date: 2019/12/30

3D Light Intensity Distribution Modal



Curves: 3D Model — Fixture — Vert. HUD — Hori. HUD —
View Angles: Orient:0 Tilt:0 Roll:0 Spin:0

Zonal Flux Tabulation


Zone(γ)	Zone Flux (lm)	Sums Flux (lm)	Zone%Lamp	Sums%Lamp	Zone(γ)	Zone Flux (lm)	Sums Flux (lm)	Zone%Lamp	Sums%Lamp
0.0-1.0	1.36	1.36	0.09	0.09	47.0-48.0	9.97	1303.95	0.68	89.29
1.0-2.0	4.09	5.45	0.28	0.37	48.0-49.0	9.22	1313.17	0.63	89.92
2.0-3.0	6.80	12.25	0.47	0.84	49.0-50.0	8.53	1321.70	0.58	90.50
3.0-4.0	9.48	21.73	0.65	1.49	50.0-51.0	7.89	1329.58	0.54	91.04
4.0-5.0	12.14	33.87	0.83	2.32	51.0-52.0	7.28	1336.86	0.50	91.54
5.0-6.0	14.77	48.64	1.01	3.33	52.0-53.0	6.72	1343.58	0.46	92.00
6.0-7.0	17.36	66.00	1.19	4.52	53.0-54.0	6.20	1349.78	0.42	92.42
7.0-8.0	19.92	85.93	1.36	5.88	54.0-55.0	5.71	1355.49	0.39	92.82
8.0-9.0	22.44	108.37	1.54	7.42	55.0-56.0	5.26	1360.76	0.36	93.18
9.0-10.0	24.90	133.26	1.70	9.13	56.0-57.0	4.85	1365.61	0.33	93.51
10.0-11.0	27.28	160.54	1.87	10.99	57.0-58.0	4.47	1370.08	0.31	93.81
11.0-12.0	29.57	190.12	2.02	13.02	58.0-59.0	4.12	1374.21	0.28	94.10
12.0-13.0	31.76	221.88	2.17	15.19	59.0-60.0	3.80	1378.01	0.26	94.36
13.0-14.0	33.84	255.71	2.32	17.51	60.0-61.0	3.49	1381.50	0.24	94.60
14.0-15.0	35.78	291.49	2.45	19.96	61.0-62.0	3.21	1384.71	0.22	94.82
15.0-16.0	37.58	329.07	2.57	22.53	62.0-63.0	2.94	1387.65	0.20	95.02
16.0-17.0	39.18	368.25	2.68	25.22	63.0-64.0	2.69	1390.34	0.18	95.20
17.0-18.0	40.57	408.82	2.78	27.99	64.0-65.0	2.46	1392.80	0.17	95.37
18.0-19.0	41.77	450.59	2.86	30.85	65.0-66.0	2.27	1395.07	0.16	95.53
19.0-20.0	42.74	493.33	2.93	33.78	66.0-67.0	2.08	1397.15	0.14	95.67
20.0-21.0	43.46	536.79	2.98	36.76	67.0-68.0	1.88	1399.03	0.13	95.80
21.0-22.0	43.91	580.70	3.01	39.76	68.0-69.0	1.72	1400.75	0.12	95.91
22.0-23.0	44.10	624.80	3.02	42.78	69.0-70.0	1.59	1402.34	0.11	96.02
23.0-24.0	44.01	668.81	3.01	45.80	70.0-71.0	1.50	1403.83	0.10	96.13
24.0-25.0	43.63	712.44	2.99	48.78	71.0-72.0	1.41	1405.24	0.10	96.22
25.0-26.0	43.01	755.45	2.94	51.73	72.0-73.0	1.33	1406.57	0.09	96.31
26.0-27.0	42.19	797.64	2.89	54.62	73.0-74.0	1.25	1407.82	0.09	96.40
27.0-28.0	41.16	838.80	2.82	57.44	74.0-75.0	1.18	1409.00	0.08	96.48
28.0-29.0	39.92	878.71	2.73	60.17	75.0-76.0	1.12	1410.12	0.08	96.56
29.0-30.0	38.47	917.18	2.63	62.80	76.0-77.0	1.07	1411.18	0.07	96.63
30.0-31.0	36.84	954.02	2.52	65.32	77.0-78.0	1.02	1412.21	0.07	96.70
31.0-32.0	35.05	989.07	2.40	67.72	78.0-79.0	0.99	1413.20	0.07	96.77
32.0-33.0	33.14	1022.21	2.27	69.99	79.0-80.0	0.95	1414.15	0.07	96.83
33.0-34.0	31.14	1053.34	2.13	72.13	80.0-81.0	0.92	1415.07	0.06	96.89
34.0-35.0	29.08	1082.43	1.99	74.12	81.0-82.0	0.89	1415.96	0.06	96.96
35.0-36.0	26.99	1109.42	1.85	75.97	82.0-83.0	0.86	1416.83	0.06	97.02
36.0-37.0	24.87	1134.29	1.70	77.67	83.0-84.0	0.83	1417.66	0.06	97.07
37.0-38.0	22.79	1157.08	1.56	79.23	84.0-85.0	0.81	1418.47	0.06	97.13
38.0-39.0	20.83	1177.91	1.43	80.66	85.0-86.0	0.78	1419.24	0.05	97.18
39.0-40.0	19.04	1196.94	1.30	81.96	86.0-87.0	0.75	1419.99	0.05	97.23
40.0-41.0	17.45	1214.39	1.19	83.15	87.0-88.0	0.72	1420.71	0.05	97.28
41.0-42.0	16.04	1230.44	1.10	84.25	88.0-89.0	0.69	1421.40	0.05	97.33
42.0-43.0	14.80	1245.23	1.01	85.27	89.0-90.0	0.66	1422.06	0.05	97.37
43.0-44.0	13.66	1258.90	0.94	86.20	90.0-91.0	0.65	1422.71	0.04	97.42
44.0-45.0	12.63	1271.52	0.86	87.07	91.0-92.0	0.63	1423.34	0.04	97.46
45.0-46.0	11.67	1283.19	0.80	87.86	92.0-93.0	0.62	1423.96	0.04	97.50
46.0-47.0	10.79	1293.98	0.74	88.60	93.0-94.0	0.60	1424.56	0.04	97.54

Zonal Flux Tabulation - (Cont.)

Zone(γ)	Zone Flux (lm)	Sums Flux (lm)	Zone%Lamp	Sums%Lamp	Zone(γ)	Zone Flux (lm)	Sums Flux (lm)	Zone%Lamp	Sums%Lamp
94.0-95.0	0.59	1425.16	0.04	97.59	141.0-142.0	0.51	1448.12	0.03	99.16
95.0-96.0	0.58	1425.73	0.04	97.62	142.0-143.0	0.51	1448.62	0.03	99.19
96.0-97.0	0.57	1426.30	0.04	97.66	143.0-144.0	0.51	1449.13	0.03	99.23
97.0-98.0	0.55	1426.86	0.04	97.70	144.0-145.0	0.50	1449.63	0.03	99.26
98.0-99.0	0.54	1427.40	0.04	97.74	145.0-146.0	0.50	1450.13	0.03	99.30
99.0-100.0	0.53	1427.93	0.04	97.78	146.0-147.0	0.50	1450.63	0.03	99.33
100.0-101.0	0.52	1428.46	0.04	97.81	147.0-148.0	0.49	1451.12	0.03	99.36
101.0-102.0	0.51	1428.97	0.04	97.85	148.0-149.0	0.49	1451.61	0.03	99.40
102.0-103.0	0.51	1429.48	0.03	97.88	149.0-150.0	0.48	1452.09	0.03	99.43
103.0-104.0	0.50	1429.98	0.03	97.92	150.0-151.0	0.47	1452.56	0.03	99.46
104.0-105.0	0.49	1430.47	0.03	97.95	151.0-152.0	0.47	1453.02	0.03	99.49
105.0-106.0	0.48	1430.95	0.03	97.98	152.0-153.0	0.46	1453.48	0.03	99.52
106.0-107.0	0.48	1431.43	0.03	98.02	153.0-154.0	0.45	1453.93	0.03	99.56
107.0-108.0	0.47	1431.90	0.03	98.05	154.0-155.0	0.44	1454.37	0.03	99.59
108.0-109.0	0.47	1432.37	0.03	98.08	155.0-156.0	0.43	1454.80	0.03	99.61
109.0-110.0	0.46	1432.83	0.03	98.11	156.0-157.0	0.42	1455.21	0.03	99.64
110.0-111.0	0.46	1433.29	0.03	98.14	157.0-158.0	0.41	1455.62	0.03	99.67
111.0-112.0	0.46	1433.75	0.03	98.17	158.0-159.0	0.39	1456.01	0.03	99.70
112.0-113.0	0.45	1434.21	0.03	98.20	159.0-160.0	0.38	1456.39	0.03	99.72
113.0-114.0	0.45	1434.66	0.03	98.24	160.0-161.0	0.37	1456.76	0.03	99.75
114.0-115.0	0.45	1435.11	0.03	98.27	161.0-162.0	0.35	1457.11	0.02	99.77
115.0-116.0	0.45	1435.56	0.03	98.30	162.0-163.0	0.34	1457.45	0.02	99.80
116.0-117.0	0.45	1436.01	0.03	98.33	163.0-164.0	0.32	1457.77	0.02	99.82
117.0-118.0	0.45	1436.47	0.03	98.36	164.0-165.0	0.31	1458.07	0.02	99.84
118.0-119.0	0.45	1436.92	0.03	98.39	165.0-166.0	0.29	1458.36	0.02	99.86
119.0-120.0	0.46	1437.37	0.03	98.42	166.0-167.0	0.27	1458.64	0.02	99.88
120.0-121.0	0.46	1437.83	0.03	98.45	167.0-168.0	0.25	1458.89	0.02	99.90
121.0-122.0	0.46	1438.29	0.03	98.48	168.0-169.0	0.24	1459.13	0.02	99.91
122.0-123.0	0.46	1438.75	0.03	98.52	169.0-170.0	0.22	1459.35	0.01	99.93
123.0-124.0	0.47	1439.22	0.03	98.55	170.0-171.0	0.20	1459.55	0.01	99.94
124.0-125.0	0.47	1439.69	0.03	98.58	171.0-172.0	0.18	1459.73	0.01	99.95
125.0-126.0	0.47	1440.16	0.03	98.61	172.0-173.0	0.16	1459.89	0.01	99.96
126.0-127.0	0.48	1440.64	0.03	98.65	173.0-174.0	0.14	1460.02	0.01	99.97
127.0-128.0	0.48	1441.12	0.03	98.68	174.0-175.0	0.12	1460.14	0.01	99.98
128.0-129.0	0.48	1441.60	0.03	98.71	175.0-176.0	0.10	1460.24	0.01	99.99
129.0-130.0	0.49	1442.09	0.03	98.74	176.0-177.0	0.08	1460.32	0.01	99.99
130.0-131.0	0.49	1442.58	0.03	98.78	177.0-178.0	0.05	1460.37	0.00	100.00
131.0-132.0	0.49	1443.07	0.03	98.81	178.0-179.0	0.03	1460.40	0.00	100.00
132.0-133.0	0.50	1443.57	0.03	98.85	179.0-180.0	0.01	1460.42	0.00	100.00
133.0-134.0	0.50	1444.07	0.03	98.88					
134.0-135.0	0.50	1444.57	0.03	98.91					
135.0-136.0	0.50	1445.07	0.03	98.95					
136.0-137.0	0.51	1445.58	0.03	98.98					
137.0-138.0	0.51	1446.08	0.03	99.02					
138.0-139.0	0.51	1446.59	0.03	99.05					
139.0-140.0	0.51	1447.10	0.03	99.09					
140.0-141.0	0.51	1447.61	0.03	99.12					

Rectangle ISO Lighting Intensity Diagram


Lum. Name:MD10-18-XX-01 2700K RA90 60D	Lum. Catalog:	Test ID:01
Lamp Name:	Lamp Catalog: LED	Test Lab: Quality peatment
Manufacture: Shenzhen Norming Lighting Co., Ltd	Test Machine:GON-2000	Test Date: 2019/12/30



Plane ISO-Illuminance Diagram

Lum. Name: MD10-18-XX-01 2700K RA90 60D	Lum. Catalog:	Test ID: 01
Lamp Name:	Lamp Catalog: LED	Test Lab: Quality peatment
Manufacture: Shenzhen Norming Lighting Co., Ltd	Test Machine:GON-2000	Test Date: 2019/12/30

Plane ISO-Illuminance Curve



Working Plane Luminaire Mounting Height(m): 3.00


Working Plane Maximum Illuminance(lx): 158.53

Working Plane Maximum Illuminance Position(d/h):H0.0 V0.0

3D Plane ISO Illuminance Diagram

Lum. Name: MD10-18-XX-01 2700K RA90 60D	Lum. Catalog:	Test ID: 01
Lamp Name:	Lamp Catalog: LED	Test Lab: Quality peatment
Manufacture: Shenzhen Norming Lighting Co., Ltd	Test Machine:GON-2000	Test Date: 2019/12/30

3D Plane Illuminance Modal




Curves: 3D Model — 90% — 80% — 70% — 60% — 50% — 40% — 30% — 20% — 10% —
 View Angles(deg): 0 Height(m): 3.0 Distance(m): 10.0

Space ISO Illuminance Diagram

Lum. Name: MD10-18-XX-01 2700K RA90 60D	Lum. Catelog:	Test ID: 01
Lamp Name:	Lamp Catelog: LED	Test Lab: QQualty peatment
Manufacture: Shenzhen Norming Lighting Co., Ltd	Test Machine:GON-2000	Test Date: 2019/12/30

Space ISO Illuminance Curve



Space Plane Maximum Illuminance and @Angle:1426.75lx,0.0deg
Plane Maximum Lighting Intensity and @Angle:1426.928cd,0eg


IES Indoor Report

Photometric Filename:MD10-18-XX-01 2700K RA90 60D.IES

Illuminance-Distance Diagram

Lum. Name: MD10-18-XX-01 2700K RA90 60D	Lum. Catalog:	Test ID: 01
Lamp Name:	Lamp Catalog: LED	Test Lab: Quality peatment
Manufacture: Shenzhen Norming Lighting Co., Ltd	Test Machine:GON-2000	Test Date: 2019/12/30

Illuminance-Distance Curve



IES Indoor Report

Photometric Filename:MD10-18-XX-01 2700K RA90 60D.IES

Indoor Luminance Limiting Curves

Lum. Name: MD10-18-XX-01 2700K RA90 60D	Lum. Catalog:	Test ID: 01
Lamp Name:	Lamp Catalog: LED	Test Lab: Quality peatment
Manufacture: Shenzhen Norming Lighting Co., Ltd	Test Machine:GON-2000	Test Date: 2019/12/30


Glare Grade Table

GI	Quality	Using Illuminance							
1.15	A	2000	1000	500	<=300				
1.5	B		2000	1000	500	<=300			
1.85	C			2000	1000	500	<=300		
2.2	D				2000	1000	500	<=300	
2.55	E	a				2000	1000	500	<=300
			b	c	d	e	f	g	h

Luminance Table

Gama(deg)	45	50	55	60	65	70	75	80	85
C0	333	231	163	117	85	64	61	71	118
C90	292	200	140	101	73	55	52	61	101


Luminance Limiting Curve



Luminous Size: Length(m)=0.550 Width(m)=0.550 Height(m)=0.850 Area(m^2)=0.770000
 Luminous Type: Without Luminous Side
 Luminous Curves: C0-C180 Color: — C90-C270 Color: —

Indoor Budgetary Estimate Table

Lum. Name:MD10-18-XX-01 2700K RA90 60D	Lum. Catelog:	Test ID:01
Lamp Name:	Lamp Catelog:LED	Test Lab:QQualty peatment
Manufacture:Shenzhen Norming Lighting Co., Ltd	Test Machine:GON-2000	Test Date:2019/12/30



Indoor Coefficient of Utilization Table

Lum. Name: MD10-18-XX-01 2700K RA90 60D	Lum. Catelog:	Test ID: 01
Lamp Name:	Lamp Catelog: LED	Test Lab: QQualty peatment
Manufacture: Shenzhen Norming Lighting Co., Ltd	Test Machine:GON-2000	Test Date: 2019/12/30

Coefficients of Utilization - Zonal Cavity Method																		
Coef.	Effective Floor Cavity Reflectance RFC=0.20																	
RhoCC (%)	80				70				50			30			10			0
RhoW (%)	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR	Coefficient of Utilization(%)																	
0	118	118	118	118	115	115	115	115	110	110	110	104	104	104	100	100	100	97
1	112	109	106	104	109	107	104	102	102	100	98	98	96	95	94	93	92	90
2	106	100	96	92	103	98	94	91	95	91	88	91	89	86	88	86	84	82
3	100	93	87	83	98	91	86	82	88	84	80	85	82	79	83	80	77	75
4	94	86	80	75	92	85	79	75	82	77	74	80	76	72	78	74	71	70
5	89	80	74	69	87	79	73	68	77	72	68	75	70	67	73	69	66	64
6	84	75	68	63	82	74	68	63	72	66	62	70	65	62	69	64	61	60
7	80	70	63	59	78	69	63	59	67	62	58	66	61	58	65	60	57	55
8	76	65	59	55	74	65	59	54	63	58	54	62	57	54	61	57	53	52
9	72	62	55	51	70	61	55	51	60	54	51	59	54	50	58	53	50	48
10	68	58	52	48	67	57	52	48	56	51	47	55	51	47	55	50	47	45

Unified Glare Rating Table

Lum. Name: MD10-18-XX-01 2700K RA90 60D	Lum. Catelog:	Test ID: 01
Lamp Name:	Lamp Catelog: LED	Test Lab: QQualty peatment
Manufacture: Shenzhen Norming Lighting Co., Ltd	Test Machine:GON-2000	Test Date: 2019/12/30

Unified Glare Rating Table

Ceiling RCC	0.70	0.70	0.50	0.50	0.30	0.70	0.70	0.50	0.50	0.30
Wall RW	0.50	0.30	0.50	0.30	0.30	0.50	0.30	0.50	0.30	0.30
Floor RFC	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20
Room Size	Vewed crosswise					Vewed endwise				
X=2H Y=2H	4.8	5.9	5.2	6.2	6.6	4.2	5.2	4.6	5.6	6.0
	4.8	5.8	5.3	6.2	6.6	4.2	5.1	4.6	5.5	6.0
	4.8	5.7	5.3	6.1	6.6	4.2	5.1	4.6	5.5	5.9
	4.9	5.7	5.4	6.1	6.6	4.2	5.0	4.7	5.5	5.9
	4.9	5.7	5.4	6.1	6.6	4.2	5.0	4.7	5.5	5.9
	5.0	5.7	5.5	6.2	6.7	4.3	5.0	4.8	5.5	6.0
X=4H Y=2H	4.7	5.6	5.1	6.0	6.4	4.1	4.9	4.5	5.4	5.8
	4.8	5.5	5.3	6.0	6.5	4.2	4.9	4.6	5.3	5.8
	4.9	5.5	5.3	6.0	6.5	4.2	4.9	4.7	5.3	5.8
	5.0	5.5	5.5	6.0	6.6	4.3	4.9	4.8	5.4	5.9
	5.1	5.6	5.6	6.1	6.6	4.4	4.9	4.9	5.4	5.9
	5.2	5.7	5.7	6.2	6.7	4.5	5.0	5.0	5.5	6.0
X=8H Y=4H	4.8	5.3	5.3	5.8	6.3	4.1	4.7	4.7	5.2	5.7
	5.0	5.4	5.5	6.0	6.5	4.3	4.7	4.9	5.3	5.9
	5.1	5.5	5.7	6.1	6.6	4.5	4.8	5.0	5.4	6.0
	5.4	5.8	6.0	6.3	6.9	4.7	5.1	5.3	5.6	6.2
X=12H Y=4H	4.7	5.2	5.3	5.7	6.3	4.1	4.6	4.6	5.1	5.6
	5.0	5.3	5.5	5.9	6.5	4.3	4.7	4.9	5.2	5.8
	5.2	5.5	5.7	6.1	6.7	4.5	4.8	5.1	5.4	6.0
Variations with the objerver position at spacings										
S=1.0H	0.1/-0.1					0.2/-0.2				
S=1.5H	0.3/-0.3					0.4/-0.3				
S=2.0H	0.9/-0.6					0.9/-0.6				
Reduced UGR Table:										
Nordic Standard Table:	BK0					BK0				
Correction Value	0.9					0.9				

o the CIE Pub.117, data has been corrected, refers to the lamp's lumens 8.2flm.

Candela Tabulation

V/H	C0.0	C90.0	C180.0	C270.0
γ 0.0	1426.75	1426.75	1426.75	1426.75
γ 1.0	1426.93	1425.32	1424.17	1424.39
γ 2.0	1426.21	1423.05	1420.78	1421.91
γ 3.0	1422.16	1417.61	1415.35	1419.13
γ 4.0	1419.88	1414.58	1408.24	1412.86
γ 5.0	1415.30	1408.00	1402.42	1406.59
γ 6.0	1411.00	1402.75	1395.13	1400.48
γ 7.0	1404.12	1395.97	1386.24	1394.60
γ 8.0	1398.76	1391.62	1376.57	1386.46
γ 9.0	1393.36	1382.26	1367.21	1379.36
γ 10.0	1383.25	1373.95	1356.24	1369.65
γ 11.0	1373.84	1362.83	1343.45	1357.34
γ 12.0	1362.40	1349.24	1327.58	1344.20
γ 13.0	1348.48	1334.03	1311.65	1328.09
γ 14.0	1333.26	1316.96	1291.67	1309.60
γ 15.0	1316.95	1296.98	1269.72	1289.97
γ 16.0	1299.17	1275.97	1242.83	1266.40
γ 17.0	1275.64	1251.99	1212.73	1238.54
γ 18.0	1249.97	1223.38	1181.80	1209.29
γ 19.0	1222.66	1192.90	1147.29	1176.33
γ 20.0	1191.63	1160.33	1108.69	1140.93
γ 21.0	1156.75	1123.29	1068.42	1102.82
γ 22.0	1117.95	1084.17	1025.00	1061.49
γ 23.0	1078.48	1042.12	978.44	1018.62
γ 24.0	1033.55	997.07	930.79	973.19
γ 25.0	986.30	949.96	880.75	924.44
γ 26.0	938.21	902.08	830.70	875.57
γ 27.0	890.07	853.62	780.86	826.13
γ 28.0	841.85	802.81	730.90	776.76
γ 29.0	791.48	751.59	680.32	726.91
γ 30.0	741.38	700.03	629.73	677.32
γ 31.0	691.13	648.58	579.70	626.90
γ 32.0	641.19	598.93	529.93	577.45
γ 33.0	591.89	549.64	481.44	528.98
γ 34.0	545.02	501.71	435.10	481.76
γ 35.0	499.23	456.25	391.13	435.78
γ 36.0	455.09	412.31	349.65	391.20
γ 37.0	412.04	370.23	310.69	349.08
γ 38.0	371.12	331.60	276.07	310.39
γ 39.0	332.36	295.67	246.32	277.32
γ 40.0	297.45	263.73	220.76	249.78
γ 41.0	266.85	236.10	198.55	226.44
γ 42.0	241.36	212.86	178.93	205.40
γ 43.0	219.12	192.69	161.07	186.48
γ 44.0	199.25	174.90	145.34	169.10
γ 45.0	181.42	158.85	131.57	153.64
γ 46.0	165.17	144.26	119.07	139.65

Candela Tabulation - (Cont.)

V/H	C0.0	C90.0	C180.0	C270.0
γ 47.0	150.48	131.04	108.02	126.99
γ 48.0	137.26	119.01	98.15	115.63
γ 49.0	125.15	108.49	89.07	105.33
γ 50.0	114.35	98.93	81.02	96.02
γ 51.0	104.33	90.01	73.65	87.30
γ 52.0	95.18	81.96	66.93	79.34
γ 53.0	86.79	74.59	60.87	72.20
γ 54.0	78.96	67.86	55.42	65.79
γ 55.0	71.81	61.78	50.42	59.90
γ 56.0	65.35	56.28	46.02	54.39
γ 57.0	59.43	51.32	42.01	49.61
γ 58.0	54.04	46.79	38.37	45.42
γ 59.0	49.23	42.67	34.94	41.45
γ 60.0	44.92	38.81	31.80	37.79
γ 61.0	40.89	35.18	28.98	34.28
γ 62.0	37.27	32.07	26.42	31.12
γ 63.0	33.76	29.18	23.93	28.17
γ 64.0	30.55	26.35	21.75	25.65
γ 65.0	27.73	23.68	19.73	23.74
γ 66.0	25.35	21.55	18.16	21.85
γ 67.0	22.94	19.58	16.48	19.27
γ 68.0	21.15	17.50	14.69	17.21
γ 69.0	18.59	15.62	13.81	16.09
γ 70.0	16.94	14.55	13.03	15.18
γ 71.0	15.85	13.66	12.27	14.26
γ 72.0	14.87	12.82	11.49	13.34
γ 73.0	13.96	11.94	10.77	12.47
γ 74.0	13.02	11.10	10.10	11.71
γ 75.0	12.16	10.33	9.59	11.07
γ 76.0	11.43	9.70	9.20	10.61
γ 77.0	10.86	9.24	8.82	10.16
γ 78.0	10.37	8.82	8.50	9.80
γ 79.0	9.95	8.49	8.19	9.45
γ 80.0	9.56	8.16	7.91	9.12
γ 81.0	9.19	7.87	7.63	8.80
γ 82.0	8.85	7.58	7.37	8.50
γ 83.0	8.52	7.31	7.12	8.21
γ 84.0	8.20	7.05	6.89	7.93
γ 85.0	7.92	6.79	6.64	7.67
γ 86.0	7.63	6.55	6.36	7.39
γ 87.0	7.34	6.27	6.08	7.05
γ 88.0	6.99	5.93	5.86	6.75
γ 89.0	6.66	5.65	5.71	6.55
γ 90.0	6.43	5.50	5.59	6.39
γ 91.0	6.27	5.38	5.47	6.25
γ 92.0	6.13	5.24	5.36	6.11
γ 93.0	5.97	5.13	5.24	5.99

Candela Tabulation - (Cont.)

V/H	C0.0	C90.0	C180.0	C270.0
γ 94.0	5.83	5.02	5.15	5.86
γ 95.0	5.71	4.92	5.06	5.74
γ 96.0	5.58	4.82	4.98	5.64
γ 97.0	5.46	4.72	4.90	5.53
γ 98.0	5.34	4.64	4.81	5.43
γ 99.0	5.24	4.56	4.75	5.33
γ 100.0	5.14	4.49	4.70	5.25
γ 101.0	5.06	4.41	4.64	5.19
γ 102.0	4.97	4.36	4.59	5.11
γ 103.0	4.89	4.31	4.55	5.04
γ 104.0	4.83	4.26	4.52	4.99
γ 105.0	4.76	4.22	4.49	4.94
γ 106.0	4.71	4.18	4.47	4.89
γ 107.0	4.65	4.17	4.45	4.85
γ 108.0	4.62	4.15	4.45	4.83
γ 109.0	4.57	4.11	4.44	4.81
γ 110.0	4.54	4.11	4.45	4.79
γ 111.0	4.53	4.11	4.47	4.78
γ 112.0	4.53	4.13	4.49	4.78
γ 113.0	4.51	4.14	4.51	4.80
γ 114.0	4.51	4.16	4.56	4.82
γ 115.0	4.54	4.20	4.60	4.84
γ 116.0	4.55	4.23	4.66	4.87
γ 117.0	4.58	4.28	4.71	4.92
γ 118.0	4.62	4.33	4.78	4.97
γ 119.0	4.66	4.39	4.86	5.03
γ 120.0	4.71	4.47	4.94	5.09
γ 121.0	4.78	4.54	5.03	5.17
γ 122.0	4.84	4.64	5.13	5.23
γ 123.0	4.91	4.72	5.22	5.33
γ 124.0	4.99	4.81	5.34	5.42
γ 125.0	5.09	4.92	5.45	5.52
γ 126.0	5.17	5.02	5.55	5.62
γ 127.0	5.27	5.14	5.70	5.72
γ 128.0	5.38	5.25	5.81	5.85
γ 129.0	5.49	5.37	5.95	5.95
γ 130.0	5.61	5.50	6.07	6.08
γ 131.0	5.73	5.63	6.21	6.20
γ 132.0	5.85	5.76	6.34	6.33
γ 133.0	5.97	5.91	6.49	6.45
γ 134.0	6.11	6.05	6.63	6.59
γ 135.0	6.24	6.17	6.78	6.72
γ 136.0	6.37	6.32	6.94	6.87
γ 137.0	6.52	6.46	7.08	7.02
γ 138.0	6.66	6.61	7.23	7.15
γ 139.0	6.80	6.76	7.39	7.30
γ 140.0	6.96	6.92	7.55	7.45

IES Indoor Report

Photometric Filename:MD10-18-XX-01 2700K RA90 60D.IES

Candela Tabulation - (Cont.)

V/H	C0.0	C90.0	C180.0	C270.0
γ 141.0	7.11	7.07	7.71	7.59
γ 142.0	7.25	7.22	7.86	7.74
γ 143.0	7.39	7.37	8.01	7.89
γ 144.0	7.57	7.53	8.16	8.02
γ 145.0	7.72	7.68	8.31	8.18
γ 146.0	7.87	7.85	8.45	8.31
γ 147.0	8.02	7.99	8.61	8.45
γ 148.0	8.17	8.13	8.74	8.59
γ 149.0	8.31	8.29	8.89	8.72
γ 150.0	8.46	8.43	9.03	8.86
γ 151.0	8.61	8.57	9.15	8.98
γ 152.0	8.74	8.72	9.29	9.12
γ 153.0	8.89	8.86	9.42	9.24
γ 154.0	9.03	8.98	9.53	9.35
γ 155.0	9.15	9.12	9.66	9.48
γ 156.0	9.28	9.24	9.78	9.59
γ 157.0	9.40	9.37	9.90	9.70
γ 158.0	9.53	9.50	10.00	9.81
γ 159.0	9.66	9.63	10.13	9.92
γ 160.0	9.78	9.75	10.23	10.04
γ 161.0	9.89	9.87	10.33	10.15
γ 162.0	10.01	10.00	10.44	10.25
γ 163.0	10.13	10.11	10.53	10.34
γ 164.0	10.24	10.21	10.64	10.45
γ 165.0	10.36	10.33	10.74	10.54
γ 166.0	10.46	10.43	10.83	10.65
γ 167.0	10.57	10.54	10.92	10.74
γ 168.0	10.68	10.64	11.02	10.83
γ 169.0	10.77	10.73	11.10	10.91
γ 170.0	10.86	10.80	11.17	11.00
γ 171.0	10.97	10.89	11.24	11.07
γ 172.0	11.05	10.98	11.31	11.14
γ 173.0	11.14	11.07	11.37	11.21
γ 174.0	11.23	11.14	11.41	11.25
γ 175.0	11.29	11.18	11.45	11.32
γ 176.0	11.35	11.25	11.49	11.37
γ 177.0	11.41	11.31	11.52	11.41
γ 178.0	11.46	11.35	11.53	11.44
γ 179.0	11.51	11.38	11.53	11.45
γ 180.0	11.51	11.51	11.51	11.51