



Indoor Luminaire Photometric Data

Description Information

Luminary Name: MD10-18-XX-01 3000K RA90 60D	Lum. Catalog:	Test ID: 01
Lamp Name:	Lamp Catalog: LED	Test Date: 2019/12/28
Manufacture: Shenzhen Norming Lighting Co., Ltd	Shld.Angle(°):	Test Machine:GON-2000
Test Lab: QUality peatment	Frequency (Hz):	Lamp CCT(K): Ra:
Lum. Size (W*L*H):0.550m*0.550m*0.850m	Lum. Area (m2):0.770	Lum. W(kg): 0.000
Test System: C, γ	Test Step: C=90.0 γ=1.0	Temp. (°C): 25
		Humidity(%):

Character Parameter

Lamp Speciality Parameter	Luminaire Speciality Parameter	
Rated Flux(lm): 1568.790	Luminary Flux(lm): 1568.789	Field Angle(10%Imax): 91.1(°)
Rated Power(W):	Luminary Efficiency: 100.00%	Down Lumens&Percent: 1528.557lm 97.44%
Rated Voltage(V):	Luminary EER(lm/W): 93.996	Up Lumens&Percent: 40.232lm 2.56%
Tested Power(W): 16.690	Max. Candela(cd): 1530.372	S/MH: C0_a180=0.929 C90_270=0.931
Lamps' Inside: 1	Max Cand@Ang. (°): C=0.0 γ=1.0	CIE Type: Semi-Direct
Tested Electrics (V, A, pf):240.2, 0.071	Beam Angle(50%Imax): 59.7(°)	ErP Φ use(90°): 1351.744lm
Lamp Size(W*L*H):0.550m*0.550m*0.850m	Left=-28.5°, Right=31.2°	IRF(%): 215.165





IES Indoor Report

Photometric Filename:MD10-18-XX-01 3000K RA90 60D.IES

2D Plane Light Intensity Distribution Curve

Lum. Name: MD10-18-XX-01 3000K RA90 60D	Lum. Catalog:	Test ID: 01
Lamp Name:	Lamp Catalog: LED	Test Lab: Quality peatment
Manufacture: Shenzhen Norming Lighting Co., Ltd	Test Machine:GON-2000	Test Date: 2019/12/28

C Plane Distribution Diagram



C Plane [50%MaxAng.] [10%MaxAng.]
— C0.0_180.0 : 59.7 91.1
— C90.0_270.0 : 59.8 91.4

Unit:cd


IES Indoor Report

Photometric Filename:MD10-18-XX-01 3000K RA90 60D.IES

3D Light Intensity Distribution Modal

Lum. Name: MD10-18-XX-01 3000K RA90 60D	Lum. Catalog:	Test ID: 01
Lamp Name:	Lamp Catalog: LED	Test Lab: Quality peatment
Manufacture: Shenzhen Norming Lighting Co., Ltd	Test Machine:GON-2000	Test Date: 2019/12/28

3D Light Intensity Distribution Modal



Curves: 3D Model — Fixture — Vert. HUD — Hori. HUD —
View Angles: Orient:0 Tilt:0 Roll:0 Spin:0

Zonal Flux Tabulation

Zone(γ)	Zone Flux (lm)	Sums Flux (lm)	Zone%Lamp	Sums%Lamp	Zone(γ)	Zone Flux (lm)	Sums Flux (lm)	Zone%Lamp	Sums%Lamp
0.0-1.0	1.46	1.46	0.09	0.09	47.0-48.0	10.42	1403.38	0.66	89.46
1.0-2.0	4.38	5.84	0.28	0.37	48.0-49.0	9.65	1413.03	0.62	90.07
2.0-3.0	7.28	13.13	0.46	0.84	49.0-50.0	8.93	1421.96	0.57	90.64
3.0-4.0	10.16	23.29	0.65	1.48	50.0-51.0	8.26	1430.22	0.53	91.17
4.0-5.0	13.00	36.29	0.83	2.31	51.0-52.0	7.64	1437.86	0.49	91.65
5.0-6.0	15.81	52.10	1.01	3.32	52.0-53.0	7.07	1444.93	0.45	92.10
6.0-7.0	18.57	70.67	1.18	4.50	53.0-54.0	6.53	1451.46	0.42	92.52
7.0-8.0	21.29	91.96	1.36	5.86	54.0-55.0	6.04	1457.50	0.38	92.91
8.0-9.0	23.95	115.91	1.53	7.39	55.0-56.0	5.57	1463.07	0.36	93.26
9.0-10.0	26.54	142.44	1.69	9.08	56.0-57.0	5.14	1468.21	0.33	93.59
10.0-11.0	29.05	171.49	1.85	10.93	57.0-58.0	4.74	1472.96	0.30	93.89
11.0-12.0	31.48	202.97	2.01	12.94	58.0-59.0	4.37	1477.33	0.28	94.17
12.0-13.0	33.80	236.77	2.15	15.09	59.0-60.0	4.04	1481.37	0.26	94.43
13.0-14.0	36.02	272.79	2.30	17.39	60.0-61.0	3.72	1485.09	0.24	94.66
14.0-15.0	38.12	310.91	2.43	19.82	61.0-62.0	3.43	1488.52	0.22	94.88
15.0-16.0	40.07	350.98	2.55	22.37	62.0-63.0	3.15	1491.67	0.20	95.08
16.0-17.0	41.85	392.83	2.67	25.04	63.0-64.0	2.89	1494.57	0.18	95.27
17.0-18.0	43.44	436.28	2.77	27.81	64.0-65.0	2.66	1497.23	0.17	95.44
18.0-19.0	44.82	481.10	2.86	30.67	65.0-66.0	2.45	1499.67	0.16	95.59
19.0-20.0	45.97	527.07	2.93	33.60	66.0-67.0	2.25	1501.93	0.14	95.74
20.0-21.0	46.85	573.91	2.99	36.58	67.0-68.0	2.07	1504.00	0.13	95.87
21.0-22.0	47.45	621.37	3.02	39.61	68.0-69.0	1.89	1505.89	0.12	95.99
22.0-23.0	47.75	669.12	3.04	42.65	69.0-70.0	1.73	1507.62	0.11	96.10
23.0-24.0	47.77	716.89	3.05	45.70	70.0-71.0	1.61	1509.23	0.10	96.20
24.0-25.0	47.54	764.43	3.03	48.73	71.0-72.0	1.52	1510.75	0.10	96.30
25.0-26.0	47.02	811.45	3.00	51.72	72.0-73.0	1.43	1512.18	0.09	96.39
26.0-27.0	46.23	857.68	2.95	54.67	73.0-74.0	1.34	1513.52	0.09	96.48
27.0-28.0	45.17	902.85	2.88	57.55	74.0-75.0	1.26	1514.77	0.08	96.56
28.0-29.0	43.87	946.73	2.80	60.35	75.0-76.0	1.19	1515.96	0.08	96.63
29.0-30.0	42.34	989.06	2.70	63.05	76.0-77.0	1.13	1517.09	0.07	96.70
30.0-31.0	40.57	1029.63	2.59	65.63	77.0-78.0	1.08	1518.17	0.07	96.77
31.0-32.0	38.61	1068.24	2.46	68.09	78.0-79.0	1.04	1519.22	0.07	96.84
32.0-33.0	36.45	1104.69	2.32	70.42	79.0-80.0	1.01	1520.22	0.06	96.90
33.0-34.0	34.11	1138.80	2.17	72.59	80.0-81.0	0.97	1521.20	0.06	96.97
34.0-35.0	31.62	1170.42	2.02	74.61	81.0-82.0	0.94	1522.14	0.06	97.03
35.0-36.0	29.05	1199.47	1.85	76.46	82.0-83.0	0.91	1523.05	0.06	97.08
36.0-37.0	26.51	1225.98	1.69	78.15	83.0-84.0	0.88	1523.93	0.06	97.14
37.0-38.0	24.10	1250.08	1.54	79.68	84.0-85.0	0.85	1524.78	0.05	97.19
38.0-39.0	21.88	1271.96	1.39	81.08	85.0-86.0	0.82	1525.60	0.05	97.25
39.0-40.0	19.89	1291.85	1.27	82.35	86.0-87.0	0.79	1526.39	0.05	97.30
40.0-41.0	18.18	1310.03	1.16	83.51	87.0-88.0	0.75	1527.14	0.05	97.35
41.0-42.0	16.70	1326.73	1.06	84.57	88.0-89.0	0.72	1527.86	0.05	97.39
42.0-43.0	15.40	1342.13	0.98	85.55	89.0-90.0	0.70	1528.56	0.04	97.44
43.0-44.0	14.24	1356.36	0.91	86.46	90.0-91.0	0.68	1529.24	0.04	97.48
44.0-45.0	13.16	1369.52	0.84	87.30	91.0-92.0	0.66	1529.90	0.04	97.52
45.0-46.0	12.17	1381.70	0.78	88.07	92.0-93.0	0.65	1530.54	0.04	97.56
46.0-47.0	11.26	1392.96	0.72	88.79	93.0-94.0	0.63	1531.18	0.04	97.60


Zonal Flux Tabulation - (Cont.)

Zone(γ)	Zone Flux (lm)	Sums Flux (lm)	Zone%Lamp	Sums%Lamp	Zone(γ)	Zone Flux (lm)	Sums Flux (lm)	Zone%Lamp	Sums%Lamp
94.0-95.0	0.62	1531.79	0.04	97.64	141.0-142.0	0.54	1555.76	0.03	99.17
95.0-96.0	0.60	1532.40	0.04	97.68	142.0-143.0	0.54	1556.30	0.03	99.20
96.0-97.0	0.59	1532.99	0.04	97.72	143.0-144.0	0.53	1556.83	0.03	99.24
97.0-98.0	0.58	1533.57	0.04	97.75	144.0-145.0	0.53	1557.37	0.03	99.27
98.0-99.0	0.57	1534.13	0.04	97.79	145.0-146.0	0.53	1557.89	0.03	99.31
99.0-100.0	0.56	1534.69	0.04	97.83	146.0-147.0	0.52	1558.42	0.03	99.34
100.0-101.0	0.55	1535.23	0.03	97.86	147.0-148.0	0.52	1558.94	0.03	99.37
101.0-102.0	0.53	1535.77	0.03	97.90	148.0-149.0	0.51	1559.45	0.03	99.40
102.0-103.0	0.53	1536.30	0.03	97.93	149.0-150.0	0.51	1559.96	0.03	99.44
103.0-104.0	0.52	1536.81	0.03	97.96	150.0-151.0	0.50	1560.46	0.03	99.47
104.0-105.0	0.51	1537.32	0.03	97.99	151.0-152.0	0.49	1560.95	0.03	99.50
105.0-106.0	0.50	1537.82	0.03	98.03	152.0-153.0	0.48	1561.44	0.03	99.53
106.0-107.0	0.50	1538.32	0.03	98.06	153.0-154.0	0.47	1561.91	0.03	99.56
107.0-108.0	0.49	1538.81	0.03	98.09	154.0-155.0	0.46	1562.38	0.03	99.59
108.0-109.0	0.48	1539.29	0.03	98.12	155.0-156.0	0.45	1562.83	0.03	99.62
109.0-110.0	0.48	1539.77	0.03	98.15	156.0-157.0	0.44	1563.27	0.03	99.65
110.0-111.0	0.48	1540.25	0.03	98.18	157.0-158.0	0.43	1563.70	0.03	99.68
111.0-112.0	0.47	1540.72	0.03	98.21	158.0-159.0	0.42	1564.12	0.03	99.70
112.0-113.0	0.47	1541.19	0.03	98.24	159.0-160.0	0.40	1564.52	0.03	99.73
113.0-114.0	0.47	1541.66	0.03	98.27	160.0-161.0	0.39	1564.91	0.02	99.75
114.0-115.0	0.47	1542.13	0.03	98.30	161.0-162.0	0.37	1565.28	0.02	99.78
115.0-116.0	0.47	1542.60	0.03	98.33	162.0-163.0	0.36	1565.64	0.02	99.80
116.0-117.0	0.47	1543.07	0.03	98.36	163.0-164.0	0.34	1565.98	0.02	99.82
117.0-118.0	0.47	1543.54	0.03	98.39	164.0-165.0	0.32	1566.30	0.02	99.84
118.0-119.0	0.47	1544.02	0.03	98.42	165.0-166.0	0.31	1566.61	0.02	99.86
119.0-120.0	0.47	1544.49	0.03	98.45	166.0-167.0	0.29	1566.90	0.02	99.88
120.0-121.0	0.48	1544.97	0.03	98.48	167.0-168.0	0.27	1567.17	0.02	99.90
121.0-122.0	0.48	1545.45	0.03	98.51	168.0-169.0	0.25	1567.42	0.02	99.91
122.0-123.0	0.48	1545.93	0.03	98.54	169.0-170.0	0.23	1567.65	0.01	99.93
123.0-124.0	0.49	1546.41	0.03	98.57	170.0-171.0	0.21	1567.86	0.01	99.94
124.0-125.0	0.49	1546.90	0.03	98.60	171.0-172.0	0.19	1568.05	0.01	99.95
125.0-126.0	0.49	1547.40	0.03	98.64	172.0-173.0	0.17	1568.22	0.01	99.96
126.0-127.0	0.50	1547.90	0.03	98.67	173.0-174.0	0.15	1568.37	0.01	99.97
127.0-128.0	0.50	1548.40	0.03	98.70	174.0-175.0	0.13	1568.50	0.01	99.98
128.0-129.0	0.51	1548.91	0.03	98.73	175.0-176.0	0.10	1568.60	0.01	99.99
129.0-130.0	0.51	1549.42	0.03	98.77	176.0-177.0	0.08	1568.68	0.01	99.99
130.0-131.0	0.51	1549.93	0.03	98.80	177.0-178.0	0.06	1568.74	0.00	100.00
131.0-132.0	0.52	1550.45	0.03	98.83	178.0-179.0	0.04	1568.78	0.00	100.00
132.0-133.0	0.52	1550.97	0.03	98.86	179.0-180.0	0.01	1568.79	0.00	100.00
133.0-134.0	0.52	1551.49	0.03	98.90					
134.0-135.0	0.53	1552.02	0.03	98.93					
135.0-136.0	0.53	1552.55	0.03	98.96					
136.0-137.0	0.53	1553.09	0.03	99.00					
137.0-138.0	0.53	1553.62	0.03	99.03					
138.0-139.0	0.54	1554.15	0.03	99.07					
139.0-140.0	0.54	1554.69	0.03	99.10					
140.0-141.0	0.54	1555.23	0.03	99.14					

Rectangle ISO Lighting Intensity Diagram

Lum. Name: MD10-18-XX-01 3000K RA90 60D	Lum. Catalog:	Test ID: 01
Lamp Name:	Lamp Catalog: LED	Test Lab: Quality Department
Manufacture: Shenzhen Norming Lighting Co., Ltd	Test Machine: GON-2000	Test Date: 2019/12/28

ISO Lighting Intensity Curve




Maximum Light Intensity(cd): 1530.37

Maximum Cand.@Angle: H=1.0°,V=0.0°

Plane ISO-Illuminance Diagram

Lum. Name: MD10-18-XX-01 3000K RA90 60D	Lum. Catalog:	Test ID: 01
Lamp Name:	Lamp Catalog: LED	Test Lab: Quality peatment
Manufacture: Shenzhen Norming Lighting Co., Ltd	Test Machine:GON-2000	Test Date: 2019/12/28

Plane ISO-Illuminance Curve



Working Plane Luminaire Mounting Height(m): 3.00


Working Plane Maximum Illuminance(lx): 169.96

Working Plane Maximum Illuminance Position(d/h):H0.0 V0.0

3D Plane ISO Illuminance Diagram

Lum. Name: MD10-18-XX-01 3000K RA90 60D	Lum. Catalog:	Test ID: 01
Lamp Name:	Lamp Catalog: LED	Test Lab: Quality peatment
Manufacture: Shenzhen Norming Lighting Co., Ltd	Test Machine:GON-2000	Test Date: 2019/12/28

3D Plane Illuminance Modal




Curves: 3D Model — 90% — 80% — 70% — 60% — 50% — 40% — 30% — 20% — 10% —
 View Angles(deg): 0 Height(m): 3.0 Distance(m): 10.0

Space ISO Illuminance Diagram

Lum. Name:MD10-18-XX-01 3000K RA90 60D	Lum. Catelog:	Test ID: 01
Lamp Name:	Lamp Catelog: LED	Test Lab: QQualty peatment
Manufacture: Shenzhen Norming Lighting Co., Ltd	Test Machine:GON-2000	Test Date: 2019/12/28

Space ISO Illuminance Curve



Space Plane Maximum Illuminance and @Angle:1529.67lx,1.0deg
Plane Maximum Lighting Intensity and @Angle:1530.372cd,0eg


IES Indoor Report

Photometric Filename:MD10-18-XX-01 3000K RA90 60D.IES

Illuminance-Distance Diagram

Lum. Name: MD10-18-XX-01 3000K RA90 60D	Lum. Catalog:	Test ID: 01
Lamp Name:	Lamp Catalog: LED	Test Lab: Quality peatment
Manufacture: Shenzhen Norming Lighting Co., Ltd	Test Machine:GON-2000	Test Date: 2019/12/28

Illuminance-Distance Curve



IES Indoor Report

Photometric Filename:MD10-18-XX-01 3000K RA90 60D.IES

Indoor Luminance Limiting Curves

Lum. Name: MD10-18-XX-01 3000K RA90 60D	Lum. Catalog:	Test ID: 01
Lamp Name:	Lamp Catalog: LED	Test Lab: Quality peatment
Manufacture: Shenzhen Norming Lighting Co., Ltd	Test Machine:GON-2000	Test Date: 2019/12/28


Glare Grade Table

GI	Quality	Using Illuminance							
1.15	A	2000	1000	500	<=300				
1.5	B		2000	1000	500	<=300			
1.85	C			2000	1000	500	<=300		
2.2	D				2000	1000	500	<=300	
2.55	E	a				2000	1000	500	<=300
			b	c	d	e	f	g	h

Luminance Table

Gama(deg)	45	50	55	60	65	70	75	80	85
C0	346	241	171	125	94	71	66	76	125
C90	294	202	143	103	75	57	54	63	104

Luminance Limiting Curve




Luminous Size: Length(m)=0.550 Width(m)=0.550 Height(m)=0.850 Area(m^2)=0.770000
 Luminous Type: Without Luminous Side
 Luminous Curves: C0-C180 Color: — C90-C270 Color: —

IES Indoor Report

Photometric Filename:MD10-18-XX-01 3000K RA90 60D.IES

Indoor Budgetary Estimate Table

Lum. Name: MD10-18-XX-01 3000K RA90 60D	Lum. Catalog:	Test ID: 01
Lamp Name:	Lamp Catalog: LED	Test Lab: Quality peatment
Manufacture: Shenzhen Norming Lighting Co., Ltd	Test Machine:GON-2000	Test Date: 2019/12/28



Parameters1: Rhocc = 0.7 Rhow = 0.5 Rhofc = 0.2 LLF = 0.8
Parameters2: Rhocc = 0.5 Rhow = 0.3 Rhofc = 0.2 LLF = 0.8
Average Illuminance(lx): 100 Cavity Height: H1(m) = 2

Indoor Coefficient of Utilization Table

Lum. Name: MD10-18-XX-01 3000K RA90 60D	Lum. Catelog:	Test ID: 01
Lamp Name:	Lamp Catelog: LED	Test Lab: QQualty peatment
Manufacture: Shenzhen Norming Lighting Co., Ltd	Test Machine:GON-2000	Test Date: 2019/12/28

Coefficients of Utilization - Zonal Cavity Method																		
Coef.	Effective Floor Cavity Reflectance RFC=0.20																	
RhoCC (%)	80				70				50			30			10			0
RhoW (%)	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR	Coefficient of Utilization(%)																	
0	118	118	118	118	115	115	115	115	110	110	110	104	104	104	100	100	100	97
1	112	109	106	104	109	107	104	102	102	100	98	98	96	95	94	93	92	90
2	106	100	96	92	103	98	94	91	95	91	89	91	89	86	88	86	84	82
3	100	93	87	83	98	91	86	82	88	84	80	85	82	79	83	80	77	76
4	94	86	80	75	92	85	79	75	82	77	74	80	76	72	78	74	71	70
5	89	80	74	69	87	79	73	69	77	72	68	75	70	67	73	69	66	64
6	84	75	68	64	83	74	68	63	72	67	63	70	66	62	69	65	61	60
7	80	70	63	59	78	69	63	59	67	62	58	66	61	58	65	60	57	56
8	76	65	59	55	74	65	59	55	63	58	54	62	57	54	61	57	53	52
9	72	62	55	51	71	61	55	51	60	54	51	59	54	50	58	53	50	49
10	68	58	52	48	67	58	52	48	56	51	47	56	51	47	55	50	47	46

Unified Glare Rating Table

Lum. Name: MD10-18-XX-01 3000K RA90 60D	Lum. Catelog:	Test ID: 01
Lamp Name:	Lamp Catelog: LED	Test Lab: QQualty peatment
Manufacture: Shenzhen Norming Lighting Co., Ltd	Test Machine:GON-2000	Test Date: 2019/12/28

Unified Glare Rating Table

Ceiling RCC	0.70	0.70	0.50	0.50	0.30	0.70	0.70	0.50	0.50	0.30
Wall RW	0.50	0.30	0.50	0.30	0.30	0.50	0.30	0.50	0.30	0.30
Floor RFC	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20
Room Size	Vewed crosswise					Vewed endwise				
X=2H Y=2H Y=3H Y=4H Y=6H Y=8H Y=12H	5.0	6.1	5.4	6.5	6.9	4.2	5.2	4.6	5.6	6.0
	5.1	6.0	5.5	6.4	6.9	4.2	5.1	4.6	5.5	6.0
	5.1	6.0	5.6	6.4	6.9	4.2	5.1	4.6	5.5	5.9
	5.1	6.0	5.6	6.4	6.8	4.2	5.0	4.7	5.5	5.9
	5.2	5.9	5.7	6.4	6.9	4.2	5.0	4.7	5.5	5.9
	5.2	6.0	5.7	6.4	6.9	4.3	5.0	4.8	5.5	6.0
X=4H Y=2H Y=3H Y=4H Y=6H Y=8H Y=12H	4.9	5.8	5.4	6.2	6.7	4.1	5.0	4.5	5.4	5.8
	5.1	5.8	5.5	6.3	6.7	4.2	4.9	4.6	5.4	5.8
	5.1	5.8	5.6	6.2	6.8	4.2	4.9	4.7	5.3	5.8
	5.2	5.8	5.7	6.3	6.8	4.3	4.9	4.8	5.4	5.9
	5.3	5.8	5.8	6.3	6.9	4.4	4.9	4.9	5.4	5.9
	5.5	5.9	6.0	6.5	7.0	4.5	5.0	5.0	5.5	6.0
X=8H Y=4H Y=6H Y=8H Y=12H	5.0	5.6	5.6	6.1	6.6	4.1	4.7	4.7	5.2	5.7
	5.2	5.7	5.8	6.2	6.8	4.3	4.7	4.9	5.3	5.9
	5.4	5.8	6.0	6.3	6.9	4.5	4.9	5.0	5.4	6.0
	5.7	6.0	6.2	6.5	7.2	4.7	5.1	5.3	5.6	6.2
X=12H Y=4H Y=6H Y=8H	5.0	5.5	5.5	6.0	6.5	4.1	4.6	4.6	5.1	5.6
	5.2	5.6	5.8	6.1	6.7	4.3	4.7	4.9	5.2	5.8
	5.4	5.8	6.0	6.3	6.9	4.5	4.9	5.1	5.4	6.0
Variations with the objerver position at spacings										
S=1.0H	0.1/-0.1					0.2/-0.2				
S=1.5H	0.4/-0.3					0.4/-0.3				
S=2.0H	0.9/-0.6					0.9/-0.6				
Reduced UGR Table:										
Nordic Standard Table:	BK0					BK0				
Correction Value	0.9					0.9				

o the CIE Pub.117, data has been corrected, refers to the lamp's lumens 8.2flm.

Candela Tabulation

V/H	C0.0	C90.0	C180.0	C270.0
γ 0.0	1528.07	1528.07	1528.07	1528.07
γ 1.0	1530.37	1526.31	1525.69	1528.16
γ 2.0	1530.34	1522.95	1520.39	1524.35
γ 3.0	1528.13	1518.05	1514.47	1521.83
γ 4.0	1524.40	1510.92	1506.00	1516.84
γ 5.0	1517.94	1503.56	1498.58	1511.23
γ 6.0	1511.76	1495.76	1489.33	1504.10
γ 7.0	1503.41	1488.36	1480.74	1496.31
γ 8.0	1495.76	1476.95	1470.56	1486.83
γ 9.0	1486.20	1469.04	1458.13	1475.83
γ 10.0	1475.05	1457.58	1443.37	1464.55
γ 11.0	1463.16	1445.72	1427.50	1452.57
γ 12.0	1450.77	1430.25	1409.73	1438.16
γ 13.0	1436.05	1413.72	1390.47	1423.51
γ 14.0	1421.97	1395.37	1369.62	1406.18
γ 15.0	1404.70	1375.71	1347.44	1386.11
γ 16.0	1385.59	1352.14	1321.90	1364.63
γ 17.0	1364.72	1325.60	1296.25	1338.85
γ 18.0	1341.09	1297.63	1264.07	1311.19
γ 19.0	1314.28	1267.44	1230.05	1279.83
γ 20.0	1283.46	1232.31	1191.37	1246.97
γ 21.0	1251.93	1196.43	1148.76	1207.54
γ 22.0	1214.85	1155.55	1102.99	1167.46
γ 23.0	1174.26	1110.61	1054.22	1123.46
γ 24.0	1130.04	1064.02	1003.93	1079.79
γ 25.0	1084.32	1015.76	953.25	1031.28
γ 26.0	1036.53	965.44	900.61	980.78
γ 27.0	986.73	912.73	846.54	929.05
γ 28.0	935.81	857.72	791.43	876.85
γ 29.0	882.94	803.89	736.27	822.84
γ 30.0	829.47	749.18	678.66	768.86
γ 31.0	775.86	694.38	621.09	714.19
γ 32.0	722.26	639.84	565.27	657.36
γ 33.0	666.52	585.23	509.95	602.37
γ 34.0	609.79	530.91	456.81	546.87
γ 35.0	553.64	476.99	405.68	492.10
γ 36.0	499.34	425.21	358.05	439.05
γ 37.0	446.70	376.30	316.15	390.50
γ 38.0	397.98	332.48	281.34	346.58
γ 39.0	352.44	293.73	252.28	307.23
γ 40.0	311.81	262.40	226.82	274.57
γ 41.0	277.73	236.43	204.79	247.12
γ 42.0	249.90	213.97	184.95	223.39
γ 43.0	226.82	194.02	167.22	202.64
γ 44.0	206.45	176.15	151.26	184.07
γ 45.0	188.12	159.84	136.93	167.14
γ 46.0	171.63	145.20	124.03	152.00

IES Indoor Report

Photometric Filename:MD10-18-XX-01 3000K RA90 60D.IES

Candela Tabulation - (Cont.)

V/H	C0.0	C90.0	C180.0	C270.0
γ 47.0	156.45	132.07	112.67	138.46
γ 48.0	143.03	120.22	102.57	125.98
γ 49.0	130.72	109.65	93.14	114.68
γ 50.0	119.26	99.90	84.85	104.58
γ 51.0	108.76	90.94	77.45	95.29
γ 52.0	99.22	82.96	70.58	87.06
γ 53.0	90.57	75.68	64.24	79.46
γ 54.0	82.76	69.10	58.47	72.61
γ 55.0	75.60	63.05	52.97	66.29
γ 56.0	69.11	57.55	48.12	60.49
γ 57.0	63.14	52.49	43.87	55.15
γ 58.0	57.72	47.82	39.78	50.35
γ 59.0	52.83	43.51	36.30	45.97
γ 60.0	48.29	39.52	33.14	42.13
γ 61.0	44.16	36.11	30.17	38.55
γ 62.0	40.28	32.92	27.36	35.24
γ 63.0	36.88	29.76	24.78	32.17
γ 64.0	33.67	26.86	22.45	29.34
γ 65.0	30.53	24.25	20.84	26.89
γ 66.0	27.61	22.27	19.23	24.53
γ 67.0	25.23	20.17	17.71	22.62
γ 68.0	22.94	18.38	15.84	20.55
γ 69.0	21.20	16.22	14.82	18.18
γ 70.0	18.81	15.07	13.95	16.80
γ 71.0	17.22	14.16	13.10	15.84
γ 72.0	16.11	13.24	12.23	14.89
γ 73.0	15.09	12.32	11.38	13.91
γ 74.0	14.10	11.43	10.65	12.94
γ 75.0	13.10	10.67	10.08	12.11
γ 76.0	12.24	10.06	9.66	11.47
γ 77.0	11.56	9.57	9.25	10.97
γ 78.0	11.01	9.15	8.92	10.53
γ 79.0	10.52	8.79	8.61	10.15
γ 80.0	10.12	8.46	8.32	9.80
γ 81.0	9.75	8.13	8.03	9.46
γ 82.0	9.41	7.83	7.75	9.14
γ 83.0	9.07	7.54	7.48	8.82
γ 84.0	8.73	7.25	7.23	8.51
γ 85.0	8.40	6.98	6.98	8.22
γ 86.0	8.10	6.72	6.67	7.93
γ 87.0	7.80	6.37	6.34	7.57
γ 88.0	7.38	6.07	6.13	7.19
γ 89.0	7.02	5.87	5.98	6.93
γ 90.0	6.74	5.70	5.85	6.75
γ 91.0	6.56	5.58	5.72	6.60
γ 92.0	6.39	5.43	5.60	6.44
γ 93.0	6.24	5.30	5.49	6.29

Candela Tabulation - (Cont.)

V/H	C0.0	C90.0	C180.0	C270.0
γ 94.0	6.10	5.20	5.38	6.16
γ 95.0	5.96	5.09	5.28	6.04
γ 96.0	5.82	4.98	5.19	5.93
γ 97.0	5.70	4.89	5.10	5.80
γ 98.0	5.57	4.80	5.03	5.70
γ 99.0	5.46	4.72	4.95	5.59
γ 100.0	5.35	4.64	4.88	5.50
γ 101.0	5.25	4.57	4.82	5.42
γ 102.0	5.17	4.49	4.76	5.33
γ 103.0	5.07	4.45	4.73	5.25
γ 104.0	5.00	4.40	4.70	5.19
γ 105.0	4.93	4.36	4.66	5.13
γ 106.0	4.87	4.32	4.64	5.09
γ 107.0	4.81	4.29	4.63	5.04
γ 108.0	4.77	4.27	4.62	5.00
γ 109.0	4.73	4.27	4.61	4.98
γ 110.0	4.70	4.26	4.63	4.97
γ 111.0	4.68	4.27	4.65	4.96
γ 112.0	4.67	4.28	4.67	4.97
γ 113.0	4.67	4.30	4.71	4.96
γ 114.0	4.67	4.33	4.76	4.99
γ 115.0	4.68	4.37	4.80	5.02
γ 116.0	4.71	4.42	4.86	5.05
γ 117.0	4.74	4.49	4.93	5.09
γ 118.0	4.77	4.54	5.01	5.14
γ 119.0	4.82	4.61	5.08	5.19
γ 120.0	4.88	4.70	5.17	5.26
γ 121.0	4.94	4.78	5.28	5.34
γ 122.0	5.01	4.88	5.38	5.42
γ 123.0	5.09	4.97	5.49	5.51
γ 124.0	5.19	5.07	5.62	5.62
γ 125.0	5.27	5.18	5.73	5.72
γ 126.0	5.38	5.31	5.86	5.82
γ 127.0	5.49	5.43	5.99	5.93
γ 128.0	5.61	5.57	6.14	6.05
γ 129.0	5.72	5.71	6.26	6.17
γ 130.0	5.85	5.84	6.40	6.30
γ 131.0	5.97	5.99	6.55	6.43
γ 132.0	6.11	6.14	6.70	6.57
γ 133.0	6.24	6.28	6.86	6.71
γ 134.0	6.39	6.41	7.01	6.85
γ 135.0	6.53	6.58	7.18	7.00
γ 136.0	6.68	6.73	7.34	7.16
γ 137.0	6.83	6.88	7.50	7.30
γ 138.0	6.98	7.04	7.67	7.45
γ 139.0	7.15	7.22	7.83	7.60
γ 140.0	7.30	7.38	8.01	7.77

IES Indoor Report

Photometric Filename:MD10-18-XX-01 3000K RA90 60D.IES

Candela Tabulation - (Cont.)

V/H	C0.0	C90.0	C180.0	C270.0
γ 141.0	7.47	7.55	8.16	7.93
γ 142.0	7.63	7.72	8.34	8.09
γ 143.0	7.79	7.88	8.50	8.23
γ 144.0	7.96	8.04	8.66	8.39
γ 145.0	8.11	8.22	8.83	8.55
γ 146.0	8.28	8.37	8.99	8.70
γ 147.0	8.44	8.54	9.14	8.85
γ 148.0	8.61	8.70	9.31	9.00
γ 149.0	8.76	8.86	9.45	9.15
γ 150.0	8.92	9.01	9.59	9.29
γ 151.0	9.07	9.16	9.73	9.43
γ 152.0	9.22	9.30	9.86	9.57
γ 153.0	9.37	9.46	10.00	9.68
γ 154.0	9.52	9.60	10.11	9.82
γ 155.0	9.65	9.74	10.25	9.96
γ 156.0	9.79	9.87	10.37	10.08
γ 157.0	9.93	10.01	10.50	10.19
γ 158.0	10.07	10.13	10.61	10.33
γ 159.0	10.19	10.27	10.74	10.45
γ 160.0	10.31	10.40	10.85	10.57
γ 161.0	10.44	10.52	10.97	10.69
γ 162.0	10.58	10.64	11.08	10.81
γ 163.0	10.69	10.78	11.18	10.92
γ 164.0	10.84	10.90	11.29	11.05
γ 165.0	10.95	11.02	11.40	11.15
γ 166.0	11.07	11.13	11.52	11.26
γ 167.0	11.19	11.24	11.61	11.37
γ 168.0	11.30	11.33	11.69	11.47
γ 169.0	11.41	11.43	11.80	11.58
γ 170.0	11.53	11.54	11.87	11.67
γ 171.0	11.63	11.62	11.97	11.74
γ 172.0	11.75	11.71	12.03	11.84
γ 173.0	11.84	11.78	12.11	11.90
γ 174.0	11.91	11.87	12.15	11.97
γ 175.0	12.01	11.94	12.21	12.03
γ 176.0	12.08	11.99	12.25	12.10
γ 177.0	12.14	12.07	12.28	12.15
γ 178.0	12.21	12.11	12.29	12.18
γ 179.0	12.25	12.13	12.31	12.20
γ 180.0	12.26	12.26	12.26	12.26