



FEATURES

- "F-connect" design for heatsink and optics.
- Low profile.
- Fit in most of MR16 LED downlight converters.
- DALI Dimmable.
- 5-year guarantee.

Technical Data

Input Voltage/Hz	AC200-240V 50/60Hz
Output Voltage/Current	DC30-40V/300mA DC30-40V/230mA
Power	13W(Max) 10W(Min)
Rated Input Current	0.054A
THD	<25%
PF value	>0.9
Ingress Protection	IP20
Operating Temperature	-10—40°C
Dimmability	DALI dimmable with DIMMATE driver
L70/B50 at 25°C	>105000H
L90/B10 at 25°C	>105000H

LED and Optical Data

LED Brand	Bridgelux COB LED
CRI	>90
SDCM	<3
Beam Angle	15°/25°/38°/60°
Colour Temperature	2700K/3000K/4000K
System luminous efficacy up to	120lm/W

Packaging

Box Dimensions	L132 x W108 x H68 mm
Box Net Weight	0.220Kg
Box Gross Weight	0.256Kg
Carton Dimensions	L522 x W276 x H160 mm/20 PCS
Carton Net Weight	5.18Kg
Carton Gross Weight	6.68Kg



CCT			Beam Angle	Lumen	Efficacy	Beam Angle			Lumen	Efficacy
2700K	CRI 90+	13W	15°	1365lm	109lm/W	10W	15°	1068lm	108lm/W	
			25°	1358lm	109lm/W		25°	1074lm	108lm/W	
			38°	1336lm	107lm/W		38°	1064lm	107lm/W	
			60°	1337lm	107lm/W		60°	1065lm	108lm/W	
3000K			15°	1407lm	112lm/W		15°	1128lm	113lm/W	
			25°	1406lm	112lm/W		25°	1124lm	113lm/W	
			38°	1385lm	111lm/W		38°	1106lm	111lm/W	
			60°	1389lm	111lm/W		60°	1109lm	112lm/W	
4000K			15°	1494lm	120lm/W		15°	1165lm	118lm/W	
			25°	1480lm	119lm/W		25°	1173lm	119lm/W	
			38°	1453lm	117lm/W		38°	1158lm	117lm/W	
			60°	1458lm	117lm/W		60°	1162lm	118lm/W	

ECLIPSE CONSEIL

Siège : +33 (1) 79 30 48 19- Showroom Paris : +33 (1) 78 95 50 14 - Mob : +33 (6) 87 82 12 04
Siège social : 7 rue Prudent Neel 92500 Rueil-Malmaison - Showroom : 1 rue Dulong 75017 PARIS