



FEATURES

- Modular Design.
- System power up to 30W.
- Interchangeable anti-glare reflector.
- 5-year guarantee.

Technical Data

Input Voltage/Hz	AC200-240V 50/60Hz
Output Voltage/Current	DC36V/580mA
Power	23W
Rated Input Current	0.115A
PF value	>0.9
THD	<20%
Ingress Protection	IP20
Operating Temperature	-10—40°C
Dimmability	Non-dimmable with AcTEC driver

Optical Data

LED Brand	Bridgelux SMD LED
CRI	Ra> 92
Beam Angle	60°/70°
Colour temperature	2700k/3000K/4000K/5000K 2500k/2700K/3500K/4500K
System luminous efficacy up to	97.9lm/W

Packaging

Box Dimensions	L245 x W156 x H165mm
Box Net Weight	1.82Kg
Box Gross Weight	2.01Kg
Carton Dimensions	L505 x W330 x H355 mm/8 PCS
Carton Net Weight	14.56Kg
Carton Gross Weight	17.18Kg



Model	CCT		Beam Angle	Lumen	Efficacy	Beam Angle	Lumen	Efficacy
PD07-25-XX-01	2700K	CRI 92+	70°	2101lm	91.5lm/W	60°	1788lm	77.8lm/W
PD07-25-XX-01	3000K		70°	2219lm	96.2lm/W	60°	1866lm	81.9lm/W
PD07-25-XX-01	4000K		70°	2289lm	97.3lm/W	60°	1922lm	83.3lm/W
PD07-25-XX-01	5000K		70°	2263lm	97.9lm/W	60°	1911lm	83.2lm/W

Reflector



Model	CCT		Beam Angle	Lumen	Efficacy
PD07-25-XX-01	2500K	CRI 92+	70°	1898lm	81lm/W
PD07-25-XX-01	2700K		70°	1943lm	85.7lm/W
PD07-25-XX-01	3500K		70°	1987lm	86.4lm/W
PD07-25-XX-01	4500K		70°	1961lm	85.6lm/W

Reflector



ECLIPSE CONSEIL

Siège : +33 (1) 79 30 48 19- Showroom Paris : +33 (1) 78 95 50 14 - Mob : +33 (6) 87 82 12 04
Siège social : 7 rue Prudent Neel 92500 Rueil-Malmaison - Showroom : 1 rue Dulong 75017 PARIS