



Packaging

Box Dimensions	L245 x W156 x H165mm
Box Net Weight	1.82Kg
Box Gross Weight	2.01Kg
Carton Dimensions	L505 x W330 x H355 mm/8 PCS
Carton Net Weight	14.56Kg
Carton Gross Weight	17.18Kg

FEATURES

- Modular Design.
- System power up to 30W.
- Interchangeable beam.
- Interchangeable anti-glare reflector.
- 5-year guarantee.

Technical Data

Input Voltage/Hz	AC200-240V 50/60Hz
Output Voltage/Current	DC36V/580mA
Power	23W
Rated Input Current	0.115A
PF value	>0.9
THD	<20%
Ingress Protection	IP20
Operating Temperature	-10—40°C
Dimmability	Non-dimmable with AcTEC driver

Optical Data

LED Brand	Bridgelux COB LED
CRI	Ra> 90
Beam Angle	15°/24°/36°/60°
Colour temperature	2700k/3000K/4000K
System luminous efficacy up to	103.7lm/W



Model	CCT	Beam Angle	Lumen	Efficacy
PD08-25-XX-01	2700K	15°	2091lm	92.1lm/W
		24°	2040lm	89.9lm/W
		36°	2159lm	94.4lm/W
		60°	2143lm	93.2lm/W
PD08-25-XX-01	3000K	15°	2279lm	98lm/W
		24°	2173lm	95.4lm/W
		36°	2244lm	99.9lm/W
		60°	2220lm	98.9lm/W
PD08-25-XX-01	4000K	15°	2065lm	88.3lm/W
		24°	2140lm	93.9lm/W
		36°	2423lm	103.6lm/W
		60°	2363lm	103.7lm/W

ECLIPSE CONSEIL

Siège : +33 (1) 79 30 48 19- Showroom Paris : +33 (1) 78 95 50 14 - Mob : +33 (6) 87 82 12 04
Siège social : 7 rue Prudent Neel 92500 Rueil-Malmaison - Showroom : 1 rue Dulong 75017 PARIS