



## FEATURES

- Modular Design.
- System power up to 40W.
- Interchangeable beam.
- Interchangeable anti-glare reflector.
- 5-year guarantee.

## Technical Data

Input Voltage/Hz	AC200-240V 50/60Hz
Output Voltage/Current	DC36V/850mA
Power	32W
Rated Input Current	0.16A
PF value	>0.9
THD	<15%
Ingress Protection	IP20
Operating Temperature	-10—40℃
Dimmability	Non-dimmable with AcTEC driver

## Optical Data

LED Brand	Bridgelux COB LED
CRI	Ra> 90
Beam Angle	15°/24°/36°/60°
Colour temperature	2700k/3000K/4000K
System luminous efficacy up to	95.4lm/W

## Packaging

Box Dimensions	L287 x W206 x H207mm
Box Net Weight	3.25Kg
Box Gross Weight	4.01Kg
Carton Dimensions	L590 x W430 x H235 mm/4 PCS
Carton Net Weight	13Kg
Carton Gross Weight	17.08Kg



Model	CCT	Beam Angle	Lumen	Efficacy
PD08-35-XX-01	2700K	15°	2585lm	81.1lm/W
		24°	2576lm	81.1lm/W
		36°	2746lm	82lm/W
		60°	2377lm	73.5lm/W
PD08-35-XX-01	3000K	15°	2726lm	84.3lm/W
		24°	2749lm	86.3lm/W
		36°	2821lm	89.3lm/W
		60°	2501lm	79lm/W
PD08-35-XX-01	4000K	15°	3022lm	95.4lm/W
		24°	2997lm	94.3lm/W
		36°	3035lm	95.4lm/W
		60°	2728lm	82.69lm/W

## ECLIPSE CONSEIL

Siège : +33 (1) 79 30 48 19- Showroom Paris : +33 (1) 78 95 50 14 - Mob : +33 (6) 87 82 12 04  
Siège social : 7 rue Prudent Neel 92500 Rueil-Malmaison - Showroom : 1 rue Dulong 75017 PARIS