



Indoor Luminaire Photometric Data

Description Information

Luminary Name: TR08-06-XX-01 4000K RA90 60D		Lum. Catalog:	Test ID: 01
Lamp Name:		Lamp Catalog: LED	Test Date: 2021/10/28
Manufacture: Shenzhen Norming Lighting Co., Ltd		Shld. Ang(°):	Test Machine:GON-2000
Test Lab: Quality Department		Frequency (Hz):	Lamp CCT (K): Ra:
Lum. Size (W*L*H):0.076m*0.076m*0.000m		Lum. Area (m2):0.005	Lum. W (kg): 0.000
Test System: C, γ	Test Step: C=90.0 γ=1.0	Temp. (°C): 25	Humidity(%): 50.0


Character Parameter

Lamp Speciality Parameter		Luminaire Speciality Parameter	
Rated Flux(lm): 584.180	Luminary Flux(lm): 584.176	Field Angle(10%Imax): 84.4(°)	
Rated Power(W):	Luminary Efficiency: 100.00%	Down Lumens&Percent: 580.860lm 99.43%	
Rated Voltage(V):	Luminary EER(lm/W): 93.995	Up Lumens&Percent: 3.316lm 0.57%	
Tested Power(W): 6.215	Max. Candela(cd): 602.701	S/MH: C0_a180=0.963 C90_270=0.960	
Lamps' Inside: 1	Max Cand@Ang. (°): C=0.0 γ=10.0	CIE Type: Semi-Direct	
Tested Electrics (V, A, pf):241.0, 0.030, 0.843	Beam Angle(50%Imax): 59.4(°)	ErP Φ use(90°): 518.336lm	
Lamp Size (W*L*H):0.076m*0.076m*0.000m	Left=-29.5°, Right=29.9°	IRF(%): 225.030	



2D Plane Light Intensity Distribution Curve


Lum. Name:TR08-06-XX-01 4000K RA90 60D	Lum. Catelog:	Test ID:01
Lamp Name:	Lamp Catelog:LED	Test Lab:Quality Department
Manufacture:Shenzhen Norming Lighting Co., Ltd	Test Machine:GON-2000	Test Date:2021/10/28



3D Light Intensity Distribution Modal

Lum. Name:TR08-06-XX-01 4000K RA90 60D	Lum. Catelog:	Test ID:01
Lamp Name:	Lamp Catelog:LED	Test Lab:Quality Department
Manufacture:Shenzhen Norming Lighting Co., Ltd	Test Machine:GON-2000	Test Date:2021/10/28

3D Light Intensity Distribution Modal



IES Indoor Report

Photometric Filename:TR08-06-XX-01 4000K RA90 60D.IES

Zonal Flux Tabulation


Zone(γ)	Zone Flux (lm)	Sums Flux (lm)	Zone%Lamp	Sums%Lamp	Zone(γ)	Zone Flux (lm)	Sums Flux (lm)	Zone%Lamp	Sums%Lamp
0.0-1.0	0.58	0.58	0.10	0.10	47.0-48.0	2.79	544.83	0.48	93.26
1.0-2.0	1.72	2.30	0.29	0.39	48.0-49.0	2.55	547.38	0.44	93.70
2.0-3.0	2.87	5.17	0.49	0.88	49.0-50.0	2.34	549.73	0.40	94.10
3.0-4.0	4.01	9.18	0.69	1.57	50.0-51.0	2.17	551.89	0.37	94.47
4.0-5.0	5.15	14.33	0.88	2.45	51.0-52.0	2.01	553.90	0.34	94.82
5.0-6.0	6.27	20.60	1.07	3.53	52.0-53.0	1.87	555.77	0.32	95.14
6.0-7.0	7.39	27.99	1.26	4.79	53.0-54.0	1.74	557.51	0.30	95.43
7.0-8.0	8.49	36.49	1.45	6.25	54.0-55.0	1.62	559.13	0.28	95.71
8.0-9.0	9.60	46.08	1.64	7.89	55.0-56.0	1.52	560.65	0.26	95.97
9.0-10.0	10.70	56.78	1.83	9.72	56.0-57.0	1.42	562.07	0.24	96.22
10.0-11.0	11.78	68.56	2.02	11.74	57.0-58.0	1.34	563.41	0.23	96.45
11.0-12.0	12.84	81.40	2.20	13.93	58.0-59.0	1.26	564.67	0.22	96.66
12.0-13.0	13.88	95.28	2.38	16.31	59.0-60.0	1.19	565.87	0.20	96.86
13.0-14.0	14.88	110.16	2.55	18.86	60.0-61.0	1.13	566.99	0.19	97.06
14.0-15.0	15.83	126.00	2.71	21.57	61.0-62.0	1.07	568.06	0.18	97.24
15.0-16.0	16.72	142.72	2.86	24.43	62.0-63.0	1.01	569.07	0.17	97.41
16.0-17.0	17.54	160.26	3.00	27.43	63.0-64.0	0.96	570.02	0.16	97.58
17.0-18.0	18.28	178.54	3.13	30.56	64.0-65.0	0.91	570.93	0.16	97.73
18.0-19.0	18.92	197.46	3.24	33.80	65.0-66.0	0.86	571.80	0.15	97.88
19.0-20.0	19.43	216.89	3.33	37.13	66.0-67.0	0.82	572.62	0.14	98.02
20.0-21.0	19.80	236.69	3.39	40.52	67.0-68.0	0.78	573.39	0.13	98.15
21.0-22.0	20.01	256.70	3.42	43.94	68.0-69.0	0.73	574.12	0.13	98.28
22.0-23.0	20.09	276.79	3.44	47.38	69.0-70.0	0.69	574.81	0.12	98.40
23.0-24.0	20.04	296.82	3.43	50.81	70.0-71.0	0.65	575.46	0.11	98.51
24.0-25.0	19.83	316.65	3.39	54.20	71.0-72.0	0.61	576.07	0.10	98.61
25.0-26.0	19.46	336.11	3.33	57.53	72.0-73.0	0.57	576.64	0.10	98.71
26.0-27.0	18.91	355.02	3.24	60.77	73.0-74.0	0.53	577.16	0.09	98.80
27.0-28.0	18.21	373.23	3.12	63.89	74.0-75.0	0.49	577.65	0.08	98.88
28.0-29.0	17.37	390.60	2.97	66.86	75.0-76.0	0.45	578.10	0.08	98.96
29.0-30.0	16.43	407.02	2.81	69.67	76.0-77.0	0.41	578.51	0.07	99.03
30.0-31.0	15.38	422.40	2.63	72.31	77.0-78.0	0.37	578.88	0.06	99.09
31.0-32.0	14.26	436.65	2.44	74.75	78.0-79.0	0.33	579.22	0.06	99.15
32.0-33.0	13.12	449.77	2.25	76.99	79.0-80.0	0.29	579.51	0.05	99.20
33.0-34.0	11.99	461.77	2.05	79.05	80.0-81.0	0.25	579.76	0.04	99.24
34.0-35.0	10.90	472.66	1.87	80.91	81.0-82.0	0.22	579.98	0.04	99.28
35.0-36.0	9.84	482.51	1.68	82.60	82.0-83.0	0.19	580.17	0.03	99.31
36.0-37.0	8.84	491.35	1.51	84.11	83.0-84.0	0.16	580.33	0.03	99.34
37.0-38.0	7.91	499.26	1.35	85.46	84.0-85.0	0.13	580.46	0.02	99.36
38.0-39.0	7.06	506.33	1.21	86.67	85.0-86.0	0.11	580.57	0.02	99.38
39.0-40.0	6.30	512.63	1.08	87.75	86.0-87.0	0.09	580.66	0.02	99.40
40.0-41.0	5.63	518.26	0.96	88.72	87.0-88.0	0.08	580.74	0.01	99.41
41.0-42.0	5.05	523.31	0.86	89.58	88.0-89.0	0.06	580.80	0.01	99.42
42.0-43.0	4.54	527.85	0.78	90.36	89.0-90.0	0.06	580.86	0.01	99.43
43.0-44.0	4.09	531.94	0.70	91.06	90.0-91.0	0.05	580.91	0.01	99.44
44.0-45.0	3.70	535.64	0.63	91.69	91.0-92.0	0.04	580.95	0.01	99.45
45.0-46.0	3.35	538.99	0.57	92.27	92.0-93.0	0.04	580.99	0.01	99.45
46.0-47.0	3.05	542.05	0.52	92.79	93.0-94.0	0.03	581.02	0.01	99.46

Zonal Flux Tabulation - (Cont.)

Zone (γ)	Zone Flux (lm)	Sums Flux (lm)	Zone%Lamp	Sums%Lamp	Zone (γ)	Zone Flux (lm)	Sums Flux (lm)	Zone%Lamp	Sums%Lamp
94.0-95.0	0.03	581.04	0.00	99.46	141.0-142.0	0.07	581.79	0.01	99.59
95.0-96.0	0.02	581.07	0.00	99.47	142.0-143.0	0.07	581.87	0.01	99.60
96.0-97.0	0.02	581.09	0.00	99.47	143.0-144.0	0.07	581.94	0.01	99.62
97.0-98.0	0.02	581.11	0.00	99.47	144.0-145.0	0.08	582.02	0.01	99.63
98.0-99.0	0.01	581.12	0.00	99.48	145.0-146.0	0.08	582.10	0.01	99.64
99.0-100.0	0.01	581.13	0.00	99.48	146.0-147.0	0.08	582.18	0.01	99.66
100.0-101.0	0.01	581.14	0.00	99.48	147.0-148.0	0.08	582.26	0.01	99.67
101.0-102.0	0.01	581.15	0.00	99.48	148.0-149.0	0.08	582.34	0.01	99.69
102.0-103.0	0.01	581.15	0.00	99.48	149.0-150.0	0.08	582.43	0.01	99.70
103.0-104.0	0.00	581.16	0.00	99.48	150.0-151.0	0.09	582.51	0.01	99.71
104.0-105.0	0.00	581.16	0.00	99.48	151.0-152.0	0.09	582.60	0.01	99.73
105.0-106.0	0.00	581.16	0.00	99.48	152.0-153.0	0.09	582.69	0.01	99.74
106.0-107.0	0.00	581.16	0.00	99.48	153.0-154.0	0.09	582.77	0.01	99.76
107.0-108.0	0.00	581.17	0.00	99.48	154.0-155.0	0.09	582.86	0.01	99.77
108.0-109.0	0.00	581.17	0.00	99.48	155.0-156.0	0.09	582.94	0.01	99.79
109.0-110.0	0.00	581.17	0.00	99.48	156.0-157.0	0.08	583.03	0.01	99.80
110.0-111.0	0.00	581.17	0.00	99.48	157.0-158.0	0.08	583.11	0.01	99.82
111.0-112.0	0.00	581.17	0.00	99.48	158.0-159.0	0.08	583.19	0.01	99.83
112.0-113.0	0.00	581.17	0.00	99.48	159.0-160.0	0.08	583.27	0.01	99.84
113.0-114.0	0.00	581.17	0.00	99.48	160.0-161.0	0.08	583.35	0.01	99.86
114.0-115.0	0.00	581.17	0.00	99.48	161.0-162.0	0.08	583.42	0.01	99.87
115.0-116.0	0.00	581.17	0.00	99.48	162.0-163.0	0.07	583.50	0.01	99.88
116.0-117.0	0.00	581.17	0.00	99.48	163.0-164.0	0.07	583.57	0.01	99.90
117.0-118.0	0.00	581.17	0.00	99.48	164.0-165.0	0.07	583.64	0.01	99.91
118.0-119.0	0.00	581.17	0.00	99.48	165.0-166.0	0.06	583.70	0.01	99.92
119.0-120.0	0.00	581.17	0.00	99.48	166.0-167.0	0.06	583.76	0.01	99.93
120.0-121.0	0.00	581.17	0.00	99.48	167.0-168.0	0.06	583.82	0.01	99.94
121.0-122.0	0.00	581.17	0.00	99.48	168.0-169.0	0.05	583.87	0.01	99.95
122.0-123.0	0.00	581.17	0.00	99.48	169.0-170.0	0.05	583.92	0.01	99.96
123.0-124.0	0.00	581.17	0.00	99.48	170.0-171.0	0.05	583.97	0.01	99.96
124.0-125.0	0.00	581.17	0.00	99.48	171.0-172.0	0.04	584.01	0.01	99.97
125.0-126.0	0.00	581.17	0.00	99.48	172.0-173.0	0.04	584.05	0.01	99.98
126.0-127.0	0.01	581.18	0.00	99.49	173.0-174.0	0.03	584.08	0.01	99.98
127.0-128.0	0.01	581.19	0.00	99.49	174.0-175.0	0.03	584.11	0.00	99.99
128.0-129.0	0.02	581.20	0.00	99.49	175.0-176.0	0.02	584.13	0.00	99.99
129.0-130.0	0.02	581.22	0.00	99.49	176.0-177.0	0.02	584.15	0.00	100.00
130.0-131.0	0.02	581.25	0.00	99.50	177.0-178.0	0.01	584.17	0.00	100.00
131.0-132.0	0.03	581.28	0.00	99.50	178.0-179.0	0.01	584.17	0.00	100.00
132.0-133.0	0.03	581.31	0.01	99.51	179.0-180.0	0.00	584.18	0.00	100.00
133.0-134.0	0.04	581.35	0.01	99.52					
134.0-135.0	0.04	581.39	0.01	99.52					
135.0-136.0	0.05	581.44	0.01	99.53					
136.0-137.0	0.05	581.49	0.01	99.54					
137.0-138.0	0.05	581.54	0.01	99.55					
138.0-139.0	0.06	581.60	0.01	99.56					
139.0-140.0	0.06	581.66	0.01	99.57					
140.0-141.0	0.07	581.73	0.01	99.58					

Rectangle ISO Lighting Intensity Diagram


Lum. Name:TR08-06-XX-01 4000K RA90 60D	Lum. Catelog:	Test ID:01
Lamp Name:	Lamp Catelog:LED	Test Lab:Quality Department
Manufacture:Shenzhen Norming Lighting Co., Ltd	Test Machine:GON-2000	Test Date:2021/10/28



Plane ISO-Illuminance Diagram

Lum. Name:TR08-06-XX-01 4000K RA90 60D	Lum. Catalog:	Test ID:01
Lamp Name:	Lamp Catalog: LED	Test Lab: Quality Department
Manufacture: Shenzhen Norming Lighting Co., Ltd	Test Machine:GON-2000	Test Date: 2021/10/28

Plane ISO-Illuminance Curve



Working Plane Luminaire Mounting Height(m): 3.00

Working Plane Maximum Illuminance(lx): 66.93

Working Plane Maximum Illuminance Position(d/h):H0.0 V0.0


IES Indoor Report

Photometric Filename:TR08-06-XX-01 4000K RA90 60D.IES

3D Plane ISO Illuminance Diagram

Lum. Name: TR08-06-XX-01 4000K RA90 60D	Lum. Catalog:	Test ID: 01
Lamp Name:	Lamp Catalog: LED	Test Lab: Quality Department
Manufacture: Shenzhen Norming Lighting Co., Ltd	Test Machine:GON-2000	Test Date: 2021/10/28

3D Plane Illuminance Modal




Curves: 3D Model — 90% — 80% — 70% — 60% — 50% — 40% — 30% — 20% — 10% —
View Angles(deg): 0 Height(m): 3.0 Distance(m): 10.0

Space ISO Illuminance Diagram

Lum. Name:TR08-06-XX-01 4000K RA90 60D	Lum. Catelog:	Test ID:01
Lamp Name:	Lamp Catelog:LED	Test Lab:Quality Department
Manufacture:Shenzhen Norming Lighting Co., Ltd	Test Machine:GON-2000	Test Date:2021/10/28


Space ISO Illuminance Curve



Space Plane Maximum Illuminance and @Angle:602.33lx,1.0deg
Plane Maximum Lighting Intensity and @Angle:602.701cd,0deg

Illuminance-Distance Diagram

Lum. Name:TR08-06-XX-01 4000K RA90 60D	Lum. Catalog:	Test ID:01
Lamp Name:	Lamp Catalog:LED	Test Lab:Quality Department
Manufacture:Shenzhen Norming Lighting Co., Ltd	Test Machine:GON-2000	Test Date:2021/10/28



Indoor Luminance Limiting Curves

Lum. Name:TR08-06-XX-01 4000K RA90 60D	Lum. Catalog:	Test ID:01
Lamp Name:	Lamp Catalog:LED	Test Lab:Quality Department
Manufacture:Shenzhen Norming Lighting Co., Ltd	Test Machine:GON-2000	Test Date:2021/10/28


Glare Grade Table

GI	Quality	Using Illuminance							
1.15	A	2000	1000	500	<=300				
1.5	B		2000	1000	500	<=300			
1.85	C			2000	1000	500	<=300		
2.2	D				2000	1000	500	<=300	
2.55	E	a				2000	1000	500	<=300
			b	c	d	e	f	g	h

Luminance Table

Gama(deg)	45	50	55	60	65	70	75	80	85
C0	14362	9782	7308	5899	5063	4437	3799	3141	2893
C90	9555	6751	5141	4230	3572	2890	2215	1156	511

Luminance Limiting Curve



Luminous Size:

Length(m)=-0.076

Width(m)=-0.076

Height(m)=0.000

Area(m^2)=0.004536

Luminous Type:

Without Luminous Side


Luminous Curves:

C0-C180 Color:

C90-C270 Color:

Indoor Budgetary Estimate Table

Lum. Name:TR08-06-XX-01 4000K RA90 60D	Lum. Catalog:	Test ID:01
Lamp Name:	Lamp Catalog: LED	Test Lab: Quality Department
Manufacture: Shenzhen Norming Lighting Co., Ltd	Test Machine:GON-2000	Test Date: 2021/10/28



Indoor Coefficient of Utilization Table

Lum. Name:TR08-06-XX-01 4000K RA90 60D	Lum. Catelog:	Test ID:01
Lamp Name:	Lamp Catelog:LED	Test Lab:Quality Department
Manufacture:Shenzhen Norming Lighting Co., Ltd	Test Machine:GON-2000	Test Date:2021/10/28

Coefficients of Utilization - Zonal Cavity Method																		
Coef.	Effective Floor Cavity Reflectance RFC=0.20																	
RhoCC (%)	80				70				50			30			10			0
RhoW (%)	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR	Coefficient of Utilization(%)																	
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	99
1	113	110	107	105	110	108	105	103	104	102	100	100	98	97	96	95	94	92
2	107	102	98	94	105	100	96	93	97	94	91	94	91	89	91	89	87	85
3	101	95	89	85	99	93	88	84	90	86	83	88	84	82	86	83	80	79
4	96	88	82	78	94	87	82	77	85	80	76	83	79	75	81	77	74	73
5	91	82	76	72	89	81	76	71	79	74	71	78	73	70	76	72	69	68
6	86	77	71	66	85	76	70	66	75	69	66	73	69	65	72	68	65	63
7	82	72	66	62	81	72	66	62	70	65	61	69	64	61	68	64	60	59
8	78	68	62	58	77	67	62	58	66	61	57	65	60	57	64	60	57	55
9	74	64	58	54	73	64	58	54	63	57	54	62	57	54	61	57	53	52
10	71	61	55	51	70	60	55	51	59	54	51	59	54	50	58	53	50	49

Unified Glare Rating Table

Lum. Name:TR08-06-XX-01 4000K RA90 60D	Lum. Catelog:	Test ID:01
Lamp Name:	Lamp Catelog:LED	Test Lab:Quality Department
Manufacture:Shenzhen Norming Lighting Co., Ltd	Test Machine:GON-2000	Test Date:2021/10/28

Unified Glare Rating Table

Ceiling RCC	0.70	0.70	0.50	0.50	0.30	0.70	0.70	0.50	0.50	0.30
Wall RW	0.50	0.30	0.50	0.30	0.30	0.50	0.30	0.50	0.30	0.30
Floor RFC	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20
Room Size	Vewed crosswise					Vewed endwise				
X=2H Y=2H	17.7	18.8	18.1	19.1	19.5	15.3	16.4	15.7	16.8	17.1
	17.9	18.9	18.3	19.2	19.6	15.5	16.5	15.9	16.8	17.2
	18.0	18.9	18.4	19.2	19.6	15.6	16.5	16.0	16.8	17.2
	18.0	18.8	18.4	19.2	19.6	15.5	16.3	15.9	16.7	17.1
	18.0	18.8	18.4	19.2	19.6	15.5	16.3	15.9	16.7	17.1
	17.9	18.7	18.4	19.1	19.5	15.4	16.2	15.9	16.6	17.0
X=4H Y=2H	17.6	18.5	18.1	18.9	19.3	15.3	16.3	15.8	16.6	17.0
	17.9	18.7	18.3	19.1	19.5	15.6	16.4	16.1	16.8	17.2
	18.0	18.7	18.5	19.2	19.6	15.7	16.4	16.2	16.8	17.3
	18.1	18.7	18.6	19.2	19.7	15.7	16.3	16.2	16.8	17.2
	18.1	18.7	18.6	19.1	19.6	15.7	16.2	16.1	16.7	17.2
	18.1	18.6	18.6	19.1	19.6	15.6	16.1	16.1	16.6	17.1
X=8H Y=4H	18.0	18.6	18.5	19.0	19.5	15.7	16.3	16.2	16.7	17.2
	18.1	18.6	18.7	19.1	19.7	15.7	16.2	16.2	16.7	17.2
	18.2	18.6	18.7	19.1	19.6	15.7	16.1	16.2	16.6	17.1
	18.2	18.6	18.7	19.1	19.7	15.6	16.0	16.2	16.5	17.1
X=12H Y=4H	18.0	18.5	18.5	18.9	19.4	15.7	16.2	16.2	16.6	17.1
	18.1	18.5	18.7	19.0	19.6	15.7	16.1	16.2	16.6	17.1
	18.2	18.5	18.7	19.1	19.6	15.7	16.0	16.2	16.5	17.1
Variations with the objerver position at spacings										
S=1.0H	0.5/-0.6					1.0/-1.2				
S=1.5H	1.0/-1.2					1.5/-2.0				
S=2.0H	1.3/-1.6					2.0/-2.6				
Reduced UGR Table:										
Nordic Standard Table:	BK0					BK0				
Correction Value	0.8					0.7				

o the CIE Pub.117,data has been corrected,refers to the lamp's lumens 8.2flm.

Candela Tabulation

V/H	C0.0	C90.0	C180.0	C270.0
γ 0.0	601.62	601.62	601.62	601.62
γ 1.0	602.61	596.67	601.68	599.79
γ 2.0	602.64	596.57	600.83	600.45
γ 3.0	602.00	595.25	600.69	600.53
γ 4.0	602.29	594.42	597.80	601.26
γ 5.0	601.68	592.31	595.71	601.53
γ 6.0	601.64	590.44	592.79	599.82
γ 7.0	600.55	588.52	591.08	597.20
γ 8.0	601.20	586.62	587.71	594.68
γ 9.0	601.91	586.42	586.79	592.12
γ 10.0	602.70	585.81	582.62	589.30
γ 11.0	601.97	585.27	580.21	586.86
γ 12.0	602.54	582.64	575.61	584.77
γ 13.0	600.10	578.61	572.16	582.57
γ 14.0	597.89	569.67	568.08	580.74
γ 15.0	593.41	559.85	565.01	578.70
γ 16.0	586.70	544.32	560.63	576.71
γ 17.0	578.53	527.98	556.11	574.13
γ 18.0	567.01	510.63	548.51	571.47
γ 19.0	554.41	490.81	537.85	569.24
γ 20.0	540.18	469.57	521.93	563.35
γ 21.0	524.48	447.32	503.75	553.92
γ 22.0	504.71	422.19	483.73	542.46
γ 23.0	486.09	396.83	462.75	530.40
γ 24.0	463.12	371.16	440.53	514.86
γ 25.0	440.45	342.32	418.17	497.50
γ 26.0	414.38	311.80	394.37	477.98
γ 27.0	387.92	281.32	367.98	456.15
γ 28.0	358.97	250.94	341.64	431.64
γ 29.0	329.29	221.39	315.23	406.54
γ 30.0	297.56	194.12	289.47	379.82
γ 31.0	265.30	168.74	261.66	353.45
γ 32.0	233.13	146.47	234.18	327.70
γ 33.0	203.52	127.24	207.58	301.65
γ 34.0	177.24	110.90	182.50	274.63
γ 35.0	154.57	97.03	158.63	247.85
γ 36.0	135.10	84.90	137.17	221.12
γ 37.0	118.61	74.43	118.32	194.84
γ 38.0	104.19	65.70	102.34	169.89
γ 39.0	91.85	58.16	88.64	147.07
γ 40.0	81.25	51.73	76.99	127.22
γ 41.0	72.16	46.19	67.23	110.19
γ 42.0	64.24	41.39	58.99	95.50
γ 43.0	57.41	37.31	52.13	83.02
γ 44.0	51.40	33.73	46.08	72.61
γ 45.0	46.07	30.65	40.73	63.72
γ 46.0	41.59	27.90	35.99	56.31

Candela Tabulation - (Cont.)

V/H	C0.0	C90.0	C180.0	C270.0
γ 47.0	37.61	25.49	32.16	49.85
γ 48.0	34.19	23.27	28.92	44.13
γ 49.0	31.16	21.40	26.19	39.17
γ 50.0	28.52	19.69	23.69	35.13
γ 51.0	26.13	18.16	21.54	31.96
γ 52.0	24.10	16.76	19.60	29.09
γ 53.0	22.21	15.50	17.99	26.45
γ 54.0	20.51	14.38	16.53	24.18
γ 55.0	19.02	13.38	15.27	22.13
γ 56.0	17.66	12.46	14.15	20.32
γ 57.0	16.44	11.65	13.18	18.74
γ 58.0	15.31	10.92	12.27	17.33
γ 59.0	14.30	10.23	11.47	16.11
γ 60.0	13.38	9.59	10.73	15.02
γ 61.0	12.53	8.97	10.08	14.03
γ 62.0	11.74	8.41	9.55	13.13
γ 63.0	11.02	7.88	9.02	12.34
γ 64.0	10.34	7.36	8.55	11.61
γ 65.0	9.71	6.85	8.11	10.98
γ 66.0	9.10	6.38	7.68	10.38
γ 67.0	8.52	5.91	7.28	9.85
γ 68.0	7.98	5.42	6.91	9.35
γ 69.0	7.43	4.92	6.55	8.88
γ 70.0	6.88	4.48	6.21	8.41
γ 71.0	6.30	4.08	5.82	8.00
γ 72.0	5.80	3.70	5.44	7.57
γ 73.0	5.33	3.32	5.07	7.15
γ 74.0	4.89	2.96	4.70	6.75
γ 75.0	4.46	2.60	4.32	6.34
γ 76.0	4.05	2.27	3.94	5.90
γ 77.0	3.66	1.93	3.57	5.46
γ 78.0	3.32	1.48	3.25	5.07
γ 79.0	2.95	1.15	2.87	4.64
γ 80.0	2.47	0.91	2.46	4.22
γ 81.0	2.04	0.69	2.12	3.81
γ 82.0	1.79	0.49	1.84	3.41
γ 83.0	1.54	0.37	1.40	3.04
γ 84.0	1.33	0.29	1.02	2.71
γ 85.0	1.14	0.20	0.79	2.34
γ 86.0	1.01	0.13	0.59	1.88
γ 87.0	0.90	0.07	0.44	1.60
γ 88.0	0.80	0.01	0.34	1.38
γ 89.0	0.73	0.00	0.27	1.17
γ 90.0	0.65	0.00	0.21	1.01
γ 91.0	0.59	0.00	0.14	0.91
γ 92.0	0.51	0.00	0.09	0.82
γ 93.0	0.46	0.00	0.05	0.74

Candela Tabulation - (Cont.)

V/H	C0.0	C90.0	C180.0	C270.0
γ 94.0	0.39	0.00	0.00	0.66
γ 95.0	0.33	0.00	0.00	0.60
γ 96.0	0.28	0.00	0.00	0.53
γ 97.0	0.23	0.00	0.00	0.48
γ 98.0	0.18	0.00	0.00	0.41
γ 99.0	0.13	0.00	0.00	0.35
γ 100.0	0.08	0.00	0.00	0.30
γ 101.0	0.05	0.00	0.00	0.26
γ 102.0	0.00	0.00	0.00	0.22
γ 103.0	0.00	0.00	0.00	0.17
γ 104.0	0.00	0.00	0.00	0.12
γ 105.0	0.00	0.00	0.00	0.09
γ 106.0	0.00	0.00	0.00	0.06
γ 107.0	0.00	0.00	0.00	0.04
γ 108.0	0.00	0.00	0.00	0.00
γ 109.0	0.00	0.00	0.00	0.00
γ 110.0	0.00	0.00	0.00	0.00
γ 111.0	0.00	0.00	0.00	0.00
γ 112.0	0.00	0.00	0.00	0.00
γ 113.0	0.00	0.00	0.00	0.00
γ 114.0	0.00	0.00	0.00	0.00
γ 115.0	0.00	0.00	0.00	0.00
γ 116.0	0.00	0.00	0.00	0.00
γ 117.0	0.00	0.00	0.00	0.00
γ 118.0	0.00	0.00	0.00	0.00
γ 119.0	0.00	0.00	0.00	0.00
γ 120.0	0.00	0.00	0.00	0.00
γ 121.0	0.00	0.00	0.00	0.00
γ 122.0	0.00	0.00	0.00	0.00
γ 123.0	0.00	0.00	0.00	0.00
γ 124.0	0.00	0.00	0.00	0.01
γ 125.0	0.03	0.00	0.00	0.04
γ 126.0	0.07	0.02	0.05	0.08
γ 127.0	0.11	0.08	0.10	0.11
γ 128.0	0.17	0.13	0.17	0.16
γ 129.0	0.22	0.19	0.21	0.20
γ 130.0	0.26	0.25	0.28	0.25
γ 131.0	0.31	0.31	0.35	0.31
γ 132.0	0.38	0.39	0.41	0.35
γ 133.0	0.44	0.45	0.47	0.40
γ 134.0	0.50	0.51	0.55	0.47
γ 135.0	0.55	0.59	0.61	0.52
γ 136.0	0.62	0.66	0.69	0.57
γ 137.0	0.69	0.72	0.76	0.65
γ 138.0	0.75	0.79	0.83	0.70
γ 139.0	0.82	0.87	0.90	0.76
γ 140.0	0.88	0.93	0.96	0.82

Candela Tabulation - (Cont.)

V/H	C0.0	C90.0	C180.0	C270.0
γ 141.0	0.96	1.00	1.03	0.89
γ 142.0	1.02	1.07	1.11	0.95
γ 143.0	1.09	1.14	1.17	1.02
γ 144.0	1.15	1.20	1.25	1.08
γ 145.0	1.23	1.27	1.31	1.14
γ 146.0	1.29	1.33	1.38	1.20
γ 147.0	1.35	1.40	1.45	1.28
γ 148.0	1.41	1.47	1.52	1.33
γ 149.0	1.48	1.53	1.58	1.40
γ 150.0	1.53	1.58	1.64	1.46
γ 151.0	1.59	1.63	1.72	1.53
γ 152.0	1.66	1.70	1.77	1.59
γ 153.0	1.71	1.75	1.83	1.64
γ 154.0	1.78	1.79	1.88	1.71
γ 155.0	1.83	1.85	1.93	1.76
γ 156.0	1.89	1.89	1.98	1.81
γ 157.0	1.93	1.95	2.03	1.87
γ 158.0	1.99	2.00	2.08	1.93
γ 159.0	2.04	2.05	2.13	1.98
γ 160.0	2.10	2.10	2.18	2.02
γ 161.0	2.14	2.15	2.22	2.07
γ 162.0	2.20	2.19	2.25	2.11
γ 163.0	2.25	2.26	2.30	2.17
γ 164.0	2.30	2.29	2.35	2.21
γ 165.0	2.35	2.33	2.39	2.24
γ 166.0	2.39	2.38	2.43	2.29
γ 167.0	2.44	2.42	2.47	2.34
γ 168.0	2.49	2.46	2.51	2.38
γ 169.0	2.54	2.51	2.55	2.43
γ 170.0	2.57	2.54	2.59	2.47
γ 171.0	2.61	2.57	2.62	2.51
γ 172.0	2.64	2.60	2.64	2.56
γ 173.0	2.67	2.62	2.68	2.58
γ 174.0	2.70	2.65	2.70	2.62
γ 175.0	2.71	2.67	2.72	2.64
γ 176.0	2.75	2.69	2.73	2.67
γ 177.0	2.76	2.69	2.76	2.70
γ 178.0	2.76	2.69	2.76	2.74
γ 179.0	2.77	2.70	2.78	2.75
γ 180.0	2.76	2.76	2.76	2.76