



## Packaging

Box Dimensions	L156 x W82 x H81mm
Box Net Weight	0.486Kg
Box Gross Weight	0.54Kg
Carton Dimensions	L425 x W325 x H345 mm/40 PCS
Carton Net Weight	19.44Kg
Carton Gross Weight	22.17Kg

## FEATURES

- Modular design, with replaceable LED light source inside.
- There are four color anti-glare reflectors optional.
- Gimbal.
- 5-year guarantee.

## Technical Data

Input Voltage/Hz	AC200-240V 50/60Hz
Output Voltage/Current	DC36V/130mA
Power	6W
Rated Input Current	0.03A
PF value	>0.85
Ingress Protection	IP20
Operating Temperature	-10—40℃
Dimmability	Triac dimmable with <b>DIMMATE</b> driver

## Optical Data

LED Brand	Bridgelux COB LED
CRI	Ra> 80, Ra> 90
Colour temperature	2700K/3000K/4000K
System luminous efficacy up to	112lm/W



Model	CCT		Beam Angle	Lumen	Efficacy		Beam Angle	Lumen	Efficacy
SD01-06-XX-01	2700K	CRI 80+	15°	500lm	86lm/W	CRI 90+	15°	453lm	78lm/W
			24°	513lm	90lm/W		24°	472lm	82lm/W
			36°	523lm	91lm/W		36°	478lm	83lm/W
			60°	483lm	84lm/W		60°	467lm	81lm/W
SD01-06-XX-01	3000K		15°	557lm	95lm/W		15°	481lm	83lm/W
			24°	586lm	101lm/W		24°	501lm	87lm/W
			36°	591lm	102lm/W		36°	515lm	89lm/W
			60°	540lm	93lm/W		60°	467lm	81lm/W
SD01-06-XX-01	4000K		15°	580lm	100lm/W		15°	483lm	83lm/W
			24°	591lm	102lm/W		24°	510lm	89lm/W
			36°	647lm	112lm/W		36°	517lm	90lm/W
			60°	592lm	101lm/W		60°	478lm	83lm/W

## ECLIPSE CONSEIL

Siège : +33 (1) 79 30 48 19- Showroom Paris : +33 (1) 78 95 50 14 - Mob : +33 (6) 87 82 12 04  
Siège social : 7 rue Prudent Neel 92500 Rueil-Malmaison - Showroom : 1 rue Dulong 75017 PARIS