



Indoor Luminaire Photometric Data

Description Information

Luminary Name:SD02-08-XX-01 2700K RA90 60D		Lum. Catalog:	Test ID: 01
Lamp Name:		Lamp Catalog: LED	Test Date: 2021/04/29
Manufacture: Shenzhen Norming Lighting Co.Ltd		Shld.Ang(°):	Test Machine:GON-2000
Test Lab: Quality Department		Frequency (Hz):	Lamp CCT (K): Ra:
Lum. Size (W*L*H):0.050m*0.000m*0.000m		Lum. Area (m2):0.002	Lum. W (kg): 0.000
Test System: C, γ	Test Step: C=90.0 γ=1.0	Temp. (°C): 25	Humidity(%): 50.0


Character Parameter

Lamp Speciality Parameter		Luminaire Speciality Parameter	
Rated Flux(lm): 564.360	Luminary Flux(lm): 564.364	Field Angle(10%Imax): 81.0(°)	
Rated Power(W):	Luminary Efficiency: 100.00%	Down Lumens&Percent: 561.817lm 99.55%	
Rated Voltage(V):	Luminary EER(lm/W): 72.494	Up Lumens&Percent: 2.547lm 0.45%	
Tested Power(W): 7.785	Max. Candela(cd): 562.498	S/MH: C0_a180=1.010 C90_270=1.007	
Lamps' Inside: 1	Max Cand@Ang. (°): C=0.0 γ=2.0	CIE Type: Semi-Direct	
Tested Electrics (V, A, pf):240.1, 0.035, 0.908	Beam Angle(50%Imax): 63.3(°)	ErP ϕ use(90°): 532.252lm	
Lamp Size (W*L*H):0.050m*0.000m*0.000m	Left=-32.0°, Right=31.3°	IRF(%): 216.560	



2D Plane Light Intensity Distribution Curve


Lum. Name: SD02-08-XX-01 2700K RA90 60D	Lum. Catelog:	Test ID: 01
Lamp Name:	Lamp Catelog: LED	Test Lab: Quality Department
Manufacture: Shenzhen Norming Lighting Co.Ltd	Test Machine:GON-2000	Test Date: 2021/04/29



3D Light Intensity Distribution Modal

Lum. Name: SD02-08-XX-01 2700K RA90 60D	Lum. Catelog:	Test ID: 01
Lamp Name:	Lamp Catelog: LED	Test Lab: Quality Department
Manufacture: Shenzhen Norming Lighting Co.Ltd	Test Machine:GON-2000	Test Date: 2021/04/29

3D Light Intensity Distribution Modal



IES Indoor Report

Photometric Filename:SD02-08-XX-01 2700K RA90 60D.IES

Zonal Flux Tabulation


Zone(γ)	Zone Flux (lm)	Sums Flux (lm)	Zone%Lamp	Sums%Lamp	Zone(γ)	Zone Flux (lm)	Sums Flux (lm)	Zone%Lamp	Sums%Lamp
0.0-1.0	0.54	0.54	0.10	0.10	47.0-48.0	1.44	538.01	0.25	95.33
1.0-2.0	1.61	2.14	0.28	0.38	48.0-49.0	1.35	539.35	0.24	95.57
2.0-3.0	2.68	4.82	0.47	0.85	49.0-50.0	1.24	540.59	0.22	95.79
3.0-4.0	3.75	8.58	0.66	1.52	50.0-51.0	1.12	541.71	0.20	95.99
4.0-5.0	4.82	13.39	0.85	2.37	51.0-52.0	1.02	542.73	0.18	96.17
5.0-6.0	5.88	19.28	1.04	3.42	52.0-53.0	0.96	543.70	0.17	96.34
6.0-7.0	6.94	26.22	1.23	4.65	53.0-54.0	0.92	544.62	0.16	96.50
7.0-8.0	7.99	34.21	1.42	6.06	54.0-55.0	0.90	545.52	0.16	96.66
8.0-9.0	9.04	43.24	1.60	7.66	55.0-56.0	0.87	546.39	0.15	96.82
9.0-10.0	10.08	53.32	1.79	9.45	56.0-57.0	0.85	547.24	0.15	96.97
10.0-11.0	11.11	64.43	1.97	11.42	57.0-58.0	0.83	548.07	0.15	97.11
11.0-12.0	12.14	76.57	2.15	13.57	58.0-59.0	0.81	548.88	0.14	97.26
12.0-13.0	13.16	89.72	2.33	15.90	59.0-60.0	0.79	549.67	0.14	97.40
13.0-14.0	14.16	103.88	2.51	18.41	60.0-61.0	0.77	550.44	0.14	97.53
14.0-15.0	15.11	118.99	2.68	21.08	61.0-62.0	0.75	551.19	0.13	97.67
15.0-16.0	15.98	134.98	2.83	23.92	62.0-63.0	0.73	551.92	0.13	97.80
16.0-17.0	16.77	151.75	2.97	26.89	63.0-64.0	0.71	552.63	0.13	97.92
17.0-18.0	17.51	169.26	3.10	29.99	64.0-65.0	0.69	553.32	0.12	98.04
18.0-19.0	18.18	187.44	3.22	33.21	65.0-66.0	0.67	554.00	0.12	98.16
19.0-20.0	18.76	206.20	3.32	36.54	66.0-67.0	0.66	554.65	0.12	98.28
20.0-21.0	19.24	225.44	3.41	39.95	67.0-68.0	0.63	555.29	0.11	98.39
21.0-22.0	19.60	245.04	3.47	43.42	68.0-69.0	0.61	555.90	0.11	98.50
22.0-23.0	19.85	264.89	3.52	46.94	69.0-70.0	0.59	556.49	0.10	98.61
23.0-24.0	19.98	284.87	3.54	50.48	70.0-71.0	0.56	557.05	0.10	98.70
24.0-25.0	19.97	304.84	3.54	54.02	71.0-72.0	0.53	557.57	0.09	98.80
25.0-26.0	19.82	324.66	3.51	57.53	72.0-73.0	0.49	558.06	0.09	98.88
26.0-27.0	19.51	344.17	3.46	60.98	73.0-74.0	0.46	558.52	0.08	98.96
27.0-28.0	19.08	363.25	3.38	64.36	74.0-75.0	0.42	558.94	0.07	99.04
28.0-29.0	18.52	381.76	3.28	67.65	75.0-76.0	0.39	559.33	0.07	99.11
29.0-30.0	17.84	399.60	3.16	70.81	76.0-77.0	0.36	559.69	0.06	99.17
30.0-31.0	17.08	416.68	3.03	73.83	77.0-78.0	0.33	560.01	0.06	99.23
31.0-32.0	16.27	432.95	2.88	76.71	78.0-79.0	0.30	560.31	0.05	99.28
32.0-33.0	15.36	448.31	2.72	79.44	79.0-80.0	0.27	560.57	0.05	99.33
33.0-34.0	14.38	462.69	2.55	81.98	80.0-81.0	0.24	560.81	0.04	99.37
34.0-35.0	13.31	476.00	2.36	84.34	81.0-82.0	0.21	561.02	0.04	99.41
35.0-36.0	12.12	488.12	2.15	86.49	82.0-83.0	0.18	561.20	0.03	99.44
36.0-37.0	10.62	498.74	1.88	88.37	83.0-84.0	0.16	561.36	0.03	99.47
37.0-38.0	8.85	507.59	1.57	89.94	84.0-85.0	0.13	561.49	0.02	99.49
38.0-39.0	7.06	514.65	1.25	91.19	85.0-86.0	0.11	561.59	0.02	99.51
39.0-40.0	5.43	520.08	0.96	92.15	86.0-87.0	0.08	561.68	0.01	99.53
40.0-41.0	4.07	524.15	0.72	92.88	87.0-88.0	0.06	561.74	0.01	99.54
41.0-42.0	3.05	527.20	0.54	93.42	88.0-89.0	0.04	561.79	0.01	99.54
42.0-43.0	2.39	529.58	0.42	93.84	89.0-90.0	0.03	561.82	0.01	99.55
43.0-44.0	2.01	531.59	0.36	94.19	90.0-91.0	0.02	561.84	0.00	99.55
44.0-45.0	1.80	533.39	0.32	94.51	91.0-92.0	0.02	561.86	0.00	99.56
45.0-46.0	1.65	535.04	0.29	94.80	92.0-93.0	0.01	561.87	0.00	99.56
46.0-47.0	1.53	536.57	0.27	95.08	93.0-94.0	0.01	561.88	0.00	99.56

Zonal Flux Tabulation - (Cont.)

Zone(γ)	Zone Flux (lm)	Sums Flux (lm)	Zone%Lamp	Sums%Lamp	Zone(γ)	Zone Flux (lm)	Sums Flux (lm)	Zone%Lamp	Sums%Lamp
94.0-95.0	0.01	561.89	0.00	99.56	141.0-142.0	0.05	562.31	0.01	99.64
95.0-96.0	0.01	561.90	0.00	99.56	142.0-143.0	0.06	562.37	0.01	99.65
96.0-97.0	0.00	561.90	0.00	99.56	143.0-144.0	0.06	562.43	0.01	99.66
97.0-98.0	0.00	561.90	0.00	99.56	144.0-145.0	0.06	562.49	0.01	99.67
98.0-99.0	0.00	561.90	0.00	99.56	145.0-146.0	0.07	562.56	0.01	99.68
99.0-100.0	0.00	561.90	0.00	99.56	146.0-147.0	0.07	562.63	0.01	99.69
100.0-101.0	0.00	561.90	0.00	99.56	147.0-148.0	0.07	562.70	0.01	99.71
101.0-102.0	0.00	561.90	0.00	99.56	148.0-149.0	0.07	562.77	0.01	99.72
102.0-103.0	0.00	561.90	0.00	99.56	149.0-150.0	0.07	562.84	0.01	99.73
103.0-104.0	0.00	561.90	0.00	99.56	150.0-151.0	0.07	562.91	0.01	99.74
104.0-105.0	0.00	561.90	0.00	99.56	151.0-152.0	0.07	562.98	0.01	99.76
105.0-106.0	0.00	561.90	0.00	99.56	152.0-153.0	0.07	563.06	0.01	99.77
106.0-107.0	0.00	561.90	0.00	99.56	153.0-154.0	0.07	563.13	0.01	99.78
107.0-108.0	0.00	561.90	0.00	99.56	154.0-155.0	0.07	563.20	0.01	99.80
108.0-109.0	0.00	561.90	0.00	99.56	155.0-156.0	0.07	563.28	0.01	99.81
109.0-110.0	0.00	561.90	0.00	99.56	156.0-157.0	0.07	563.35	0.01	99.82
110.0-111.0	0.00	561.90	0.00	99.56	157.0-158.0	0.07	563.42	0.01	99.83
111.0-112.0	0.00	561.90	0.00	99.56	158.0-159.0	0.07	563.49	0.01	99.85
112.0-113.0	0.00	561.90	0.00	99.56	159.0-160.0	0.07	563.56	0.01	99.86
113.0-114.0	0.00	561.90	0.00	99.56	160.0-161.0	0.07	563.62	0.01	99.87
114.0-115.0	0.00	561.90	0.00	99.56	161.0-162.0	0.07	563.69	0.01	99.88
115.0-116.0	0.00	561.90	0.00	99.56	162.0-163.0	0.06	563.75	0.01	99.89
116.0-117.0	0.00	561.90	0.00	99.56	163.0-164.0	0.06	563.82	0.01	99.90
117.0-118.0	0.00	561.90	0.00	99.56	164.0-165.0	0.06	563.88	0.01	99.91
118.0-119.0	0.00	561.90	0.00	99.56	165.0-166.0	0.06	563.93	0.01	99.92
119.0-120.0	0.00	561.90	0.00	99.56	166.0-167.0	0.05	563.99	0.01	99.93
120.0-121.0	0.00	561.90	0.00	99.56	167.0-168.0	0.05	564.04	0.01	99.94
121.0-122.0	0.00	561.90	0.00	99.56	168.0-169.0	0.05	564.09	0.01	99.95
122.0-123.0	0.00	561.90	0.00	99.56	169.0-170.0	0.05	564.13	0.01	99.96
123.0-124.0	0.00	561.90	0.00	99.56	170.0-171.0	0.04	564.18	0.01	99.97
124.0-125.0	0.00	561.90	0.00	99.56	171.0-172.0	0.04	564.21	0.01	99.97
125.0-126.0	0.00	561.90	0.00	99.56	172.0-173.0	0.03	564.25	0.01	99.98
126.0-127.0	0.00	561.90	0.00	99.56	173.0-174.0	0.03	564.28	0.01	99.99
127.0-128.0	0.00	561.90	0.00	99.56	174.0-175.0	0.03	564.30	0.00	99.99
128.0-129.0	0.00	561.91	0.00	99.57	175.0-176.0	0.02	564.33	0.00	99.99
129.0-130.0	0.01	561.91	0.00	99.57	176.0-177.0	0.02	564.34	0.00	100.00
130.0-131.0	0.01	561.92	0.00	99.57	177.0-178.0	0.01	564.35	0.00	100.00
131.0-132.0	0.01	561.94	0.00	99.57	178.0-179.0	0.01	564.36	0.00	100.00
132.0-133.0	0.02	561.96	0.00	99.57	179.0-180.0	0.00	564.36	0.00	100.00
133.0-134.0	0.02	561.98	0.00	99.58					
134.0-135.0	0.03	562.01	0.00	99.58					
135.0-136.0	0.03	562.04	0.01	99.59					
136.0-137.0	0.04	562.07	0.01	99.59					
137.0-138.0	0.04	562.11	0.01	99.60					
138.0-139.0	0.04	562.16	0.01	99.61					
139.0-140.0	0.05	562.20	0.01	99.62					
140.0-141.0	0.05	562.26	0.01	99.63					

Rectangle ISO Lighting Intensity Diagram


Lum. Name: SD02-08-XX-01 2700K RA90 60D	Lum. Catalog:	Test ID: 01
Lamp Name:	Lamp Catalog: LED	Test Lab: Quality Department
Manufacture: Shenzhen Norming Lighting Co.Ltd	Test Machine:GON-2000	Test Date: 2021/04/29



Plane ISO-Illuminance Diagram

Lum. Name: SD02-08-XX-01 2700K RA90 60D	Lum. Catalog:	Test ID: 01
Lamp Name:	Lamp Catalog: LED	Test Lab: Quality Department
Manufacture: Shenzhen Norming Lighting Co.Ltd	Test Machine:GON-2000	Test Date: 2021/04/29

Plane ISO-Illuminance Curve




Working Plane Luminaire Mounting Height(m): 3.00
Working Plane Maximum Illuminance(lx): 62.41
Working Plane Maximum Illuminance Position(d/h):H0.0 V0.0

3D Plane ISO Illuminance Diagram

Lum. Name: SD02-08-XX-01 2700K RA90 60D	Lum. Catelog:	Test ID: 01
Lamp Name:	Lamp Catelog: LED	Test Lab: Quality Department
Manufacture: Shenzhen Norming Lighting Co.Ltd	Test Machine:GON-2000	Test Date: 2021/04/29


3D Plane Illuminance Modal



Space ISO Illuminance Diagram

Lum. Name: SD02-08-XX-01 2700K RA90 60D	Lum. Catelog:	Test ID: 01
Lamp Name:	Lamp Catelog: LED	Test Lab: Quality Department
Manufacture: Shenzhen Norming Lighting Co.Ltd	Test Machine:GON-2000	Test Date: 2021/04/29


Space ISO Illuminance Curve



Space Plane Maximum Illuminance and @Angle:561.66lx,1.0deg
Plane Maximum Lighting Intensity and @Angle:562.498cd,0deg

Illuminance-Distance Diagram

Lum. Name: SD02-08-XX-01 2700K RA90 60D	Lum. Catelog:	Test ID: 01
Lamp Name:	Lamp Catelog: LED	Test Lab: Quality Department
Manufacture: Shenzhen Norming Lighting Co.Ltd	Test Machine:GON-2000	Test Date: 2021/04/29



Indoor Luminance Limiting Curves

Lum. Name: SD02-08-XX-01 2700K RA90 60D	Lum. Catalog:	Test ID: 01
Lamp Name:	Lamp Catalog: LED	Test Lab: Quality Department
Manufacture: Shenzhen Norming Lighting Co.Ltd	Test Machine:GON-2000	Test Date: 2021/04/29


Glare Grade Table

GI	Quality	Using Illuminance							
1.15	A	2000	1000	500	<=300				
1.5	B		2000	1000	500	<=300			
1.85	C			2000	1000	500	<=300		
2.2	D				2000	1000	500	<=300	
2.55	E	a				2000	1000	500	<=300
			b	c	d	e	f	g	h

Luminance Table

Gama(deg)	45	50	55	60	65	70	75	80	85
C0	16841	11978	10047	9415	9036	8742	7863	7241	7228
C90	14900	10427	8680	8089	7666	7221	6100	4942	3191

Luminance Limiting Curve



Luminous Size:

Length(m)=0.000

Width(m)=-0.050

Height(m)=0.000

Area(m^2)=0.001963

Luminous Type:

Without Luminous Side


Luminous Curves:

C0-C180 Color: —

C90-C270 Color: —

Indoor Budgetary Estimate Table

Lum. Name: SD02-08-XX-01 2700K RA90 60D	Lum. Catalog:	Test ID: 01
Lamp Name:	Lamp Catalog: LED	Test Lab: Quality Department
Manufacture: Shenzhen Norming Lighting Co.Ltd	Test Machine:GON-2000	Test Date: 2021/04/29



Indoor Coefficient of Utilization Table

Lum. Name: SD02-08-XX-01 2700K RA90 60D	Lum. Catelog:	Test ID: 01
Lamp Name:	Lamp Catelog: LED	Test Lab: Quality Department
Manufacture: Shenzhen Norming Lighting Co.Ltd	Test Machine:GON-2000	Test Date: 2021/04/29

Coefficients of Utilization - Zonal Cavity Method																		
Coef.	Effective Floor Cavity Reflectance RFC=0.20																	
RhoCC (%)	80				70				50			30			10			0
RhoW (%)	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR	Coefficient of Utilization(%)																	
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	113	110	108	105	111	108	106	104	104	102	100	100	99	97	97	95	94	93
2	107	102	98	95	105	100	97	93	97	94	91	94	92	89	91	89	87	86
3	102	95	90	86	100	94	89	85	91	87	84	89	85	82	86	83	81	79
4	97	89	83	79	95	88	82	78	85	81	77	83	79	76	81	78	75	74
5	92	83	77	73	90	82	76	72	80	75	72	78	74	71	77	73	70	69
6	87	78	72	67	85	77	71	67	75	70	67	74	70	66	73	69	66	64
7	83	73	67	63	81	72	67	63	71	66	62	70	65	62	69	65	61	60
8	78	69	63	59	77	68	62	58	67	62	58	66	61	58	65	61	58	56
9	75	65	59	55	74	64	59	55	63	58	55	62	58	54	62	57	54	53
10	71	61	55	52	70	61	55	51	60	55	51	59	54	51	58	54	51	50

Unified Glare Rating Table

Lum. Name: SD02-08-XX-01 2700K RA90 60D	Lum. Catelog:	Test ID: 01
Lamp Name:	Lamp Catalog: LED	Test Lab: Quality Department
Manufacture: Shenzhen Norming Lighting Co.Ltd	Test Machine:GON-2000	Test Date: 2021/04/29

Unified Glare Rating Table

Ceiling RCC	0.70	0.70	0.50	0.50	0.30	0.70	0.70	0.50	0.50	0.30
Wall RW	0.50	0.30	0.50	0.30	0.30	0.50	0.30	0.50	0.30	0.30
Floor RFC	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20
Room Size	Vewed crosswise					Vewed endwise				
X=2H Y=2H	20.4	21.4	20.8	21.7	22.0	20.1	21.1	20.5	21.4	21.8
	20.5	21.3	20.9	21.7	22.1	20.2	21.0	20.5	21.4	21.7
	20.5	21.3	20.9	21.7	22.1	20.2	21.0	20.6	21.3	21.7
	20.5	21.3	21.0	21.7	22.1	20.1	20.9	20.6	21.3	21.7
	20.5	21.2	21.0	21.6	22.1	20.1	20.8	20.5	21.2	21.6
	20.5	21.2	21.0	21.6	22.0	20.1	20.7	20.5	21.1	21.6
X=4H Y=2H	20.2	21.0	20.6	21.4	21.8	19.9	20.7	20.4	21.1	21.5
	20.4	21.1	20.8	21.5	21.9	20.1	20.7	20.5	21.1	21.5
	20.5	21.1	21.0	21.5	22.0	20.1	20.7	20.5	21.1	21.6
	20.6	21.1	21.1	21.6	22.1	20.1	20.6	20.6	21.1	21.6
	20.6	21.1	21.1	21.6	22.0	20.1	20.6	20.6	21.0	21.5
	20.6	21.0	21.1	21.5	22.0	20.1	20.5	20.6	21.0	21.5
X=8H Y=4H	20.4	20.9	20.9	21.4	21.9	20.0	20.5	20.5	21.0	21.4
	20.6	21.0	21.1	21.5	22.0	20.1	20.5	20.6	21.0	21.5
	20.7	21.0	21.2	21.5	22.0	20.1	20.4	20.6	20.9	21.5
	20.7	21.0	21.3	21.5	22.1	20.1	20.4	20.6	20.9	21.5
X=12H Y=4H	20.4	20.8	20.9	21.3	21.8	20.0	20.4	20.5	20.9	21.4
	20.6	20.9	21.1	21.4	21.9	20.1	20.4	20.6	20.9	21.4
	20.7	21.0	21.2	21.5	22.1	20.1	20.4	20.6	20.9	21.5
Variations with the objverver position at spacings										
S=1.0H	0.4/-0.4					0.6/-0.7				
S=1.5H	0.8/-0.9					1.1/-1.2				
S=2.0H	1.0/-1.2					1.3/-1.7				
Reduced UGR Table:										
Nordic Standard Table:	BK0					BK0				
Correction Value	0.8					0.5				

o the CIE Pub.117, data has been corrected, refers to the lamp's lumens 8.2flm.

IES Indoor Report

Photometric Filename:SD02-08-XX-01 2700K RA90 60D.IES

Candela Tabulation

V/H	C0.0	C90.0	C180.0	C270.0
γ 0.0	560.60	560.60	560.60	560.60
γ 1.0	561.92	558.77	561.68	559.03
γ 2.0	562.50	558.66	561.76	558.03
γ 3.0	562.03	558.65	561.83	558.59
γ 4.0	562.31	558.84	561.60	558.66
γ 5.0	562.22	558.50	560.14	558.57
γ 6.0	561.48	557.95	560.76	557.75
γ 7.0	560.80	556.79	559.46	557.41
γ 8.0	560.31	556.35	558.56	556.09
γ 9.0	559.46	555.44	557.77	555.48
γ 10.0	559.03	554.74	557.02	554.69
γ 11.0	558.45	553.93	555.99	554.02
γ 12.0	557.55	553.56	554.83	553.04
γ 13.0	558.04	552.85	553.09	551.81
γ 14.0	555.66	550.60	552.04	550.49
γ 15.0	551.86	547.07	548.17	546.84
γ 16.0	545.57	540.29	542.19	541.17
γ 17.0	538.03	531.97	534.83	534.53
γ 18.0	529.54	524.07	527.75	526.91
γ 19.0	519.94	514.28	518.92	518.09
γ 20.0	508.44	503.41	508.93	508.68
γ 21.0	495.14	489.13	497.35	497.00
γ 22.0	480.88	474.38	483.76	483.75
γ 23.0	463.82	457.85	469.69	469.94
γ 24.0	445.22	439.07	454.11	455.37
γ 25.0	425.45	418.78	437.37	438.03
γ 26.0	403.71	396.84	417.89	419.74
γ 27.0	381.26	374.37	397.24	399.25
γ 28.0	358.16	351.58	375.02	376.91
γ 29.0	335.15	328.58	351.61	353.85
γ 30.0	311.76	304.63	326.95	330.01
γ 31.0	288.67	282.20	304.12	306.82
γ 32.0	266.19	259.45	280.47	283.33
γ 33.0	243.43	236.46	256.57	260.09
γ 34.0	219.77	212.53	233.81	237.36
γ 35.0	197.90	190.64	209.54	213.37
γ 36.0	169.64	162.48	187.55	191.76
γ 37.0	137.51	130.96	159.15	163.20
γ 38.0	107.60	101.53	128.26	132.37
γ 39.0	81.01	75.68	98.35	102.41
γ 40.0	59.62	54.87	73.70	77.28
γ 41.0	43.77	39.71	52.55	55.93
γ 42.0	34.02	30.48	37.85	40.96
γ 43.0	28.85	25.66	28.46	31.32
γ 44.0	25.75	22.82	23.68	26.36
γ 45.0	23.38	20.69	20.87	23.31
γ 46.0	21.49	18.98	18.78	21.03

Candela Tabulation - (Cont.)

V/H	C0.0	C90.0	C180.0	C270.0
γ 47.0	19.92	17.58	17.15	19.26
γ 48.0	18.50	16.31	15.72	17.76
γ 49.0	16.96	14.87	14.51	16.39
γ 50.0	15.12	13.16	13.07	14.86
γ 51.0	13.77	11.91	11.20	12.88
γ 52.0	12.93	11.19	9.92	11.53
γ 53.0	12.27	10.59	9.23	10.77
γ 54.0	11.78	10.19	8.74	10.21
γ 55.0	11.31	9.77	8.44	9.84
γ 56.0	10.89	9.38	8.16	9.51
γ 57.0	10.45	9.01	7.92	9.20
γ 58.0	10.03	8.64	7.67	8.92
γ 59.0	9.61	8.27	7.43	8.63
γ 60.0	9.24	7.94	7.21	8.37
γ 61.0	8.87	7.61	7.03	8.14
γ 62.0	8.52	7.29	6.86	7.94
γ 63.0	8.17	6.98	6.68	7.74
γ 64.0	7.83	6.66	6.51	7.54
γ 65.0	7.50	6.36	6.35	7.34
γ 66.0	7.17	6.06	6.18	7.14
γ 67.0	6.86	5.77	6.00	6.94
γ 68.0	6.53	5.48	5.80	6.72
γ 69.0	6.21	5.17	5.58	6.49
γ 70.0	5.87	4.85	5.34	6.22
γ 71.0	5.47	4.48	5.07	5.93
γ 72.0	5.08	4.11	4.71	5.56
γ 73.0	4.70	3.76	4.36	5.20
γ 74.0	4.34	3.43	4.03	4.86
γ 75.0	4.00	3.10	3.69	4.50
γ 76.0	3.67	2.80	3.39	4.16
γ 77.0	3.35	2.50	3.08	3.84
γ 78.0	3.05	2.21	2.79	3.51
γ 79.0	2.76	1.95	2.48	3.22
γ 80.0	2.47	1.68	2.20	2.93
γ 81.0	2.20	1.43	1.94	2.64
γ 82.0	1.96	1.20	1.68	2.37
γ 83.0	1.71	0.97	1.43	2.10
γ 84.0	1.46	0.76	1.20	1.85
γ 85.0	1.24	0.55	0.97	1.60
γ 86.0	1.03	0.35	0.75	1.37
γ 87.0	0.82	0.17	0.54	1.15
γ 88.0	0.62	0.00	0.35	0.94
γ 89.0	0.43	0.00	0.15	0.73
γ 90.0	0.36	0.00	0.00	0.53
γ 91.0	0.29	0.00	0.00	0.44
γ 92.0	0.23	0.00	0.00	0.37
γ 93.0	0.17	0.00	0.00	0.30

Candela Tabulation - (Cont.)

V/H	C0.0	C90.0	C180.0	C270.0
γ 94.0	0.12	0.00	0.00	0.25
γ 95.0	0.06	0.00	0.00	0.18
γ 96.0	0.00	0.00	0.00	0.13
γ 97.0	0.00	0.00	0.00	0.08
γ 98.0	0.00	0.00	0.00	0.03
γ 99.0	0.00	0.00	0.00	0.00
γ 100.0	0.00	0.00	0.00	0.00
γ 101.0	0.00	0.00	0.00	0.00
γ 102.0	0.00	0.00	0.00	0.00
γ 103.0	0.00	0.00	0.00	0.00
γ 104.0	0.00	0.00	0.00	0.00
γ 105.0	0.00	0.00	0.00	0.00
γ 106.0	0.00	0.00	0.00	0.00
γ 107.0	0.00	0.00	0.00	0.00
γ 108.0	0.00	0.00	0.00	0.00
γ 109.0	0.00	0.00	0.00	0.00
γ 110.0	0.00	0.00	0.00	0.00
γ 111.0	0.00	0.00	0.00	0.00
γ 112.0	0.00	0.00	0.00	0.00
γ 113.0	0.00	0.00	0.00	0.00
γ 114.0	0.00	0.00	0.00	0.00
γ 115.0	0.00	0.00	0.00	0.00
γ 116.0	0.00	0.00	0.00	0.00
γ 117.0	0.00	0.00	0.00	0.00
γ 118.0	0.00	0.00	0.00	0.00
γ 119.0	0.00	0.00	0.00	0.00
γ 120.0	0.00	0.00	0.00	0.00
γ 121.0	0.00	0.00	0.00	0.00
γ 122.0	0.00	0.00	0.00	0.00
γ 123.0	0.00	0.00	0.00	0.00
γ 124.0	0.00	0.00	0.00	0.00
γ 125.0	0.00	0.00	0.00	0.00
γ 126.0	0.00	0.00	0.00	0.02
γ 127.0	0.00	0.00	0.00	0.06
γ 128.0	0.02	0.00	0.00	0.10
γ 129.0	0.07	0.00	0.00	0.16
γ 130.0	0.13	0.00	0.06	0.21
γ 131.0	0.18	0.00	0.11	0.25
γ 132.0	0.23	0.04	0.18	0.32
γ 133.0	0.29	0.10	0.25	0.37
γ 134.0	0.35	0.17	0.30	0.43
γ 135.0	0.41	0.23	0.36	0.50
γ 136.0	0.47	0.30	0.43	0.55
γ 137.0	0.53	0.35	0.50	0.62
γ 138.0	0.61	0.43	0.57	0.68
γ 139.0	0.67	0.50	0.64	0.74
γ 140.0	0.74	0.56	0.70	0.81

Candela Tabulation - (Cont.)

V/H	C0.0	C90.0	C180.0	C270.0
γ 141.0	0.79	0.64	0.78	0.87
γ 142.0	0.87	0.70	0.85	0.93
γ 143.0	0.93	0.77	0.92	1.00
γ 144.0	0.99	0.84	0.98	1.06
γ 145.0	1.05	0.91	1.05	1.12
γ 146.0	1.11	0.97	1.12	1.18
γ 147.0	1.16	1.03	1.18	1.25
γ 148.0	1.22	1.08	1.24	1.30
γ 149.0	1.28	1.15	1.29	1.36
γ 150.0	1.33	1.20	1.34	1.41
γ 151.0	1.37	1.24	1.40	1.45
γ 152.0	1.42	1.30	1.45	1.50
γ 153.0	1.46	1.35	1.50	1.56
γ 154.0	1.52	1.40	1.55	1.59
γ 155.0	1.57	1.45	1.60	1.64
γ 156.0	1.62	1.50	1.66	1.69
γ 157.0	1.67	1.55	1.71	1.74
γ 158.0	1.71	1.60	1.76	1.79
γ 159.0	1.77	1.66	1.81	1.84
γ 160.0	1.83	1.71	1.86	1.88
γ 161.0	1.88	1.76	1.91	1.93
γ 162.0	1.92	1.82	1.95	1.99
γ 163.0	1.98	1.87	2.01	2.02
γ 164.0	2.02	1.92	2.06	2.06
γ 165.0	2.08	1.97	2.10	2.11
γ 166.0	2.12	2.02	2.14	2.16
γ 167.0	2.17	2.06	2.19	2.19
γ 168.0	2.22	2.12	2.23	2.25
γ 169.0	2.26	2.16	2.29	2.29
γ 170.0	2.31	2.20	2.33	2.32
γ 171.0	2.34	2.25	2.36	2.36
γ 172.0	2.38	2.28	2.40	2.40
γ 173.0	2.41	2.33	2.43	2.43
γ 174.0	2.45	2.36	2.47	2.46
γ 175.0	2.49	2.39	2.50	2.48
γ 176.0	2.51	2.42	2.53	2.49
γ 177.0	2.54	2.44	2.55	2.51
γ 178.0	2.55	2.46	2.56	2.54
γ 179.0	2.56	2.47	2.57	2.54
γ 180.0	2.56	2.56	2.56	2.56