



Indoor Luminaire Photometric Data

Description Information

Luminary Name:SD02-09-XX-01 3000K RA90 60D		Lum. Catalog:	Test ID: 01
Lamp Name:		Lamp Catalog: LED	Test Date: 2021/03/23
Manufacture: Shenzhen Norming Lighting Co.Ltd		Shld.Ang(°):	Test Machine:GON-2000
Test Lab: Quality Department		Frequency (Hz):	Lamp CCT (K): Ra:
Lum. Size (W*L*H):0.050m*0.000m*0.000m		Lum. Area (m2):0.002	Lum. W (kg): 0.000
Test System: C, γ	Test Step: C=90.0 γ=1.0	Temp. (°C): 25	Humidity(%): 50.0


Character Parameter

Lamp Speciality Parameter		Luminaire Speciality Parameter	
Rated Flux(lm): 687.080	Luminary Flux(lm): 687.076	Field Angle(10%Imax): 80.6(°)	
Rated Power(W):	Luminary Efficiency: 100.00%	Down Lumens&Percent: 684.670lm 99.65%	
Rated Voltage(V):	Luminary EER(lm/W): 75.148	Up Lumens&Percent: 2.406lm 0.35%	
Tested Power(W): 9.143	Max. Candela(cd): 698.818	S/MH: C0_a180=0.999 C90_270=0.998	
Lamps' Inside: 1	Max Cand@Ang. (°): C=0.0 γ=4.0	CIE Type: Semi-Direct	
Tested Electrics (V, A, pf):240.1, 0.041, 0.928	Beam Angle(50%Imax): 62.6(°)	ErP ϕ use(90°): 650.092lm	
Lamp Size (W*L*H):0.050m*0.000m*0.000m	Left=-31.6°, Right=31.6°	IRF(%): 220.272	



2D Plane Light Intensity Distribution Curve


Lum. Name: SD02-09-XX-01 3000K RA90 60D	Lum. Catalog:	Test ID: 01
Lamp Name:	Lamp Catalog: LED	Test Lab: Quality Department
Manufacture: Shenzhen Norming Lighting Co.Ltd	Test Machine:GON-2000	Test Date: 2021/03/23



3D Light Intensity Distribution Modal

Lum. Name: SD02-09-XX-01 3000K RA90 60D	Lum. Catelog:	Test ID: 01
Lamp Name:	Lamp Catelog: LED	Test Lab: Quality Department
Manufacture: Shenzhen Norming Lighting Co.Ltd	Test Machine:GON-2000	Test Date: 2021/03/23

3D Light Intensity Distribution Modal



Zonal Flux Tabulation

Zone(γ)	Zone Flux (lm)	Sums Flux (lm)	Zone%Lamp	Sums%Lamp	Zone(γ)	Zone Flux (lm)	Sums Flux (lm)	Zone%Lamp	Sums%Lamp
0.0-1.0	0.67	0.67	0.10	0.10	47.0-48.0	1.69	657.33	0.25	95.67
1.0-2.0	2.00	2.66	0.29	0.39	48.0-49.0	1.58	658.91	0.23	95.90
2.0-3.0	3.33	5.99	0.48	0.87	49.0-50.0	1.46	660.37	0.21	96.11
3.0-4.0	4.65	10.64	0.68	1.55	50.0-51.0	1.31	661.68	0.19	96.30
4.0-5.0	5.98	16.62	0.87	2.42	51.0-52.0	1.20	662.89	0.17	96.48
5.0-6.0	7.30	23.92	1.06	3.48	52.0-53.0	1.13	664.02	0.16	96.64
6.0-7.0	8.61	32.52	1.25	4.73	53.0-54.0	1.08	665.10	0.16	96.80
7.0-8.0	9.91	42.44	1.44	6.18	54.0-55.0	1.05	666.15	0.15	96.95
8.0-9.0	11.21	53.64	1.63	7.81	55.0-56.0	1.02	667.17	0.15	97.10
9.0-10.0	12.50	66.14	1.82	9.63	56.0-57.0	0.99	668.16	0.14	97.25
10.0-11.0	13.78	79.92	2.01	11.63	57.0-58.0	0.97	669.13	0.14	97.39
11.0-12.0	15.04	94.96	2.19	13.82	58.0-59.0	0.94	670.07	0.14	97.52
12.0-13.0	16.29	111.26	2.37	16.19	59.0-60.0	0.92	670.99	0.13	97.66
13.0-14.0	17.51	128.77	2.55	18.74	60.0-61.0	0.89	671.88	0.13	97.79
14.0-15.0	18.68	147.45	2.72	21.46	61.0-62.0	0.87	672.75	0.13	97.91
15.0-16.0	19.76	167.21	2.88	24.34	62.0-63.0	0.85	673.60	0.12	98.04
16.0-17.0	20.76	187.97	3.02	27.36	63.0-64.0	0.83	674.43	0.12	98.16
17.0-18.0	21.67	209.64	3.15	30.51	64.0-65.0	0.80	675.23	0.12	98.28
18.0-19.0	22.46	232.10	3.27	33.78	65.0-66.0	0.78	676.01	0.11	98.39
19.0-20.0	23.15	255.25	3.37	37.15	66.0-67.0	0.76	676.77	0.11	98.50
20.0-21.0	23.69	278.94	3.45	40.60	67.0-68.0	0.73	677.50	0.11	98.61
21.0-22.0	24.09	303.03	3.51	44.10	68.0-69.0	0.70	678.20	0.10	98.71
22.0-23.0	24.37	327.40	3.55	47.65	69.0-70.0	0.67	678.88	0.10	98.81
23.0-24.0	24.50	351.90	3.57	51.22	70.0-71.0	0.64	679.52	0.09	98.90
24.0-25.0	24.45	376.34	3.56	54.77	71.0-72.0	0.60	680.12	0.09	98.99
25.0-26.0	24.21	400.56	3.52	58.30	72.0-73.0	0.56	680.67	0.08	99.07
26.0-27.0	23.81	424.36	3.46	61.76	73.0-74.0	0.52	681.19	0.08	99.14
27.0-28.0	23.22	447.58	3.38	65.14	74.0-75.0	0.48	681.67	0.07	99.21
28.0-29.0	22.49	470.07	3.27	68.42	75.0-76.0	0.44	682.10	0.06	99.28
29.0-30.0	21.62	491.69	3.15	71.56	76.0-77.0	0.40	682.50	0.06	99.33
30.0-31.0	20.67	512.36	3.01	74.57	77.0-78.0	0.36	682.86	0.05	99.39
31.0-32.0	19.65	532.01	2.86	77.43	78.0-79.0	0.32	683.18	0.05	99.43
32.0-33.0	18.54	550.55	2.70	80.13	79.0-80.0	0.29	683.47	0.04	99.47
33.0-34.0	17.32	567.87	2.52	82.65	80.0-81.0	0.25	683.72	0.04	99.51
34.0-35.0	16.01	583.89	2.33	84.98	81.0-82.0	0.22	683.94	0.03	99.54
35.0-36.0	14.57	598.46	2.12	87.10	82.0-83.0	0.19	684.13	0.03	99.57
36.0-37.0	12.73	611.19	1.85	88.95	83.0-84.0	0.16	684.29	0.02	99.59
37.0-38.0	10.55	621.74	1.54	90.49	84.0-85.0	0.13	684.41	0.02	99.61
38.0-39.0	8.35	630.09	1.22	91.71	85.0-86.0	0.10	684.51	0.01	99.63
39.0-40.0	6.37	636.46	0.93	92.63	86.0-87.0	0.07	684.58	0.01	99.64
40.0-41.0	4.73	641.19	0.69	93.32	87.0-88.0	0.05	684.63	0.01	99.64
41.0-42.0	3.52	644.71	0.51	93.83	88.0-89.0	0.03	684.66	0.00	99.65
42.0-43.0	2.76	647.47	0.40	94.24	89.0-90.0	0.01	684.67	0.00	99.65
43.0-44.0	2.34	649.81	0.34	94.58	90.0-91.0	0.01	684.68	0.00	99.65
44.0-45.0	2.10	651.91	0.31	94.88	91.0-92.0	0.00	684.68	0.00	99.65
45.0-46.0	1.93	653.84	0.28	95.16	92.0-93.0	0.00	684.68	0.00	99.65
46.0-47.0	1.80	655.64	0.26	95.42	93.0-94.0	0.00	684.68	0.00	99.65

IES Indoor Report


Photometric Filename:SD02-09-XX-01 3000K RA90 60D.IES

Zonal Flux Tabulation - (Cont.)

Zone(γ)	Zone Flux (lm)	Sums Flux (lm)	Zone%Lamp	Sums%Lamp	Zone(γ)	Zone Flux (lm)	Sums Flux (lm)	Zone%Lamp	Sums%Lamp
94.0-95.0	0.00	684.68	0.00	99.65	141.0-142.0	0.05	684.93	0.01	99.69
95.0-96.0	0.00	684.68	0.00	99.65	142.0-143.0	0.05	684.99	0.01	99.70
96.0-97.0	0.00	684.68	0.00	99.65	143.0-144.0	0.06	685.04	0.01	99.70
97.0-98.0	0.00	684.68	0.00	99.65	144.0-145.0	0.06	685.10	0.01	99.71
98.0-99.0	0.00	684.68	0.00	99.65	145.0-146.0	0.06	685.17	0.01	99.72
99.0-100.0	0.00	684.68	0.00	99.65	146.0-147.0	0.07	685.23	0.01	99.73
100.0-101.0	0.00	684.68	0.00	99.65	147.0-148.0	0.07	685.30	0.01	99.74
101.0-102.0	0.00	684.68	0.00	99.65	148.0-149.0	0.07	685.37	0.01	99.75
102.0-103.0	0.00	684.68	0.00	99.65	149.0-150.0	0.07	685.44	0.01	99.76
103.0-104.0	0.00	684.68	0.00	99.65	150.0-151.0	0.07	685.52	0.01	99.77
104.0-105.0	0.00	684.68	0.00	99.65	151.0-152.0	0.07	685.59	0.01	99.78
105.0-106.0	0.00	684.68	0.00	99.65	152.0-153.0	0.08	685.67	0.01	99.79
106.0-107.0	0.00	684.68	0.00	99.65	153.0-154.0	0.08	685.74	0.01	99.81
107.0-108.0	0.00	684.68	0.00	99.65	154.0-155.0	0.08	685.82	0.01	99.82
108.0-109.0	0.00	684.68	0.00	99.65	155.0-156.0	0.08	685.89	0.01	99.83
109.0-110.0	0.00	684.68	0.00	99.65	156.0-157.0	0.08	685.97	0.01	99.84
110.0-111.0	0.00	684.68	0.00	99.65	157.0-158.0	0.08	686.05	0.01	99.85
111.0-112.0	0.00	684.68	0.00	99.65	158.0-159.0	0.07	686.12	0.01	99.86
112.0-113.0	0.00	684.68	0.00	99.65	159.0-160.0	0.07	686.19	0.01	99.87
113.0-114.0	0.00	684.68	0.00	99.65	160.0-161.0	0.07	686.27	0.01	99.88
114.0-115.0	0.00	684.68	0.00	99.65	161.0-162.0	0.07	686.34	0.01	99.89
115.0-116.0	0.00	684.68	0.00	99.65	162.0-163.0	0.07	686.41	0.01	99.90
116.0-117.0	0.00	684.68	0.00	99.65	163.0-164.0	0.07	686.47	0.01	99.91
117.0-118.0	0.00	684.68	0.00	99.65	164.0-165.0	0.07	686.54	0.01	99.92
118.0-119.0	0.00	684.68	0.00	99.65	165.0-166.0	0.06	686.60	0.01	99.93
119.0-120.0	0.00	684.68	0.00	99.65	166.0-167.0	0.06	686.66	0.01	99.94
120.0-121.0	0.00	684.68	0.00	99.65	167.0-168.0	0.06	686.72	0.01	99.95
121.0-122.0	0.00	684.68	0.00	99.65	168.0-169.0	0.05	686.77	0.01	99.96
122.0-123.0	0.00	684.68	0.00	99.65	169.0-170.0	0.05	686.82	0.01	99.96
123.0-124.0	0.00	684.68	0.00	99.65	170.0-171.0	0.05	686.87	0.01	99.97
124.0-125.0	0.00	684.68	0.00	99.65	171.0-172.0	0.04	686.91	0.01	99.98
125.0-126.0	0.00	684.68	0.00	99.65	172.0-173.0	0.04	686.95	0.01	99.98
126.0-127.0	0.00	684.68	0.00	99.65	173.0-174.0	0.03	686.98	0.00	99.99
127.0-128.0	0.00	684.68	0.00	99.65	174.0-175.0	0.03	687.01	0.00	99.99
128.0-129.0	0.00	684.68	0.00	99.65	175.0-176.0	0.02	687.03	0.00	99.99
129.0-130.0	0.00	684.68	0.00	99.65	176.0-177.0	0.02	687.05	0.00	100.00
130.0-131.0	0.00	684.68	0.00	99.65	177.0-178.0	0.01	687.07	0.00	100.00
131.0-132.0	0.00	684.68	0.00	99.65	178.0-179.0	0.01	687.07	0.00	100.00
132.0-133.0	0.00	684.69	0.00	99.65	179.0-180.0	0.00	687.08	0.00	100.00
133.0-134.0	0.01	684.69	0.00	99.65					
134.0-135.0	0.01	684.71	0.00	99.65					
135.0-136.0	0.02	684.72	0.00	99.66					
136.0-137.0	0.02	684.74	0.00	99.66					
137.0-138.0	0.03	684.77	0.00	99.66					
138.0-139.0	0.03	684.81	0.00	99.67					
139.0-140.0	0.04	684.84	0.01	99.67					
140.0-141.0	0.04	684.89	0.01	99.68					

Rectangle ISO Lighting Intensity Diagram


Lum. Name: SD02-09-XX-01 3000K RA90 60D	Lum. Catalog:	Test ID: 01
Lamp Name:	Lamp Catalog: LED	Test Lab: Quality Department
Manufacture: Shenzhen Norming Lighting Co.Ltd	Test Machine:GON-2000	Test Date: 2021/03/23



Plane ISO-Illuminance Diagram

Lum. Name: SD02-09-XX-01 3000K RA90 60D	Lum. Catalog:	Test ID: 01
Lamp Name:	Lamp Catalog: LED	Test Lab: Quality Department
Manufacture: Shenzhen Norming Lighting Co.Ltd	Test Machine:GON-2000	Test Date: 2021/03/23

Plane ISO-Illuminance Curve



Working Plane Luminaire Mounting Height(m): 3.00

Working Plane Maximum Illuminance(lx): 77.53

Working Plane Maximum Illuminance Position(d/h):H0.0 V-0.0


# IES Indoor Report

Photometric Filename:SD02-09-XX-01 3000K RA90 60D.IES

## 3D Plane ISO Illuminance Diagram

Lum. Name: SD02-09-XX-01 3000K RA90 60D	Lum. Catalog:	Test ID: 01
Lamp Name:	Lamp Catalog: LED	Test Lab: Quality Department
Manufacture: Shenzhen Norming Lighting Co.Ltd	Test Machine:GON-2000	Test Date: 2021/03/23

## 3D Plane Illuminance Modal




Curves: 3D Model — 90% — 80% — 70% — 60% — 50% — 40% — 30% — 20% — 10% —  
View Angles(deg): 0 Height(m): 3.0 Distance(m): 10.0



Space ISO Illuminance Diagram

Lum. Name: SD02-09-XX-01 3000K RA90 60D	Lum. Catelog:	Test ID: 01
Lamp Name:	Lamp Catelog: LED	Test Lab: Quality Department
Manufacture: Shenzhen Norming Lighting Co.Ltd	Test Machine:GON-2000	Test Date: 2021/03/23


Space ISO Illuminance Curve



Space Plane Maximum Illuminance and @Angle:696.85lx,1.0deg  
Plane Maximum Lighting Intensity and @Angle:698.818cd,0deg

Illuminance-Distance Diagram

Lum. Name: SD02-09-XX-01 3000K RA90 60D	Lum. Catalog:	Test ID: 01
Lamp Name:	Lamp Catalog: LED	Test Lab: Quality Department
Manufacture: Shenzhen Norming Lighting Co.Ltd	Test Machine:GON-2000	Test Date: 2021/03/23



Indoor Luminance Limiting Curves

Lum. Name: SD02-09-XX-01 3000K RA90 60D	Lum. Catalog:	Test ID: 01
Lamp Name:	Lamp Catalog: LED	Test Lab: Quality Department
Manufacture: Shenzhen Norming Lighting Co.Ltd	Test Machine:GON-2000	Test Date: 2021/03/23


Glare Grade Table

GI	Quality	Using Illuminance							
1.15	A	2000	1000	500	<=300				
1.5	B		2000	1000	500	<=300			
1.85	C			2000	1000	500	<=300		
2.2	D				2000	1000	500	<=300	
2.55	E	a				2000	1000	500	<=300
			b	c	d	e	f	g	h

Luminance Table

Gama(deg)	45	50	55	60	65	70	75	80	85
C0	20405	14388	11778	10970	10460	9969	8747	7705	6814
C90	17882	12671	10379	9648	9182	8678	7249	5684	3009

Luminance Limiting Curve




Luminous Size: Length(m)=0.000 Width(m)=-0.050 Height(m)=0.000 Area(m^2)=0.001963

Luminous Type: Without Luminous Side

Luminous Curves: C0-C180 Color: — C90-C270 Color: —

Indoor Budgetary Estimate Table

Lum. Name: SD02-09-XX-01 3000K RA90 60D	Lum. Catalog:	Test ID: 01
Lamp Name:	Lamp Catalog: LED	Test Lab: Quality Department
Manufacture: Shenzhen Norming Lighting Co.Ltd	Test Machine:GON-2000	Test Date: 2021/03/23



Indoor Coefficient of Utilization Table

Lum. Name: SD02-09-XX-01 3000K RA90 60D	Lum. Catelog:	Test ID: 01
Lamp Name:	Lamp Catelog: LED	Test Lab: Quality Department
Manufacture: Shenzhen Norming Lighting Co.Ltd	Test Machine:GON-2000	Test Date: 2021/03/23

Coefficients of Utilization - Zonal Cavity Method																		
Coef.	Effective Floor Cavity Reflectance RFC=0.20																	
RhoCC (%)	80				70				50			30			10			0
RhoW (%)	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR	Coefficient of Utilization(%)																	
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	113	110	108	105	111	108	106	104	104	102	100	100	99	97	97	96	95	93
2	107	102	98	95	105	101	97	94	97	94	92	94	92	90	92	89	88	86
3	102	95	90	86	100	94	89	86	91	87	84	89	85	83	86	84	81	80
4	97	89	83	79	95	88	83	79	86	81	78	84	80	77	82	78	76	74
5	92	83	77	73	90	82	77	73	81	76	72	79	75	71	77	74	71	69
6	87	78	72	68	86	77	72	68	76	71	67	74	70	67	73	69	66	65
7	83	73	67	63	81	73	67	63	71	66	63	70	66	62	69	65	62	60
8	79	69	63	59	78	69	63	59	67	62	59	66	62	58	65	61	58	57
9	75	65	59	55	74	65	59	55	64	59	55	63	58	55	62	58	55	53
10	71	62	56	52	70	61	56	52	60	55	52	60	55	52	59	55	51	50

Unified Glare Rating Table

Lum. Name: SD02-09-XX-01 3000K RA90 60D	Lum. Catelog:	Test ID: 01
Lamp Name:	Lamp Catelog: LED	Test Lab: Quality Department
Manufacture: Shenzhen Norming Lighting Co.Ltd	Test Machine:GON-2000	Test Date: 2021/03/23

Unified Glare Rating Table

Ceiling RCC	0.70	0.70	0.50	0.50	0.30	0.70	0.70	0.50	0.50	0.30
Wall RW	0.50	0.30	0.50	0.30	0.30	0.50	0.30	0.50	0.30	0.30
Floor RFC	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20
Room Size	Vewed crosswise					Vewed endwise				
X=2H    Y=2H	21.0	21.9	21.3	22.3	22.6	20.7	21.7	21.1	22.0	22.3
	21.0	21.9	21.4	22.2	22.6	20.7	21.6	21.1	21.9	22.3
	21.1	21.9	21.5	22.2	22.6	20.7	21.5	21.2	21.9	22.3
	21.1	21.8	21.5	22.2	22.6	20.7	21.4	21.1	21.8	22.2
	21.0	21.7	21.5	22.1	22.5	20.7	21.4	21.1	21.8	22.2
	21.0	21.7	21.5	22.1	22.5	20.6	21.3	21.1	21.7	22.1
X=4H    Y=2H	20.8	21.6	21.2	21.9	22.3	20.5	21.3	20.9	21.7	22.1
	20.9	21.6	21.3	22.0	22.4	20.6	21.3	21.1	21.7	22.1
	21.0	21.6	21.4	22.0	22.5	20.7	21.3	21.1	21.7	22.1
	21.1	21.6	21.5	22.0	22.5	20.7	21.2	21.2	21.6	22.1
	21.1	21.5	21.6	22.0	22.5	20.7	21.1	21.1	21.6	22.1
	21.1	21.5	21.6	22.0	22.4	20.6	21.0	21.1	21.5	22.0
X=8H    Y=4H	20.9	21.4	21.4	21.9	22.3	20.6	21.1	21.1	21.5	22.0
	21.0	21.4	21.6	21.9	22.4	20.6	21.0	21.2	21.5	22.0
	21.1	21.4	21.6	21.9	22.4	20.6	21.0	21.2	21.5	22.0
	21.1	21.4	21.6	21.9	22.5	20.6	20.9	21.1	21.4	22.0
X=12H    Y=4H	20.9	21.3	21.4	21.8	22.3	20.5	20.9	21.0	21.4	21.9
	21.0	21.3	21.5	21.8	22.4	20.6	20.9	21.1	21.4	22.0
	21.1	21.3	21.6	21.9	22.4	20.6	20.9	21.1	21.4	22.0
Variations with the objverver position at spacings										
S=1.0H	0.5/-0.5					0.7/-0.7				
S=1.5H	0.9/-1.0					1.1/-1.3				
S=2.0H	1.1/-1.4					1.3/-1.8				
Reduced UGR Table:										
Nordic Standard Table:	BK0					BK0				
Correction Value	0.6					0.5				

o the CIE Pub.117, data has been corrected, refers to the lamp's lumens 8.2flm.

IES Indoor Report

Photometric Filename:SD02-09-XX-01 3000K RA90 60D.IES

---

Candela Tabulation

V/H	C0.0	C90.0	C180.0	C270.0
γ 0.0	696.22	696.22	696.22	696.22
γ 1.0	697.17	692.15	698.06	692.76
γ 2.0	698.06	691.64	697.55	693.71
γ 3.0	698.02	691.26	697.80	693.89
γ 4.0	698.82	690.26	697.43	693.65
γ 5.0	698.54	690.11	696.70	693.51
γ 6.0	697.22	688.53	696.22	692.93
γ 7.0	697.60	688.01	694.26	692.28
γ 8.0	696.16	687.18	693.22	691.21
γ 9.0	695.74	686.01	692.36	690.53
γ 10.0	693.79	684.64	690.91	690.28
γ 11.0	693.46	682.61	690.09	689.61
γ 12.0	691.68	680.04	688.59	688.85
γ 13.0	690.74	676.58	687.57	687.76
γ 14.0	687.85	671.78	684.77	685.73
γ 15.0	683.05	664.96	680.78	682.38
γ 16.0	675.13	656.03	674.17	678.22
γ 17.0	664.57	647.38	666.41	671.48
γ 18.0	651.28	637.27	657.59	660.09
γ 19.0	637.81	624.97	647.43	647.65
γ 20.0	622.56	610.31	634.23	633.90
γ 21.0	604.53	593.45	617.79	618.44
γ 22.0	583.79	576.18	600.66	600.48
γ 23.0	563.09	557.44	581.84	582.09
γ 24.0	540.74	535.36	560.08	561.77
γ 25.0	516.22	510.93	536.57	538.74
γ 26.0	491.22	483.57	510.74	515.32
γ 27.0	463.89	455.67	483.06	488.72
γ 28.0	435.74	426.05	454.10	461.30
γ 29.0	406.63	396.50	425.41	432.59
γ 30.0	373.29	368.12	396.21	403.97
γ 31.0	348.42	339.33	367.28	374.44
γ 32.0	319.33	311.39	337.79	345.85
γ 33.0	291.37	284.18	309.06	317.93
γ 34.0	262.11	254.62	281.04	289.46
γ 35.0	235.84	227.76	250.84	260.51
γ 36.0	202.70	195.36	224.23	233.16
γ 37.0	163.01	158.43	188.37	196.58
γ 38.0	127.02	122.21	150.70	157.73
γ 39.0	94.50	91.78	114.42	120.64
γ 40.0	69.53	65.92	84.73	89.11
γ 41.0	51.04	47.67	59.83	63.73
γ 42.0	40.30	36.25	42.90	45.82
γ 43.0	34.53	30.44	32.69	34.86
γ 44.0	31.03	27.22	27.47	29.33
γ 45.0	28.33	24.83	24.30	25.87
γ 46.0	26.10	22.98	21.87	23.39

Candela Tabulation - (Cont.)

V/H	C0.0	C90.0	C180.0	C270.0
γ 47.0	24.21	21.25	19.98	21.45
γ 48.0	22.42	19.77	18.35	19.78
γ 49.0	20.51	18.10	16.92	18.28
γ 50.0	18.16	15.99	15.32	16.48
γ 51.0	16.43	14.35	13.30	14.25
γ 52.0	15.38	13.48	11.78	12.95
γ 53.0	14.46	12.71	10.96	12.19
γ 54.0	13.85	12.17	10.31	11.65
γ 55.0	13.26	11.69	9.94	11.21
γ 56.0	12.73	11.22	9.59	10.79
γ 57.0	12.23	10.77	9.28	10.42
γ 58.0	11.70	10.32	8.98	10.06
γ 59.0	11.22	9.88	8.69	9.72
γ 60.0	10.77	9.47	8.41	9.42
γ 61.0	10.32	9.09	8.19	9.15
γ 62.0	9.91	8.71	7.98	8.91
γ 63.0	9.47	8.34	7.78	8.65
γ 64.0	9.08	7.97	7.57	8.43
γ 65.0	8.68	7.62	7.37	8.20
γ 66.0	8.30	7.26	7.16	7.96
γ 67.0	7.91	6.93	6.94	7.72
γ 68.0	7.52	6.57	6.70	7.46
γ 69.0	7.13	6.21	6.46	7.17
γ 70.0	6.70	5.83	6.17	6.86
γ 71.0	6.21	5.38	5.84	6.49
γ 72.0	5.75	4.92	5.45	6.08
γ 73.0	5.29	4.49	5.05	5.66
γ 74.0	4.86	4.08	4.64	5.24
γ 75.0	4.45	3.68	4.25	4.82
γ 76.0	4.04	3.31	3.86	4.43
γ 77.0	3.66	2.95	3.48	4.04
γ 78.0	3.31	2.58	3.13	3.66
γ 79.0	2.96	2.26	2.78	3.32
γ 80.0	2.63	1.94	2.44	2.99
γ 81.0	2.31	1.63	2.12	2.65
γ 82.0	2.02	1.34	1.81	2.34
γ 83.0	1.72	1.06	1.52	2.04
γ 84.0	1.43	0.78	1.23	1.74
γ 85.0	1.17	0.51	0.95	1.46
γ 86.0	0.91	0.28	0.70	1.19
γ 87.0	0.67	0.05	0.44	0.94
γ 88.0	0.43	0.00	0.21	0.70
γ 89.0	0.20	0.00	0.00	0.47
γ 90.0	0.10	0.00	0.00	0.26
γ 91.0	0.02	0.00	0.00	0.16
γ 92.0	0.00	0.00	0.00	0.07
γ 93.0	0.00	0.00	0.00	0.00



Candela Tabulation - (Cont.)

V/H	C0.0	C90.0	C180.0	C270.0
γ 94.0	0.00	0.00	0.00	0.00
γ 95.0	0.00	0.00	0.00	0.00
γ 96.0	0.00	0.00	0.00	0.00
γ 97.0	0.00	0.00	0.00	0.00
γ 98.0	0.00	0.00	0.00	0.00
γ 99.0	0.00	0.00	0.00	0.00
γ 100.0	0.00	0.00	0.00	0.00
γ 101.0	0.00	0.00	0.00	0.00
γ 102.0	0.00	0.00	0.00	0.00
γ 103.0	0.00	0.00	0.00	0.00
γ 104.0	0.00	0.00	0.00	0.00
γ 105.0	0.00	0.00	0.00	0.00
γ 106.0	0.00	0.00	0.00	0.00
γ 107.0	0.00	0.00	0.00	0.00
γ 108.0	0.00	0.00	0.00	0.00
γ 109.0	0.00	0.00	0.00	0.00
γ 110.0	0.00	0.00	0.00	0.00
γ 111.0	0.00	0.00	0.00	0.00
γ 112.0	0.00	0.00	0.00	0.00
γ 113.0	0.00	0.00	0.00	0.00
γ 114.0	0.00	0.00	0.00	0.00
γ 115.0	0.00	0.00	0.00	0.00
γ 116.0	0.00	0.00	0.00	0.00
γ 117.0	0.00	0.00	0.00	0.00
γ 118.0	0.00	0.00	0.00	0.00
γ 119.0	0.00	0.00	0.00	0.00
γ 120.0	0.00	0.00	0.00	0.00
γ 121.0	0.00	0.00	0.00	0.00
γ 122.0	0.00	0.00	0.00	0.00
γ 123.0	0.00	0.00	0.00	0.00
γ 124.0	0.00	0.00	0.00	0.00
γ 125.0	0.00	0.00	0.00	0.00
γ 126.0	0.00	0.00	0.00	0.00
γ 127.0	0.00	0.00	0.00	0.00
γ 128.0	0.00	0.00	0.00	0.00
γ 129.0	0.00	0.00	0.00	0.00
γ 130.0	0.00	0.00	0.00	0.00
γ 131.0	0.00	0.00	0.00	0.00
γ 132.0	0.01	0.00	0.00	0.06
γ 133.0	0.07	0.00	0.06	0.14
γ 134.0	0.15	0.00	0.14	0.20
γ 135.0	0.22	0.00	0.22	0.27
γ 136.0	0.30	0.08	0.29	0.34
γ 137.0	0.38	0.16	0.38	0.41
γ 138.0	0.45	0.24	0.46	0.48
γ 139.0	0.54	0.33	0.54	0.57
γ 140.0	0.63	0.41	0.63	0.64

---

Candela Tabulation - (Cont.)

V/H	C0.0	C90.0	C180.0	C270.0
γ 141.0	0.69	0.49	0.72	0.73
γ 142.0	0.79	0.57	0.80	0.80
γ 143.0	0.87	0.66	0.88	0.88
γ 144.0	0.94	0.74	0.96	0.96
γ 145.0	1.02	0.83	1.05	1.03
γ 146.0	1.09	0.89	1.12	1.11
γ 147.0	1.17	0.97	1.21	1.17
γ 148.0	1.24	1.05	1.28	1.24
γ 149.0	1.29	1.12	1.36	1.31
γ 150.0	1.36	1.18	1.42	1.37
γ 151.0	1.40	1.25	1.48	1.43
γ 152.0	1.47	1.31	1.55	1.48
γ 153.0	1.53	1.37	1.61	1.55
γ 154.0	1.59	1.44	1.68	1.61
γ 155.0	1.65	1.49	1.74	1.67
γ 156.0	1.71	1.57	1.80	1.73
γ 157.0	1.78	1.63	1.86	1.78
γ 158.0	1.84	1.69	1.93	1.84
γ 159.0	1.89	1.76	1.99	1.91
γ 160.0	1.96	1.83	2.05	1.98
γ 161.0	2.01	1.88	2.10	2.03
γ 162.0	2.08	1.94	2.16	2.10
γ 163.0	2.14	2.01	2.23	2.14
γ 164.0	2.20	2.08	2.29	2.20
γ 165.0	2.26	2.12	2.34	2.27
γ 166.0	2.32	2.19	2.40	2.32
γ 167.0	2.38	2.26	2.46	2.38
γ 168.0	2.43	2.32	2.51	2.43
γ 169.0	2.49	2.36	2.58	2.48
γ 170.0	2.55	2.42	2.62	2.52
γ 171.0	2.60	2.48	2.67	2.58
γ 172.0	2.65	2.52	2.71	2.62
γ 173.0	2.69	2.57	2.75	2.67
γ 174.0	2.74	2.61	2.79	2.70
γ 175.0	2.77	2.65	2.84	2.74
γ 176.0	2.81	2.69	2.86	2.77
γ 177.0	2.84	2.73	2.88	2.80
γ 178.0	2.86	2.76	2.90	2.82
γ 179.0	2.87	2.77	2.92	2.83
γ 180.0	2.87	2.87	2.87	2.87