



Indoor Luminaire Photometric Data

Description Information

Luminary Name: SD03-06-DW-01 2000-3000K RA95 36D	Lum. Catalog:	Test ID: 01
Lamp Name:	Lamp Catalog: LED	Test Date: 2021/05/06
Manufacture: Shenzhen Norming Lighting Co.Ltd	Shld.Ang(°):	Test Machine:GON-2000
Test Lab: Quality Department	Frequency (Hz):	Lamp CCT(K): Ra:
Lum. Size (W*L*H):0.050m*0.000m*0.000m	Lum. Area (m2):0.002	Lum. W(kg): 0.000
Test System: C, γ	Test Step: C=90.0 γ=1.0	Temp. (°C): 25
		Humidity(%): 50.0


Character Parameter

Lamp Speciality Parameter	Luminaire Speciality Parameter	
Rated Flux(lm): 349.440	Luminary Flux(lm): 349.437	Field Angle(10%Imax): 62.0(°)
Rated Power(W):	Luminary Efficiency: 100.00%	Down Lumens&Percent: 348.459lm 99.72%
Rated Voltage(V):	Luminary EER(lm/W): 60.227	Up Lumens&Percent: 0.978lm 0.28%
Tested Power(W): 5.802	Max. Candela(cd): 797.221	S/MH: C0_a180=0.630 C90_270=0.627
Lamps' Inside: 1	Max Cand@Ang. (°): C=270.0 γ=5.0	CIE Type: Semi-Direct
Tested Electrics (V, A, pf):240.2, 0.028, 0.860	Beam Angle(50%Imax): 36.7(°)	ErP Φ use(90°): 339.653lm
Lamp Size (W*L*H):0.050m*0.000m*0.000m	Left=-18.1°, Right=18.6°	IRF(%): 487.033



2D Plane Light Intensity Distribution Curve


Lum. Name:SD03-06-DW-01 2000-3000K RA95 36D	Lum. Catalog:	Test ID:01
Lamp Name:	Lamp Catalog:LED	Test Lab:Quality Department
Manufacture:Shenzhen Norming Lighting Co.Ltd	Test Machine:GON-2000	Test Date:2021/05/06



3D Light Intensity Distribution Modal

Lum. Name:SD03-06-DW-01 2000-3000K RA95 36D	Lum. Catelog:	Test ID:01
Lamp Name:	Lamp Catelog:LED	Test Lab:Quality Department
Manufacture:Shenzhen Norming Lighting Co.Ltd	Test Machine:GON-2000	Test Date:2021/05/06

3D Light Intensity Distribution Modal



Zonal Flux Tabulation


Zone(γ)	Zone Flux (lm)	Sums Flux (lm)	Zone%Lamp	Sums%Lamp	Zone(γ)	Zone Flux (lm)	Sums Flux (lm)	Zone%Lamp	Sums%Lamp
0.0-1.0	0.74	0.74	0.21	0.21	47.0-48.0	0.54	341.03	0.15	97.59
1.0-2.0	2.22	2.96	0.64	0.85	48.0-49.0	0.51	341.54	0.15	97.74
2.0-3.0	3.72	6.69	1.07	1.91	49.0-50.0	0.48	342.01	0.14	97.87
3.0-4.0	5.24	11.93	1.50	3.41	50.0-51.0	0.44	342.45	0.13	98.00
4.0-5.0	6.75	18.68	1.93	5.35	51.0-52.0	0.40	342.85	0.12	98.12
5.0-6.0	8.24	26.92	2.36	7.70	52.0-53.0	0.38	343.23	0.11	98.22
6.0-7.0	9.67	36.59	2.77	10.47	53.0-54.0	0.35	343.59	0.10	98.32
7.0-8.0	11.00	47.59	3.15	13.62	54.0-55.0	0.34	343.92	0.10	98.42
8.0-9.0	12.20	59.79	3.49	17.11	55.0-56.0	0.32	344.24	0.09	98.51
9.0-10.0	13.26	73.05	3.79	20.90	56.0-57.0	0.31	344.55	0.09	98.60
10.0-11.0	14.17	87.22	4.06	24.96	57.0-58.0	0.29	344.85	0.08	98.69
11.0-12.0	14.92	102.14	4.27	29.23	58.0-59.0	0.28	345.13	0.08	98.77
12.0-13.0	15.47	117.62	4.43	33.66	59.0-60.0	0.27	345.39	0.08	98.84
13.0-14.0	15.78	133.40	4.52	38.18	60.0-61.0	0.26	345.65	0.07	98.92
14.0-15.0	15.85	149.25	4.53	42.71	61.0-62.0	0.24	345.90	0.07	98.99
15.0-16.0	15.66	164.91	4.48	47.19	62.0-63.0	0.23	346.13	0.07	99.05
16.0-17.0	15.24	180.15	4.36	51.55	63.0-64.0	0.22	346.35	0.06	99.12
17.0-18.0	14.58	194.73	4.17	55.73	64.0-65.0	0.21	346.56	0.06	99.18
18.0-19.0	13.71	208.45	3.92	59.65	65.0-66.0	0.20	346.76	0.06	99.23
19.0-20.0	12.71	221.16	3.64	63.29	66.0-67.0	0.19	346.95	0.05	99.29
20.0-21.0	11.66	232.82	3.34	66.63	67.0-68.0	0.18	347.12	0.05	99.34
21.0-22.0	10.62	243.44	3.04	69.66	68.0-69.0	0.17	347.29	0.05	99.38
22.0-23.0	9.62	253.06	2.75	72.42	69.0-70.0	0.16	347.45	0.04	99.43
23.0-24.0	8.71	261.77	2.49	74.91	70.0-71.0	0.14	347.59	0.04	99.47
24.0-25.0	7.91	269.68	2.26	77.17	71.0-72.0	0.13	347.72	0.04	99.51
25.0-26.0	7.20	276.88	2.06	79.23	72.0-73.0	0.12	347.84	0.03	99.54
26.0-27.0	6.60	283.48	1.89	81.12	73.0-74.0	0.11	347.95	0.03	99.57
27.0-28.0	6.07	289.55	1.74	82.86	74.0-75.0	0.10	348.04	0.03	99.60
28.0-29.0	5.60	295.15	1.60	84.46	75.0-76.0	0.08	348.13	0.02	99.62
29.0-30.0	5.18	300.33	1.48	85.95	76.0-77.0	0.07	348.20	0.02	99.65
30.0-31.0	4.78	305.11	1.37	87.31	77.0-78.0	0.06	348.26	0.02	99.66
31.0-32.0	4.40	309.51	1.26	88.57	78.0-79.0	0.05	348.31	0.01	99.68
32.0-33.0	4.04	313.56	1.16	89.73	79.0-80.0	0.04	348.35	0.01	99.69
33.0-34.0	3.70	317.26	1.06	90.79	80.0-81.0	0.03	348.38	0.01	99.70
34.0-35.0	3.37	320.63	0.96	91.75	81.0-82.0	0.02	348.41	0.01	99.71
35.0-36.0	3.05	323.67	0.87	92.63	82.0-83.0	0.02	348.43	0.01	99.71
36.0-37.0	2.75	326.42	0.79	93.41	83.0-84.0	0.01	348.44	0.00	99.71
37.0-38.0	2.48	328.91	0.71	94.12	84.0-85.0	0.01	348.45	0.00	99.72
38.0-39.0	2.24	331.14	0.64	94.76	85.0-86.0	0.00	348.46	0.00	99.72
39.0-40.0	2.01	333.16	0.58	95.34	86.0-87.0	0.00	348.46	0.00	99.72
40.0-41.0	1.80	334.96	0.52	95.86	87.0-88.0	0.00	348.46	0.00	99.72
41.0-42.0	1.53	336.49	0.44	96.29	88.0-89.0	0.00	348.46	0.00	99.72
42.0-43.0	1.18	337.66	0.34	96.63	89.0-90.0	0.00	348.46	0.00	99.72
43.0-44.0	0.89	338.56	0.26	96.89	90.0-91.0	0.00	348.46	0.00	99.72
44.0-45.0	0.73	339.28	0.21	97.09	91.0-92.0	0.00	348.46	0.00	99.72
45.0-46.0	0.63	339.91	0.18	97.27	92.0-93.0	0.00	348.46	0.00	99.72
46.0-47.0	0.58	340.49	0.16	97.44	93.0-94.0	0.00	348.46	0.00	99.72

Zonal Flux Tabulation - (Cont.)

Zone(γ)	Zone Flux (lm)	Sums Flux (lm)	Zone%Lamp	Sums%Lamp	Zone(γ)	Zone Flux (lm)	Sums Flux (lm)	Zone%Lamp	Sums%Lamp
94.0-95.0	0.00	348.46	0.00	99.72	141.0-142.0	0.01	348.47	0.00	99.72
95.0-96.0	0.00	348.46	0.00	99.72	142.0-143.0	0.01	348.48	0.00	99.72
96.0-97.0	0.00	348.46	0.00	99.72	143.0-144.0	0.01	348.49	0.00	99.73
97.0-98.0	0.00	348.46	0.00	99.72	144.0-145.0	0.02	348.50	0.00	99.73
98.0-99.0	0.00	348.46	0.00	99.72	145.0-146.0	0.02	348.52	0.01	99.74
99.0-100.0	0.00	348.46	0.00	99.72	146.0-147.0	0.02	348.55	0.01	99.74
100.0-101.0	0.00	348.46	0.00	99.72	147.0-148.0	0.03	348.57	0.01	99.75
101.0-102.0	0.00	348.46	0.00	99.72	148.0-149.0	0.03	348.60	0.01	99.76
102.0-103.0	0.00	348.46	0.00	99.72	149.0-150.0	0.03	348.63	0.01	99.77
103.0-104.0	0.00	348.46	0.00	99.72	150.0-151.0	0.03	348.67	0.01	99.78
104.0-105.0	0.00	348.46	0.00	99.72	151.0-152.0	0.04	348.70	0.01	99.79
105.0-106.0	0.00	348.46	0.00	99.72	152.0-153.0	0.04	348.74	0.01	99.80
106.0-107.0	0.00	348.46	0.00	99.72	153.0-154.0	0.04	348.78	0.01	99.81
107.0-108.0	0.00	348.46	0.00	99.72	154.0-155.0	0.04	348.82	0.01	99.82
108.0-109.0	0.00	348.46	0.00	99.72	155.0-156.0	0.04	348.85	0.01	99.83
109.0-110.0	0.00	348.46	0.00	99.72	156.0-157.0	0.04	348.89	0.01	99.84
110.0-111.0	0.00	348.46	0.00	99.72	157.0-158.0	0.04	348.93	0.01	99.86
111.0-112.0	0.00	348.46	0.00	99.72	158.0-159.0	0.04	348.97	0.01	99.87
112.0-113.0	0.00	348.46	0.00	99.72	159.0-160.0	0.04	349.01	0.01	99.88
113.0-114.0	0.00	348.46	0.00	99.72	160.0-161.0	0.04	349.05	0.01	99.89
114.0-115.0	0.00	348.46	0.00	99.72	161.0-162.0	0.04	349.09	0.01	99.90
115.0-116.0	0.00	348.46	0.00	99.72	162.0-163.0	0.04	349.13	0.01	99.91
116.0-117.0	0.00	348.46	0.00	99.72	163.0-164.0	0.03	349.16	0.01	99.92
117.0-118.0	0.00	348.46	0.00	99.72	164.0-165.0	0.03	349.19	0.01	99.93
118.0-119.0	0.00	348.46	0.00	99.72	165.0-166.0	0.03	349.22	0.01	99.94
119.0-120.0	0.00	348.46	0.00	99.72	166.0-167.0	0.03	349.25	0.01	99.95
120.0-121.0	0.00	348.46	0.00	99.72	167.0-168.0	0.03	349.28	0.01	99.95
121.0-122.0	0.00	348.46	0.00	99.72	168.0-169.0	0.02	349.30	0.01	99.96
122.0-123.0	0.00	348.46	0.00	99.72	169.0-170.0	0.02	349.33	0.01	99.97
123.0-124.0	0.00	348.46	0.00	99.72	170.0-171.0	0.02	349.35	0.01	99.97
124.0-125.0	0.00	348.46	0.00	99.72	171.0-172.0	0.02	349.36	0.01	99.98
125.0-126.0	0.00	348.46	0.00	99.72	172.0-173.0	0.02	349.38	0.00	99.98
126.0-127.0	0.00	348.46	0.00	99.72	173.0-174.0	0.01	349.40	0.00	99.99
127.0-128.0	0.00	348.46	0.00	99.72	174.0-175.0	0.01	349.41	0.00	99.99
128.0-129.0	0.00	348.46	0.00	99.72	175.0-176.0	0.01	349.42	0.00	99.99
129.0-130.0	0.00	348.46	0.00	99.72	176.0-177.0	0.01	349.43	0.00	100.00
130.0-131.0	0.00	348.46	0.00	99.72	177.0-178.0	0.01	349.43	0.00	100.00
131.0-132.0	0.00	348.46	0.00	99.72	178.0-179.0	0.00	349.44	0.00	100.00
132.0-133.0	0.00	348.46	0.00	99.72	179.0-180.0	0.00	349.44	0.00	100.00
133.0-134.0	0.00	348.46	0.00	99.72					
134.0-135.0	0.00	348.46	0.00	99.72					
135.0-136.0	0.00	348.46	0.00	99.72					
136.0-137.0	0.00	348.46	0.00	99.72					
137.0-138.0	0.00	348.46	0.00	99.72					
138.0-139.0	0.00	348.46	0.00	99.72					
139.0-140.0	0.00	348.46	0.00	99.72					
140.0-141.0	0.00	348.46	0.00	99.72					

Rectangle ISO Lighting Intensity Diagram


Lum. Name:SD03-06-DW-01 2000-3000K RA95 36D	Lum. Catalog:	Test ID:01
Lamp Name:	Lamp Catalog:LED	Test Lab:Quality Department
Manufacture:Shenzhen Norming Lighting Co.Ltd	Test Machine:GON-2000	Test Date:2021/05/06



Plane ISO-Illuminance Diagram

Lum. Name:SD03-06-DW-01 2000-3000K RA95 36D	Lum. Catalog:	Test ID: 01
Lamp Name:	Lamp Catalog: LED	Test Lab: Quality Department
Manufacture: Shenzhen Norming Lighting Co.Ltd	Test Machine:GON-2000	Test Date: 2021/05/06

Plane ISO-Illuminance Curve



Working Plane Luminaire Mounting Height(m): 3.00

Working Plane Maximum Illuminance(lx): 87.57

Working Plane Maximum Illuminance Position(d/h):H-0.1 V-0.0


# IES Indoor Report

Photometric Filename:SD03-06-DW-01 2000-3000K RA95 36D.IES

## 3D Plane ISO Illuminance Diagram

Lum. Name: SD03-06-DW-01 2000-3000K RA95 36D	Lum. Catalog:	Test ID: 01
Lamp Name:	Lamp Catalog: LED	Test Lab: Quality Department
Manufacture: Shenzhen Norming Lighting Co.Ltd	Test Machine:GON-2000	Test Date: 2021/05/06

## 3D Plane Illuminance Modal




Curves: 3D Model — 90% — 80% — 70% — 60% — 50% — 40% — 30% — 20% — 10% —  
View Angles(deg): 0 Height(m): 3.0 Distance(m): 10.0



Space ISO Illuminance Diagram

Lum. Name:SD03-06-DW-01 2000-3000K RA95 36D	Lum. Catelog:	Test ID:01
Lamp Name:	Lamp Catelog:LED	Test Lab:Quality Department
Manufacture:Shenzhen Norming Lighting Co.Ltd	Test Machine:GON-2000	Test Date:2021/05/06


Space ISO Illuminance Curve



Space Plane Maximum Illuminance and @Angle:779.78lx,3.0deg  
Plane Maximum Lighting Intensity and @Angle:784.984cd,0deg

Illuminance-Distance Diagram

Lum. Name:SD03-06-DW-01 2000-3000K RA95 36D	Lum. Catelog:	Test ID:01
Lamp Name:	Lamp Catelog:LED	Test Lab:Quality Department
Manufacture:Shenzhen Norming Lighting Co.Ltd	Test Machine:GON-2000	Test Date:2021/05/06



Indoor Luminance Limiting Curves

Lum. Name: SD03-06-DW-01 2000-3000K RA95 36D	Lum. Catalog:	Test ID: 01
Lamp Name:	Lamp Catalog: LED	Test Lab: Quality Department
Manufacture: Shenzhen Norming Lighting Co.Ltd	Test Machine:GON-2000	Test Date: 2021/05/06


Glare Grade Table

GI	Quality	Using Illuminance							
1.15	A	2000	1000	500	<=300				
1.5	B		2000	1000	500	<=300			
1.85	C			2000	1000	500	<=300		
2.2	D				2000	1000	500	<=300	
2.55	E	a				2000	1000	500	<=300
			b	c	d	e	f	g	h

Luminance Table

Gama(deg)	45	50	55	60	65	70	75	80	85
C0	7288	5185	3860	3312	2919	2612	2165	1628	579
C90	6037	4107	2900	2359	1944	1514	852	0	0

Luminance Limiting Curve



Luminous Size: Length(m)=0.000 Width(m)=-0.050 Height(m)=0.000 Area(m^2)=0.001963

Luminous Type: Without Luminous Side


Luminous Curves: C0-C180 Color: C90-C270 Color:

# IES Indoor Report

Photometric Filename:SD03-06-DW-01 2000-3000K RA95 36D.IES

## Indoor Budgetary Estimate Table

Lum. Name: SD03-06-DW-01 2000-3000K RA95 36D	Lum. Catalog:	Test ID: 01
Lamp Name:	Lamp Catalog: LED	Test Lab: Quality Department
Manufacture: Shenzhen Norming Lighting Co.Ltd	Test Machine:GON-2000	Test Date: 2021/05/06



Parameters1: Rhocc = 0.7 Rhow = 0.5 Rhofc = 0.2 LLF = 0.8  
Parameters2: Rhocc = 0.5 Rhow = 0.3 Rhofc = 0.2 LLF = 0.8  
Average Illuminance(lx): 100 Cavity Height: H1(m) = 2

Indoor Coefficient of Utilization Table

Lum. Name: SD03-06-DW-01 2000-3000K RA95 36D	Lum. Catelog:	Test ID: 01
Lamp Name:	Lamp Catelog: LED	Test Lab: Quality Department
Manufacture: Shenzhen Norming Lighting Co.Ltd	Test Machine:GON-2000	Test Date: 2021/05/06

Coefficients of Utilization - Zonal Cavity Method																		
Coef.	Effective Floor Cavity Reflectance RFC=0.20																	
RhoCC (%)	80				70				50			30			10			0
RhoW (%)	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR	Coefficient of Utilization(%)																	
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	114	112	110	108	112	110	108	106	106	104	103	102	101	99	98	97	97	95
2	110	105	102	99	107	104	100	98	100	98	96	97	95	94	95	93	92	90
3	105	100	95	92	103	98	94	91	96	92	90	93	91	88	91	89	87	86
4	101	95	90	86	99	93	89	86	91	88	85	89	86	84	88	85	83	81
5	97	90	85	81	95	89	84	81	87	83	80	86	82	80	84	81	79	78
6	93	86	81	77	92	85	80	77	84	79	76	82	79	76	81	78	75	74
7	90	82	77	74	89	81	77	73	80	76	73	79	75	73	78	75	72	71
8	87	79	74	70	85	78	73	70	77	73	70	76	72	69	75	72	69	68
9	83	75	71	67	82	75	70	67	74	70	67	73	69	67	72	69	66	65
10	81	73	68	64	80	72	68	64	71	67	64	71	67	64	70	66	64	63

Unified Glare Rating Table

Lum. Name:SD03-06-DW-01 2000-3000K RA95 36D	Lum. Catelog:	Test ID:01
Lamp Name:	Lamp Catelog:LED	Test Lab:Quality Department
Manufacture:Shenzhen Norming Lighting Co.Ltd	Test Machine:GON-2000	Test Date:2021/05/06

Unified Glare Rating Table

Ceiling RCC	0.70	0.70	0.50	0.50	0.30	0.70	0.70	0.50	0.50	0.30
Wall RW	0.50	0.30	0.50	0.30	0.30	0.50	0.30	0.50	0.30	0.30
Floor RFC	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20
Room Size	Vewed crosswise					Vewed endwise				
X=2H    Y=2H	13.9	14.8	14.2	15.1	15.4	13.2	14.2	13.6	14.5	14.8
	13.9	14.8	14.3	15.1	15.5	13.2	14.0	13.6	14.3	14.7
	14.0	14.7	14.4	15.1	15.5	13.1	13.9	13.5	14.2	14.6
	13.9	14.6	14.4	15.0	15.4	13.0	13.7	13.4	14.1	14.5
	13.9	14.5	14.3	14.9	15.4	12.9	13.6	13.4	14.0	14.4
	13.8	14.5	14.3	14.8	15.3	12.9	13.5	13.3	13.9	14.3
X=4H    Y=2H	13.7	14.5	14.1	14.8	15.2	13.1	13.8	13.5	14.2	14.6
	13.9	14.5	14.3	14.9	15.3	13.0	13.7	13.5	14.1	14.5
	13.9	14.5	14.4	14.9	15.3	13.0	13.5	13.4	14.0	14.4
	13.9	14.4	14.4	14.9	15.3	12.9	13.3	13.3	13.8	14.3
	13.9	14.3	14.4	14.8	15.3	12.8	13.2	13.3	13.7	14.2
	13.8	14.2	14.3	14.7	15.2	12.7	13.1	13.2	13.6	14.1
X=8H    Y=4H	13.8	14.2	14.3	14.7	15.2	12.8	13.3	13.3	13.7	14.2
	13.8	14.2	14.4	14.7	15.2	12.7	13.1	13.2	13.6	14.1
	13.8	14.1	14.4	14.6	15.2	12.6	13.0	13.2	13.5	14.0
	13.8	14.0	14.3	14.5	15.1	12.6	12.9	13.1	13.4	13.9
X=12H    Y=4H	13.7	14.1	14.2	14.6	15.1	12.8	13.1	13.3	13.6	14.1
	13.8	14.1	14.3	14.6	15.1	12.7	13.0	13.2	13.4	14.0
	13.8	14.0	14.3	14.5	15.1	12.6	12.9	13.1	13.4	13.9
Variations with the objerver position at spacings										
S=1.0H	0.7/-0.8					2.0/-3.0				
S=1.5H	1.3/-1.5					2.6/-4.3				
S=2.0H	1.6/-2.1					2.7/-4.9				
Reduced UGR Table:										
Nordic Standard Table:	BK0					BK0				
Correction Value	0.5					0.2				

to the CIE Pub.117, data has been corrected, refers to the lamp's lumens 8.2flm.

Candela Tabulation

V/H	C0.0	C90.0	C180.0	C270.0
γ 0.0	772.19	772.19	772.19	772.19
γ 1.0	774.31	767.94	774.48	773.11
γ 2.0	777.93	768.77	777.98	779.77
γ 3.0	782.99	770.27	783.56	786.86
γ 4.0	784.98	770.79	788.43	793.58
γ 5.0	784.38	769.33	790.48	797.22
γ 6.0	778.84	764.84	792.56	795.79
γ 7.0	766.21	754.48	787.88	791.22
γ 8.0	749.19	740.27	778.99	778.86
γ 9.0	728.10	720.54	763.86	761.88
γ 10.0	703.95	697.92	744.25	739.97
γ 11.0	677.19	672.16	721.52	716.47
γ 12.0	646.28	643.46	694.72	689.03
γ 13.0	611.28	610.96	662.94	656.29
γ 14.0	573.11	573.94	626.96	617.28
γ 15.0	530.82	535.23	585.47	574.01
γ 16.0	487.50	493.47	541.51	527.07
γ 17.0	441.34	449.27	495.86	479.40
γ 18.0	393.66	403.39	446.95	427.94
γ 19.0	346.40	358.62	398.10	378.05
γ 20.0	302.52	314.30	349.94	330.77
γ 21.0	263.47	273.17	305.74	288.34
γ 22.0	228.96	237.05	265.73	250.64
γ 23.0	198.96	205.07	229.74	218.39
γ 24.0	174.04	178.00	198.72	190.97
γ 25.0	153.63	155.35	172.72	167.30
γ 26.0	136.48	136.46	151.33	147.25
γ 27.0	122.25	120.58	133.79	130.61
γ 28.0	109.78	107.06	119.13	116.36
γ 29.0	98.75	95.50	106.47	103.68
γ 30.0	88.84	85.21	95.33	93.05
γ 31.0	79.86	76.23	85.43	83.09
γ 32.0	71.74	67.92	76.18	74.56
γ 33.0	64.19	60.19	67.75	66.57
γ 34.0	57.37	53.51	60.23	59.27
γ 35.0	51.14	47.10	52.72	52.61
γ 36.0	45.14	41.35	46.19	46.52
γ 37.0	40.02	36.49	40.59	40.89
γ 38.0	35.55	32.25	35.60	36.08
γ 39.0	31.52	28.38	31.16	31.79
γ 40.0	27.97	24.89	27.24	28.05
γ 41.0	24.68	21.61	23.21	24.68
γ 42.0	19.60	16.55	16.86	20.82
γ 43.0	14.57	12.35	11.55	14.74
γ 44.0	11.93	10.00	8.58	10.90
γ 45.0	10.12	8.38	6.84	8.91
γ 46.0	9.04	7.45	6.03	7.74

Candela Tabulation - (Cont.)

V/H	C0.0	C90.0	C180.0	C270.0
γ 47.0	8.28	6.80	5.54	7.05
γ 48.0	7.66	6.25	5.18	6.56
γ 49.0	7.10	5.74	4.82	6.16
γ 50.0	6.54	5.18	4.43	5.79
γ 51.0	5.86	4.53	3.93	5.29
γ 52.0	5.39	4.13	3.62	4.81
γ 53.0	4.97	3.79	3.38	4.50
γ 54.0	4.63	3.50	3.17	4.25
γ 55.0	4.35	3.27	3.01	4.03
γ 56.0	4.10	3.05	2.86	3.83
γ 57.0	3.86	2.84	2.72	3.65
γ 58.0	3.63	2.65	2.58	3.47
γ 59.0	3.44	2.47	2.44	3.32
γ 60.0	3.25	2.32	2.32	3.17
γ 61.0	3.08	2.16	2.20	3.01
γ 62.0	2.90	2.02	2.07	2.87
γ 63.0	2.74	1.87	1.96	2.73
γ 64.0	2.59	1.74	1.84	2.59
γ 65.0	2.42	1.61	1.72	2.45
γ 66.0	2.29	1.49	1.61	2.34
γ 67.0	2.15	1.37	1.51	2.22
γ 68.0	2.02	1.24	1.41	2.09
γ 69.0	1.89	1.15	1.31	1.98
γ 70.0	1.75	1.02	1.21	1.85
γ 71.0	1.62	0.90	1.09	1.72
γ 72.0	1.47	0.78	0.97	1.59
γ 73.0	1.35	0.65	0.85	1.46
γ 74.0	1.22	0.54	0.73	1.34
γ 75.0	1.10	0.43	0.63	1.21
γ 76.0	0.98	0.34	0.52	1.09
γ 77.0	0.86	0.24	0.42	0.98
γ 78.0	0.75	0.14	0.32	0.87
γ 79.0	0.65	0.06	0.22	0.75
γ 80.0	0.56	0.00	0.12	0.65
γ 81.0	0.45	0.00	0.04	0.54
γ 82.0	0.36	0.00	0.00	0.43
γ 83.0	0.27	0.00	0.00	0.35
γ 84.0	0.19	0.00	0.00	0.26
γ 85.0	0.10	0.00	0.00	0.17
γ 86.0	0.02	0.00	0.00	0.08
γ 87.0	0.00	0.00	0.00	0.00
γ 88.0	0.00	0.00	0.00	0.00
γ 89.0	0.00	0.00	0.00	0.00
γ 90.0	0.00	0.00	0.00	0.00
γ 91.0	0.00	0.00	0.00	0.00
γ 92.0	0.00	0.00	0.00	0.00
γ 93.0	0.00	0.00	0.00	0.00

---



Candela Tabulation - (Cont.)

V/H	C0.0	C90.0	C180.0	C270.0
γ 94.0	0.00	0.00	0.00	0.00
γ 95.0	0.00	0.00	0.00	0.00
γ 96.0	0.00	0.00	0.00	0.00
γ 97.0	0.00	0.00	0.00	0.00
γ 98.0	0.00	0.00	0.00	0.00
γ 99.0	0.00	0.00	0.00	0.00
γ 100.0	0.00	0.00	0.00	0.00
γ 101.0	0.00	0.00	0.00	0.00
γ 102.0	0.00	0.00	0.00	0.00
γ 103.0	0.00	0.00	0.00	0.00
γ 104.0	0.00	0.00	0.00	0.00
γ 105.0	0.00	0.00	0.00	0.00
γ 106.0	0.00	0.00	0.00	0.00
γ 107.0	0.00	0.00	0.00	0.00
γ 108.0	0.00	0.00	0.00	0.00
γ 109.0	0.00	0.00	0.00	0.00
γ 110.0	0.00	0.00	0.00	0.00
γ 111.0	0.00	0.00	0.00	0.00
γ 112.0	0.00	0.00	0.00	0.00
γ 113.0	0.00	0.00	0.00	0.00
γ 114.0	0.00	0.00	0.00	0.00
γ 115.0	0.00	0.00	0.00	0.00
γ 116.0	0.00	0.00	0.00	0.00
γ 117.0	0.00	0.00	0.00	0.00
γ 118.0	0.00	0.00	0.00	0.00
γ 119.0	0.00	0.00	0.00	0.00
γ 120.0	0.00	0.00	0.00	0.00
γ 121.0	0.00	0.00	0.00	0.00
γ 122.0	0.00	0.00	0.00	0.00
γ 123.0	0.00	0.00	0.00	0.00
γ 124.0	0.00	0.00	0.00	0.00
γ 125.0	0.00	0.00	0.00	0.00
γ 126.0	0.00	0.00	0.00	0.00
γ 127.0	0.00	0.00	0.00	0.00
γ 128.0	0.00	0.00	0.00	0.00
γ 129.0	0.00	0.00	0.00	0.00
γ 130.0	0.00	0.00	0.00	0.00
γ 131.0	0.00	0.00	0.00	0.00
γ 132.0	0.00	0.00	0.00	0.00
γ 133.0	0.00	0.00	0.00	0.00
γ 134.0	0.00	0.00	0.00	0.00
γ 135.0	0.00	0.00	0.00	0.00
γ 136.0	0.00	0.00	0.00	0.00
γ 137.0	0.00	0.00	0.00	0.00
γ 138.0	0.00	0.00	0.00	0.00
γ 139.0	0.00	0.00	0.00	0.00
γ 140.0	0.00	0.00	0.00	0.06

---

Candela Tabulation - (Cont.)

V/H	C0.0	C90.0	C180.0	C270.0
γ 141.0	0.05	0.00	0.04	0.12
γ 142.0	0.12	0.00	0.10	0.18
γ 143.0	0.18	0.05	0.17	0.24
γ 144.0	0.24	0.11	0.23	0.30
γ 145.0	0.31	0.16	0.30	0.36
γ 146.0	0.36	0.23	0.36	0.42
γ 147.0	0.44	0.29	0.43	0.48
γ 148.0	0.50	0.35	0.50	0.55
γ 149.0	0.55	0.41	0.56	0.60
γ 150.0	0.61	0.47	0.63	0.65
γ 151.0	0.66	0.53	0.69	0.71
γ 152.0	0.72	0.58	0.74	0.77
γ 153.0	0.77	0.63	0.79	0.82
γ 154.0	0.82	0.68	0.85	0.86
γ 155.0	0.87	0.74	0.89	0.92
γ 156.0	0.91	0.79	0.93	0.95
γ 157.0	0.95	0.83	0.98	0.98
γ 158.0	0.99	0.86	1.02	1.03
γ 159.0	1.01	0.89	1.06	1.05
γ 160.0	1.04	0.93	1.09	1.07
γ 161.0	1.07	0.96	1.11	1.10
γ 162.0	1.10	0.98	1.13	1.11
γ 163.0	1.11	1.00	1.15	1.13
γ 164.0	1.12	1.01	1.15	1.14
γ 165.0	1.11	1.02	1.16	1.14
γ 166.0	1.13	1.03	1.18	1.15
γ 167.0	1.14	1.03	1.18	1.15
γ 168.0	1.14	1.04	1.18	1.16
γ 169.0	1.15	1.05	1.18	1.16
γ 170.0	1.15	1.05	1.18	1.16
γ 171.0	1.17	1.06	1.18	1.15
γ 172.0	1.17	1.07	1.19	1.17
γ 173.0	1.18	1.09	1.19	1.17
γ 174.0	1.20	1.11	1.19	1.17
γ 175.0	1.21	1.12	1.20	1.19
γ 176.0	1.21	1.13	1.21	1.19
γ 177.0	1.22	1.14	1.22	1.21
γ 178.0	1.24	1.15	1.22	1.21
γ 179.0	1.24	1.17	1.22	1.22
γ 180.0	1.22	1.22	1.22	1.22