



## Packaging

Box Dimensions	L156 x W82 x H81mm
Box Net Weight	0.369Kg
Box Gross Weight	0.423Kg
Carton Dimensions	L425 x W325 x H345 mm/40 PCS
Carton Net Weight	14.76Kg
Carton Gross Weight	18.06Kg

## FEATURES

- Modular design, with replaceable LED light source inside.
- There are four color anti-glare reflectors optional.
- 5-year guarantee.

## Technical Data

Input Voltage/Hz	AC200-240V 50/60Hz
Output Voltage/Current	DC36V/120mA
Power	5.5W
Rated Input Current	0.03A
PF value	>0.78
THD	<35%
Ingress Protection	IP20
Operating Temperature	-10–40°C
Dimmability	Triac dimmable with <b>DIMMATE</b> driver

## Optical Data

LED Brand	Bridgelux COB LED
CRI	Ra> 80, Ra> 90
Colour temperature	2700K/3000K/4000K
System luminous efficacy up to	112lm/W



Model	CCT		Beam Angle	Lumen	Efficacy		Beam Angle	Lumen	Efficacy
SD06-06-XX-01	2700K	CRI 80+	15°	418lm	72lm/W	CRI 90+	15°	365lm	64lm/W
			24°	439lm	76lm/W		24°	383lm	68lm/W
			36°	436lm	76lm/W		36°	389lm	68lm/W
			60°	408lm	71lm/W		60°	368lm	64lm/W
SD06-06-XX-01	3000K		15°	457lm	78lm/W		15°	391lm	69lm/W
			24°	470lm	81lm/W		24°	418lm	74lm/W
			36°	469lm	81lm/W		36°	411lm	73lm/W
			60°	440lm	76lm/W		60°	380lm	68lm/W
SD06-06-XX-01	4000K		15°	462lm	83lm/W		15°	404lm	72lm/W
			24°	514lm	92lm/W		24°	427lm	76lm/W
			36°	520lm	93lm/W		36°	433lm	77lm/W
			60°	496lm	87lm/W		60°	411lm	72lm/W

## ECLIPSE CONSEIL

Siège : +33 (1) 79 30 48 19- Showroom Paris : +33 (1) 78 95 50 14 - Mob : +33 (6) 87 82 12 04  
Siège social : 7 rue Prudent Neel 92500 Rueil-Malmaison - Showroom : 1 rue Dulong 75017 PARIS