



## FEATURES

- Modular Design.
- System power up to 30W.
- Interchangeable anti-glare reflector.
- 5-year guarantee.




## Technical Data

|                        |                                |
|------------------------|--------------------------------|
| Input Voltage/Hz       | AC200-240V 50/60Hz             |
| Output Voltage/Current | DC36V/580mA                    |
| Power                  | 23W                            |
| Rated Input Current    | 0.115A                         |
| PF value               | >0.9                           |
| THD                    | <20%                           |
| Ingress Protection     | IP20                           |
| Operating Temperature  | -10—40°C                       |
| Dimmability            | Non-dimmable with AcTEC driver |

## Optical Data

|                                |                                                    |
|--------------------------------|----------------------------------------------------|
| LED Brand                      | Bridgelux SMD LED                                  |
| CRI                            | Ra > 92                                            |
| Beam Angle                     | 60°/70°                                            |
| Colour temperature             | 2700k/3000K/4000K/5000K<br>2500k/2700K/3500K/4500K |
| System luminous efficacy up to | 97.9lm/W                                           |



## Packaging

|                     |                              |
|---------------------|------------------------------|
| Box Dimensions      | L155 x W155 x H200mm         |
| Box Net Weight      | 1.55Kg                       |
| Box Gross Weight    | 1.82Kg                       |
| Carton Dimensions   | L480 x W325 x H425 mm/12 PCS |
| Carton Net Weight   | 18.6Kg                       |
| Carton Gross Weight | 22.5Kg                       |



| Model         | CCT   |         | Beam Angle | Lumen  | Efficacy | Beam Angle | Lumen  | Efficacy |
|---------------|-------|---------|------------|--------|----------|------------|--------|----------|
| SD07-25-XX-01 | 2700K | CRI 92+ | 70°        | 2101lm | 91.5lm/W | 60°        | 1788lm | 77.8lm/W |
| SD07-25-XX-01 | 3000K |         | 70°        | 2219lm | 96.2lm/W | 60°        | 1866lm | 81.9lm/W |
| SD07-25-XX-01 | 4000K |         | 70°        | 2289lm | 97.3lm/W | 60°        | 1922lm | 83.3lm/W |
| SD07-25-XX-01 | 5000K |         | 70°        | 2263lm | 97.9lm/W | 60°        | 1911lm | 83.2lm/W |

Reflector



| Model         | CCT   |         | Beam Angle | Lumen  | Efficacy |
|---------------|-------|---------|------------|--------|----------|
| SD07-25-XX-01 | 2500K | CRI 92+ | 70°        | 1898lm | 81lm/W   |
| SD07-25-XX-01 | 2700K |         | 70°        | 1943lm | 85.7lm/W |
| SD07-25-XX-01 | 3500K |         | 70°        | 1987lm | 86.4lm/W |
| SD07-25-XX-01 | 4500K |         | 70°        | 1961lm | 85.6lm/W |

Reflector



## ECLIPSE CONSEIL

Siège : +33 (1) 79 30 48 19- Showroom Paris : +33 (1) 78 95 50 14 - Mob : +33 (6) 87 82 12 04  
Siège social : 7 rue Prudent Neel 92500 Rueil-Malmaison - Showroom : 1 rue Dulong 75017 PARIS