


6W 9W  
POWER



Black / White



## Packaging

Box Dimensions	L175 x W165 x H145mm
Box Net Weight	0.684Kg
Box Gross Weight	0.94Kg
Carton Dimensions	L540 x W510 x H315 mm/18 PCS
Carton Net Weight	12.31Kg
Carton Gross Weight	17.62Kg

## FEATURES

- Maximum 45° vertical rotation can be created on the main body.
- Optic interchangeable.
- Power selectable.
- Flicker-free internal driver.
- Compatible with leading and trailing edge phase cut dimmers.
- 5-year guarantee.

## Technical Data

Input Voltage/Hz	AC200-240V 50/60Hz
Output Voltage/Current	DC32.5V/210mA(8.2W)   DC31.5V/145mA(6W)
Power	8.2W   6W
Rated Input Current	0.041A(8.2W)   0.030A(6W)
THD	<25%(8.2W)   <35%(6W)
PF value	>0.9(8.2W)   >0.8(6W)
Ingress Protection	IP20
Operating Temperature	-10—40°C
Dimmability	Triac dimmable with <b>DIMMATE</b> driver

## Optical Data

LED Brand	Bridgelux COB LED
CRI	Ra > 90
Beam Angle	150°
Colour temperatures	1800K-3000K
System luminous efficacy up to	69lm/W



RoHS CE



Model	CCT		Beam Angle	Lumen	Efficacy		Beam Angle	Lumen	Efficacy
SD09-09-DW-03	1800K-3000K	6W	150°	374lm	64lm/W	8.2W	150°	576lm	69lm/W

## ECLIPSE CONSEIL

Siège : +33 (1) 79 30 48 19- Showroom Paris : +33 (1) 78 95 50 14 - Mob : +33 (6) 87 82 12 04  
Siège social : 7 rue Prudent Neel 92500 Rueil-Malmaison - Showroom : 1 rue Dulong 75017 PARIS