


6W 9W  
POWER



Black / White



## Packaging

Box Dimensions	L175 x W165 x H145mm
Box Net Weight	0.684Kg
Box Gross Weight	0.94Kg
Carton Dimensions	L540 x W510 x H315 mm/18 PCS
Carton Net Weight	12.31Kg
Carton Gross Weight	17.62Kg

## FEATURES

- Maximum 45°vertical rotation can be created on the main body.
- Optic interchangeable.
- Power selectable.
- Flicker-free internal driver.
- Compatible with leading and trailing edge phase cut dimmers.
- 5-year guarantee.

## Technical Data

Input Voltage/Hz	AC200-240V 50/60Hz
Output Voltage/Current	DC34V/210mA(9W) DC33V/145mA(6W)
Power	9W 6W
Rated Input Current	0.045A
THD	<25%(9W)   <35%(6W)
PF value	>0.9(9W)   >0.8(6W)
Ingress Protection	IP20
Operating Temperature	-10—40℃
Dimmability	Triac dimmable with <b>DIMMATE</b> driver

## Optical Data

LED Brand	Bridgelux COB LED
CRI	Ra> 90
Beam Angle	150°
Colour temperatures	2700K/3000K/4000K
System luminous efficacy up to	82lm/W



Model	CCT	Beam Angle	Lumen	Efficacy	Beam Angle	Lumen	Efficacy
SD09-09-XX-03	2700K	150°	441lm	73lm/W	150°	655lm	75lm/W
SD09-09-XX-03	3000K	150°	475lm	78lm/W	150°	695lm	80lm/W
SD09-09-XX-03	4000K	150°	496lm	81lm/W	150°	726lm	83lm/W

## ECLIPSE CONSEIL

Siège : +33 (1) 79 30 48 19- Showroom Paris : +33 (1) 78 95 50 14 - Mob : +33 (6) 87 82 12 04  
Siège social : 7 rue Prudent Neel 92500 Rueil-Malmaison - Showroom : 1 rue Dulong 75017 PARIS