



Indoor Luminaire Photometric Data

Description Information

Luminary Name:ST02-03-PR-06 3000K RA90		Lum. Catalog:	Test ID: 01
Lamp Name:		Lamp Catalog: LED	Test Date: 2020/12/25
Manufacture: Shenzhen Norming Lighting Co.Ltd		Shld.Ang(°):	Test Machine:GON-2000
Test Lab: Quality Department		Frequency (Hz):	Lamp CCT (K): Ra:
Lum. Size (W*L*H):0.000m*0.000m*0.000m		Lum. Area (m2):0.000	Lum. W (kg): 0.000
Test System: C, γ	Test Step: C=30.0 γ=1.0	Temp. (°C): 25	Humidity(%): 50.0


Character Parameter

Lamp Speciality Parameter		Luminaire Speciality Parameter	
Rated Flux(lm): 66.900	Luminary Flux(lm): 66.903	Field Angle(10%Imax): 80.0(°)	
Rated Power(W):	Luminary Efficiency: 100.00%	Down Lumens&Percent: 66.903lm 100.00%	
Rated Voltage(V):	Luminary EER(lm/W): 22.353	Up Lumens&Percent: 0.000lm 0.00%	
Tested Power(W): 2.993	Max. Candela(cd): 95.706	S/MH: C0_a180=0.978 C90_270=0.649	
Lamps' Inside: 1	Max Cand@Ang. (°): C=0.0 γ=21.0	CIE Type: Semi-Direct	
Tested Electrics (V, A, pf):240.4, 0.014, 0.855	Beam Angle(50%Imax): 53.9(°)	ErP ϕ use(90°): 59.626lm	
Lamp Size (W*L*H):0.000m*0.000m*0.000m	Left=-10.0°, Right=43.9°	IRF(%): 182.259	



2D Plane Light Intensity Distribution Curve


Lum. Name: ST02-03-PR-06 3000K RA90	Lum. Catelog:	Test ID: 01
Lamp Name:	Lamp Catelog: LED	Test Lab: Quality Deparment
Manufacture: Shenzhen Norming Lighting Co.Ltd	Test Machine:GON-2000	Test Date: 2020/12/25



3D Light Intensity Distribution Modal

Lum. Name: ST02-03-PR-06 3000K RA90	Lum. Catalog:	Test ID: 01
Lamp Name:	Lamp Catalog: LED	Test Lab: Quality Department
Manufacture: Shenzhen Norming Lighting Co.Ltd	Test Machine:GON-2000	Test Date: 2020/12/25

3D Light Intensity Distribution Modal



Zonal Flux Tabulation


Zone(γ)	Zone Flux (lm)	Sums Flux (lm)	Zone%Lamp	Sums%Lamp	Zone(γ)	Zone Flux (lm)	Sums Flux (lm)	Zone%Lamp	Sums%Lamp
0.0-1.0	0.07	0.07	0.10	0.10	47.0-48.0	0.60	61.68	0.90	92.20
1.0-2.0	0.21	0.28	0.31	0.42	48.0-49.0	0.54	62.22	0.81	93.01
2.0-3.0	0.35	0.63	0.52	0.94	49.0-50.0	0.49	62.71	0.73	93.74
3.0-4.0	0.49	1.12	0.73	1.67	50.0-51.0	0.45	63.16	0.67	94.41
4.0-5.0	0.63	1.75	0.94	2.61	51.0-52.0	0.41	63.58	0.62	95.03
5.0-6.0	0.76	2.51	1.14	3.75	52.0-53.0	0.38	63.96	0.57	95.61
6.0-7.0	0.89	3.40	1.33	5.08	53.0-54.0	0.36	64.32	0.53	96.14
7.0-8.0	1.01	4.40	1.50	6.58	54.0-55.0	0.33	64.64	0.49	96.63
8.0-9.0	1.12	5.52	1.67	8.25	55.0-56.0	0.30	64.95	0.45	97.08
9.0-10.0	1.22	6.74	1.82	10.07	56.0-57.0	0.28	65.22	0.41	97.49
10.0-11.0	1.31	8.05	1.96	12.04	57.0-58.0	0.25	65.47	0.37	97.87
11.0-12.0	1.39	9.45	2.08	14.12	58.0-59.0	0.23	65.70	0.34	98.21
12.0-13.0	1.46	10.91	2.18	16.30	59.0-60.0	0.20	65.90	0.30	98.51
13.0-14.0	1.52	12.42	2.27	18.57	60.0-61.0	0.18	66.08	0.27	98.78
14.0-15.0	1.57	13.99	2.35	20.92	61.0-62.0	0.16	66.24	0.24	99.02
15.0-16.0	1.61	15.61	2.41	23.33	62.0-63.0	0.14	66.38	0.21	99.23
16.0-17.0	1.65	17.25	2.46	25.79	63.0-64.0	0.12	66.50	0.18	99.41
17.0-18.0	1.67	18.92	2.50	28.28	64.0-65.0	0.10	66.61	0.15	99.56
18.0-19.0	1.69	20.61	2.53	30.81	65.0-66.0	0.09	66.69	0.13	99.69
19.0-20.0	1.71	22.32	2.55	33.36	66.0-67.0	0.07	66.76	0.10	99.79
20.0-21.0	1.72	24.04	2.57	35.93	67.0-68.0	0.05	66.81	0.08	99.87
21.0-22.0	1.73	25.76	2.58	38.51	68.0-69.0	0.04	66.85	0.06	99.92
22.0-23.0	1.73	27.49	2.59	41.10	69.0-70.0	0.02	66.87	0.04	99.96
23.0-24.0	1.74	29.23	2.60	43.70	70.0-71.0	0.02	66.89	0.02	99.98
24.0-25.0	1.74	30.98	2.60	46.30	71.0-72.0	0.01	66.90	0.01	100.00
25.0-26.0	1.74	32.72	2.60	48.91	72.0-73.0	0.00	66.90	0.01	100.00
26.0-27.0	1.74	34.46	2.60	51.50	73.0-74.0	0.00	66.90	0.00	100.00
27.0-28.0	1.73	36.18	2.58	54.08	74.0-75.0	0.00	66.90	0.00	100.00
28.0-29.0	1.71	37.90	2.56	56.65	75.0-76.0	0.00	66.90	0.00	100.00
29.0-30.0	1.70	39.60	2.54	59.19	76.0-77.0	0.00	66.90	0.00	100.00
30.0-31.0	1.68	41.28	2.51	61.70	77.0-78.0	0.00	66.90	0.00	100.00
31.0-32.0	1.66	42.93	2.47	64.18	78.0-79.0	0.00	66.90	0.00	100.00
32.0-33.0	1.62	44.56	2.42	66.60	79.0-80.0	0.00	66.90	0.00	100.00
33.0-34.0	1.58	46.13	2.36	68.96	80.0-81.0	0.00	66.90	0.00	100.00
34.0-35.0	1.53	47.67	2.29	71.25	81.0-82.0	0.00	66.90	0.00	100.00
35.0-36.0	1.49	49.16	2.22	73.48	82.0-83.0	0.00	66.90	0.00	100.00
36.0-37.0	1.43	50.59	2.14	75.62	83.0-84.0	0.00	66.90	0.00	100.00
37.0-38.0	1.37	51.96	2.05	77.67	84.0-85.0	0.00	66.90	0.00	100.00
38.0-39.0	1.31	53.27	1.96	79.63	85.0-86.0	0.00	66.90	0.00	100.00
39.0-40.0	1.25	54.52	1.86	81.49	86.0-87.0	0.00	66.90	0.00	100.00
40.0-41.0	1.18	55.70	1.77	83.26	87.0-88.0	0.00	66.90	0.00	100.00
41.0-42.0	1.11	56.81	1.66	84.92	88.0-89.0	0.00	66.90	0.00	100.00
42.0-43.0	1.02	57.84	1.53	86.45	89.0-90.0	0.00	66.90	0.00	100.00
43.0-44.0	0.93	58.77	1.40	87.85	90.0-91.0	0.00	66.90	0.00	100.00
44.0-45.0	0.85	59.63	1.28	89.13	91.0-92.0	0.00	66.90	0.00	100.00
45.0-46.0	0.77	60.40	1.15	90.28	92.0-93.0	0.00	66.90	0.00	100.00
46.0-47.0	0.68	61.08	1.02	91.30	93.0-94.0	0.00	66.90	0.00	100.00

Zonal Flux Tabulation - (Cont.)

Zone(γ)	Zone Flux (lm)	Sums Flux (lm)	Zone%Lamp	Sums%Lamp	Zone(γ)	Zone Flux (lm)	Sums Flux (lm)	Zone%Lamp	Sums%Lamp
94.0-95.0	0.00	66.90	0.00	100.00	141.0-142.0	0.00	66.90	0.00	100.00
95.0-96.0	0.00	66.90	0.00	100.00	142.0-143.0	0.00	66.90	0.00	100.00
96.0-97.0	0.00	66.90	0.00	100.00	143.0-144.0	0.00	66.90	0.00	100.00
97.0-98.0	0.00	66.90	0.00	100.00	144.0-145.0	0.00	66.90	0.00	100.00
98.0-99.0	0.00	66.90	0.00	100.00	145.0-146.0	0.00	66.90	0.00	100.00
99.0-100.0	0.00	66.90	0.00	100.00	146.0-147.0	0.00	66.90	0.00	100.00
100.0-101.0	0.00	66.90	0.00	100.00	147.0-148.0	0.00	66.90	0.00	100.00
101.0-102.0	0.00	66.90	0.00	100.00	148.0-149.0	0.00	66.90	0.00	100.00
102.0-103.0	0.00	66.90	0.00	100.00	149.0-150.0	0.00	66.90	0.00	100.00
103.0-104.0	0.00	66.90	0.00	100.00	150.0-151.0	0.00	66.90	0.00	100.00
104.0-105.0	0.00	66.90	0.00	100.00	151.0-152.0	0.00	66.90	0.00	100.00
105.0-106.0	0.00	66.90	0.00	100.00	152.0-153.0	0.00	66.90	0.00	100.00
106.0-107.0	0.00	66.90	0.00	100.00	153.0-154.0	0.00	66.90	0.00	100.00
107.0-108.0	0.00	66.90	0.00	100.00	154.0-155.0	0.00	66.90	0.00	100.00
108.0-109.0	0.00	66.90	0.00	100.00	155.0-156.0	0.00	66.90	0.00	100.00
109.0-110.0	0.00	66.90	0.00	100.00	156.0-157.0	0.00	66.90	0.00	100.00
110.0-111.0	0.00	66.90	0.00	100.00	157.0-158.0	0.00	66.90	0.00	100.00
111.0-112.0	0.00	66.90	0.00	100.00	158.0-159.0	0.00	66.90	0.00	100.00
112.0-113.0	0.00	66.90	0.00	100.00	159.0-160.0	0.00	66.90	0.00	100.00
113.0-114.0	0.00	66.90	0.00	100.00	160.0-161.0	0.00	66.90	0.00	100.00
114.0-115.0	0.00	66.90	0.00	100.00	161.0-162.0	0.00	66.90	0.00	100.00
115.0-116.0	0.00	66.90	0.00	100.00	162.0-163.0	0.00	66.90	0.00	100.00
116.0-117.0	0.00	66.90	0.00	100.00	163.0-164.0	0.00	66.90	0.00	100.00
117.0-118.0	0.00	66.90	0.00	100.00	164.0-165.0	0.00	66.90	0.00	100.00
118.0-119.0	0.00	66.90	0.00	100.00	165.0-166.0	0.00	66.90	0.00	100.00
119.0-120.0	0.00	66.90	0.00	100.00	166.0-167.0	0.00	66.90	0.00	100.00
120.0-121.0	0.00	66.90	0.00	100.00	167.0-168.0	0.00	66.90	0.00	100.00
121.0-122.0	0.00	66.90	0.00	100.00	168.0-169.0	0.00	66.90	0.00	100.00
122.0-123.0	0.00	66.90	0.00	100.00	169.0-170.0	0.00	66.90	0.00	100.00
123.0-124.0	0.00	66.90	0.00	100.00	170.0-171.0	0.00	66.90	0.00	100.00
124.0-125.0	0.00	66.90	0.00	100.00	171.0-172.0	0.00	66.90	0.00	100.00
125.0-126.0	0.00	66.90	0.00	100.00	172.0-173.0	0.00	66.90	0.00	100.00
126.0-127.0	0.00	66.90	0.00	100.00	173.0-174.0	0.00	66.90	0.00	100.00
127.0-128.0	0.00	66.90	0.00	100.00	174.0-175.0	0.00	66.90	0.00	100.00
128.0-129.0	0.00	66.90	0.00	100.00	175.0-176.0	0.00	66.90	0.00	100.00
129.0-130.0	0.00	66.90	0.00	100.00	176.0-177.0	0.00	66.90	0.00	100.00
130.0-131.0	0.00	66.90	0.00	100.00	177.0-178.0	0.00	66.90	0.00	100.00
131.0-132.0	0.00	66.90	0.00	100.00	178.0-179.0	0.00	66.90	0.00	100.00
132.0-133.0	0.00	66.90	0.00	100.00	179.0-180.0	0.00	66.90	0.00	100.00
133.0-134.0	0.00	66.90	0.00	100.00					
134.0-135.0	0.00	66.90	0.00	100.00					
135.0-136.0	0.00	66.90	0.00	100.00					
136.0-137.0	0.00	66.90	0.00	100.00					
137.0-138.0	0.00	66.90	0.00	100.00					
138.0-139.0	0.00	66.90	0.00	100.00					
139.0-140.0	0.00	66.90	0.00	100.00					
140.0-141.0	0.00	66.90	0.00	100.00					

Rectangle ISO Lighting Intensity Diagram


Lum. Name: ST02-03-PR-06 3000K RA90	Lum. Catalog:	Test ID: 01
Lamp Name:	Lamp Catalog: LED	Test Lab: Quality Department
Manufacture: Shenzhen Norming Lighting Co.Ltd	Test Machine:GON-2000	Test Date: 2020/12/25



## Plane ISO-Illuminance Diagram

Lum. Name: ST02-03-PR-06 3000K RA90	Lum. Catalog:	Test ID: 01
Lamp Name:	Lamp Catalog: LED	Test Lab: Quality Department
Manufacture: Shenzhen Norming Lighting Co.Ltd	Test Machine:GON-2000	Test Date: 2020/12/25

### Plane ISO-Illuminance Curve



Working Plane Maximum Illuminance Position(d/h):H0.0 V0.2


# IES Indoor Report

Photometric Filename:ST02-03-PR-06 3000K RA90 .IES

## 3D Plane ISO Illuminance Diagram

Lum. Name: ST02-03-PR-06 3000K RA90	Lum. Catalog:	Test ID: 01
Lamp Name:	Lamp Catalog: LED	Test Lab: Quality Department
Manufacture: Shenzhen Norming Lighting Co.Ltd	Test Machine:GON-2000	Test Date: 2020/12/25

## 3D Plane Illuminance Modal




Curves: 3D Model — 90% — 80% — 70% — 60% — 50% — 40% — 30% — 20% — 10% —  
View Angles(deg): 0 Height(m): 3.0 Distance(m): 10.0



Space ISO Illuminance Diagram

Lum. Name: ST02-03-PR-06 3000K RA90	Lum. Catalog:	Test ID: 01
Lamp Name:	Lamp Catalog: LED	Test Lab: Quality Department
Manufacture: Shenzhen Norming Lighting Co.Ltd	Test Machine:GON-2000	Test Date: 2020/12/25


Space ISO Illuminance Curve



Space Plane Maximum Illuminance and @Angle:85.12lx,12.0deg  
Plane Maximum Lighting Intensity and @Angle:95.706cd,0deg

Illuminance-Distance Diagram

Lum. Name: ST02-03-PR-06 3000K RA90	Lum. Catalog:	Test ID: 01
Lamp Name:	Lamp Catalog: LED	Test Lab: Quality Department
Manufacture: Shenzhen Norming Lighting Co.Ltd	Test Machine:GON-2000	Test Date: 2020/12/25



Indoor Luminance Limiting Curves

Lum. Name: ST02-03-PR-06 3000K RA90	Lum. Catalog:	Test ID: 01
Lamp Name:	Lamp Catalog: LED	Test Lab: Quality Department
Manufacture: Shenzhen Norming Lighting Co.Ltd	Test Machine:GON-2000	Test Date: 2020/12/25

Glare Grade Table

GI	Quality	Using Illuminance							
1.15	A	2000	1000	500	<=300				
1.5	B		2000	1000	500	<=300			
1.85	C			2000	1000	500	<=300		
2.2	D				2000	1000	500	<=300	
2.55	E	a				2000	1000	500	<=300
			b	c	d	e	f	g	h

Luminance Table

Gama(deg)	45	50	55	60	65	70	75	80	85
C0	0	0	0	0	0	0	0	0	0
C90	0	0	0	0	0	0	0	0	0


Luminance Limiting Curve



Luminous Size: Length(m)=0.000 Width(m)=0.000 Height(m)=0.000 Area(m^2)=0.000000  
Luminous Type: Without Luminous Side  
Luminous Curves: C0-C180 Color: C90-C270 Color:

Indoor Budgetary Estimate Table

Lum. Name: ST02-03-PR-06 3000K RA90	Lum. Catalog:	Test ID: 01
Lamp Name:	Lamp Catalog: LED	Test Lab: Quality Department
Manufacture: Shenzhen Norming Lighting Co.Ltd	Test Machine:GON-2000	Test Date: 2020/12/25



Indoor Coefficient of Utilization Table

Lum. Name: ST02-03-PR-06 3000K RA90	Lum. Catelog:	Test ID: 01
Lamp Name:	Lamp Catelog: LED	Test Lab: Quality Deparment
Manufacture: Shenzhen Norming Lighting Co.Ltd	Test Machine:GON-2000	Test Date: 2020/12/25

Coefficients of Utilization - Zonal Cavity Method																		
Coef.	Effective Floor Cavity Reflectance RFC=0.20																	
RhoCC (%)	80				70				50			30			10			0
RhoW (%)	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR	Coefficient of Utilization(%)																	
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	113	110	107	105	110	108	105	103	104	102	100	100	98	97	97	95	94	92
2	107	101	97	93	104	100	96	92	96	93	90	93	91	88	91	88	86	85
3	101	94	88	84	99	92	87	83	89	85	82	87	83	80	85	82	79	77
4	95	87	80	76	93	85	80	75	83	78	74	81	77	74	79	76	73	71
5	89	80	74	69	88	79	73	69	77	72	68	76	71	68	74	70	67	65
6	84	75	68	63	83	74	68	63	72	67	63	71	66	62	69	65	62	60
7	80	70	63	59	78	69	63	58	68	62	58	66	61	58	65	61	57	56
8	76	65	59	54	74	65	59	54	64	58	54	62	57	54	61	57	53	52
9	72	61	55	51	71	61	55	51	60	54	50	59	54	50	58	53	50	49
10	68	58	51	47	67	57	51	47	56	51	47	56	51	47	55	50	47	45

Unified Glare Rating Table

Lum. Name: ST02-03-PR-06 3000K RA90	Lum. Catelog:	Test ID: 01
Lamp Name:	Lamp Catalog: LED	Test Lab: Quality Deparment
Manufacture: Shenzhen Norming Lighting Co.Ltd	Test Machine:GON-2000	Test Date: 2020/12/25

Unified Glare Rating Table

Ceiling RCC	0.70	0.70	0.50	0.50	0.30	0.70	0.70	0.50	0.50	0.30	
Wall RW	0.50	0.30	0.50	0.30	0.30	0.50	0.30	0.50	0.30	0.30	
Floor RFC	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	
Room Size	Vewed crosswise					Vewed endwise					
X=2H    Y=2H	-10.4	-9.3	-10.1	-9.0	-8.7	-10.4	-9.3	-10.1	-9.0	-8.7	
	Y=3H	-10.6	-9.6	-10.2	-9.3	-8.9	-10.6	-9.6	-10.2	-9.3	-8.9
	Y=4H	-10.7	-9.8	-10.3	-9.4	-9.1	-10.7	-9.8	-10.3	-9.4	-9.1
	Y=6H	-10.8	-10.0	-10.4	-9.6	-9.2	-10.8	-10.0	-10.4	-9.6	-9.2
	Y=8H	-10.9	-10.1	-10.4	-9.7	-9.3	-10.9	-10.1	-10.4	-9.7	-9.3
	Y=12H	-10.9	-10.2	-10.5	-9.8	-9.3	-10.9	-10.2	-10.5	-9.8	-9.3
X=4H    Y=2H	-10.7	-9.8	-10.3	-9.4	-9.1	-10.7	-9.8	-10.3	-9.4	-9.1	
	Y=3H	-10.9	-10.2	-10.5	-9.7	-9.3	-10.9	-10.2	-10.5	-9.7	-9.3
	Y=4H	-11.0	-10.3	-10.6	-9.9	-9.5	-11.0	-10.3	-10.6	-9.9	-9.5
	Y=6H	-11.1	-10.5	-10.6	-10.1	-9.6	-11.1	-10.5	-10.6	-10.1	-9.6
	Y=8H	-11.2	-10.6	-10.7	-10.2	-9.7	-11.2	-10.6	-10.7	-10.2	-9.7
	Y=12H	-11.2	-10.8	-10.7	-10.3	-9.8	-11.2	-10.8	-10.7	-10.3	-9.8
X=8H    Y=4H	-11.2	-10.6	-10.7	-10.2	-9.7	-11.2	-10.6	-10.7	-10.2	-9.7	
	Y=6H	-11.3	-10.9	-10.8	-10.4	-9.8	-11.3	-10.9	-10.8	-10.4	-9.8
	Y=8H	-11.4	-11.0	-10.8	-10.5	-10.0	-11.4	-11.0	-10.8	-10.5	-10.0
	Y=12H	-11.4	-11.1	-10.9	-10.6	-10.0	-11.4	-11.1	-10.9	-10.6	-10.0
X=12H    Y=4H	-11.2	-10.8	-10.7	-10.3	-9.8	-11.2	-10.8	-10.7	-10.3	-9.8	
	Y=6H	-11.3	-11.0	-10.8	-10.5	-10.0	-11.3	-11.0	-10.8	-10.5	-10.0
	Y=8H	-11.4	-11.1	-10.9	-10.6	-10.0	-11.4	-11.1	-10.9	-10.6	-10.0
Variations with the objerver position at spacings											
S=1.0H	0.0/0.0					0.0/0.0					
S=1.5H	0.0/0.0					0.0/0.0					
S=2.0H	0.0/0.0					0.0/0.0					
Reduced UGR Table:											
Nordic Standard Table:	BK0					BK0					
Correction Value	0.0					0.0					

o the CIE Pub.117, data has been corrected, refers to the lamp's lumens 8.2flm.

IES Indoor Report

Photometric Filename:ST02-03-PR-06 3000K RA90 .IES

---

Candela Tabulation

V/H	C0. 0	C30. 0	C60. 0	C90. 0	C120. 0	C150. 0	C180. 0
γ 0. 0	73. 19	73. 19	73. 19	73. 19	73. 19	73. 19	73. 19
γ 1. 0	74. 47	74. 64	72. 11	71. 53	72. 94	72. 71	75. 37
γ 2. 0	76. 34	76. 19	73. 36	71. 69	72. 24	71. 08	73. 51
γ 3. 0	78. 13	77. 79	74. 31	71. 70	71. 47	69. 48	71. 59
γ 4. 0	79. 91	79. 33	75. 20	71. 57	70. 43	67. 48	69. 58
γ 5. 0	81. 56	80. 63	75. 89	71. 15	69. 03	65. 25	67. 20
γ 6. 0	83. 18	81. 75	76. 37	70. 56	67. 15	62. 41	64. 48
γ 7. 0	84. 63	82. 88	76. 79	69. 63	64. 72	58. 96	60. 95
γ 8. 0	85. 96	83. 97	77. 03	68. 42	61. 83	55. 12	56. 54
γ 9. 0	87. 36	84. 87	77. 14	66. 98	59. 03	51. 23	51. 75
γ 10. 0	88. 74	85. 74	77. 12	64. 96	56. 37	47. 24	47. 88
γ 11. 0	89. 91	86. 56	77. 03	62. 68	53. 40	42. 60	44. 07
γ 12. 0	90. 96	87. 22	76. 64	60. 20	49. 44	37. 54	39. 19
γ 13. 0	91. 98	87. 57	76. 08	57. 54	44. 67	33. 21	34. 51
γ 14. 0	92. 86	87. 87	75. 32	54. 75	39. 90	30. 04	29. 60
γ 15. 0	93. 68	88. 11	74. 31	51. 90	35. 80	26. 70	25. 84
γ 16. 0	94. 26	88. 29	73. 01	48. 87	32. 33	22. 60	22. 59
γ 17. 0	94. 80	88. 29	71. 55	45. 71	28. 89	18. 75	19. 45
γ 18. 0	95. 32	88. 03	69. 72	42. 47	25. 17	16. 33	17. 02
γ 19. 0	95. 50	87. 75	67. 52	38. 70	21. 54	14. 65	15. 39
γ 20. 0	95. 65	87. 30	64. 99	34. 65	18. 77	13. 23	13. 94
γ 21. 0	95. 71	86. 73	62. 05	30. 66	16. 77	12. 06	12. 95
γ 22. 0	95. 43	85. 95	59. 11	26. 92	15. 24	11. 45	12. 32
γ 23. 0	94. 98	85. 02	56. 15	23. 56	13. 93	10. 96	11. 71
γ 24. 0	94. 23	83. 93	53. 44	20. 62	13. 10	10. 43	10. 97
γ 25. 0	93. 39	82. 83	50. 58	18. 09	12. 56	9. 75	10. 31
γ 26. 0	92. 47	81. 56	47. 20	16. 12	12. 03	9. 15	9. 73
γ 27. 0	91. 61	80. 18	43. 63	14. 63	11. 44	8. 65	9. 22
γ 28. 0	90. 44	78. 67	39. 97	13. 37	10. 74	8. 17	8. 73
γ 29. 0	89. 11	77. 05	36. 51	12. 48	10. 14	7. 73	8. 27
γ 30. 0	87. 45	75. 27	33. 37	11. 95	9. 63	7. 33	7. 83
γ 31. 0	85. 90	73. 26	30. 05	11. 44	9. 12	6. 93	7. 42
γ 32. 0	84. 17	71. 04	26. 56	10. 89	8. 66	6. 56	7. 03
γ 33. 0	82. 35	68. 53	23. 03	10. 24	8. 23	6. 21	6. 68
γ 34. 0	80. 50	65. 61	19. 99	9. 59	7. 85	5. 86	6. 32
γ 35. 0	78. 42	62. 13	17. 79	9. 05	7. 46	5. 54	5. 98
γ 36. 0	76. 32	58. 10	16. 11	8. 56	7. 09	5. 22	5. 66
γ 37. 0	74. 08	53. 39	14. 67	8. 10	6. 74	4. 93	5. 34
γ 38. 0	71. 53	48. 35	13. 64	7. 67	6. 40	4. 65	5. 07
γ 39. 0	68. 96	43. 49	12. 98	7. 28	6. 08	4. 38	4. 78
γ 40. 0	66. 33	38. 98	12. 32	6. 89	5. 78	4. 12	4. 50
γ 41. 0	63. 33	34. 77	11. 68	6. 51	5. 49	3. 88	4. 24
γ 42. 0	58. 96	30. 13	10. 89	6. 16	5. 20	3. 63	3. 99
γ 43. 0	53. 04	25. 68	10. 13	5. 83	4. 93	3. 40	3. 73
γ 44. 0	47. 38	21. 97	9. 49	5. 49	4. 67	3. 19	3. 50
γ 45. 0	42. 03	18. 93	8. 92	5. 19	4. 41	2. 96	3. 28
γ 46. 0	35. 27	15. 76	8. 37	4. 88	4. 17	2. 75	3. 06

---





**Photometric Filename:ST02-03-PR-06 3000K RA90 .IES**

## Candela Tabulation - (Cont.)

[illegible]

**Photometric Filename:ST02-03-PR-06 3000K RA90 .IES**

## Candela Tabulation - (Cont.)

[illegible]