



Cut-out: Ø45mm

FEATURES

- Made of die-casting.
- Powder coating finish from AkzoNobel.
- Interchangeable faceplate with magnetic design.
- High density COB with uniform lighting distribution.
- Compatible with leading and trailing edge phase cut dimmers.
- 5-year guarantee.

Technical Data

Input Voltage/Hz	AC200-240V 50/60Hz
Output Voltage/Current	DC33V/60mA
Power	3W
Rated Input Current	0.015A
THD	<30%
PF value	>0.82
Ingress Protection	IP54
Operating Temperature	-10—40°C
Dimmability	Triac dimmable with DIMMATE driver

Optical Data

LED Brand	Bridgelux COB LED
CRI	Ra>80, Ra>90
Colour temperatures	2700K/3000K/4000K
System luminous efficacy up to	27lm/W

Packaging

Box Dimensions	L65 x W65 x H110mm
Box Net Weight	0.108Kg
Box Gross Weight	0.133Kg
Carton Dimensions	L340 x W340 x H240 mm/50 PCS
Carton Net Weight	5.400Kg
Carton Gross Weight	7.320Kg



Specifications (White)

CCT	Asymmetric Beam Angle	CRI	Lumen	Efficacy	CRI	Lumen	Efficacy
2700K	15°		65lm	24lm/W		56lm	20lm/W
3000K	15°	80+	74lm	25lm/W	90+	54lm	20lm/W
4000K	15°		78lm	27lm/W		60lm	22lm/W

Specifications (Black)

CCT	Asymmetric Beam Angle	CRI	Lumen	Efficacy	CRI	Lumen	Efficacy
2700K	15°		28lm	10lm/W		25lm	9lm/W
3000K	15°	80+	30lm	11lm/W	90+	23lm	8lm/W
4000K	15°		33lm	11lm/W		26lm	9lm/W

ECLIPSE CONSEIL

Siège : +33 (1) 79 30 48 19- Showroom Paris : +33 (1) 78 95 50 14 - Mob : +33 (6) 87 82 12 04
Siège social : 7 rue Prudent Neel 92500 Rueil-Malmaison - Showroom : 1 rue Dulong 75017 PARIS