



Indoor Luminaire Photometric Data

Description Information

Luminary Name: ST02		Lum. Catalog:	Test ID: 01
Lamp Name:		Lamp Catalog: LED	Test Date: 2021/02/01
Manufacture: Shenzhen Norming Lighting Co.Ltd		Shld.Ang(°):	Test Machine:GON-2000
Test Lab: Quality Department		Frequency (Hz):	Lamp CCT (K): Ra:
Lum. Size (W*L*H):0.050m*0.000m*0.000m		Lum. Area (m2):0.002	Lum. W (kg): 0.000
Test System: C, γ	Test Step: C=30.0 γ=1.0	Temp. (°C): 25	Humidity(%): 50.0


Character Parameter

Lamp Speciality Parameter		Luminaire Speciality Parameter	
Rated Flux(lm): 78.480	Luminary Flux(lm): 78.482	Field Angle(10%Imax): 79.7(°)	
Rated Power(W):	Luminary Efficiency: 100.00%	Down Lumens&Percent: 78.482lm 100.00%	
Rated Voltage(V):	Luminary EER(lm/W): 28.716	Up Lumens&Percent: 0.000lm 0.00%	
Tested Power(W): 2.733	Max. Candela(cd): 120.277	S/MH: C0_a180=1.048 C90_270=0.592	
Lamps' Inside: 1	Max Cand@Ang. (°): C=0.0 γ=23.0	CIE Type: Semi-Direct	
Tested Electrics (V, A, pf):240.2, 0.013, 0.836	Beam Angle(50%Imax): 57.5(°)	ErP ϕ use(90°): 68.719lm	
Lamp Size (W*L*H):0.050m*0.000m*0.000m	Left=-9.6°, Right=47.9°	IRF(%): 187.972	



2D Plane Light Intensity Distribution Curve


Lum. Name:ST02	Lum. Catelog:	Test ID:01
Lamp Name:	Lamp Catelog:LED	Test Lab:Quality Department
Manufacture:Shenzhen Norming Lighting Co.Ltd	Test Machine:GON-2000	Test Date:2021/02/01



3D Light Intensity Distribution Modal

Lum. Name: ST02	Lum. Catalog:	Test ID: 01
Lamp Name:	Lamp Catalog: LED	Test Lab: Quality Department
Manufacture: Shenzhen Norming Lighting Co.Ltd	Test Machine:GON-2000	Test Date: 2021/02/01

3D Light Intensity Distribution Modal



IES Indoor Report

Photometric Filename:ST02-03-xx-05 4000K RA90.IES

Zonal Flux Tabulation

Zone(γ)	Zone Flux (lm)	Sums Flux (lm)	Zone%Lamp	Sums%Lamp	Zone(γ)	Zone Flux (lm)	Sums Flux (lm)	Zone%Lamp	Sums%Lamp
0.0-1.0	0.08	0.08	0.11	0.11	47.0-48.0	0.86	71.54	1.10	91.16
1.0-2.0	0.25	0.33	0.32	0.43	48.0-49.0	0.79	72.33	1.00	92.16
2.0-3.0	0.42	0.76	0.54	0.96	49.0-50.0	0.71	73.04	0.91	93.07
3.0-4.0	0.59	1.34	0.75	1.71	50.0-51.0	0.64	73.68	0.81	93.88
4.0-5.0	0.75	2.10	0.96	2.67	51.0-52.0	0.57	74.25	0.72	94.60
5.0-6.0	0.91	3.01	1.16	3.83	52.0-53.0	0.50	74.75	0.64	95.24
6.0-7.0	1.06	4.07	1.35	5.18	53.0-54.0	0.44	75.19	0.56	95.81
7.0-8.0	1.20	5.27	1.53	6.71	54.0-55.0	0.39	75.58	0.50	96.31
8.0-9.0	1.33	6.59	1.69	8.40	55.0-56.0	0.35	75.93	0.45	96.76
9.0-10.0	1.44	8.03	1.83	10.23	56.0-57.0	0.32	76.26	0.41	97.17
10.0-11.0	1.53	9.56	1.96	12.19	57.0-58.0	0.30	76.56	0.38	97.55
11.0-12.0	1.62	11.18	2.06	14.25	58.0-59.0	0.27	76.83	0.35	97.90
12.0-13.0	1.69	12.87	2.15	16.40	59.0-60.0	0.25	77.07	0.31	98.21
13.0-14.0	1.75	14.62	2.23	18.63	60.0-61.0	0.22	77.29	0.28	98.49
14.0-15.0	1.80	16.42	2.29	20.92	61.0-62.0	0.20	77.49	0.25	98.74
15.0-16.0	1.84	18.26	2.34	23.26	62.0-63.0	0.18	77.67	0.22	98.96
16.0-17.0	1.86	20.12	2.38	25.64	63.0-64.0	0.16	77.82	0.20	99.16
17.0-18.0	1.88	22.00	2.40	28.04	64.0-65.0	0.14	77.96	0.17	99.33
18.0-19.0	1.90	23.90	2.42	30.46	65.0-66.0	0.12	78.07	0.15	99.48
19.0-20.0	1.92	25.82	2.44	32.90	66.0-67.0	0.10	78.17	0.13	99.61
20.0-21.0	1.94	27.76	2.47	35.37	67.0-68.0	0.08	78.25	0.10	99.71
21.0-22.0	1.95	29.71	2.49	37.85	68.0-69.0	0.07	78.32	0.08	99.80
22.0-23.0	1.96	31.67	2.50	40.35	69.0-70.0	0.05	78.37	0.07	99.86
23.0-24.0	1.97	33.64	2.51	42.87	70.0-71.0	0.04	78.41	0.05	99.91
24.0-25.0	1.98	35.62	2.52	45.38	71.0-72.0	0.03	78.44	0.04	99.95
25.0-26.0	1.98	37.60	2.52	47.90	72.0-73.0	0.02	78.46	0.02	99.97
26.0-27.0	1.98	39.57	2.52	50.42	73.0-74.0	0.01	78.47	0.01	99.99
27.0-28.0	1.97	41.54	2.51	52.93	74.0-75.0	0.01	78.48	0.01	100.00
28.0-29.0	1.96	43.50	2.50	55.43	75.0-76.0	0.00	78.48	0.00	100.00
29.0-30.0	1.94	45.44	2.47	57.90	76.0-77.0	0.00	78.48	0.00	100.00
30.0-31.0	1.91	47.36	2.44	60.34	77.0-78.0	0.00	78.48	0.00	100.00
31.0-32.0	1.88	49.23	2.39	62.73	78.0-79.0	0.00	78.48	0.00	100.00
32.0-33.0	1.83	51.06	2.34	65.07	79.0-80.0	0.00	78.48	0.00	100.00
33.0-34.0	1.79	52.86	2.28	67.35	80.0-81.0	0.00	78.48	0.00	100.00
34.0-35.0	1.75	54.60	2.22	69.58	81.0-82.0	0.00	78.48	0.00	100.00
35.0-36.0	1.70	56.30	2.16	71.74	82.0-83.0	0.00	78.48	0.00	100.00
36.0-37.0	1.64	57.94	2.09	73.83	83.0-84.0	0.00	78.48	0.00	100.00
37.0-38.0	1.59	59.53	2.02	75.85	84.0-85.0	0.00	78.48	0.00	100.00
38.0-39.0	1.52	61.05	1.94	77.80	85.0-86.0	0.00	78.48	0.00	100.00
39.0-40.0	1.46	62.51	1.86	79.65	86.0-87.0	0.00	78.48	0.00	100.00
40.0-41.0	1.39	63.90	1.77	81.43	87.0-88.0	0.00	78.48	0.00	100.00
41.0-42.0	1.32	65.22	1.68	83.11	88.0-89.0	0.00	78.48	0.00	100.00
42.0-43.0	1.24	66.46	1.58	84.69	89.0-90.0	0.00	78.48	0.00	100.00
43.0-44.0	1.16	67.63	1.48	86.17	90.0-91.0	0.00	78.48	0.00	100.00
44.0-45.0	1.09	68.72	1.39	87.56	91.0-92.0	0.00	78.48	0.00	100.00
45.0-46.0	1.02	69.74	1.30	88.86	92.0-93.0	0.00	78.48	0.00	100.00
46.0-47.0	0.94	70.68	1.20	90.06	93.0-94.0	0.00	78.48	0.00	100.00

IES Indoor Report


Photometric Filename:ST02-03-xx-05 4000K RA90.IES

Zonal Flux Tabulation - (Cont.)

Zone(γ)	Zone Flux (lm)	Sums Flux (lm)	Zone%Lamp	Sums%Lamp	Zone(γ)	Zone Flux (lm)	Sums Flux (lm)	Zone%Lamp	Sums%Lamp
94.0-95.0	0.00	78.48	0.00	100.00	141.0-142.0	0.00	78.48	0.00	100.00
95.0-96.0	0.00	78.48	0.00	100.00	142.0-143.0	0.00	78.48	0.00	100.00
96.0-97.0	0.00	78.48	0.00	100.00	143.0-144.0	0.00	78.48	0.00	100.00
97.0-98.0	0.00	78.48	0.00	100.00	144.0-145.0	0.00	78.48	0.00	100.00
98.0-99.0	0.00	78.48	0.00	100.00	145.0-146.0	0.00	78.48	0.00	100.00
99.0-100.0	0.00	78.48	0.00	100.00	146.0-147.0	0.00	78.48	0.00	100.00
100.0-101.0	0.00	78.48	0.00	100.00	147.0-148.0	0.00	78.48	0.00	100.00
101.0-102.0	0.00	78.48	0.00	100.00	148.0-149.0	0.00	78.48	0.00	100.00
102.0-103.0	0.00	78.48	0.00	100.00	149.0-150.0	0.00	78.48	0.00	100.00
103.0-104.0	0.00	78.48	0.00	100.00	150.0-151.0	0.00	78.48	0.00	100.00
104.0-105.0	0.00	78.48	0.00	100.00	151.0-152.0	0.00	78.48	0.00	100.00
105.0-106.0	0.00	78.48	0.00	100.00	152.0-153.0	0.00	78.48	0.00	100.00
106.0-107.0	0.00	78.48	0.00	100.00	153.0-154.0	0.00	78.48	0.00	100.00
107.0-108.0	0.00	78.48	0.00	100.00	154.0-155.0	0.00	78.48	0.00	100.00
108.0-109.0	0.00	78.48	0.00	100.00	155.0-156.0	0.00	78.48	0.00	100.00
109.0-110.0	0.00	78.48	0.00	100.00	156.0-157.0	0.00	78.48	0.00	100.00
110.0-111.0	0.00	78.48	0.00	100.00	157.0-158.0	0.00	78.48	0.00	100.00
111.0-112.0	0.00	78.48	0.00	100.00	158.0-159.0	0.00	78.48	0.00	100.00
112.0-113.0	0.00	78.48	0.00	100.00	159.0-160.0	0.00	78.48	0.00	100.00
113.0-114.0	0.00	78.48	0.00	100.00	160.0-161.0	0.00	78.48	0.00	100.00
114.0-115.0	0.00	78.48	0.00	100.00	161.0-162.0	0.00	78.48	0.00	100.00
115.0-116.0	0.00	78.48	0.00	100.00	162.0-163.0	0.00	78.48	0.00	100.00
116.0-117.0	0.00	78.48	0.00	100.00	163.0-164.0	0.00	78.48	0.00	100.00
117.0-118.0	0.00	78.48	0.00	100.00	164.0-165.0	0.00	78.48	0.00	100.00
118.0-119.0	0.00	78.48	0.00	100.00	165.0-166.0	0.00	78.48	0.00	100.00
119.0-120.0	0.00	78.48	0.00	100.00	166.0-167.0	0.00	78.48	0.00	100.00
120.0-121.0	0.00	78.48	0.00	100.00	167.0-168.0	0.00	78.48	0.00	100.00
121.0-122.0	0.00	78.48	0.00	100.00	168.0-169.0	0.00	78.48	0.00	100.00
122.0-123.0	0.00	78.48	0.00	100.00	169.0-170.0	0.00	78.48	0.00	100.00
123.0-124.0	0.00	78.48	0.00	100.00	170.0-171.0	0.00	78.48	0.00	100.00
124.0-125.0	0.00	78.48	0.00	100.00	171.0-172.0	0.00	78.48	0.00	100.00
125.0-126.0	0.00	78.48	0.00	100.00	172.0-173.0	0.00	78.48	0.00	100.00
126.0-127.0	0.00	78.48	0.00	100.00	173.0-174.0	0.00	78.48	0.00	100.00
127.0-128.0	0.00	78.48	0.00	100.00	174.0-175.0	0.00	78.48	0.00	100.00
128.0-129.0	0.00	78.48	0.00	100.00	175.0-176.0	0.00	78.48	0.00	100.00
129.0-130.0	0.00	78.48	0.00	100.00	176.0-177.0	0.00	78.48	0.00	100.00
130.0-131.0	0.00	78.48	0.00	100.00	177.0-178.0	0.00	78.48	0.00	100.00
131.0-132.0	0.00	78.48	0.00	100.00	178.0-179.0	0.00	78.48	0.00	100.00
132.0-133.0	0.00	78.48	0.00	100.00	179.0-180.0	0.00	78.48	0.00	100.00
133.0-134.0	0.00	78.48	0.00	100.00					
134.0-135.0	0.00	78.48	0.00	100.00					
135.0-136.0	0.00	78.48	0.00	100.00					
136.0-137.0	0.00	78.48	0.00	100.00					
137.0-138.0	0.00	78.48	0.00	100.00					
138.0-139.0	0.00	78.48	0.00	100.00					
139.0-140.0	0.00	78.48	0.00	100.00					
140.0-141.0	0.00	78.48	0.00	100.00					

Rectangle ISO Lighting Intensity Diagram


Lum. Name: ST02	Lum. Catalog:	Test ID: 01
Lamp Name:	Lamp Catalog: LED	Test Lab: Quality Department
Manufacture: Shenzhen Norming Lighting Co.Ltd	Test Machine:GON-2000	Test Date: 2021/02/01



Plane ISO-Illuminance Diagram

Lum. Name: ST02	Lum. Catalog:	Test ID: 01
Lamp Name:	Lamp Catalog: LED	Test Lab: Quality Department
Manufacture: Shenzhen Norming Lighting Co.Ltd	Test Machine:GON-2000	Test Date: 2021/02/01

Plane ISO-Illuminance Curve



Working Plane Luminaire Mounting Height(m): 3.00
Working Plane Maximum Illuminance(lx): 11.45
Working Plane Maximum Illuminance Position(d/h):H0.0 V0.2


IES Indoor Report

Photometric Filename:ST02-03-xx-05 4000K RA90.IES

3D Plane ISO Illuminance Diagram

Lum. Name: ST02	Lum. Catalog:	Test ID: 01
Lamp Name:	Lamp Catalog: LED	Test Lab: Quality Department
Manufacture: Shenzhen Norming Lighting Co.Ltd	Test Machine:GON-2000	Test Date: 2021/02/01

3D Plane Illuminance Modal




Curves: 3D Model — 90% — 80% — 70% — 60% — 50% — 40% — 30% — 20% — 10% —
View Angles(deg): 0 Height(m): 3.0 Distance(m): 10.0

Space ISO Illuminance Diagram

Lum. Name: ST02	Lum. Catalog:	Test ID: 01
Lamp Name:	Lamp Catalog: LED	Test Lab: Quality Department
Manufacture: Shenzhen Norming Lighting Co.Ltd	Test Machine:GON-2000	Test Date: 2021/02/01


Space ISO Illuminance Curve



Space Plane Maximum Illuminance and @Angle:103.08lx,14.0deg
Plane Maximum Lighting Intensity and @Angle:120.277cd,0deg

Illuminance-Distance Diagram

Lum. Name: ST02	Lum. Catalog:	Test ID: 01
Lamp Name:	Lamp Catalog: LED	Test Lab: Quality Department
Manufacture: Shenzhen Norming Lighting Co.Ltd	Test Machine:GON-2000	Test Date: 2021/02/01



Indoor Luminance Limiting Curves

Lum. Name: ST02	Lum. Catalog:	Test ID: 01
Lamp Name:	Lamp Catalog: LED	Test Lab: Quality Department
Manufacture: Shenzhen Norming Lighting Co.Ltd	Test Machine:GON-2000	Test Date: 2021/02/01


Glare Grade Table

GI	Quality	Using Illuminance							
1.15	A	2000	1000	500	<=300				
1.5	B		2000	1000	500	<=300			
1.85	C			2000	1000	500	<=300		
2.2	D				2000	1000	500	<=300	
2.55	E	a				2000	1000	500	<=300
			b	c	d	e	f	g	h

Luminance Table

Gama(deg)	45	50	55	60	65	70	75	80	85
C0	58531	33309	11865	7861	5324	3221	921	0	0
C90	3728	3027	2357	1664	844	0	0	0	0

Luminance Limiting Curve



Luminous Size:

Length(m)=0.000

Width(m)=-0.050

Height(m)=0.000

Area(m^2)=0.001963

Luminous Type:

Without Luminous Side


Luminous Curves:

C0-C180 Color: —

C90-C270 Color: —

Indoor Budgetary Estimate Table

Lum. Name: ST02	Lum. Catalog:	Test ID: 01
Lamp Name:	Lamp Catalog: LED	Test Lab: Quality Department
Manufacture: Shenzhen Norming Lighting Co.Ltd	Test Machine:GON-2000	Test Date: 2021/02/01



Indoor Coefficient of Utilization Table

Lum. Name: ST02	Lum. Catelog:	Test ID: 01
Lamp Name:	Lamp Catelog: LED	Test Lab: Quality Department
Manufacture: Shenzhen Norming Lighting Co.Ltd	Test Machine:GON-2000	Test Date: 2021/02/01

Coefficients of Utilization - Zonal Cavity Method																		
Coef.	Effective Floor Cavity Reflectance RFC=0.20																	
RhoCC (%)	80				70				50			30			10			0
RhoW (%)	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR	Coefficient of Utilization(%)																	
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	113	110	107	105	110	108	105	103	104	102	100	100	98	97	96	95	94	92
2	106	101	97	93	104	99	95	92	96	93	90	93	90	88	90	88	86	84
3	100	93	88	83	98	92	87	83	89	85	81	87	83	80	84	81	79	77
4	94	86	80	75	93	85	79	75	83	78	74	81	76	73	79	75	72	70
5	89	80	73	69	87	79	73	68	77	72	68	75	71	67	74	70	66	65
6	84	74	68	63	82	73	67	63	72	66	62	70	65	62	69	65	61	60
7	79	69	63	58	78	68	62	58	67	62	57	66	61	57	65	60	57	55
8	75	65	58	54	74	64	58	54	63	57	53	62	57	53	61	56	53	51
9	71	61	54	50	70	60	54	50	59	54	50	58	53	50	57	53	49	48
10	68	57	51	47	67	57	51	47	56	50	47	55	50	46	54	50	46	45

Unified Glare Rating Table

Lum. Name: ST02	Lum. Catalog:	Test ID: 01
Lamp Name:	Lamp Catalog: LED	Test Lab: Quality Department
Manufacture: Shenzhen Norming Lighting Co.Ltd	Test Machine:GON-2000	Test Date: 2021/02/01

Unified Glare Rating Table

Ceiling RCC	0.70	0.70	0.50	0.50	0.30	0.70	0.70	0.50	0.50	0.30
Wall RW	0.50	0.30	0.50	0.30	0.30	0.50	0.30	0.50	0.30	0.30
Floor RFC	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20
Room Size	Vewed crosswise					Vewed endwise				
X=2H Y=2H	24.2	25.4	24.6	25.7	26.0	13.0	14.1	13.3	14.4	14.7
	24.1	25.1	24.5	25.5	25.8	12.9	13.9	13.3	14.2	14.6
	24.1	25.0	24.5	25.3	25.7	12.8	13.8	13.2	14.1	14.5
	24.0	24.8	24.4	25.2	25.6	12.7	13.6	13.1	14.0	14.3
	23.9	24.7	24.3	25.1	25.5	12.7	13.5	13.1	13.9	14.3
	23.9	24.6	24.3	25.0	25.4	12.6	13.4	13.1	13.8	14.2
X=4H Y=2H	24.0	24.9	24.4	25.3	25.7	13.2	14.1	13.6	14.5	14.9
	23.9	24.7	24.3	25.1	25.5	13.2	14.0	13.6	14.4	14.8
	23.8	24.5	24.3	24.9	25.4	13.1	13.8	13.5	14.2	14.6
	23.7	24.3	24.2	24.7	25.2	13.0	13.6	13.5	14.0	14.5
	23.7	24.2	24.1	24.6	25.1	12.9	13.5	13.4	13.9	14.4
	23.6	24.1	24.1	24.5	25.0	12.9	13.3	13.4	13.8	14.3
X=8H Y=4H	23.7	24.2	24.1	24.6	25.1	12.9	13.5	13.4	13.9	14.4
	23.5	24.0	24.0	24.5	25.0	12.8	13.3	13.3	13.8	14.3
	23.5	23.9	24.0	24.4	24.9	12.8	13.1	13.3	13.7	14.2
	23.4	23.8	23.9	24.3	24.8	12.7	13.0	13.2	13.5	14.1
X=12H Y=4H	23.6	24.1	24.1	24.6	25.0	12.9	13.4	13.4	13.8	14.3
	23.5	23.9	24.0	24.3	24.9	12.8	13.2	13.3	13.6	14.2
	23.4	23.8	23.9	24.3	24.8	12.7	13.0	13.2	13.5	14.1
Variations with the objerver position at spacings										
S=1.0H	5.0/0.0					0.0/0.0				
S=1.5H	5.0/0.0					7.5/0.0				
S=2.0H	5.7/-16.3					6.6/0.0				
Reduced UGR Table:										
Nordic Standard Table:	BK0					BK0				
Correction Value	0.1					0.3				

o the CIE Pub.117, data has been corrected, refers to the lamp's lumens 8.2flm.

IES Indoor Report

Photometric Filename:ST02-03-xx-05 4000K RA90.IES

Candela Tabulation

V/H	C0. 0	C30. 0	C60. 0	C90. 0	C120. 0	C150. 0	C180. 0
γ 0. 0	87. 06	87. 06	87. 06	87. 06	87. 06	87. 06	87. 06
γ 1. 0	84. 92	84. 63	85. 11	86. 63	88. 94	89. 76	94. 12
γ 2. 0	87. 95	87. 26	87. 02	86. 81	88. 01	87. 74	91. 88
γ 3. 0	90. 51	89. 43	88. 45	86. 81	86. 88	85. 45	89. 53
γ 4. 0	93. 01	91. 60	89. 74	86. 53	85. 44	82. 94	87. 02
γ 5. 0	95. 35	93. 50	90. 75	86. 10	83. 50	79. 69	84. 06
γ 6. 0	97. 53	95. 12	91. 55	85. 25	80. 94	75. 38	80. 22
γ 7. 0	99. 65	96. 63	92. 03	84. 02	77. 55	70. 68	75. 30
γ 8. 0	101. 77	98. 14	92. 42	82. 20	73. 42	65. 36	69. 92
γ 9. 0	103. 84	99. 25	92. 50	79. 79	68. 82	59. 68	63. 99
γ 10. 0	105. 82	100. 31	92. 56	76. 71	64. 02	53. 60	57. 55
γ 11. 0	107. 68	101. 29	92. 30	73. 08	58. 87	47. 49	51. 06
γ 12. 0	109. 51	102. 11	91. 69	68. 98	53. 57	41. 83	45. 01
γ 13. 0	111. 22	102. 98	90. 83	64. 60	48. 44	36. 42	39. 22
γ 14. 0	112. 84	103. 52	89. 54	60. 30	43. 43	31. 41	33. 66
γ 15. 0	114. 34	103. 97	87. 84	56. 00	38. 34	26. 74	29. 09
γ 16. 0	115. 63	104. 30	85. 56	51. 64	33. 36	22. 60	24. 82
γ 17. 0	116. 82	104. 32	82. 68	46. 91	28. 63	19. 13	20. 85
γ 18. 0	117. 73	104. 30	79. 50	42. 24	24. 39	16. 48	18. 02
γ 19. 0	118. 63	104. 05	76. 12	37. 72	20. 88	14. 55	15. 90
γ 20. 0	119. 23	103. 68	72. 67	33. 30	18. 32	13. 24	14. 59
γ 21. 0	119. 83	103. 24	68. 97	28. 90	16. 30	12. 61	13. 90
γ 22. 0	120. 19	102. 55	64. 74	24. 68	14. 84	12. 11	13. 32
γ 23. 0	120. 28	101. 71	60. 25	21. 17	14. 09	11. 58	12. 71
γ 24. 0	120. 27	100. 75	55. 87	18. 43	13. 52	10. 97	11. 98
γ 25. 0	120. 06	99. 54	51. 38	16. 22	12. 94	10. 19	11. 19
γ 26. 0	119. 65	98. 28	46. 92	14. 48	12. 31	9. 59	10. 58
γ 27. 0	119. 14	96. 82	42. 38	13. 53	11. 60	9. 08	10. 01
γ 28. 0	118. 44	94. 88	37. 90	12. 97	10. 94	8. 57	9. 47
γ 29. 0	117. 46	92. 40	33. 72	12. 44	10. 37	8. 11	8. 98
γ 30. 0	116. 38	89. 23	29. 90	11. 89	9. 83	7. 65	8. 52
γ 31. 0	115. 11	85. 74	26. 22	11. 26	9. 33	7. 23	8. 07
γ 32. 0	113. 68	81. 94	22. 59	10. 50	8. 86	6. 84	7. 64
γ 33. 0	112. 01	77. 99	19. 66	9. 94	8. 42	6. 47	7. 25
γ 34. 0	110. 24	73. 60	17. 46	9. 40	8. 00	6. 11	6. 86
γ 35. 0	108. 22	68. 65	15. 87	8. 91	7. 62	5. 78	6. 50
γ 36. 0	106. 28	63. 15	15. 01	8. 43	7. 24	5. 45	6. 16
γ 37. 0	104. 15	57. 51	14. 32	7. 99	6. 88	5. 15	5. 83
γ 38. 0	101. 97	51. 95	13. 66	7. 59	6. 54	4. 84	5. 49
γ 39. 0	99. 42	46. 46	12. 96	7. 20	6. 23	4. 56	5. 20
γ 40. 0	96. 93	41. 16	12. 17	6. 82	5. 91	4. 29	4. 90
γ 41. 0	94. 37	36. 03	11. 37	6. 45	5. 60	4. 02	4. 63
γ 42. 0	91. 68	30. 85	10. 69	6. 11	5. 32	3. 77	4. 35
γ 43. 0	88. 51	25. 70	10. 09	5. 80	5. 03	3. 53	4. 10
γ 44. 0	85. 14	21. 13	9. 52	5. 48	4. 76	3. 30	3. 84
γ 45. 0	81. 26	17. 51	8. 99	5. 18	4. 49	3. 07	3. 58
γ 46. 0	75. 06	14. 79	8. 49	4. 89	4. 26	2. 84	3. 35

Photometric Filename:ST02-03-xx-05 4000K RA90.IES[illegible]

Photometric Filename:ST02-03-xx-05 4000K RA90.IES

Candela Tabulation - (Cont.)

[illegible]