



Cut-out: Ø45mm

## FEATURES

- Made of die-casting.
- Powder coating finish from AkzoNobel.
- Interchangeable faceplate with magnetic design.
- High density COB with uniform lighting distribution.
- Compatible with leading and trailing edge phase cut dimmers.
- 5-year guarantee.

## Technical Data

Input Voltage/Hz	AC200-240V 50/60Hz
Output Voltage/Current	DC33V/60mA
Power	3W
Rated Input Current	0.015A
THD	<30%
PF value	>0.82
Ingress Protection	IP54
Operating Temperature	-10—40°C
Dimmability	Triac dimmable with <b>DIMMATE</b> driver

## LED and Optical Data

LED Brand	Bridgelux COB LED
CRI	>80, >90
SDCM	<3
Colour temperatures	2700K/3000K/4000K
System luminous efficacy up to	51lm/W

## Packaging

Box Dimensions	L65 x W65 x H110mm
Box Net Weight	0.108Kg
Box Gross Weight	0.133Kg
Carton Dimensions	L340 x W340 x H240 mm/50 PCS
Carton Net Weight	5.400Kg
Carton Gross Weight	7.320Kg



## Specifications (White)

CCT	Asymmetric Beam Angle	CRI	Lumen	Efficacy	CRI	Lumen	Efficacy
2700K	20°		122lm	45lm/W		106lm	38lm/W
3000K	20°	80+	129lm	46lm/W	90+	109lm	37lm/W
4000K	20°		146lm	51lm/W		111lm	41lm/W

## Specifications (Black)

CCT	Asymmetric Beam Angle	CRI	Lumen	Efficacy	CRI	Lumen	Efficacy
2700K	20°		57lm	21lm/W		51lm	18lm/W
3000K	20°	80+	61lm	22lm/W	90+	48lm	17lm/W
4000K	20°		68lm	24lm/W		53lm	19lm/W

## ECLIPSE CONSEIL

Siège : +33 (1) 79 30 48 19- Showroom Paris : +33 (1) 78 95 50 14 - Mob : +33 (6) 87 82 12 04  
Siège social : 7 rue Prudent Neel 92500 Rueil-Malmaison - Showroom : 1 rue Dulong 75017 PARIS