




Black / White



Packaging

Box Dimensions	L190 x W110 x H70mm
Box Net Weight	0.34Kg
Box Gross Weight	0.42Kg
Carton Dimensions	L565 x W390 x H370 mm/50 PCS
Carton Net Weight	17Kg
Carton Gross Weight	22Kg

Specifications

CCT	Beam Angle	Lumen	Efficacy
1800K-3000K	15°	737lm	69lm/W
	24°	734lm	68lm/W
	36°	706lm	65lm/W
	60°	674lm	61lm/W

FEATURES

- Heat sink design better for air convection, good heat dissipation.
- Dimming capability. Suits triac dimmers including OPUS, Clipsal, HPM, Niko, Lumeo Domus, Lumeo Eco. The driver with SAA, RCM and CE certification.
- 3-year guarantee.

Technical Data

Input Voltage/Hz	AC200-240V 50/60Hz
Output Voltage/Current	DC33V/270mA
Power	12W
Rated Input Current	0.055A
PF value	>0.9
Ingress Protection	IP20
Operating Temperature	-10—40°C
Dimmability	Triac dimmable with DIMMATE driver

Optical Data

LED Brand	Bridgelux COB LED
CRI	Ra>95
SDCM	<3
Beam Angle	15°/24°/36°/60°
Colour Temperature	1800K-3000K
System luminous efficacy up to	69lm/W



ECLIPSE CONSEIL

Siège : +33 (1) 79 30 48 19- Showroom Paris : +33 (1) 78 95 50 14 - Mob : +33 (6) 87 82 12 04
Siège social : 7 rue Prudent Neel 92500 Rueil-Malmaison - Showroom : 1 rue Dulong 75017 PARIS