





Black / White



## Packaging

|                     |                              |
|---------------------|------------------------------|
| Box Dimensions      | L190 x W110 x H70mm          |
| Box Net Weight      | 0.34Kg                       |
| Box Gross Weight    | 0.42Kg                       |
| Carton Dimensions   | L565 x W390 x H370 mm/50 PCS |
| Carton Net Weight   | 17Kg                         |
| Carton Gross Weight | 22Kg                         |

## FEATURES

- Heat sink design better for air convection, good heat dissipation.
- Dimming capability. Suits triac dimmers including OPUS, Clipsal, HPM, Niko, Lumeo Domus, Lumeo Eco. The driver with SAA, RCM and CE certification.
- 3-year guarantee.

## Technical Data

|                        |                                           |
|------------------------|-------------------------------------------|
| Input Voltage/Hz       | AC200~240V 50/60Hz                        |
| Output Voltage/Current | DC35V/230mA                               |
| Power                  | 10W                                       |
| Rated Input Current    | 0.05A                                     |
| PF value               | >0.9                                      |
| Ingress Protection     | IP20                                      |
| Operating Temperature  | -10~40°C                                  |
| Dimmability            | Triac dimmable with <b>DIMMATE</b> driver |

## Optical Data

|                                |                         |
|--------------------------------|-------------------------|
| LED Brand                      | CREE COB LED            |
| CRI                            | Ra>80, Ra>90            |
| SDCM                           | <3                      |
| Beam Angle                     | 15°/24°/36°/60°         |
| Colour Temperature             | 2700K/3000K/4000K/5000K |
| System luminous efficacy up to | 99lm/W                  |



**RoHS**   

## Specifications (White)

| CCT   |            | Beam Angle | Lumen  | Efficacy |            |        | Beam Angle | Lumen  | Efficacy |
|-------|------------|------------|--------|----------|------------|--------|------------|--------|----------|
| 2700K | CRI<br>80+ | 15°        | 1121lm | 92lm/W   | CRI<br>90+ | 15°    | 944lm      | 77lm/W |          |
|       |            | 24°        | 1111lm | 91lm/W   |            | 24°    | 937lm      | 77lm/W |          |
|       |            | 36°        | 1071lm | 89lm/W   |            | 36°    | 901lm      | 74lm/W |          |
|       |            | 60°        | 1028lm | 85lm/W   |            | 60°    | 863lm      | 72lm/W |          |
| 15°   |            | 1125lm     | 91lm/W | 15°      |            | 976lm  | 77lm/W     |        |          |
| 24°   |            | 1117lm     | 91lm/W | 24°      |            | 966lm  | 77lm/W     |        |          |
| 36°   |            | 1079lm     | 88lm/W | 36°      |            | 979lm  | 77lm/W     |        |          |
| 60°   |            | 1035lm     | 85lm/W | 60°      |            | 901lm  | 72lm/W     |        |          |
| 15°   |            | 1191lm     | 97lm/W | 15°      |            | 1031lm | 84lm/W     |        |          |
| 24°   |            | 1178lm     | 96lm/W | 24°      |            | 1022lm | 83lm/W     |        |          |
| 36°   |            | 1135lm     | 93lm/W | 36°      |            | 983lm  | 80lm/W     |        |          |
| 60°   |            | 1092lm     | 90lm/W | 60°      |            | 947lm  | 78lm/W     |        |          |
| 5000K |            | 15°        | 1212lm | 99lm/W   |            | 15°    | 1060lm     | 84lm/W |          |
|       |            | 24°        | 1198lm | 98lm/W   |            | 24°    | 1051lm     | 84lm/W |          |
|       |            | 36°        | 1155lm | 95lm/W   |            | 36°    | 1010lm     | 81lm/W |          |
|       |            | 60°        | 1111lm | 92lm/W   |            | 60°    | 969lm      | 78lm/W |          |

## ECLIPSE CONSEIL

Siège : +33 (1) 79 30 48 19- Showroom Paris : +33 (1) 78 95 50 14 - Mob : +33 (6) 87 82 12 04  
Siège social : 7 rue Prudent Neel 92500 Rueil-Malmaison - Showroom : 1 rue Dulong 75017 PARIS

## Specifications (Black)

| CCT   |            | Beam Angle | Lumen  | Efficacy |            | Beam Angle | Lumen  | Efficacy |
|-------|------------|------------|--------|----------|------------|------------|--------|----------|
| 2700K | CRI<br>80+ | 15°        | 1107lm | 90lm/W   | CRI<br>90+ | 15°        | 891lm  | 73lm/W   |
|       |            | 24°        | 1099lm | 90lm/W   |            | 24°        | 898lm  | 74lm/W   |
|       |            | 36°        | 1041lm | 85lm/W   |            | 36°        | 859lm  | 71lm/W   |
|       |            | 60°        | 980lm  | 80lm/W   |            | 60°        | 807lm  | 67lm/W   |
| 15°   |            | 1107lm     | 89lm/W | 15°      |            | 963lm      | 76lm/W |          |
| 24°   |            | 1098lm     | 89lm/W | 24°      |            | 957lm      | 76lm/W |          |
| 36°   |            | 1038lm     | 84lm/W | 36°      |            | 907lm      | 72lm/W |          |
| 60°   |            | 974lm      | 79lm/W | 60°      |            | 849lm      | 68lm/W |          |
| 15°   |            | 1158lm     | 94lm/W | 15°      |            | 1005lm     | 80lm/W |          |
| 24°   |            | 1151lm     | 94lm/W | 24°      |            | 999lm      | 80lm/W |          |
| 36°   |            | 1088lm     | 89lm/W | 36°      |            | 944lm      | 76lm/W |          |
| 60°   |            | 1024lm     | 84lm/W | 60°      |            | 887lm      | 72lm/W |          |
| 5000K |            | 15°        | 1178lm | 96lm/W   |            | 15°        | 1025lm | 81lm/W   |
|       |            | 24°        | 1171lm | 96lm/W   |            | 24°        | 1013lm | 80lm/W   |
|       |            | 36°        | 1107lm | 91lm/W   |            | 36°        | 961lm  | 77lm/W   |
|       |            | 60°        | 1042lm | 85lm/W   |            | 60°        | 900lm  | 72lm/W   |

## ECLIPSE CONSEIL

Siège : +33 (1) 79 30 48 19- Showroom Paris : +33 (1) 78 95 50 14 - Mob : +33 (6) 87 82 12 04  
Siège social : 7 rue Prudent Neel 92500 Rueil-Malmaison - Showroom : 1 rue Dulong 75017 PARIS