




Black / White



Packaging

Box Dimensions	L190 x W110 x H70mm
Box Net Weight	0.34Kg
Box Gross Weight	0.42Kg
Carton Dimensions	L565 x W390 x H370 mm/50 PCS
Carton Net Weight	17Kg
Carton Gross Weight	22Kg

FEATURES

- Heat sink design better for air convection, good heat dissipation.
- Dimming capability. Suits triac dimmers including OPUS, Clipsal, HPM, Niko, Lumeo Domus, Lumeo Eco. The driver with SAA, RCM and CE certification.
- 3-year guarantee.

Technical Data

Input Voltage/Hz	AC200-240V 50/60Hz
Output Voltage/Current	DC35V/230mA
Power	10W
Rated Input Current	0.05A
PF value	>0.9
Ingress Protection	IP20
Operating Temperature	-10-40°C
Dimmability	Triac dimmable with DIMMATE driver

Optical Data

LED Brand	CREE COB LED
CRI	Ra>80, Ra>90
SDCM	<3
Beam Angle	15°/24°/36°/60°
Colour Temperature	2700K/3000K/4000K/5000K
System luminous efficacy up to	99lm/W



RoHS CE

Specifications (White)

CCT		Beam Angle	Lumen	Efficacy		Beam Angle	Lumen	Efficacy
2700K	CRI 80+	15°	1121lm	92lm/W	CRI 90+	15°	944lm	77lm/W
		24°	1111lm	91lm/W		24°	937lm	77lm/W
		36°	1071lm	89lm/W		36°	901lm	74lm/W
		60°	1028lm	85lm/W		60°	863lm	72lm/W
15°		1125lm	91lm/W	15°		976lm	77lm/W	
24°		1117lm	91lm/W	24°		966lm	77lm/W	
36°		1079lm	88lm/W	36°		979lm	77lm/W	
60°		1035lm	85lm/W	60°		901lm	72lm/W	
4000K		15°	1191lm	97lm/W		15°	1031lm	84lm/W
		24°	1178lm	96lm/W		24°	1022lm	83lm/W
		36°	1135lm	93lm/W		36°	983lm	80lm/W
		60°	1092lm	90lm/W		60°	947lm	78lm/W
5000K		15°	1212lm	99lm/W		15°	1060lm	84lm/W
		24°	1198lm	98lm/W		24°	1051lm	84lm/W
		36°	1155lm	95lm/W		36°	1010lm	81lm/W
		60°	1111lm	92lm/W		60°	969lm	78lm/W

ECLIPSE CONSEIL

Siège : +33 (1) 79 30 48 19- Showroom Paris : +33 (1) 78 95 50 14 - Mob : +33 (6) 87 82 12 04
Siège social : 7 rue Prudent Neel 92500 Rueil-Malmaison - Showroom : 1 rue Dulong 75017 PARIS

Specifications (Black)

CCT		Beam Angle	Lumen	Efficacy			Beam Angle	Lumen	Efficacy
2700K	CRI 80+	15°	1107lm	90lm/W	CRI 90+	15°	891lm	73lm/W	
		24°	1099lm	90lm/W		24°	898lm	74lm/W	
		36°	1041lm	85lm/W		36°	859lm	71lm/W	
		60°	980lm	80lm/W		60°	807lm	67lm/W	
15°		1107lm	89lm/W	15°		963lm	76lm/W		
24°		1098lm	89lm/W	24°		957lm	76lm/W		
36°		1038lm	84lm/W	36°		907lm	72lm/W		
60°		974lm	79lm/W	60°		849lm	68lm/W		
15°		1158lm	94lm/W	15°		1005lm	80lm/W		
24°		1151lm	94lm/W	24°		999lm	80lm/W		
36°		1088lm	89lm/W	36°		944lm	76lm/W		
60°		1024lm	84lm/W	60°		887lm	72lm/W		
15°		1178lm	96lm/W	15°		1025lm	81lm/W		
24°		1171lm	96lm/W	24°		1013lm	80lm/W		
36°		1107lm	91lm/W	36°		961lm	77lm/W		
60°		1042lm	85lm/W	60°		900lm	72lm/W		

ECLIPSE CONSEIL

Siège : +33 (1) 79 30 48 19- Showroom Paris : +33 (1) 78 95 50 14 - Mob : +33 (6) 87 82 12 04
Siège social : 7 rue Prudent Neel 92500 Rueil-Malmaison - Showroom : 1 rue Dulong 75017 PARIS