



Black / White



Honeycomb filter



FEATURES

- Flicker-free driver to creates healthy lighting environment that make people enjoy photograph in any commercial occasions.
- Thoughtful friction on the track arm, get rid of loose track arm experience.
- Bridgelux LED adopted, dim to warm available.
- Variety of optic options, make your choice flexible.
- Dimming capability. Suits triac dimmers including OPUS, Clipsal, HPM, Niko, Lumeo Domus, Lumeo Eco. The driver with CE, RCM and SAA certification.

Technical Data

Input Voltage/Hz	AC200-240V 50/60Hz
Output Voltage/Current	DC33V/230mA
Power	10W
Rated Input Current	0.05A
THD	<15%
PF value	>0.9
Ingress Protection	IP20
Operating Temperature	-10-40°C
Dimmability	Triac dimmable with DIMMATE driver
Lifespan L70/B50 at 25°C	>326000H
Lifespan L90/B10 at 25°C	>88000H

Optical Data

LED Brand	Bridgelux COB LED
CRI	Ra>95
Beam Angle	24°/36°/60°
Colour temperatures	1800K-3000K
System luminous efficacy up to	59lm/W

Packaging

Box Dimensions	L95 x W70 x H219 x T2mm
Box Net Weight	0.364Kg
Box Gross Weight	0.408Kg
Carton Dimensions	L490 x W365 x H240 mm/25 PCS
Carton Net Weight	9.1Kg
Carton Gross Weight	11.2Kg



CCT		Beam Angle	Lumen	Efficacy
3000K	CRI 95+	24°	572lm	59lm/W
		36°	559lm	58lm/W
		60°	539lm	56lm/W

ECLIPSE CONSEIL

Siège : +33 (1) 79 30 48 19- Showroom Paris : +33 (1) 78 95 50 14 - Mob : +33 (6) 87 82 12 04
Siège social : 7 rue Prudent Neel 92500 Rueil-Malmaison - Showroom : 1 rue Dulong 75017 PARIS