



Black / White




Honeycomb filter

Black

White

Golden



Packaging

| | |
|---------------------|------------------------------|
| Box Dimensions | L296 x W165 x H58mm |
| Box Net Weight | 0.428Kg |
| Box Gross Weight | 0.546Kg |
| Carton Dimensions | L510 x W310 x H255 mm/12 PCS |
| Carton Net Weight | 5.136Kg |
| Carton Gross Weight | 6.552Kg |

HEP (with NFC)

| CCT | | Beam Angle | Lumen | Efficacy |
|-------------|-----|------------|-------|----------|
| 1800K-3000K | CRI | 24° | 572lm | 57lm/W |
| | 95+ | 36° | 559lm | 56lm/W |
| | | 60° | 539lm | 54lm/W |

Note: 1. Wider angle of the lens influences the luminous efficacy.

2. The light efficiency will be effected by the black anti-glare ring; the color temperature will be effected by the golden anti-glare ring.

FEATURES

- Controlled by in-track DALI-2 DT6 driver.
- Thoughtful friction on the track arm, get rid of loose track arm experience.
- Variety of less-glare optic options.
- 5-year guarantee.

Technical Data

| | |
|------------------------|-----------------------|
| Input Voltage/Hz | AC200-240V 50/60Hz |
| Output Voltage/Current | DC35V/230mA |
| Power | 10W |
| Rated Input Current | 0.065A |
| THD | <13% |
| PF value | >0.95 |
| Ingress Protection | IP20 |
| Operating Temperature | -10—40°C |
| Dimmability | HEP (with NFC) DALI |

Optical Data

| | |
|--------------------------------|-------------------|
| LED Brand | Bridgelux COB LED |
| CRI | Ra > 95 |
| Beam Angle | 24°/36°/60° |
| Colour temperatures | 1800K-3000K |
| System luminous efficacy up to | 57lm/W |



ECLIPSE CONSEIL

Siège : +33 (1) 79 30 48 19- Showroom Paris : +33 (1) 78 95 50 14 - Mob : +33 (6) 87 82 12 04
Siège social : 7 rue Prudent Neel 92500 Rueil-Malmaison - Showroom : 1 rue Dulong 75017 PARIS