



## Packaging

|                     |                              |
|---------------------|------------------------------|
| Box Dimensions      | L103 x W85 x H268mm          |
| Box Net Weight      | 0.536Kg                      |
| Box Gross Weight    | 0.625Kg                      |
| Carton Dimensions   | L440 x W427 x H285 mm/20 PCS |
| Carton Net Weight   | 10.72Kg                      |
| Carton Gross Weight | 13.5Kg                       |

## FEATURES

- Flicker-free driver to create healthy lighting environment.
- Compatible with leading and trailing edge phase cut dimmers.
- Thoughtful friction on the track arm, get rid of loose track arm experience.
- Variety of less-glare optic options.
- 5-year guarantee.

## Technical Data

|                        |                                           |
|------------------------|-------------------------------------------|
| Input Voltage/Hz       | AC200-240V 50/60Hz                        |
| Output Voltage/Current | DC36V/350mA                               |
| Power                  | 15W                                       |
| Rated Input Current    | 0.075A                                    |
| THD                    | <20%                                      |
| PF value               | >0.96                                     |
| Ingress Protection     | IP20                                      |
| Operating Temperature  | -10—40℃                                   |
| Dimmability            | Triac dimmable with <b>DIMMATE</b> driver |

## Optical Data

|                                |                   |
|--------------------------------|-------------------|
| LED Brand                      | Bridgelux COB LED |
| CRI                            | Ra> 80,Ra> 90     |
| Beam Angle                     | 15°/24°/36°/60°   |
| Colour temperatures            | 2700K/3000K/4000K |
| System luminous efficacy up to | 103lm/W           |



| Model         | CCT   |            | Beam Angle | Lumen  | Efficacy |            | Beam Angle | Lumen  | Efficacy |
|---------------|-------|------------|------------|--------|----------|------------|------------|--------|----------|
| TR04-15-XX-01 | 2700K | CRI<br>80+ | 15°        | 1341lm | 91lm/W   | CRI<br>90+ | 15°        | 1264lm | 85lm/W   |
|               |       |            | 24°        | 1352lm | 91lm/W   |            | 24°        | 1239m  | 83lm/W   |
|               |       |            | 36°        | 1325lm | 89lm/W   |            | 36°        | 1142lm | 76lm/W   |
|               |       |            | 60°        | 1419lm | 95lm/W   |            | 60°        | 1162lm | 79lm/W   |
| TR04-15-XX-01 | 3000K |            | 15°        | 1531lm | 103lm/W  |            | 15°        | 1327lm | 89lm/W   |
|               |       |            | 24°        | 1491lm | 100m/W   |            | 24°        | 1275lm | 87m/W    |
|               |       |            | 36°        | 1490lm | 98lm/W   |            | 36°        | 1165lm | 79lm/W   |
|               |       |            | 60°        | 1424lm | 95lm/W   |            | 60°        | 1208lm | 83lm/W   |
| TR04-15-XX-01 | 4000K |            | 15°        | 1563lm | 103lm/W  |            | 15°        | 1420lm | 95lm/W   |
|               |       |            | 24°        | 1493lm | 100lm/W  |            | 24°        | 1367lm | 93lm/W   |
|               |       |            | 36°        | 1522lm | 100lm/W  |            | 36°        | 1322lm | 90lm/W   |
|               |       |            | 60°        | 1473lm | 99lm/W   |            | 60°        | 1312lm | 88lm/W   |

Note: 1. Wider angle of the lens influences the luminous efficacy.

2. The light efficiency will be effected by the black anti-glare ring; the color temperature will be effected by the golden anti-glare ring.

## ECLIPSE CONSEIL

Siège : +33 (1) 79 30 48 19- Showroom Paris : +33 (1) 78 95 50 14 - Mob : +33 (6) 87 82 12 04  
Siège social : 7 rue Prudent Neel 92500 Rueil-Malmaison - Showroom : 1 rue Dulong 75017 PARIS