



FEATURES

- Controlled by in-track DALI-2 DT6 driver.
- Thoughtful friction on the track arm, get rid of loose track arm experience.
- Variety of less-glare optic options.
- 5-year guarantee.

Technical Data

Input Voltage/Hz	AC200-240V 50/60Hz
Output Voltage/Current	DC35V/350mA
Power	15W(HEP DALI) 16W(TRIDONIC DALI)
Rated Input Current	0.075A(HEP DALI) 0.08A(TRIDONIC DALI)
THD	<13%
PF value	>0.8(HEP DALI) >0.88(TRIDONIC DALI)
Ingress Protection	IP20
Operating Temperature	-10—40℃
Dimmability	HEP (with NFC) DALI TRIDONIC DALI

Optical Data

LED Brand	Bridgelux COB LED
CRI	Ra> 80,Ra> 90
Beam Angle	18°/24°/36°/60°
Colour temperatures	2700K/3000K/4000K
System luminous efficacy up to	105lm/W

Packaging

Box Dimensions	L295 x W178 x H65mm
Box Net Weight	0.428Kg
Box Gross Weight	0.546Kg
Carton Dimensions	L368 x W308 x H350 mm/12 PCS
Carton Net Weight	5.136Kg
Carton Gross Weight	6.552Kg



HEP (with NFC)

CCT	Beam Angle	Lumen	Efficacy	Beam Angle	Lumen	Efficacy
2700K	15°	1341lm	90lm/W	15°	1264lm	85lm/W
	24°	1352lm	91lm/W	24°	1239lm	83lm/W
	36°	1325lm	89lm/W	36°	1142lm	77lm/W
	60°	1419lm	95lm/W	60°	1162lm	78lm/W
3000K	15°	1531lm	102lm/W	15°	1327lm	89lm/W
	24°	1491lm	100lm/W	24°	1275lm	85lm/W
	36°	1490lm	100lm/W	36°	1165lm	78lm/W
	60°	1424lm	96lm/W	60°	1208lm	81lm/W
4000K	15°	1563lm	105lm/W	15°	1420lm	95lm/W
	24°	1493lm	100lm/W	24°	1367lm	92lm/W
	36°	1522lm	102lm/W	36°	1322lm	88lm/W
	60°	1473lm	99lm/W	60°	1312lm	88lm/W

Note:1. Wider angle of the lens influences the luminous efficacy.

2. The light efficiency will be effected by the black anti-glare ring; the color temperature will be effected by the golden anti-glare ring.

ECLIPSE CONSEIL

Siège : +33 (1) 79 30 48 19- Showroom Paris : +33 (1) 78 95 50 14 - Mob : +33 (6) 87 82 12 04
Siège social : 7 rue Prudent Neel 92500 Rueil-Malmaison - Showroom : 1 rue Dulong 75017 PARIS

TRIDONIC DALI

CCT		Beam Angle	Lumen	Efficacy		Beam Angle	Lumen	Efficacy
2700K	CRI 80+	15°	1341lm	84lm/W	CRI 90+	15°	1264lm	80lm/W
		24°	1352lm	85lm/W		24°	1239lm	77lm/W
		36°	1325lm	83lm/W		36°	1142lm	71lm/W
		60°	1419lm	89lm/W		60°	1162lm	73lm/W
3000K		15°	1531lm	96lm/W		15°	1327lm	83lm/W
		24°	1491lm	93lm/W		24°	1275lm	80lm/W
		36°	1490lm	93lm/W		36°	1165lm	73lm/W
		60°	1424lm	90lm/W		60°	1208lm	76lm/W
4000K		15°	1563lm	95lm/W		15°	1420lm	89lm/W
		24°	1493lm	93lm/W		24°	1367lm	86lm/W
		36°	1522lm	95lm/W		36°	1322lm	83lm/W
		60°	1473lm	92lm/W		60°	1312lm	82lm/W

- Note: 1. Wider angle of the lens influences the luminous efficacy.
2. The light efficiency will be effected by the black anti-glare ring; the color temperature will be effected by the golden anti-glare ring.

ECLIPSE CONSEIL

Siège : +33 (1) 79 30 48 19- Showroom Paris : +33 (1) 78 95 50 14 - Mob : +33 (6) 87 82 12 04
Siège social : 7 rue Prudent Neel 92500 Rueil-Malmaison - Showroom : 1 rue Dulong 75017 PARIS