



## Packaging

Box Dimensions	L296 x W198 x H68mm
Box Net Weight	0.428Kg
Box Gross Weight	0.546Kg
Carton Dimensions	L610 x W310 x H292 mm/12 PCS
Carton Net Weight	5.136Kg
Carton Gross Weight	6.552Kg

## HEP ( with NFC )

CCT	Beam Angle	Lumen	Efficacy	Beam Angle	Lumen	Efficacy
2700K	15°	1607lm	80lm/W	15°	1607lm	73lm/W
	25°	1614lm	83lm/W	25°	1614lm	77lm/W
	38°	1598lm	81lm/W	38°	1598lm	73lm/W
	60°	1564lm	81lm/W	60°	1564lm	75lm/W
3000K	15°	1612lm	97lm/W	15°	1612lm	78lm/W
	25°	1610lm	97lm/W	25°	1610lm	81lm/W
	38°	1619lm	92lm/W	38°	1619lm	80lm/W
	60°	1589lm	95lm/W	60°	1589lm	79lm/W
4000K	15°	1737lm	96lm/W	15°	1737lm	85lm/W
	25°	1725lm	98lm/W	25°	1725lm	86lm/W
	38°	1720lm	95lm/W	38°	1720lm	83lm/W
	60°	1712lm	99lm/W	60°	1712lm	85lm/W

Note: 1. Wider angle of the lens influences the luminous efficacy.

2. The light efficiency will be effected by the black anti-glare ring; the color temperature will be effected by the golden anti-glare ring.

## FEATURES

- Controlled by in-track DALI-2 DT6 driver.
- Thoughtful friction on the track arm, get rid of loose track arm experience.
- Variety of less-glare optic options.
- 5-year guarantee.

## Technical Data

Input Voltage/Hz	AC200-240V 50/60Hz
Output Voltage/Current	DC35V/470mA
Power	20W(HEP DALI)   21W(TRIDONIC DALI)
Rated Input Current	0.1A(HEP DALI)   0.105A(TRIDONIC DALI)
THD	<13%
PF value	>0.9(HEP DALI)   >0.95(TRIDONIC DALI)
Ingress Protection	IP20
Operating Temperature	-10—40℃
Dimmability	HEP ( with NFC ) DALI TRIDONIC DALI

## Optical Data

LED Brand	Bridgelux COB LED
CRI	Ra> 80,Ra> 90
Beam Angle	15°/25°/38°/60°
Colour temperatures	2700K/3000K/4000K
System luminous efficacy up to	98lm/W



## ECLIPSE CONSEIL

Siège : +33 (1) 79 30 48 19- Showroom Paris : +33 (1) 78 95 50 14 - Mob : +33 (6) 87 82 12 04  
Siège social : 7 rue Prudent Neel 92500 Rueil-Malmaison - Showroom : 1 rue Dulong 75017 PARIS

## TRIDONIC DALI

CCT		Beam Angle	Lumen	Efficacy		Beam Angle	Lumen	Efficacy
2700K	CRI 80+	15°	1607lm	77lm/W	CRI 90+	15°	1337lm	64lm/W
		25°	1614lm	77lm/W		25°	1352lm	65lm/W
		38°	1598lm	77lm/W		38°	1352lm	65lm/W
		60°	1564lm	75lm/W		60°	1360lm	65lm/W
3000K		15°	1612lm	77lm/W		15°	1415lm	68lm/W
		25°	1610lm	77lm/W		25°	1408lm	67lm/W
		38°	1619lm	77lm/W		38°	1425lm	68lm/W
		60°	1598lm	76lm/W		60°	1437lm	69lm/W
4000K		15°	1737lm	83lm/W		15°	1470lm	70lm/W
		25°	1725lm	84lm/W		25°	1469lm	70lm/W
		38°	1720lm	83lm/W		38°	1443lm	69lm/W
		60°	1712lm	82lm/W		60°	1459lm	70lm/W

Note: 1. Wider angle of the lens influences the luminous efficacy.  
 2. The light efficiency will be effected by the black anti-glare ring; the color temperature will be effected by the golden anti-glare ring.

## ECLIPSE CONSEIL

Siège : +33 (1) 79 30 48 19- Showroom Paris : +33 (1) 78 95 50 14 - Mob : +33 (6) 87 82 12 04  
 Siège social : 7 rue Prudent Neel 92500 Rueil-Malmaison - Showroom : 1 rue Dulong 75017 PARIS