



## FEATURES

- Controlled by in-track DALI-2 DT6 driver.
- Thoughtful friction on the track arm, get rid of loose track arm experience.
- Variety of less-glare optic options.
- 5-year guarantee.

## Technical Data

Input Voltage/Hz	AC200-240V 50/60Hz
Output Voltage/Current	DC35V/590mA
Power	25W(HEP DALI)   26W(TRIDONIC DALI)
Rated Input Current	0.125A(HEP DALI)   0.13A(TRIDONIC DALI)
THD	<13%
PF value	>0.9(HEP DALI)   >0.95(TRIDONIC DALI)
Ingress Protection	IP20
Operating Temperature	-10-40°C
Dimmability	HEP ( with NFC) DALI TRIDONIC DALI

## Optical Data

LED Brand	Bridgelux COB LED
CRI	Ra> 80,Ra> 90
Beam Angle	15°/25°/38°/60°
Colour temperatures	2700K/3000K/4000K
System luminous efficacy up to	83lm/W

## Packaging

Box Dimensions	L296 x W198 x H68mm
Box Net Weight	0.428Kg
Box Gross Weight	0.546Kg
Carton Dimensions	L610 x W310 x H292 mm/12 PCS
Carton Net Weight	5.136Kg
Carton Gross Weight	6.552Kg



## HEP ( with NFC )

CCT	Beam Angle	Lumen	Efficacy	Beam Angle	Lumen	Efficacy
2700K	15°	1887lm	76lm/W	15°	1616lm	65lm/W
	25°	1883lm	76lm/W	25°	1607lm	65lm/W
	38°	1855lm	74lm/W	38°	1599lm	64lm/W
	60°	1845lm	74lm/W	60°	1564lm	63lm/W
3000K	15°	1892lm	76lm/W	15°	1703lm	68lm/W
	25°	1886lm	76lm/W	25°	1710lm	68lm/W
	38°	1874lm	75lm/W	38°	1682lm	68lm/W
	60°	1856lm	75lm/W	60°	1658lm	67lm/W
4000K	15°	2071lm	83lm/W	15°	1834lm	74lm/W
	25°	2051lm	82lm/W	25°	1785lm	72lm/W
	38°	2048lm	82lm/W	38°	1788lm	72lm/W
	60°	2013lm	81lm/W	60°	1810lm	72lm/W

Note: 1. Wider angle of the lens influences the luminous efficacy.

2. The light efficiency will be effected by the black anti-glare ring; the color temperature will be effected by the golden anti-glare ring.

## ECLIPSE CONSEIL

Siège : +33 (1) 79 30 48 19- Showroom Paris : +33 (1) 78 95 50 14 - Mob : +33 (6) 87 82 12 04  
Siège social : 7 rue Prudent Neel 92500 Rueil-Malmaison - Showroom : 1 rue Dulong 75017 PARIS

TRIDONIC DALI

CCT		Beam Angle	Lumen	Efficacy		Beam Angle	Lumen	Efficacy
2700K	CRI 80+	15°	1887lm	72lm/W	CRI 90+	15°	1616lm	61lm/W
		25°	1883lm	72lm/W		25°	1607lm	61lm/W
		38°	1855lm	70lm/W		38°	1599lm	61lm/W
		60°	1845lm	70lm/W		60°	1564lm	59lm/W
3000K		15°	1892lm	72lm/W		15°	1703lm	65lm/W
		25°	1886lm	72lm/W		25°	1710lm	65lm/W
		38°	1874lm	71lm/W		38°	1682lm	64lm/W
		60°	1856lm	70lm/W		60°	1658lm	63lm/W
4000K		15°	2071lm	79lm/W		15°	1834lm	70lm/W
		25°	2051lm	78lm/W		25°	1785lm	68lm/W
		38°	2048lm	78lm/W		38°	1788lm	68lm/W
		60°	2013lm	76lm/W		60°	1810lm	69lm/W

Note: 1. Wider angle of the lens influences the luminous efficacy.

2. The light efficiency will be effected by the black anti-glare ring; the color temperature will be effected by the golden anti-glare ring.

ECLIPSE CONSEIL

Siège : +33 (1) 79 30 48 19- Showroom Paris : +33 (1) 78 95 50 14 - Mob : +33 (6) 87 82 12 04  
Siège social : 7 rue Prudent Neel 92500 Rueil-Malmaison - Showroom : 1 rue Dulong 75017 PARIS