



FEATURES

- Flicker-free driver to create healthy lighting environment.
- Compatible with leading and trailing edge phase cut dimmers.
- Thoughtful friction on the track arm, get rid of loose track arm experience.
- Variety of less-glare optico ptions.
- 5-year guarantee.

Technical Data

Input Voltage/Hz	AC200-240V 50/60Hz
Output Voltage/Current	DC36V/710mA
Power	30W
Rated Input Current	0.150A
THD	<10%
PF value	>0.9
Ingress Protection	IP20
Operating Temperature	-10—40℃
Dimmability	Triac dimmable with DIMMATE driver

Optical Data

LED Brand	bridgelux COB LED
CRI	Ra> 80,Ra> 90
Beam Angle	24°/36°/60°
Colour temperatures	2700K/3000K/4000K
System luminous efficacy up to	108lm/W

Packaging

Box Dimensions	L113 x W97 x H312mm
Box Net Weight	0978Kg
Box Gross Weight	1.063Kg
Carton Dimensions	L500 x W355 x H325 mm/15 PCS
Carton Net Weight	14.67Kg
Carton Gross Weight	16.75Kg



Model	CCT		Beam Angle	Lumen	Efficacy		Beam Angle	Lumen	Efficacy
TR04-30-XX-01	2700K	CRI 80+	24°	3128lm	101lm/W	CRI 90+	24°	2356lm	77lm/W
			36°	2972lm	97lm/W		36°	2300lm	75lm/W
			60°	2895lm	95lm/W		60°	2305lm	74lm/W
TR04-30-XX-01	3000K		24°	3158lm	107lm/W		24°	2515lm	83lm/W
			36°	3058lm	103lm/W		36°	2313lm	78lm/W
			60°	3038lm	102lm/W		60°	2394lm	78lm/W
TR04-30-XX-01	4000K		24°	3291lm	108lm/W		24°	2511lm	83lm/W
			36°	3076lm	102lm/W		36°	2421lm	80lm/W
			60°	2991lm	99lm/W		60°	2445lm	82lm/W

Note:1. Wider angle of the lens influenences the luminons efficacy.

2. The light efficiency will be effected by the black anti-glare ring; the color temperature will be effected by the golden anti-glare ring.

ECLIPSE CONSEIL

Siège : +33 (1) 79 30 48 19- Showroom Paris : +33 (1) 78 95 50 14 - Mob : +33 (6) 87 82 12 04
Siège social : 7 rue Prudent Neel 92500 Rueil-Malmaison - Showroom : 1 rue Dulong 75017 PARIS