



FEATURES

- Controlled by in-track DALI-2 DT6 driver.
- Thoughtful friction on the track arm, get rid of loose track arm experience.
- Variety of less-glare optic options.
- 5-year guarantee.

Technical Data

Input Voltage/Hz	AC200-240V 50/60Hz
Output Voltage/Current	DC35V/710mA
Power	30W(HEP DALI) 31W(TRIDONIC DALI)
Rated Input Current	0.15A(HEP DALI) 0.155A(TRIDONIC DALI)
THD	<13%
PF value	>0.93(HEP DALI) >0.95(TRIDONIC DALI)
Ingress Protection	IP20
Operating Temperature	-10-40°C
Dimmability	HEP (with NFC) DALI TRIDONIC DALI

Optical Data

LED Brand	Bridgelux COB LED
CRI	Ra> 80,Ra> 90
Beam Angle	24°/36°/60°
Colour temperatures	2700K/3000K/4000K
System luminous efficacy up to	107lm/W

Packaging

Box Dimensions	L307 x W208 x H80mm
Box Net Weight	0.428Kg
Box Gross Weight	0.546Kg
Carton Dimensions	L428 x W320 x H425 mm/12 PCS
Carton Net Weight	5.136Kg
Carton Gross Weight	6.552Kg



HEP (with NFC)

CCT	Beam Angle	Lumen	Efficacy	Beam Angle	Lumen	Efficacy
2700K	24°	3128lm	101lm/W	24°	2356lm	78lm/W
	36°	2972lm	97lm/W	36°	2300lm	76lm/W
	60°	2895lm	95lm/W	60°	2305lm	76lm/W
3000K	24°	3158lm	107lm/W	24°	2515lm	83lm/W
	36°	3058lm	101lm/W	36°	2313lm	76lm/W
	60°	3038lm	100lm/W	60°	2394lm	79lm/W
4000K	24°	3291lm	102lm/W	24°	2511lm	83lm/W
	36°	3076lm	102lm/W	36°	2421lm	80lm/W
	60°	2991lm	99lm/W	60°	2445lm	81lm/W

Note:1. Wider angle of the lens influences the luminous efficacy.

2. The light efficiency will be effected by the black anti-glare ring; the color temperature will be effected by the golden anti-glare ring.

ECLIPSE CONSEIL

Siège : +33 (1) 79 30 48 19- Showroom Paris : +33 (1) 78 95 50 14 - Mob : +33 (6) 87 82 12 04
Siège social : 7 rue Prudent Neel 92500 Rueil-Malmaison - Showroom : 1 rue Dulong 75017 PARIS



FEATURES

- Controlled by in-track DALI-2 DT6 driver.
- Thoughtful friction on the track arm, get rid of loose track arm experience.
- Variety of less-glare optic options.
- 5-year guarantee.

Technical Data

Input Voltage/Hz	AC200-240V 50/60Hz
Output Voltage/Current	DC35V/710mA
Power	30W(HEP DALI) 31W(TRIDONIC DALI)
Rated Input Current	0.15A(HEP DALI) 0.155A(TRIDONIC DALI)
THD	<13%
PF value	>0.93(HEP DALI) >0.95(TRIDONIC DALI)
Ingress Protection	IP20
Operating Temperature	-10-40°C
Dimmability	HEP (with NFC) DALI TRIDONIC DALI

Optical Data

LED Brand	Bridgelux COB LED
CRI	Ra> 80,Ra> 90
Beam Angle	24°/36°/60°
Colour temperatures	2700K/3000K/4000K
System luminous efficacy up to	107lm/W

Packaging

Box Dimensions	L307 x W208 x H80mm
Box Net Weight	0.428Kg
Box Gross Weight	0.546Kg
Carton Dimensions	L428 x W320 x H425 mm/12 PCS
Carton Net Weight	5.136Kg
Carton Gross Weight	6.552Kg



HEP (with NFC)

CCT	Beam Angle	Lumen	Efficacy	Beam Angle	Lumen	Efficacy
2700K	24°	3128lm	101lm/W	24°	2356lm	78lm/W
	36°	2972lm	97lm/W	36°	2300lm	76lm/W
	60°	2895lm	95lm/W	60°	2305lm	76lm/W
3000K	24°	3158lm	107lm/W	24°	2515lm	83lm/W
	36°	3058lm	101lm/W	36°	2313lm	76lm/W
	60°	3038lm	100lm/W	60°	2394lm	79lm/W
4000K	24°	3291lm	102lm/W	24°	2511lm	83lm/W
	36°	3076lm	102lm/W	36°	2421lm	80lm/W
	60°	2991lm	99lm/W	60°	2445lm	81lm/W

Note:1. Wider angle of the lens influences the luminous efficacy.

2. The light efficiency will be effected by the black anti-glare ring; the color temperature will be effected by the golden anti-glare ring.

ECLIPSE CONSEIL

Siège : +33 (1) 79 30 48 19- Showroom Paris : +33 (1) 78 95 50 14 - Mob : +33 (6) 87 82 12 04
Siège social : 7 rue Prudent Neel 92500 Rueil-Malmaison - Showroom : 1 rue Dulong 75017 PARIS