



FEATURES

- Flicker-free driver to create healthy lighting environment.
- Compatible with leading and trailing edge phase cut dimmers.
- Patented surface mounted box gives better friction on rotation and create pleasant gear noise.
- Variety of less-glare optic options.
- 5-year guarantee.

Technical Data

Input Voltage/Hz	AC200-240V 50/60Hz
Output Voltage/Current	DC36V/590mA
Power	25W
Rated Input Current	0.125A
THD	<10%
PF value	>0.95
Ingress Protection	IP20
Operating Temperature	-10-40°C
Dimmability	Triac dimmable with DIMMATE driver

Optical Data

LED Brand	CITIZEN COB LED
CRI	Ra> 80,Ra> 90
Beam Angle	18°/24°/36°/60°
Colour temperatures	2700K/3000K/4000K
System luminous efficacy up to	90lm/W

Packaging

Box Dimensions	L110 x W85 x H287mm
Box Net Weight	0.754Kg
Box Gross Weight	0.843Kg
Carton Dimensions	L440 x W345 x H310 mm/15 PCS
Carton Net Weight	11.31Kg
Carton Gross Weight	13.45Kg



Model	CCT		Beam Angle	Lumen	Efficacy		Beam Angle	Lumen	Efficacy
TR05-25-XX-01	2700K	CRI 80+	18°	2160lm	85lm/W	CRI 90+	18°	1705lm	71lm/W
			24°	2100lm	85lm/W		24°	1705lm	71lm/W
			36°	2020lm	82lm/W		36°	1710lm	71lm/W
			60°	2025lm	83lm/W		60°	1705lm	70lm/W
TR05-25-XX-01	3000K		18°	2030lm	85lm/W		18°	1835lm	75lm/W
			24°	2030lm	84m/W		24°	1820lm	75lm/W
			36°	1990lm	82lm/W		36°	1795lm	74lm/W
			60°	1995lm	83lm/W		60°	1835lm	74lm/W
TR05-25-XX-01	4000K		18°	2295lm	90lm/W		18°	1990lm	77lm/W
			24°	2235lm	91lm/W		24°	1975lm	78lm/W
			36°	2170lm	88lm/W		36°	1935lm	79lm/W
			60°	2285lm	89lm/W		60°	1980lm	80lm/W

Note: 1. Wider angle of the lens influences the luminous efficacy.

2. The light efficiency will be effected by the black anti-glare ring; the color temperature will be effected by the golden anti-glare ring.

ECLIPSE CONSEIL

Siège : +33 (1) 79 30 48 19- Showroom Paris : +33 (1) 78 95 50 14 - Mob : +33 (6) 87 82 12 04
Siège social : 7 rue Prudent Neel 92500 Rueil-Malmaison - Showroom : 1 rue Dulong 75017 PARIS