



Black / White



Honeycomb filter




Black



White



Golden



Cut out: Ø68mm

## FEATURES

- Flicker-free driver to create healthy lighting environment.
- Compatible with leading and trailing edge phase cut dimmers.
- Patented recessed case gives better friction on rotation and create pleasant gear noise.
- Installation-friendly spring to protect installer and ceiling.
- Variety of less-glare optic options.
- 5-year guarantee.

## Technical Data

Input Voltage/Hz	AC200-240V 50/60Hz
Output Voltage/Current	DC33V/230mA
Power	10W
Rated Input Current	0.05A
THD	<15%
PF value	>0.9
Ingress Protection	IP20
Operating Temperature	-10—40°C
Dimmability	Triac dimmable with <b>DIMMATE</b> driver
Lifespan L70/B50 at 25°C	>326000H
Lifespan L90/B10 at 25°C	>88000H

## Optical Data

LED Brand	Bridgelux COB LED
CRI	Ra>95
Beam Angle	24°/36°/60°
Colour temperatures	1800K-3000K
System luminous efficacy up to	59lm/W

## Packaging

Box Dimensions	L110 x W85 x H219 x T2 mm
Box Net Weight	0.446Kg
Box Gross Weight	0.512Kg
Carton Dimensions	L565 x W440 x H240 mm/25 PCS
Carton Net Weight	11.15Kg
Carton Gross Weight	13.60Kg



CCT		Beam Angle	Lumen	Efficacy
1800K-3000K	CRI 95+	24°	572lm	59lm/W
		36°	559lm	58lm/W
		60°	539lm	56lm/W

Note: 1. Wider angle of the lens influences the luminous efficacy.

2. The light efficiency will be effected by the black anti-glare ring; the color temperature will be effected by the golden anti-glare ring.

## ECLIPSE CONSEIL

Siège : +33 (1) 79 30 48 19- Showroom Paris : +33 (1) 78 95 50 14 - Mob : +33 (6) 87 82 12 04  
Siège social : 7 rue Prudent Neel 92500 Rueil-Malmaison - Showroom : 1 rue Dulong 75017 PARIS