



FEATURES

- Flicker-free driver to creates healthy lighting environment.
- Compatible with leading and trailing edge phase cut dimmers.
- Patented recessed case gives better friction on rotation and create pleasant gear noise.
- Installation-friendly spring to protect installer and ceiling.
- Variety of less-glare optic options.
- 5-year guarantee.

Technical Data

Input Voltage/Hz	AC200-240V 50/60Hz
Output Voltage/Current	DC35V/230mA
Power	10W
Rated Input Current	0.05A
THD	<15%
PF value	>0.9
Ingress Protection	IP20
Operating Temperature	-10—40°C
Dimmability	Triac dimmable with DIMMATE driver

Optical Data

LED Brand	Bridgelux COB LED
CRI	Ra> 80,Ra> 90
Beam Angle	15°/24°/36°/60°
Colour temperatures	2700K/3000K/4000K
System luminous efficacy up to	90lm/W

Packaging

Box Dimensions	L110 x W85 x H219mm
Box Net Weight	0.446Kg
Box Gross Weight	0.512Kg
Carton Dimensions	L565 x W440 x H240 mm/25 PCS
Carton Net Weight	11.15Kg
Carton Gross Weight	13.6Kg



Model	CCT		Beam Angle	Lumen	Efficacy		Beam Angle	Lumen	Efficacy
TR06-10-XX-01	2700K	CRI 80+	15°	840lm	83lm/W	CRI 90+	15°	735lm	72lm/W
			24°	860lm	84lm/W		24°	740lm	73lm/W
			36°	810lm	81lm/W		36°	710lm	70lm/W
			60°	800lm	79lm/W		60°	700lm	69lm/W
TR06-10-XX-01	3000K		15°	890lm	85lm/W		15°	765lm	75lm/W
			24°	890lm	86m/W		24°	770lm	76lm/W
			36°	870lm	84lm/W		36°	730lm	72lm/W
			60°	850lm	83lm/W		60°	720lm	71lm/W
TR06-10-XX-01	4000K		15°	875lm	87lm/W		15°	850lm	84lm/W
			24°	900lm	90lm/W		24°	850lm	84lm/W
			36°	910lm	90lm/W		36°	820lm	81lm/W
			60°	870lm	86lm/W		60°	810lm	80lm/W

Note: 1. Wider angle of the lens influences the luminous efficacy.

2. The light efficiency will be effected by the black anti-glare ring; the color temperature will be effected by the golden anti-glare ring.

ECLIPSE CONSEIL

Siège : +33 (1) 79 30 48 19- Showroom Paris : +33 (1) 78 95 50 14 - Mob : +33 (6) 87 82 12 04
Siège social : 7 rue Prudent Neel 92500 Reuil-Malmaison - Showroom : 1 rue Dulong 75017 PARIS