




Black / White

Honeycomb filter

Black

White

Golden



Cut out: Ø68mm

Packaging

Box Dimensions	L110 x W85 x H287mm
Box Net Weight	0.780Kg
Box Gross Weight	0.851Kg
Carton Dimensions	L440 x W345 x H310 mm/15 PCS
Carton Net Weight	11.70Kg
Carton Gross Weight	13.57Kg

FEATURES

- Flicker-free driver to create healthy lighting environment.
- Compatible with leading and trailing edge phase cut dimmers.
- Patented recessed case gives better friction on rotation and create pleasant gear noise.
- Installation-friendly spring to protect installer and ceiling.
- Variety of less-glare optic options.
- 3-year guarantee.

Technical Data

Input Voltage/Hz	AC200-240V 50/60Hz
Output Voltage/Current	DC36V/590mA
Power	25W
Rated Input Current	0.125A
THD	<10%
PF value	>0.95
Ingress Protection	IP20
Operating Temperature	-10-40°C
Dimmability	Triac dimmable with DIMMATE driver

Optical Data

LED Brand	CITIZEN COB LED
CRI	Ra>80, Ra>90
SDCM	<6
Beam Angle	18°/24°/36°/60°
Colour temperatures	2700K/3000K/4000K
System luminous efficacy up to	91lm/W

CITIZEN
LED

RoHS CE



CCT	Beam Angle	Lumen	Efficacy	Beam Angle	Lumen	Efficacy
2700K	18°	2159lm	85lm/W	18°	1704lm	71lm/W
	24°	2099lm	85lm/W	24°	1704lm	71lm/W
	36°	2019lm	82lm/W	36°	1710lm	71lm/W
	60°	2025lm	83lm/W	60°	1704lm	70lm/W
3000K	18°	2031lm	85lm/W	18°	1834lm	75lm/W
	24°	2033lm	84lm/W	24°	1823lm	75lm/W
	36°	1992lm	82lm/W	36°	1795lm	74lm/W
	60°	1995lm	83lm/W	60°	1835lm	74lm/W
4000K	18°	2294lm	90lm/W	18°	1993lm	77lm/W
	24°	2235lm	91lm/W	24°	1976lm	78lm/W
	36°	2168lm	88lm/W	36°	1936lm	79lm/W
	60°	2284lm	89lm/W	60°	1978lm	80lm/W

ECLIPSE CONSEIL

Siège : +33 (1) 79 30 48 19- Showroom Paris : +33 (1) 78 95 50 14 - Mob : +33 (6) 87 82 12 04
Siège social : 7 rue Prudent Neel 92500 Rueil-Malmaison - Showroom : 1 rue Dulong 75017 PARIS