


6W 9W
POWER

Black / White



FEATURES

- Maximum 45° vertical rotation can be created on the main body.
- Optic interchangeable.
- Power selectable.
- Flicker-free internal driver.
- Compatible with leading and trailing edge phase cut dimmers.
- 5-year guarantee.

Technical Data

Input Voltage/Hz	AC200-240V 50/60Hz
Output Voltage/Current	DC34V/210mA(9W) DC33V/145mA(6W)
Power	9W 6W
Rated Input Current	0.045A
THD	<25%(9W) <35%(6W)
PF value	>0.9(9W) >0.8(6W)
Ingress Protection	IP20
Operating Temperature	-10—40°C
Dimmability	Triac dimmable with DIMMATE driver

Optical Data

LED Brand	Bridgelux COB LED
CRI	Ra > 90
Beam Angle	150°
Colour temperatures	2700K/3000K/4000K
System luminous efficacy up to	82lm/W

Packaging

Box Dimensions	L150 x W150 x H165mm
Box Net Weight	0.542Kg
Box Gross Weight	0.628Kg
Carton Dimensions	L465 x W465 x H350 mm/18 PCS
Carton Net Weight	9.76Kg
Carton Gross Weight	12.11Kg



Model	CCT	6W	Beam Angle	Lumen	Efficacy	9W	Beam Angle	Lumen	Efficacy
TR09-09-XX-03	2700K		150°	462lm	74lm/W		150°	692lm	78lm/W
TR09-09-XX-03	3000K		150°	479lm	76lm/W		150°	640lm	72lm/W
TR09-09-XX-03	4000K		150°	492lm	79lm/W		150°	726lm	82lm/W

ECLIPSE CONSEIL

Siège : +33 (1) 79 30 48 19- Showroom Paris : +33 (1) 78 95 50 14 - Mob : +33 (6) 87 82 12 04
Siège social : 7 rue Prudent Neel 92500 Rueil-Malmaison - Showroom : 1 rue Dulong 75017 PARIS