



Indoor Luminaire Photometric Data

Description Information

Luminary Name: TR09-06-XX-03 2700K RA90 150D		Lum. Catalog:	Test ID: 01
Lamp Name:		Lamp Catalog: LED	Test Date: 2022/02/21
Manufacture: Shenzhen Norming Lightin		Shld. Ang(°):	Test Machine:GON-2000
Test Lab: Quality Department		Frequency (Hz):	Lamp CCT (K): Ra:
Lum. Size (W*L*H):0.100m*0.000m*-0.100m		Lum. Area (m2):0.063	Lum. W (kg): 0.000
Test System: C, γ	Test Step: C=90.0 γ=1.0	Temp. (°C): 25	Humidity(%):


Character Parameter

Lamp Speciality Parameter		Luminaire Speciality Parameter	
Rated Flux(lm): 426.430	Luminary Flux(lm): 426.425	Field Angle(10%Imax): 226.7(°)	
Rated Power(W):	Luminary Efficiency: 100.00%	Down Lumens&Percent: 375.050lm 87.95%	
Rated Voltage(V):	Luminary EER(lm/W): 70.124	Up Lumens&Percent: 51.375lm 12.05%	
Tested Power(W): 6.081	Max. Candela(cd): 97.105	S/MH: C0_a180=1.324 C90_270=1.312	
Lamps' Inside: 1	Max Cand@Ang. (°): C=180.0 γ=4.0	CIE Type: General Diffuse	
Tested Electrics (V, A, pf):241.2, 0.029	Beam Angle(50%Imax): 139.4(°)	ErP Φ use(120°): 240.641lm	
Lamp Size(W*L*H):0.100m*0.000m*-0.100m	Left=-65.7°, Right=73.7°	IRF(%): 101.767	



2D Plane Light Intensity Distribution Curve


Lum. Name:TR09-06-XX-03 2700K RA90 150D	Lum. Catalog:	Test ID:01
Lamp Name:	Lamp Catalog:LED	Test Lab:Quality Department
Manufacture:Shenzhen Norming Lightin	Test Machine:GON-2000	Test Date:2022/02/21



3D Light Intensity Distribution Modal

Lum. Name:TR09-06-XX-03 2700K RA90 150D	Lum. Catelog:	Test ID:01
Lamp Name:	Lamp Catelog:LED	Test Lab:Quality Department
Manufacture:Shenzhen Norming Lightin	Test Machine:GON-2000	Test Date:2022/02/21

3D Light Intensity Distribution Modal



IES Indoor Report

Photometric Filename:TR09-06-XX-03 2700K RA90 150D.IES

Zonal Flux Tabulation


Zone(γ)	Zone Flux (lm)	Sums Flux (lm)	Zone%Lamp	Sums%Lamp	Zone(γ)	Zone Flux (lm)	Sums Flux (lm)	Zone%Lamp	Sums%Lamp
0.0-1.0	0.09	0.09	0.02	0.02	47.0-48.0	5.72	172.90	1.34	40.55
1.0-2.0	0.28	0.37	0.07	0.09	48.0-49.0	5.73	178.63	1.34	41.89
2.0-3.0	0.46	0.83	0.11	0.20	49.0-50.0	5.74	184.37	1.35	43.24
3.0-4.0	0.65	1.48	0.15	0.35	50.0-51.0	5.74	190.11	1.35	44.58
4.0-5.0	0.83	2.31	0.19	0.54	51.0-52.0	5.74	195.84	1.34	45.93
5.0-6.0	1.01	3.32	0.24	0.78	52.0-53.0	5.73	201.57	1.34	47.27
6.0-7.0	1.19	4.51	0.28	1.06	53.0-54.0	5.71	207.28	1.34	48.61
7.0-8.0	1.37	5.88	0.32	1.38	54.0-55.0	5.69	212.97	1.34	49.94
8.0-9.0	1.55	7.44	0.36	1.74	55.0-56.0	5.67	218.65	1.33	51.27
9.0-10.0	1.73	9.16	0.41	2.15	56.0-57.0	5.65	224.29	1.32	52.60
10.0-11.0	1.90	11.07	0.45	2.60	57.0-58.0	5.62	229.91	1.32	53.92
11.0-12.0	2.08	13.14	0.49	3.08	58.0-59.0	5.58	235.49	1.31	55.22
12.0-13.0	2.25	15.39	0.53	3.61	59.0-60.0	5.54	241.03	1.30	56.52
13.0-14.0	2.41	17.80	0.57	4.17	60.0-61.0	5.50	246.53	1.29	57.81
14.0-15.0	2.58	20.38	0.60	4.78	61.0-62.0	5.45	251.98	1.28	59.09
15.0-16.0	2.74	23.12	0.64	5.42	62.0-63.0	5.40	257.38	1.27	60.36
16.0-17.0	2.90	26.02	0.68	6.10	63.0-64.0	5.35	262.73	1.25	61.61
17.0-18.0	3.06	29.08	0.72	6.82	64.0-65.0	5.29	268.02	1.24	62.85
18.0-19.0	3.21	32.29	0.75	7.57	65.0-66.0	5.23	273.25	1.23	64.08
19.0-20.0	3.36	35.65	0.79	8.36	66.0-67.0	5.17	278.41	1.21	65.29
20.0-21.0	3.51	39.16	0.82	9.18	67.0-68.0	5.10	283.51	1.20	66.48
21.0-22.0	3.65	42.81	0.86	10.04	68.0-69.0	5.03	288.54	1.18	67.66
22.0-23.0	3.79	46.59	0.89	10.93	69.0-70.0	4.96	293.50	1.16	68.83
23.0-24.0	3.92	50.52	0.92	11.85	70.0-71.0	4.89	298.39	1.15	69.97
24.0-25.0	4.05	54.57	0.95	12.80	71.0-72.0	4.81	303.20	1.13	71.10
25.0-26.0	4.18	58.75	0.98	13.78	72.0-73.0	4.73	307.93	1.11	72.21
26.0-27.0	4.30	63.05	1.01	14.78	73.0-74.0	4.65	312.58	1.09	73.30
27.0-28.0	4.42	67.46	1.04	15.82	74.0-75.0	4.57	317.15	1.07	74.37
28.0-29.0	4.53	71.99	1.06	16.88	75.0-76.0	4.49	321.64	1.05	75.43
29.0-30.0	4.64	76.63	1.09	17.97	76.0-77.0	4.40	326.04	1.03	76.46
30.0-31.0	4.74	81.37	1.11	19.08	77.0-78.0	4.32	330.36	1.01	77.47
31.0-32.0	4.84	86.21	1.13	20.22	78.0-79.0	4.23	334.58	0.99	78.46
32.0-33.0	4.93	91.15	1.16	21.37	79.0-80.0	4.14	338.72	0.97	79.43
33.0-34.0	5.02	96.17	1.18	22.55	80.0-81.0	4.05	342.77	0.95	80.38
34.0-35.0	5.11	101.27	1.20	23.75	81.0-82.0	3.96	346.72	0.93	81.31
35.0-36.0	5.18	106.46	1.22	24.96	82.0-83.0	3.87	350.59	0.91	82.21
36.0-37.0	5.26	111.71	1.23	26.20	83.0-84.0	3.77	354.36	0.89	83.10
37.0-38.0	5.33	117.04	1.25	27.45	84.0-85.0	3.68	358.04	0.86	83.96
38.0-39.0	5.39	122.43	1.26	28.71	85.0-86.0	3.59	361.63	0.84	84.80
39.0-40.0	5.45	127.88	1.28	29.99	86.0-87.0	3.49	365.13	0.82	85.62
40.0-41.0	5.50	133.38	1.29	31.28	87.0-88.0	3.40	368.53	0.80	86.42
41.0-42.0	5.55	138.93	1.30	32.58	88.0-89.0	3.31	371.84	0.78	87.20
42.0-43.0	5.59	144.52	1.31	33.89	89.0-90.0	3.21	375.05	0.75	87.95
43.0-44.0	5.63	150.14	1.32	35.21	90.0-91.0	3.12	378.17	0.73	88.68
44.0-45.0	5.66	155.80	1.33	36.54	91.0-92.0	3.03	381.20	0.71	89.39
45.0-46.0	5.68	161.48	1.33	37.87	92.0-93.0	2.94	384.14	0.69	90.08
46.0-47.0	5.70	167.18	1.34	39.20	93.0-94.0	2.85	386.98	0.67	90.75

Zonal Flux Tabulation - (Cont.)

Zone(γ)	Zone Flux (lm)	Sums Flux (lm)	Zone%Lamp	Sums%Lamp	Zone(γ)	Zone Flux (lm)	Sums Flux (lm)	Zone%Lamp	Sums%Lamp
94.0-95.0	2.76	389.74	0.65	91.40	141.0-142.0	0.00	426.43	0.00	100.00
95.0-96.0	2.67	392.41	0.63	92.02	142.0-143.0	0.00	426.43	0.00	100.00
96.0-97.0	2.58	394.98	0.60	92.63	143.0-144.0	0.00	426.43	0.00	100.00
97.0-98.0	2.48	397.47	0.58	93.21	144.0-145.0	0.00	426.43	0.00	100.00
98.0-99.0	2.39	399.86	0.56	93.77	145.0-146.0	0.00	426.43	0.00	100.00
99.0-100.0	2.30	402.17	0.54	94.31	146.0-147.0	0.00	426.43	0.00	100.00
100.0-101.0	2.21	404.38	0.52	94.83	147.0-148.0	0.00	426.43	0.00	100.00
101.0-102.0	2.12	406.50	0.50	95.33	148.0-149.0	0.00	426.43	0.00	100.00
102.0-103.0	2.02	408.52	0.47	95.80	149.0-150.0	0.00	426.43	0.00	100.00
103.0-104.0	1.87	410.40	0.44	96.24	150.0-151.0	0.00	426.43	0.00	100.00
104.0-105.0	1.68	412.08	0.39	96.64	151.0-152.0	0.00	426.43	0.00	100.00
105.0-106.0	1.53	413.61	0.36	96.99	152.0-153.0	0.00	426.43	0.00	100.00
106.0-107.0	1.43	415.03	0.33	97.33	153.0-154.0	0.00	426.43	0.00	100.00
107.0-108.0	1.33	416.36	0.31	97.64	154.0-155.0	0.00	426.43	0.00	100.00
108.0-109.0	1.21	417.57	0.28	97.92	155.0-156.0	0.00	426.43	0.00	100.00
109.0-110.0	1.08	418.64	0.25	98.17	156.0-157.0	0.00	426.43	0.00	100.00
110.0-111.0	0.97	419.61	0.23	98.40	157.0-158.0	0.00	426.43	0.00	100.00
111.0-112.0	0.89	420.51	0.21	98.61	158.0-159.0	0.00	426.43	0.00	100.00
112.0-113.0	0.85	421.36	0.20	98.81	159.0-160.0	0.00	426.43	0.00	100.00
113.0-114.0	0.81	422.16	0.19	99.00	160.0-161.0	0.00	426.43	0.00	100.00
114.0-115.0	0.71	422.88	0.17	99.17	161.0-162.0	0.00	426.43	0.00	100.00
115.0-116.0	0.57	423.45	0.13	99.30	162.0-163.0	0.00	426.43	0.00	100.00
116.0-117.0	0.46	423.91	0.11	99.41	163.0-164.0	0.00	426.43	0.00	100.00
117.0-118.0	0.41	424.31	0.10	99.50	164.0-165.0	0.00	426.43	0.00	100.00
118.0-119.0	0.36	424.67	0.08	99.59	165.0-166.0	0.00	426.43	0.00	100.00
119.0-120.0	0.28	424.95	0.07	99.65	166.0-167.0	0.00	426.43	0.00	100.00
120.0-121.0	0.20	425.14	0.05	99.70	167.0-168.0	0.00	426.43	0.00	100.00
121.0-122.0	0.14	425.28	0.03	99.73	168.0-169.0	0.00	426.43	0.00	100.00
122.0-123.0	0.11	425.40	0.03	99.76	169.0-170.0	0.00	426.43	0.00	100.00
123.0-124.0	0.11	425.50	0.03	99.78	170.0-171.0	0.00	426.43	0.00	100.00
124.0-125.0	0.11	425.62	0.03	99.81	171.0-172.0	0.00	426.43	0.00	100.00
125.0-126.0	0.11	425.73	0.03	99.84	172.0-173.0	0.00	426.43	0.00	100.00
126.0-127.0	0.10	425.83	0.02	99.86	173.0-174.0	0.00	426.43	0.00	100.00
127.0-128.0	0.09	425.92	0.02	99.88	174.0-175.0	0.00	426.43	0.00	100.00
128.0-129.0	0.08	426.00	0.02	99.90	175.0-176.0	0.00	426.43	0.00	100.00
129.0-130.0	0.07	426.07	0.02	99.92	176.0-177.0	0.00	426.43	0.00	100.00
130.0-131.0	0.07	426.14	0.02	99.93	177.0-178.0	0.00	426.43	0.00	100.00
131.0-132.0	0.06	426.21	0.01	99.95	178.0-179.0	0.00	426.43	0.00	100.00
132.0-133.0	0.05	426.26	0.01	99.96	179.0-180.0	0.00	426.43	0.00	100.00
133.0-134.0	0.04	426.30	0.01	99.97					
134.0-135.0	0.04	426.34	0.01	99.98					
135.0-136.0	0.03	426.37	0.01	99.99					
136.0-137.0	0.02	426.39	0.01	99.99					
137.0-138.0	0.02	426.41	0.00	100.00					
138.0-139.0	0.01	426.42	0.00	100.00					
139.0-140.0	0.00	426.43	0.00	100.00					
140.0-141.0	0.00	426.43	0.00	100.00					

Rectangle ISO Lighting Intensity Diagram


Lum. Name:TR09-06-XX-03 2700K RA90 150D	Lum. Catalog:	Test ID:01
Lamp Name:	Lamp Catalog: LED	Test Lab: Quality Department
Manufacture: Shenzhen Norming Lightin	Test Machine:GON-2000	Test Date: 2022/02/21



Plane ISO-Illuminance Diagram

Lum. Name:TR09-06-XX-03 2700K RA90 150D	Lum. Catalog:	Test ID:01
Lamp Name:	Lamp Catalog: LED	Test Lab: Quality Department
Manufacture: Shenzhen Norming Lightin	Test Machine:GON-2000	Test Date: 2022/02/21

Plane ISO-Illuminance Curve




Working Plane Luminaire Mounting Height(m): 3.00
Working Plane Maximum Illuminance(lx): 10.77
Working Plane Maximum Illuminance Position(d/h):H0.0 V-0.0

3D Plane ISO Illuminance Diagram

Lum. Name:TR09-06-XX-03 2700K RA90 150D	Lum. Catelog:	Test ID:01
Lamp Name:	Lamp Catelog:LED	Test Lab:Quality Department
Manufacture:Shenzhen Norming Lightin	Test Machine:GON-2000	Test Date:2022/02/21


3D Plane Illuminance Modal



Space ISO Illuminance Diagram

Lum. Name:TR09-06-XX-03 2700K RA90 150D	Lum. Catelog:	Test ID:01
Lamp Name:	Lamp Catelog:LED	Test Lab:Quality Department
Manufacture:Shenzhen Norming Lightin	Test Machine:GON-2000	Test Date:2022/02/21


Space ISO Illuminance Curve



Space Plane Maximum Illuminance and @Angle:96.81lx,1.0deg
Plane Maximum Lighting Intensity and @Angle:96.854cd,0deg

Illuminance-Distance Diagram

Lum. Name:TR09-06-XX-03 2700K RA90 150D	Lum. Catelog:	Test ID:01
Lamp Name:	Lamp Catelog:LED	Test Lab:Quality Department
Manufacture:Shenzhen Norming Lightin	Test Machine:GON-2000	Test Date:2022/02/21



Indoor Luminance Limiting Curves

Lum. Name:TR09-06-XX-03 2700K RA90 150D	Lum. Catalog:Lum. Catalog: LED	Test ID:01
Lamp Name:	Lamp Catalog:LED	Test Lab:Quality Department
Manufacture:Shenzhen Norming Lightin	Test Machine:GON-2000	Test Date:2022/02/21


Glare Grade Table

GI	Quality	Using Illuminance							
1.15	A	2000	1000	500	<=300				
1.5	B		2000	1000	500	<=300			
1.85	C			2000	1000	500	<=300		
2.2	D				2000	1000	500	<=300	
2.55	E	a				2000	1000	500	<=300
			b	c	d	e	f	g	h

Luminance Table

Gama(deg)	45	50	55	60	65	70	75	80	85
C0	1573	1605	1654	1732	1854	2053	2409	3163	5497
C90	1527	1551	1589	1654	1759	1936	2257	2941	5065


Luminance Limiting Curve



Luminous Size: Length(m)=0.000 Width(m)=-0.100 Height(m)=-0.100 Area(m^2)=0.062832
Luminous Type: Without Luminous Side
Luminous Curves: C0-C180 Color: C90-C270 Color:

Indoor Budgetary Estimate Table

Lum. Name:TR09-06-XX-03 2700K RA90 150D	Lum. Catalog:	Test ID:01
Lamp Name:	Lamp Catalog: LED	Test Lab: Quality Department
Manufacture: Shenzhen Norming Lightin	Test Machine:GON-2000	Test Date: 2022/02/21



Indoor Coefficient of Utilization Table

Lum. Name:TR09-06-XX-03 2700K RA90 150D	Lum. Catelog:	Test ID:01
Lamp Name:	Lamp Catelog:LED	Test Lab:Quality Department
Manufacture:Shenzhen Norming Lightin	Test Machine:GON-2000	Test Date:2022/02/21

Coefficients of Utilization - Zonal Cavity Method																		
Coef.	Effective Floor Cavity Reflectance RFC=0.20																	
RhoCC (%)	80				70				50			30			10			0
RhoW (%)	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR	Coefficient of Utilization(%)																	
0	116	116	116	116	112	112	112	112	104	104	104	97	97	97	91	91	91	88
1	102	96	91	86	98	93	88	83	86	82	78	80	77	74	74	72	69	66
2	92	82	74	67	88	79	72	65	73	67	62	68	63	59	63	59	55	52
3	83	71	62	54	79	68	60	53	64	56	50	59	53	48	55	50	46	43
4	76	62	53	45	72	60	51	44	56	48	42	52	46	40	48	43	38	36
5	69	55	45	38	66	53	44	37	50	42	36	46	40	34	43	38	33	30
6	64	49	40	33	61	48	39	32	45	37	31	42	35	30	39	33	29	26
7	59	45	35	29	56	43	34	28	40	33	27	38	31	26	36	30	25	23
8	55	41	32	25	52	39	31	25	37	29	24	35	28	23	33	27	22	20
9	51	37	29	23	49	36	28	22	34	27	22	32	25	21	30	24	20	18
10	48	34	26	20	46	33	25	20	31	24	19	30	23	19	28	22	18	16

Unified Glare Rating Table

Lum. Name:TR09-06-XX-03 2700K RA90 150D	Lum. Catelog:	Test ID:01
Lamp Name:	Lamp Catelog:LED	Test Lab:Quality Department
Manufacture:Shenzhen Norming Lightin	Test Machine:GON-2000	Test Date:2022/02/21

Unified Glare Rating Table

Ceiling RCC	0.70	0.70	0.50	0.50	0.30	0.70	0.70	0.50	0.50	0.30
Wall RW	0.50	0.30	0.50	0.30	0.30	0.50	0.30	0.50	0.30	0.30
Floor RFC	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20
Room Size	Vewed crosswise					Vewed endwise				
X=2H Y=2H	13.0	14.5	13.5	15.0	15.6	12.8	14.3	13.3	14.8	15.4
	Y=3H	15.4	16.8	15.9	17.3	17.9	15.1	16.5	15.7	17.1
	Y=4H	16.7	18.0	17.2	18.6	19.2	16.4	17.7	16.9	18.3
	Y=6H	18.1	19.3	18.7	19.9	20.6	17.7	19.0	18.3	19.5
	Y=8H	18.9	20.0	19.4	20.6	21.3	18.5	19.7	19.1	20.3
	Y=12H	19.7	20.9	20.3	21.5	22.2	19.3	20.5	19.9	21.1
X=4H Y=2H	14.0	15.3	14.5	15.9	16.5	13.8	15.1	14.4	15.7	16.3
	Y=3H	16.6	17.7	17.2	18.3	19.0	16.4	17.5	17.0	18.1
	Y=4H	18.1	19.1	18.7	19.7	20.4	17.8	18.8	18.4	19.4
	Y=6H	19.7	20.6	20.3	21.2	21.9	19.3	20.3	19.9	20.9
	Y=8H	20.5	21.4	21.1	22.0	22.8	20.2	21.1	20.8	21.7
	Y=12H	21.5	22.3	22.2	23.0	23.7	21.1	21.9	21.8	22.6
X=8H Y=4H	18.7	19.6	19.4	20.3	21.0	18.5	19.4	19.1	20.0	20.7
	Y=6H	20.6	21.4	21.3	22.0	22.9	20.3	21.1	21.0	21.7
	Y=8H	21.7	22.3	22.3	23.0	23.8	21.3	22.0	22.0	22.7
	Y=12H	22.9	23.5	23.5	24.2	25.0	22.5	23.1	23.2	23.8
X=12H Y=4H	18.9	19.7	19.6	20.4	21.1	18.7	19.5	19.3	20.2	20.9
	Y=6H	20.9	21.6	21.6	22.2	23.0	20.6	21.3	21.3	22.0
	Y=8H	22.1	22.7	22.7	23.3	24.1	21.7	22.4	22.4	23.0
Variations with the objerver position at spacings										
S=1.0H	0.1/-0.1					0.1/-0.1				
S=1.5H	0.1/-0.2					0.2/-0.2				
S=2.0H	0.1/-0.1					0.1/-0.1				
Reduced UGR Table:										
Nordic Standard Table:	BK0					BK0				
Correction Value	5.6					5.5				

o the CIE Pub.117, data has been corrected, refers to the lamp's lumens 8.2flm.

Candela Tabulation

V/H	C0.0	C90.0	C180.0	C270.0
γ 0.0	96.76	96.76	96.76	96.76
γ 1.0	96.85	96.34	97.01	96.59
γ 2.0	96.68	96.14	96.94	96.61
γ 3.0	96.45	95.95	97.07	96.62
γ 4.0	96.30	95.72	97.11	96.79
γ 5.0	96.13	95.50	97.08	96.60
γ 6.0	95.80	95.23	97.07	96.63
γ 7.0	95.46	94.95	96.97	96.63
γ 8.0	95.24	94.64	96.94	96.44
γ 9.0	94.92	94.33	96.74	96.48
γ 10.0	94.68	93.93	96.64	96.32
γ 11.0	94.17	93.53	96.46	96.10
γ 12.0	93.84	93.09	96.23	95.97
γ 13.0	93.41	92.69	95.94	95.71
γ 14.0	92.89	92.18	95.86	95.41
γ 15.0	92.47	91.78	95.46	95.19
γ 16.0	92.03	91.31	95.24	94.96
γ 17.0	91.46	90.74	94.91	94.65
γ 18.0	90.94	90.17	94.61	94.30
γ 19.0	90.45	89.61	94.28	93.88
γ 20.0	89.86	89.01	93.83	93.52
γ 21.0	89.26	88.28	93.42	93.12
γ 22.0	88.72	87.72	93.03	92.69
γ 23.0	88.05	87.01	92.54	92.28
γ 24.0	87.49	86.24	92.08	91.84
γ 25.0	86.66	85.71	91.56	91.21
γ 26.0	86.11	84.97	91.05	90.74
γ 27.0	85.34	84.18	90.45	90.22
γ 28.0	84.65	83.35	89.96	89.74
γ 29.0	83.90	82.57	89.34	89.13
γ 30.0	83.15	81.79	88.82	88.42
γ 31.0	82.36	80.97	88.11	87.82
γ 32.0	81.54	80.14	87.45	87.21
γ 33.0	80.81	79.29	86.86	86.52
γ 34.0	79.91	78.38	86.17	85.87
γ 35.0	79.15	77.50	85.45	85.19
γ 36.0	78.26	76.61	84.81	84.35
γ 37.0	77.29	75.69	84.02	83.70
γ 38.0	76.47	74.74	83.30	82.99
γ 39.0	75.55	73.81	82.58	82.20
γ 40.0	74.62	72.90	81.71	81.41
γ 41.0	73.73	71.87	80.93	80.68
γ 42.0	72.76	70.90	80.10	79.83
γ 43.0	71.80	69.86	79.25	79.08
γ 44.0	70.88	68.79	78.41	78.15
γ 45.0	69.87	67.85	77.39	77.25
γ 46.0	68.85	66.77	76.71	76.36

Candela Tabulation - (Cont.)

V/H	C0.0	C90.0	C180.0	C270.0
γ 47.0	67.89	65.74	75.76	75.50
γ 48.0	66.92	64.70	74.88	74.60
γ 49.0	65.84	63.63	73.93	73.68
γ 50.0	64.84	62.66	73.03	72.74
γ 51.0	63.82	61.62	72.10	71.78
γ 52.0	62.80	60.49	71.12	70.91
γ 53.0	61.71	59.47	70.07	69.94
γ 54.0	60.68	58.37	69.13	69.03
γ 55.0	59.59	57.28	68.16	68.02
γ 56.0	58.59	56.21	67.20	67.07
γ 57.0	57.54	55.15	66.18	66.10
γ 58.0	56.51	54.13	65.10	65.06
γ 59.0	55.47	53.04	64.07	64.08
γ 60.0	54.41	51.97	63.08	63.07
γ 61.0	53.39	50.92	61.93	62.02
γ 62.0	52.35	49.88	61.00	61.04
γ 63.0	51.29	48.77	59.88	59.98
γ 64.0	50.26	47.69	58.87	58.98
γ 65.0	49.23	46.71	57.78	57.99
γ 66.0	48.19	45.65	56.75	56.97
γ 67.0	47.18	44.60	55.71	55.91
γ 68.0	46.10	43.63	54.59	54.90
γ 69.0	45.11	42.59	53.58	53.88
γ 70.0	44.11	41.60	52.56	52.90
γ 71.0	43.14	40.62	51.48	51.91
γ 72.0	42.15	39.62	50.37	50.92
γ 73.0	41.13	38.61	49.34	49.85
γ 74.0	40.13	37.64	48.28	48.84
γ 75.0	39.18	36.71	47.26	47.82
γ 76.0	38.21	35.74	46.22	46.88
γ 77.0	37.26	34.84	45.25	45.83
γ 78.0	36.33	33.88	44.18	44.87
γ 79.0	35.42	32.97	43.14	43.81
γ 80.0	34.51	32.09	42.15	42.87
γ 81.0	33.60	31.17	41.11	41.90
γ 82.0	32.74	30.28	40.11	40.93
γ 83.0	31.84	29.45	39.12	39.95
γ 84.0	30.96	28.59	38.19	39.03
γ 85.0	30.10	27.74	37.15	38.08
γ 86.0	29.26	26.90	36.18	37.08
γ 87.0	28.43	26.09	35.27	36.18
γ 88.0	27.59	25.27	34.33	35.24
γ 89.0	26.79	24.46	33.40	34.33
γ 90.0	25.96	23.65	32.49	33.45
γ 91.0	25.17	22.90	31.55	32.53
γ 92.0	24.37	22.12	30.70	31.69
γ 93.0	23.58	21.37	29.82	30.83

Candela Tabulation - (Cont.)

V/H	C0.0	C90.0	C180.0	C270.0
γ 94.0	22.83	20.64	28.94	30.00
γ 95.0	22.09	19.90	28.12	29.19
γ 96.0	21.36	19.17	27.31	28.32
γ 97.0	20.64	18.36	26.45	27.52
γ 98.0	19.92	17.58	25.65	26.69
γ 99.0	19.25	16.82	24.82	25.86
γ 100.0	18.54	16.02	24.02	25.09
γ 101.0	17.87	15.21	23.26	24.32
γ 102.0	17.22	14.09	22.48	23.57
γ 103.0	16.57	12.41	21.71	22.83
γ 104.0	15.91	8.12	20.98	22.08
γ 105.0	15.29	2.96	20.25	21.33
γ 106.0	14.62	0.98	19.53	20.62
γ 107.0	13.34	0.70	18.84	19.91
γ 108.0	10.81	0.68	18.16	19.25
γ 109.0	7.20	0.64	17.46	18.54
γ 110.0	4.64	0.18	16.80	17.79
γ 111.0	2.84	0.00	16.14	17.06
γ 112.0	2.26	0.00	15.48	16.33
γ 113.0	2.48	0.00	14.87	15.63
γ 114.0	3.18	0.00	14.25	13.70
γ 115.0	3.77	0.00	13.65	8.73
γ 116.0	3.90	0.00	13.03	2.99
γ 117.0	3.66	0.00	12.45	1.41
γ 118.0	3.46	0.00	11.08	1.47
γ 119.0	3.54	0.00	7.92	2.03
γ 120.0	3.86	0.00	3.59	2.30
γ 121.0	4.00	0.00	1.22	1.57
γ 122.0	3.71	0.00	0.64	0.89
γ 123.0	3.41	0.00	0.87	0.38
γ 124.0	3.06	0.00	1.64	0.10
γ 125.0	2.73	0.00	2.39	0.00
γ 126.0	2.36	0.00	2.61	0.00
γ 127.0	2.00	0.00	2.39	0.00
γ 128.0	1.63	0.00	2.21	0.00
γ 129.0	1.25	0.00	2.15	0.00
γ 130.0	0.86	0.00	2.52	0.00
γ 131.0	0.47	0.00	2.89	0.00
γ 132.0	0.10	0.00	2.70	0.00
γ 133.0	0.00	0.00	2.39	0.00
γ 134.0	0.00	0.00	2.08	0.00
γ 135.0	0.00	0.00	1.75	0.00
γ 136.0	0.00	0.00	1.42	0.00
γ 137.0	0.00	0.00	1.10	0.00
γ 138.0	0.00	0.00	0.75	0.00
γ 139.0	0.00	0.00	0.39	0.00
γ 140.0	0.00	0.00	0.03	0.00

Candela Tabulation - (Cont.)

V/H	C0.0	C90.0	C180.0	C270.0
γ 141.0	0.00	0.00	0.00	0.00
γ 142.0	0.00	0.00	0.00	0.00
γ 143.0	0.00	0.00	0.00	0.00
γ 144.0	0.00	0.00	0.00	0.00
γ 145.0	0.00	0.00	0.00	0.00
γ 146.0	0.00	0.00	0.00	0.00
γ 147.0	0.00	0.00	0.00	0.00
γ 148.0	0.00	0.00	0.00	0.00
γ 149.0	0.00	0.00	0.00	0.00
γ 150.0	0.00	0.00	0.00	0.00
γ 151.0	0.00	0.00	0.00	0.00
γ 152.0	0.00	0.00	0.00	0.00
γ 153.0	0.00	0.00	0.00	0.00
γ 154.0	0.00	0.00	0.00	0.00
γ 155.0	0.00	0.00	0.00	0.00
γ 156.0	0.00	0.00	0.00	0.00
γ 157.0	0.00	0.00	0.00	0.00
γ 158.0	0.00	0.00	0.00	0.00
γ 159.0	0.00	0.00	0.00	0.00
γ 160.0	0.00	0.00	0.00	0.00
γ 161.0	0.00	0.00	0.00	0.00
γ 162.0	0.00	0.00	0.00	0.00
γ 163.0	0.00	0.00	0.00	0.00
γ 164.0	0.00	0.00	0.00	0.00
γ 165.0	0.00	0.00	0.00	0.00
γ 166.0	0.00	0.00	0.00	0.00
γ 167.0	0.00	0.00	0.00	0.00
γ 168.0	0.00	0.00	0.00	0.00
γ 169.0	0.00	0.00	0.00	0.00
γ 170.0	0.00	0.00	0.00	0.00
γ 171.0	0.00	0.00	0.00	0.00
γ 172.0	0.00	0.00	0.00	0.00
γ 173.0	0.00	0.00	0.00	0.00
γ 174.0	0.00	0.00	0.00	0.00
γ 175.0	0.00	0.00	0.00	0.00
γ 176.0	0.00	0.00	0.00	0.00
γ 177.0	0.00	0.00	0.00	0.00
γ 178.0	0.00	0.00	0.00	0.00
γ 179.0	0.00	0.00	0.00	0.00
γ 180.0	0.00	0.00	0.00	0.00