



Indoor Luminaire Photometric Data

Description Information

Luminary Name:WL02-06-XX-01 3000K RA90 60D		Lum. Catalog:	Test ID: 01
Lamp Name:		Lamp Catalog: LED	Test Date: 2021/10/27
Manufacture: Shenzhen Norming Lighting Co., Ltd		Shld.Ang(°):	Test Machine:GON-2000
Test Lab: Quality Department		Frequency (Hz):	Lamp CCT (K): Ra:
Lum. Size (W*L*H):0.076m*-0.076m*0.000m		Lum. Area (m2):0.005	Lum. W (kg): 0.000
Test System: C, γ	Test Step: C=90.0 γ=1.0	Temp. (°C): 25	Humidity(%): 50.0


Character Parameter

Lamp Speciality Parameter		Luminaire Speciality Parameter	
Rated Flux(lm): 536.620	Luminary Flux(lm): 536.619	Field Angle(10%Imax): 84.1(°)	
Rated Power(W):	Luminary Efficiency: 100.00%	Down Lumens&Percent: 534.678lm 99.64%	
Rated Voltage(V):	Luminary EER(lm/W): 86.663	Up Lumens&Percent: 1.941lm 0.36%	
Tested Power(W): 6.192	Max. Candela(cd): 559.628	S/MH: C0_a180=0.964 C90_270=0.950	
Lamps' Inside: 1	Max Cand@Ang. (°): C=0.0 γ=4.0	CIE Type: Semi-Direct	
Tested Electrics (V, A, pf):241.1, 0.030, 0.844	Beam Angle(50%Imax): 59.5(°)	ErP ϕ use(90°): 466.529lm	
Lamp Size (W*L*H):0.076m*-0.076m*0.000m	Left=-26.2°, Right=33.3°	IRF(%): 207.025	



2D Plane Light Intensity Distribution Curve


Lum. Name: WL02-06-XX-01 3000K RA90 60D	Lum. Catelog:	Test ID: 01
Lamp Name:	Lamp Catelog: LED	Test Lab: Quality Department
Manufacture: Shenzhen Norming Lighting Co., Ltd	Test Machine:GON-2000	Test Date: 2021/10/27



3D Light Intensity Distribution Modal

Lum. Name: WL02-06-XX-01 3000K RA90 60D	Lum. Catelog:	Test ID: 01
Lamp Name:	Lamp Catelog: LED	Test Lab: Quality Department
Manufacture: Shenzhen Norming Lighting Co., Ltd	Test Machine:GON-2000	Test Date: 2021/10/27

3D Light Intensity Distribution Modal



Zonal Flux Tabulation


Zone(γ)	Zone Flux (lm)	Sums Flux (lm)	Zone%Lamp	Sums%Lamp	Zone(γ)	Zone Flux (lm)	Sums Flux (lm)	Zone%Lamp	Sums%Lamp
0.0-1.0	0.53	0.53	0.10	0.10	47.0-48.0	2.57	502.82	0.48	93.70
1.0-2.0	1.60	2.13	0.30	0.40	48.0-49.0	2.35	505.17	0.44	94.14
2.0-3.0	2.66	4.79	0.50	0.89	49.0-50.0	2.16	507.33	0.40	94.54
3.0-4.0	3.72	8.51	0.69	1.59	50.0-51.0	1.99	509.32	0.37	94.91
4.0-5.0	4.78	13.29	0.89	2.48	51.0-52.0	1.84	511.16	0.34	95.26
5.0-6.0	5.83	19.12	1.09	3.56	52.0-53.0	1.70	512.86	0.32	95.57
6.0-7.0	6.87	25.99	1.28	4.84	53.0-54.0	1.58	514.44	0.29	95.87
7.0-8.0	7.90	33.89	1.47	6.31	54.0-55.0	1.47	515.92	0.27	96.14
8.0-9.0	8.91	42.80	1.66	7.98	55.0-56.0	1.37	517.29	0.26	96.40
9.0-10.0	9.93	52.73	1.85	9.83	56.0-57.0	1.28	518.57	0.24	96.64
10.0-11.0	10.93	63.66	2.04	11.86	57.0-58.0	1.21	519.78	0.22	96.86
11.0-12.0	11.92	75.58	2.22	14.08	58.0-59.0	1.13	520.91	0.21	97.07
12.0-13.0	12.87	88.45	2.40	16.48	59.0-60.0	1.07	521.98	0.20	97.27
13.0-14.0	13.79	102.24	2.57	19.05	60.0-61.0	1.00	522.98	0.19	97.46
14.0-15.0	14.66	116.90	2.73	21.79	61.0-62.0	0.95	523.93	0.18	97.63
15.0-16.0	15.46	132.37	2.88	24.67	62.0-63.0	0.90	524.82	0.17	97.80
16.0-17.0	16.19	148.56	3.02	27.68	63.0-64.0	0.85	525.67	0.16	97.96
17.0-18.0	16.84	165.39	3.14	30.82	64.0-65.0	0.80	526.47	0.15	98.11
18.0-19.0	17.41	182.80	3.24	34.07	65.0-66.0	0.76	527.23	0.14	98.25
19.0-20.0	17.87	200.67	3.33	37.40	66.0-67.0	0.71	527.94	0.13	98.38
20.0-21.0	18.20	218.88	3.39	40.79	67.0-68.0	0.67	528.61	0.13	98.51
21.0-22.0	18.41	237.28	3.43	44.22	68.0-69.0	0.63	529.24	0.12	98.63
22.0-23.0	18.45	255.74	3.44	47.66	69.0-70.0	0.59	529.83	0.11	98.73
23.0-24.0	18.37	274.10	3.42	51.08	70.0-71.0	0.55	530.38	0.10	98.84
24.0-25.0	18.13	292.24	3.38	54.46	71.0-72.0	0.51	530.89	0.10	98.93
25.0-26.0	17.75	309.98	3.31	57.77	72.0-73.0	0.48	531.37	0.09	99.02
26.0-27.0	17.21	327.19	3.21	60.97	73.0-74.0	0.44	531.81	0.08	99.10
27.0-28.0	16.54	343.73	3.08	64.05	74.0-75.0	0.40	532.21	0.08	99.18
28.0-29.0	15.77	359.50	2.94	66.99	75.0-76.0	0.37	532.58	0.07	99.25
29.0-30.0	14.92	374.42	2.78	69.77	76.0-77.0	0.33	532.91	0.06	99.31
30.0-31.0	14.01	388.44	2.61	72.39	77.0-78.0	0.29	533.21	0.05	99.36
31.0-32.0	13.09	401.53	2.44	74.83	78.0-79.0	0.26	533.47	0.05	99.41
32.0-33.0	12.16	413.69	2.27	77.09	79.0-80.0	0.23	533.69	0.04	99.45
33.0-34.0	11.21	424.89	2.09	79.18	80.0-81.0	0.19	533.89	0.04	99.49
34.0-35.0	10.24	435.14	1.91	81.09	81.0-82.0	0.17	534.05	0.03	99.52
35.0-36.0	9.29	444.43	1.73	82.82	82.0-83.0	0.14	534.19	0.03	99.55
36.0-37.0	8.36	452.79	1.56	84.38	83.0-84.0	0.12	534.31	0.02	99.57
37.0-38.0	7.48	460.27	1.39	85.77	84.0-85.0	0.10	534.41	0.02	99.59
38.0-39.0	6.67	466.94	1.24	87.01	85.0-86.0	0.08	534.49	0.01	99.60
39.0-40.0	5.93	472.87	1.11	88.12	86.0-87.0	0.06	534.55	0.01	99.61
40.0-41.0	5.28	478.15	0.98	89.10	87.0-88.0	0.05	534.60	0.01	99.62
41.0-42.0	4.71	482.86	0.88	89.98	88.0-89.0	0.04	534.64	0.01	99.63
42.0-43.0	4.22	487.08	0.79	90.77	89.0-90.0	0.03	534.68	0.01	99.64
43.0-44.0	3.80	490.88	0.71	91.48	90.0-91.0	0.03	534.70	0.00	99.64
44.0-45.0	3.43	494.31	0.64	92.12	91.0-92.0	0.02	534.73	0.00	99.65
45.0-46.0	3.11	497.42	0.58	92.70	92.0-93.0	0.02	534.74	0.00	99.65
46.0-47.0	2.82	500.25	0.53	93.22	93.0-94.0	0.01	534.76	0.00	99.65

Zonal Flux Tabulation - (Cont.)

Zone(γ)	Zone Flux (lm)	Sums Flux (lm)	Zone%Lamp	Sums%Lamp	Zone(γ)	Zone Flux (lm)	Sums Flux (lm)	Zone%Lamp	Sums%Lamp
94.0-95.0	0.01	534.77	0.00	99.65	141.0-142.0	0.04	534.97	0.01	99.69
95.0-96.0	0.01	534.77	0.00	99.66	142.0-143.0	0.04	535.01	0.01	99.70
96.0-97.0	0.00	534.77	0.00	99.66	143.0-144.0	0.04	535.05	0.01	99.71
97.0-98.0	0.00	534.78	0.00	99.66	144.0-145.0	0.05	535.09	0.01	99.72
98.0-99.0	0.00	534.78	0.00	99.66	145.0-146.0	0.05	535.14	0.01	99.72
99.0-100.0	0.00	534.78	0.00	99.66	146.0-147.0	0.05	535.19	0.01	99.73
100.0-101.0	0.00	534.78	0.00	99.66	147.0-148.0	0.05	535.24	0.01	99.74
101.0-102.0	0.00	534.78	0.00	99.66	148.0-149.0	0.05	535.30	0.01	99.75
102.0-103.0	0.00	534.78	0.00	99.66	149.0-150.0	0.06	535.35	0.01	99.76
103.0-104.0	0.00	534.78	0.00	99.66	150.0-151.0	0.06	535.41	0.01	99.77
104.0-105.0	0.00	534.78	0.00	99.66	151.0-152.0	0.06	535.47	0.01	99.79
105.0-106.0	0.00	534.78	0.00	99.66	152.0-153.0	0.06	535.53	0.01	99.80
106.0-107.0	0.00	534.78	0.00	99.66	153.0-154.0	0.06	535.59	0.01	99.81
107.0-108.0	0.00	534.78	0.00	99.66	154.0-155.0	0.06	535.65	0.01	99.82
108.0-109.0	0.00	534.78	0.00	99.66	155.0-156.0	0.06	535.71	0.01	99.83
109.0-110.0	0.00	534.78	0.00	99.66	156.0-157.0	0.06	535.77	0.01	99.84
110.0-111.0	0.00	534.78	0.00	99.66	157.0-158.0	0.06	535.83	0.01	99.85
111.0-112.0	0.00	534.78	0.00	99.66	158.0-159.0	0.06	535.88	0.01	99.86
112.0-113.0	0.00	534.78	0.00	99.66	159.0-160.0	0.06	535.94	0.01	99.87
113.0-114.0	0.00	534.78	0.00	99.66	160.0-161.0	0.06	536.00	0.01	99.88
114.0-115.0	0.00	534.78	0.00	99.66	161.0-162.0	0.06	536.05	0.01	99.89
115.0-116.0	0.00	534.78	0.00	99.66	162.0-163.0	0.05	536.11	0.01	99.90
116.0-117.0	0.00	534.78	0.00	99.66	163.0-164.0	0.05	536.16	0.01	99.91
117.0-118.0	0.00	534.78	0.00	99.66	164.0-165.0	0.05	536.21	0.01	99.92
118.0-119.0	0.00	534.78	0.00	99.66	165.0-166.0	0.05	536.26	0.01	99.93
119.0-120.0	0.00	534.78	0.00	99.66	166.0-167.0	0.05	536.30	0.01	99.94
120.0-121.0	0.00	534.78	0.00	99.66	167.0-168.0	0.04	536.35	0.01	99.95
121.0-122.0	0.00	534.78	0.00	99.66	168.0-169.0	0.04	536.39	0.01	99.96
122.0-123.0	0.00	534.78	0.00	99.66	169.0-170.0	0.04	536.43	0.01	99.96
123.0-124.0	0.00	534.78	0.00	99.66	170.0-171.0	0.04	536.46	0.01	99.97
124.0-125.0	0.00	534.78	0.00	99.66	171.0-172.0	0.03	536.49	0.01	99.98
125.0-126.0	0.00	534.78	0.00	99.66	172.0-173.0	0.03	536.52	0.01	99.98
126.0-127.0	0.00	534.78	0.00	99.66	173.0-174.0	0.03	536.55	0.00	99.99
127.0-128.0	0.00	534.78	0.00	99.66	174.0-175.0	0.02	536.57	0.00	99.99
128.0-129.0	0.00	534.78	0.00	99.66	175.0-176.0	0.02	536.59	0.00	99.99
129.0-130.0	0.00	534.78	0.00	99.66	176.0-177.0	0.01	536.60	0.00	100.00
130.0-131.0	0.00	534.78	0.00	99.66	177.0-178.0	0.01	536.61	0.00	100.00
131.0-132.0	0.00	534.78	0.00	99.66	178.0-179.0	0.01	536.62	0.00	100.00
132.0-133.0	0.00	534.78	0.00	99.66	179.0-180.0	0.00	536.62	0.00	100.00
133.0-134.0	0.01	534.79	0.00	99.66					
134.0-135.0	0.01	534.80	0.00	99.66					
135.0-136.0	0.01	534.81	0.00	99.66					
136.0-137.0	0.02	534.83	0.00	99.67					
137.0-138.0	0.02	534.85	0.00	99.67					
138.0-139.0	0.02	534.87	0.00	99.67					
139.0-140.0	0.03	534.90	0.01	99.68					
140.0-141.0	0.03	534.93	0.01	99.69					

Rectangle ISO Lighting Intensity Diagram


Lum. Name: WL02-06-XX-01 3000K RA90 60D	Lum. Catalog:	Test ID: 01
Lamp Name:	Lamp Catalog: LED	Test Lab: Quality Department
Manufacture: Shenzhen Norming Lighting Co., Ltd	Test Machine:GON-2000	Test Date: 2021/10/27



Plane ISO-Illuminance Diagram

Lum. Name: WL02-06-XX-01 3000K RA90 60D	Lum. Catalog:	Test ID: 01
Lamp Name:	Lamp Catalog: LED	Test Lab: Quality Department
Manufacture: Shenzhen Norming Lighting Co., Ltd	Test Machine:GON-2000	Test Date: 2021/10/27

Plane ISO-Illuminance Curve




# IES Indoor Report

Photometric Filename:WL02-06-XX-01 3000K RA90 60D.IES

## 3D Plane ISO Illuminance Diagram

Lum. Name: WL02-06-XX-01 3000K RA90 60D	Lum. Catalog:	Test ID: 01
Lamp Name:	Lamp Catalog: LED	Test Lab: Quality Department
Manufacture: Shenzhen Norming Lighting Co., Ltd	Test Machine:GON-2000	Test Date: 2021/10/27

## 3D Plane Illuminance Modal




Curves: 3D Model — 90% — 80% — 70% — 60% — 50% — 40% — 30% — 20% — 10% —  
View Angles(deg): 0 Height(m): 3.0 Distance(m): 10.0



Space ISO Illuminance Diagram

Lum. Name: WL02-06-XX-01 3000K RA90 60D	Lum. Catalog:	Test ID: 01
Lamp Name:	Lamp Catalog: LED	Test Lab: Quality Department
Manufacture: Shenzhen Norming Lighting Co., Ltd	Test Machine:GON-2000	Test Date: 2021/10/27


Space ISO Illuminance Curve



Space Plane Maximum Illuminance and @Angle:556.86lx,3.0deg  
Plane Maximum Lighting Intensity and @Angle:559.628cd,0deg

Illuminance-Distance Diagram

Lum. Name: WL02-06-XX-01 3000K RA90 60D	Lum. Catalog:	Test ID: 01
Lamp Name:	Lamp Catalog: LED	Test Lab: Quality Department
Manufacture: Shenzhen Norming Lighting Co., Ltd	Test Machine:GON-2000	Test Date: 2021/10/27



Indoor Luminance Limiting Curves

Lum. Name: WL02-06-XX-01 3000K RA90 60D	Lum. Catalog:	Test ID: 01
Lamp Name:	Lamp Catalog: LED	Test Lab: Quality Department
Manufacture: Shenzhen Norming Lighting Co., Ltd	Test Machine:GON-2000	Test Date: 2021/10/27


Glare Grade Table

GI	Quality	Using Illuminance							
1.15	A	2000	1000	500	<=300				
1.5	B		2000	1000	500	<=300			
1.85	C			2000	1000	500	<=300		
2.2	D				2000	1000	500	<=300	
2.55	E	a				2000	1000	500	<=300
			b	c	d	e	f	g	h

Luminance Table

Gama(deg)	45	50	55	60	65	70	75	80	85
C0	18977	11856	8323	6412	5382	4841	4601	4402	4618
C90	9052	6325	4714	3822	3196	2575	1915	856	0

Luminance Limiting Curve




Luminous Size: Length(m)=-0.076 Width(m)=-0.076 Height(m)=0.000 Area(m^2)=0.004536

Luminous Type: Without Luminous Side

Luminous Curves: C0-C180 Color: C90-C270 Color:

Indoor Budgetary Estimate Table

Lum. Name: WL02-06-XX-01 3000K RA90 60D	Lum. Catalog:	Test ID: 01
Lamp Name:	Lamp Catalog: LED	Test Lab: Quality Department
Manufacture: Shenzhen Norming Lighting Co., Ltd	Test Machine:GON-2000	Test Date: 2021/10/27



Indoor Coefficient of Utilization Table

Lum. Name: WL02-06-XX-01 3000K RA90 60D	Lum. Catelog:	Test ID: 01
Lamp Name:	Lamp Catelog: LED	Test Lab: Quality Department
Manufacture: Shenzhen Norming Lighting Co., Ltd	Test Machine:GON-2000	Test Date: 2021/10/27

Coefficients of Utilization - Zonal Cavity Method																		
Coef.	Effective Floor Cavity Reflectance RFC=0.20																	
RhoCC (%)	80				70				50			30			10			0
RhoW (%)	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR	Coefficient of Utilization(%)																	
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	113	110	107	105	111	108	106	103	104	102	100	100	98	97	96	95	94	92
2	107	102	98	94	105	100	96	93	97	94	91	94	91	89	91	89	87	85
3	101	95	90	85	99	93	89	85	91	87	83	88	85	82	86	83	81	79
4	96	88	82	78	94	87	82	78	85	80	77	83	79	76	81	78	75	73
5	91	82	76	72	89	81	76	72	80	75	71	78	74	70	76	73	70	68
6	86	77	71	67	85	76	71	66	75	70	66	73	69	65	72	68	65	63
7	82	73	66	62	81	72	66	62	71	65	61	69	65	61	68	64	61	59
8	78	68	62	58	77	68	62	58	67	61	58	65	61	57	64	60	57	56
9	74	64	58	54	73	64	58	54	63	58	54	62	57	54	61	57	54	52
10	71	61	55	51	70	60	55	51	60	54	51	59	54	51	58	54	50	49

Unified Glare Rating Table

Lum. Name: WL02-06-XX-01 3000K RA90 60D	Lum. Catelog:	Test ID: 01
Lamp Name:	Lamp Catalog: LED	Test Lab: Quality Department
Manufacture: Shenzhen Norming Lighting Co., Ltd	Test Machine:GON-2000	Test Date: 2021/10/27

Unified Glare Rating Table

Ceiling RCC	0.70	0.70	0.50	0.50	0.30	0.70	0.70	0.50	0.50	0.30
Wall RW	0.50	0.30	0.50	0.30	0.30	0.50	0.30	0.50	0.30	0.30
Floor RFC	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20
Room Size	Vewed crosswise					Vewed endwise				
X=2H    Y=2H	19.5	20.6	19.8	20.9	21.2	15.4	16.6	15.8	16.9	17.2
	19.5	20.5	19.9	20.9	21.3	15.6	16.6	15.9	16.9	17.3
	19.6	20.5	20.0	20.9	21.3	15.6	16.5	16.0	16.9	17.3
	19.6	20.5	20.0	20.9	21.3	15.5	16.4	15.9	16.8	17.2
	19.6	20.4	20.0	20.8	21.3	15.4	16.3	15.9	16.7	17.1
	19.6	20.4	20.1	20.8	21.2	15.4	16.2	15.8	16.6	17.0
X=4H    Y=2H	19.3	20.2	19.7	20.6	21.0	15.4	16.4	15.8	16.7	17.1
	19.4	20.2	19.9	20.7	21.1	15.6	16.4	16.0	16.8	17.2
	19.5	20.3	20.0	20.7	21.1	15.7	16.4	16.1	16.8	17.3
	19.6	20.3	20.1	20.7	21.2	15.6	16.3	16.1	16.7	17.2
	19.7	20.3	20.1	20.7	21.2	15.6	16.2	16.0	16.6	17.1
	19.7	20.2	20.2	20.7	21.2	15.5	16.1	16.0	16.5	17.0
X=8H    Y=4H	19.5	20.1	19.9	20.5	21.0	15.6	16.2	16.1	16.7	17.2
	19.6	20.1	20.1	20.6	21.2	15.6	16.1	16.1	16.6	17.2
	19.7	20.1	20.2	20.7	21.2	15.5	16.0	16.1	16.5	17.0
	19.8	20.2	20.3	20.7	21.3	15.5	15.9	16.0	16.4	17.0
X=12H    Y=4H	19.4	19.9	19.9	20.4	20.9	15.6	16.1	16.1	16.6	17.1
	19.6	20.0	20.1	20.5	21.1	15.6	16.0	16.1	16.5	17.1
	19.7	20.1	20.2	20.6	21.2	15.5	15.9	16.1	16.4	17.0
Variations with the objerver position at spacings										
S=1.0H	0.4/-0.4					1.2/-1.6				
S=1.5H	0.7/-0.8					1.7/-2.3				
S=2.0H	1.0/-1.1					2.2/-2.9				
Reduced UGR Table:										
Nordic Standard Table:	BK0					BK0				
Correction Value	0.7					0.6				

o the CIE Pub.117, data has been corrected, refers to the lamp's lumens 8.2flm.

Candela Tabulation

V/H	C0.0	C90.0	C180.0	C270.0
γ 0.0	556.84	556.84	556.84	556.84
γ 1.0	556.95	556.52	555.26	557.43
γ 2.0	557.86	555.70	555.08	557.39
γ 3.0	559.16	554.62	552.91	557.14
γ 4.0	559.63	554.12	551.78	557.39
γ 5.0	559.39	553.09	550.96	557.51
γ 6.0	558.38	552.61	548.60	556.81
γ 7.0	557.39	550.91	545.88	555.91
γ 8.0	556.38	549.72	543.32	554.01
γ 9.0	554.45	548.39	541.71	551.90
γ 10.0	552.76	547.83	541.00	549.87
γ 11.0	551.47	546.41	538.85	547.83
γ 12.0	550.93	543.51	535.89	545.36
γ 13.0	550.21	538.24	531.29	543.45
γ 14.0	549.61	531.38	524.43	541.71
γ 15.0	549.47	520.86	514.22	540.06
γ 16.0	548.40	507.72	501.80	538.65
γ 17.0	545.74	492.05	487.12	536.86
γ 18.0	542.63	475.88	471.25	533.42
γ 19.0	538.99	458.14	453.20	529.17
γ 20.0	532.40	439.36	432.52	521.50
γ 21.0	524.97	419.46	410.79	511.03
γ 22.0	514.21	397.57	388.34	497.36
γ 23.0	498.94	374.37	364.81	482.34
γ 24.0	483.66	351.28	340.16	464.68
γ 25.0	466.54	326.09	313.24	444.49
γ 26.0	448.61	299.44	285.57	423.08
γ 27.0	429.08	271.46	256.15	400.12
γ 28.0	408.42	243.16	228.18	376.33
γ 29.0	385.85	216.49	201.13	351.94
γ 30.0	361.89	190.15	175.04	327.84
γ 31.0	337.91	165.70	152.04	303.77
γ 32.0	313.45	143.79	132.38	278.95
γ 33.0	288.13	125.19	115.11	253.58
γ 34.0	262.22	108.69	100.30	228.00
γ 35.0	235.53	94.67	87.46	202.55
γ 36.0	209.55	82.66	76.50	178.23
γ 37.0	184.04	72.34	67.10	155.35
γ 38.0	160.22	63.70	58.97	134.80
γ 39.0	138.62	56.25	51.96	116.92
γ 40.0	119.47	49.94	45.64	101.32
γ 41.0	103.24	44.52	40.33	88.34
γ 42.0	89.78	39.79	35.82	77.03
γ 43.0	78.30	35.61	31.98	67.50
γ 44.0	68.87	32.13	28.67	59.49
γ 45.0	60.87	29.04	25.68	52.58
γ 46.0	54.04	26.37	23.10	46.36

Candela Tabulation - (Cont.)

V/H	C0.0	C90.0	C180.0	C270.0
γ 47.0	48.18	24.01	20.90	41.05
γ 48.0	43.06	21.95	18.99	36.52
γ 49.0	38.51	20.07	17.29	32.81
γ 50.0	34.57	18.44	15.80	29.66
γ 51.0	31.22	16.94	14.52	26.92
γ 52.0	28.33	15.58	13.38	24.51
γ 53.0	25.80	14.37	12.35	22.33
γ 54.0	23.62	13.24	11.42	20.39
γ 55.0	21.66	12.27	10.60	18.70
γ 56.0	19.90	11.39	9.87	17.18
γ 57.0	18.38	10.64	9.23	15.82
γ 58.0	16.97	9.91	8.66	14.65
γ 59.0	15.69	9.25	8.13	13.60
γ 60.0	14.54	8.67	7.63	12.67
γ 61.0	13.53	8.10	7.17	11.84
γ 62.0	12.61	7.57	6.74	11.14
γ 63.0	11.77	7.08	6.31	10.47
γ 64.0	11.01	6.60	5.91	9.89
γ 65.0	10.32	6.13	5.51	9.30
γ 66.0	9.67	5.69	5.14	8.79
γ 67.0	9.09	5.28	4.76	8.31
γ 68.0	8.54	4.87	4.32	7.87
γ 69.0	8.02	4.45	3.90	7.41
γ 70.0	7.51	3.99	3.53	7.01
γ 71.0	7.06	3.61	3.20	6.62
γ 72.0	6.60	3.26	2.89	6.23
γ 73.0	6.19	2.91	2.56	5.82
γ 74.0	5.80	2.57	2.25	5.39
γ 75.0	5.40	2.25	1.95	4.98
γ 76.0	4.99	1.94	1.64	4.60
γ 77.0	4.54	1.65	1.29	4.24
γ 78.0	4.16	1.35	0.89	3.87
γ 79.0	3.80	0.95	0.69	3.52
γ 80.0	3.47	0.67	0.46	3.17
γ 81.0	3.13	0.44	0.25	2.82
γ 82.0	2.81	0.24	0.09	2.45
γ 83.0	2.48	0.05	0.00	2.14
γ 84.0	2.16	0.00	0.00	1.75
γ 85.0	1.83	0.00	0.00	1.42
γ 86.0	1.41	0.00	0.00	1.17
γ 87.0	1.16	0.00	0.00	0.95
γ 88.0	0.94	0.00	0.00	0.77
γ 89.0	0.73	0.00	0.00	0.62
γ 90.0	0.56	0.00	0.00	0.52
γ 91.0	0.43	0.00	0.00	0.44
γ 92.0	0.34	0.00	0.00	0.36
γ 93.0	0.25	0.00	0.00	0.29



Candela Tabulation - (Cont.)

V/H	C0.0	C90.0	C180.0	C270.0
γ 94.0	0.18	0.00	0.00	0.22
γ 95.0	0.13	0.00	0.00	0.16
γ 96.0	0.07	0.00	0.00	0.10
γ 97.0	0.00	0.00	0.00	0.05
γ 98.0	0.00	0.00	0.00	0.00
γ 99.0	0.00	0.00	0.00	0.00
γ 100.0	0.00	0.00	0.00	0.00
γ 101.0	0.00	0.00	0.00	0.00
γ 102.0	0.00	0.00	0.00	0.00
γ 103.0	0.00	0.00	0.00	0.00
γ 104.0	0.00	0.00	0.00	0.00
γ 105.0	0.00	0.00	0.00	0.00
γ 106.0	0.00	0.00	0.00	0.00
γ 107.0	0.00	0.00	0.00	0.00
γ 108.0	0.00	0.00	0.00	0.00
γ 109.0	0.00	0.00	0.00	0.00
γ 110.0	0.00	0.00	0.00	0.00
γ 111.0	0.00	0.00	0.00	0.00
γ 112.0	0.00	0.00	0.00	0.00
γ 113.0	0.00	0.00	0.00	0.00
γ 114.0	0.00	0.00	0.00	0.00
γ 115.0	0.00	0.00	0.00	0.00
γ 116.0	0.00	0.00	0.00	0.00
γ 117.0	0.00	0.00	0.00	0.00
γ 118.0	0.00	0.00	0.00	0.00
γ 119.0	0.00	0.00	0.00	0.00
γ 120.0	0.00	0.00	0.00	0.00
γ 121.0	0.00	0.00	0.00	0.00
γ 122.0	0.00	0.00	0.00	0.00
γ 123.0	0.00	0.00	0.00	0.00
γ 124.0	0.00	0.00	0.00	0.00
γ 125.0	0.00	0.00	0.00	0.00
γ 126.0	0.00	0.00	0.00	0.00
γ 127.0	0.00	0.00	0.00	0.00
γ 128.0	0.00	0.00	0.00	0.00
γ 129.0	0.00	0.00	0.00	0.00
γ 130.0	0.00	0.00	0.02	0.00
γ 131.0	0.00	0.00	0.09	0.00
γ 132.0	0.00	0.00	0.14	0.00
γ 133.0	0.00	0.00	0.20	0.03
γ 134.0	0.00	0.03	0.27	0.08
γ 135.0	0.00	0.09	0.34	0.15
γ 136.0	0.00	0.15	0.41	0.19
γ 137.0	0.04	0.21	0.47	0.25
γ 138.0	0.11	0.28	0.54	0.31
γ 139.0	0.16	0.34	0.60	0.37
γ 140.0	0.22	0.40	0.67	0.42

Candela Tabulation - (Cont.)

V/H	C0.0	C90.0	C180.0	C270.0
γ 141.0	0.28	0.47	0.73	0.47
γ 142.0	0.34	0.53	0.80	0.53
γ 143.0	0.40	0.60	0.87	0.59
γ 144.0	0.47	0.66	0.93	0.65
γ 145.0	0.53	0.72	0.99	0.71
γ 146.0	0.60	0.78	1.04	0.77
γ 147.0	0.66	0.84	1.10	0.83
γ 148.0	0.72	0.89	1.17	0.89
γ 149.0	0.79	0.95	1.21	0.94
γ 150.0	0.84	1.00	1.27	0.99
γ 151.0	0.91	1.05	1.31	1.06
γ 152.0	0.97	1.10	1.37	1.11
γ 153.0	1.04	1.14	1.41	1.16
γ 154.0	1.09	1.20	1.46	1.21
γ 155.0	1.14	1.25	1.50	1.26
γ 156.0	1.20	1.29	1.55	1.30
γ 157.0	1.25	1.34	1.59	1.36
γ 158.0	1.30	1.39	1.62	1.40
γ 159.0	1.36	1.44	1.67	1.44
γ 160.0	1.41	1.48	1.71	1.48
γ 161.0	1.45	1.53	1.75	1.52
γ 162.0	1.50	1.57	1.78	1.56
γ 163.0	1.55	1.61	1.82	1.61
γ 164.0	1.61	1.65	1.86	1.65
γ 165.0	1.65	1.71	1.89	1.70
γ 166.0	1.70	1.75	1.93	1.74
γ 167.0	1.74	1.80	1.96	1.78
γ 168.0	1.80	1.84	1.99	1.82
γ 169.0	1.84	1.88	2.02	1.87
γ 170.0	1.89	1.91	2.03	1.90
γ 171.0	1.93	1.94	2.05	1.93
γ 172.0	1.96	1.96	2.07	1.96
γ 173.0	2.00	2.00	2.10	2.00
γ 174.0	2.04	2.02	2.11	2.02
γ 175.0	2.07	2.03	2.11	2.04
γ 176.0	2.10	2.05	2.12	2.08
γ 177.0	2.12	2.07	2.13	2.10
γ 178.0	2.13	2.07	2.14	2.12
γ 179.0	2.15	2.07	2.13	2.13
γ 180.0	2.13	2.13	2.13	2.13