



Indoor Luminaire Photometric Data

Description Information

Luminary Name:WL02-09-XX-01 2700K RA90 24D		Lum. Catalog:	Test ID: 01
Lamp Name:		Lamp Catalog: LED	Test Date: 2021/10/22
Manufacture: Shenzhen Norming Lighting Co., Ltd		Shld.Ang(°):	Test Machine:GON-2000
Test Lab: Quality Department		Frequency (Hz):	Lamp CCT (K): Ra:
Lum. Size (W*L*H):0.076m*0.076m*0.000m		Lum. Area (m2):0.005	Lum. W (kg): 0.000
Test System: C, γ	Test Step: C=90.0 γ=1.0	Temp. (°C): 25	Humidity(%): 50.0


Character Parameter

Lamp Speciality Parameter		Luminaire Speciality Parameter	
Rated Flux(lm): 698.900	Luminary Flux(lm): 698.903	Field Angle(10%Imax): 33.2(°)	
Rated Power(W):	Luminary Efficiency: 100.00%	Down Lumens&Percent: 698.903lm 100.00%	
Rated Voltage(V):	Luminary EER(lm/W): 78.511	Up Lumens&Percent: 0.000lm 0.00%	
Tested Power(W): 8.902	Max. Candela(cd): 4934.237	S/MH: C0_a180=0.326 C90_270=0.347	
Lamps' Inside: 1	Max Cand@Ang. (°): C=270.0 γ=5.0	CIE Type: Semi-Direct	
Tested Electrics (V, A, pf):240.9, 0.041, 0.899	Beam Angle(50%Imax): 19.1(°)	ErP ϕ use(90°): 633.258lm	
Lamp Size(W*L*H):0.076m*0.076m*0.000m	Left=-4.9°, Right=14.1°	IRF(%): 1592.237	



2D Plane Light Intensity Distribution Curve


Lum. Name: WL02-09-XX-01 2700K RA90 24D	Lum. Catalog:	Test ID: 01
Lamp Name:	Lamp Catalog: LED	Test Lab: Quality Department
Manufacture: Shenzhen Norming Lighting Co., Ltd	Test Machine:GON-2000	Test Date: 2021/10/22



3D Light Intensity Distribution Modal

Lum. Name: WL02-09-XX-01 2700K RA90 24D	Lum. Catelog:	Test ID: 01
Lamp Name:	Lamp Catelog: LED	Test Lab: Quality Department
Manufacture: Shenzhen Norming Lighting Co., Ltd	Test Machine:GON-2000	Test Date: 2021/10/22

3D Light Intensity Distribution Modal



IES Indoor Report

Photometric Filename:WL02-09-XX-01 2700K RA90 24D.IES

Zonal Flux Tabulation


Zone(γ)	Zone Flux (lm)	Sums Flux (lm)	Zone%Lamp	Sums%Lamp	Zone(γ)	Zone Flux (lm)	Sums Flux (lm)	Zone%Lamp	Sums%Lamp
0.0-1.0	4.26	4.26	0.61	0.61	47.0-48.0	1.06	691.67	0.15	98.97
1.0-2.0	12.55	16.81	1.80	2.41	48.0-49.0	0.97	692.65	0.14	99.11
2.0-3.0	20.38	37.19	2.92	5.32	49.0-50.0	0.89	693.54	0.13	99.23
3.0-4.0	27.43	64.62	3.93	9.25	50.0-51.0	0.80	694.34	0.11	99.35
4.0-5.0	33.45	98.07	4.79	14.03	51.0-52.0	0.72	695.06	0.10	99.45
5.0-6.0	38.25	136.32	5.47	19.51	52.0-53.0	0.64	695.70	0.09	99.54
6.0-7.0	41.67	177.99	5.96	25.47	53.0-54.0	0.56	696.26	0.08	99.62
7.0-8.0	43.65	221.64	6.25	31.71	54.0-55.0	0.49	696.75	0.07	99.69
8.0-9.0	44.22	265.86	6.33	38.04	55.0-56.0	0.42	697.17	0.06	99.75
9.0-10.0	43.56	309.42	6.23	44.27	56.0-57.0	0.36	697.53	0.05	99.80
10.0-11.0	41.83	351.25	5.98	50.26	57.0-58.0	0.31	697.84	0.04	99.85
11.0-12.0	39.15	390.40	5.60	55.86	58.0-59.0	0.26	698.10	0.04	99.89
12.0-13.0	35.83	426.22	5.13	60.98	59.0-60.0	0.21	698.31	0.03	99.91
13.0-14.0	32.18	458.40	4.60	65.59	60.0-61.0	0.16	698.47	0.02	99.94
14.0-15.0	28.40	486.80	4.06	69.65	61.0-62.0	0.12	698.59	0.02	99.96
15.0-16.0	24.66	511.46	3.53	73.18	62.0-63.0	0.10	698.69	0.01	99.97
16.0-17.0	21.16	532.62	3.03	76.21	63.0-64.0	0.08	698.76	0.01	99.98
17.0-18.0	18.07	550.69	2.59	78.79	64.0-65.0	0.06	698.82	0.01	99.99
18.0-19.0	15.44	566.14	2.21	81.00	65.0-66.0	0.04	698.87	0.01	100.00
19.0-20.0	13.28	579.42	1.90	82.90	66.0-67.0	0.03	698.89	0.00	100.00
20.0-21.0	11.52	590.93	1.65	84.55	67.0-68.0	0.01	698.90	0.00	100.00
21.0-22.0	10.08	601.02	1.44	85.99	68.0-69.0	0.00	698.90	0.00	100.00
22.0-23.0	8.91	609.93	1.27	87.27	69.0-70.0	0.00	698.90	0.00	100.00
23.0-24.0	7.94	617.86	1.14	88.40	70.0-71.0	0.00	698.90	0.00	100.00
24.0-25.0	7.13	624.99	1.02	89.42	71.0-72.0	0.00	698.90	0.00	100.00
25.0-26.0	6.43	631.42	0.92	90.35	72.0-73.0	0.00	698.90	0.00	100.00
26.0-27.0	5.83	637.25	0.83	91.18	73.0-74.0	0.00	698.90	0.00	100.00
27.0-28.0	5.31	642.56	0.76	91.94	74.0-75.0	0.00	698.90	0.00	100.00
28.0-29.0	4.83	647.39	0.69	92.63	75.0-76.0	0.00	698.90	0.00	100.00
29.0-30.0	4.41	651.80	0.63	93.26	76.0-77.0	0.00	698.90	0.00	100.00
30.0-31.0	4.04	655.84	0.58	93.84	77.0-78.0	0.00	698.90	0.00	100.00
31.0-32.0	3.70	659.54	0.53	94.37	78.0-79.0	0.00	698.90	0.00	100.00
32.0-33.0	3.39	662.93	0.49	94.85	79.0-80.0	0.00	698.90	0.00	100.00
33.0-34.0	3.11	666.05	0.45	95.30	80.0-81.0	0.00	698.90	0.00	100.00
34.0-35.0	2.87	668.91	0.41	95.71	81.0-82.0	0.00	698.90	0.00	100.00
35.0-36.0	2.65	671.56	0.38	96.09	82.0-83.0	0.00	698.90	0.00	100.00
36.0-37.0	2.44	674.00	0.35	96.44	83.0-84.0	0.00	698.90	0.00	100.00
37.0-38.0	2.26	676.26	0.32	96.76	84.0-85.0	0.00	698.90	0.00	100.00
38.0-39.0	2.10	678.37	0.30	97.06	85.0-86.0	0.00	698.90	0.00	100.00
39.0-40.0	1.95	680.32	0.28	97.34	86.0-87.0	0.00	698.90	0.00	100.00
40.0-41.0	1.81	682.13	0.26	97.60	87.0-88.0	0.00	698.90	0.00	100.00
41.0-42.0	1.69	683.82	0.24	97.84	88.0-89.0	0.00	698.90	0.00	100.00
42.0-43.0	1.57	685.39	0.22	98.07	89.0-90.0	0.00	698.90	0.00	100.00
43.0-44.0	1.46	686.85	0.21	98.28	90.0-91.0	0.00	698.90	0.00	100.00
44.0-45.0	1.35	688.20	0.19	98.47	91.0-92.0	0.00	698.90	0.00	100.00
45.0-46.0	1.25	689.45	0.18	98.65	92.0-93.0	0.00	698.90	0.00	100.00
46.0-47.0	1.16	690.61	0.17	98.81	93.0-94.0	0.00	698.90	0.00	100.00

Zonal Flux Tabulation - (Cont.)

Zone(γ)	Zone Flux (lm)	Sums Flux (lm)	Zone%Lamp	Sums%Lamp	Zone(γ)	Zone Flux (lm)	Sums Flux (lm)	Zone%Lamp	Sums%Lamp
94. 0-95. 0	0. 00	698. 90	0. 00	100. 00	141. 0-142. 0	0. 00	698. 90	0. 00	100. 00
95. 0-96. 0	0. 00	698. 90	0. 00	100. 00	142. 0-143. 0	0. 00	698. 90	0. 00	100. 00
96. 0-97. 0	0. 00	698. 90	0. 00	100. 00	143. 0-144. 0	0. 00	698. 90	0. 00	100. 00
97. 0-98. 0	0. 00	698. 90	0. 00	100. 00	144. 0-145. 0	0. 00	698. 90	0. 00	100. 00
98. 0-99. 0	0. 00	698. 90	0. 00	100. 00	145. 0-146. 0	0. 00	698. 90	0. 00	100. 00
99. 0-100. 0	0. 00	698. 90	0. 00	100. 00	146. 0-147. 0	0. 00	698. 90	0. 00	100. 00
100. 0-101. 0	0. 00	698. 90	0. 00	100. 00	147. 0-148. 0	0. 00	698. 90	0. 00	100. 00
101. 0-102. 0	0. 00	698. 90	0. 00	100. 00	148. 0-149. 0	0. 00	698. 90	0. 00	100. 00
102. 0-103. 0	0. 00	698. 90	0. 00	100. 00	149. 0-150. 0	0. 00	698. 90	0. 00	100. 00
103. 0-104. 0	0. 00	698. 90	0. 00	100. 00	150. 0-151. 0	0. 00	698. 90	0. 00	100. 00
104. 0-105. 0	0. 00	698. 90	0. 00	100. 00	151. 0-152. 0	0. 00	698. 90	0. 00	100. 00
105. 0-106. 0	0. 00	698. 90	0. 00	100. 00	152. 0-153. 0	0. 00	698. 90	0. 00	100. 00
106. 0-107. 0	0. 00	698. 90	0. 00	100. 00	153. 0-154. 0	0. 00	698. 90	0. 00	100. 00
107. 0-108. 0	0. 00	698. 90	0. 00	100. 00	154. 0-155. 0	0. 00	698. 90	0. 00	100. 00
108. 0-109. 0	0. 00	698. 90	0. 00	100. 00	155. 0-156. 0	0. 00	698. 90	0. 00	100. 00
109. 0-110. 0	0. 00	698. 90	0. 00	100. 00	156. 0-157. 0	0. 00	698. 90	0. 00	100. 00
110. 0-111. 0	0. 00	698. 90	0. 00	100. 00	157. 0-158. 0	0. 00	698. 90	0. 00	100. 00
111. 0-112. 0	0. 00	698. 90	0. 00	100. 00	158. 0-159. 0	0. 00	698. 90	0. 00	100. 00
112. 0-113. 0	0. 00	698. 90	0. 00	100. 00	159. 0-160. 0	0. 00	698. 90	0. 00	100. 00
113. 0-114. 0	0. 00	698. 90	0. 00	100. 00	160. 0-161. 0	0. 00	698. 90	0. 00	100. 00
114. 0-115. 0	0. 00	698. 90	0. 00	100. 00	161. 0-162. 0	0. 00	698. 90	0. 00	100. 00
115. 0-116. 0	0. 00	698. 90	0. 00	100. 00	162. 0-163. 0	0. 00	698. 90	0. 00	100. 00
116. 0-117. 0	0. 00	698. 90	0. 00	100. 00	163. 0-164. 0	0. 00	698. 90	0. 00	100. 00
117. 0-118. 0	0. 00	698. 90	0. 00	100. 00	164. 0-165. 0	0. 00	698. 90	0. 00	100. 00
118. 0-119. 0	0. 00	698. 90	0. 00	100. 00	165. 0-166. 0	0. 00	698. 90	0. 00	100. 00
119. 0-120. 0	0. 00	698. 90	0. 00	100. 00	166. 0-167. 0	0. 00	698. 90	0. 00	100. 00
120. 0-121. 0	0. 00	698. 90	0. 00	100. 00	167. 0-168. 0	0. 00	698. 90	0. 00	100. 00
121. 0-122. 0	0. 00	698. 90	0. 00	100. 00	168. 0-169. 0	0. 00	698. 90	0. 00	100. 00
122. 0-123. 0	0. 00	698. 90	0. 00	100. 00	169. 0-170. 0	0. 00	698. 90	0. 00	100. 00
123. 0-124. 0	0. 00	698. 90	0. 00	100. 00	170. 0-171. 0	0. 00	698. 90	0. 00	100. 00
124. 0-125. 0	0. 00	698. 90	0. 00	100. 00	171. 0-172. 0	0. 00	698. 90	0. 00	100. 00
125. 0-126. 0	0. 00	698. 90	0. 00	100. 00	172. 0-173. 0	0. 00	698. 90	0. 00	100. 00
126. 0-127. 0	0. 00	698. 90	0. 00	100. 00	173. 0-174. 0	0. 00	698. 90	0. 00	100. 00
127. 0-128. 0	0. 00	698. 90	0. 00	100. 00	174. 0-175. 0	0. 00	698. 90	0. 00	100. 00
128. 0-129. 0	0. 00	698. 90	0. 00	100. 00	175. 0-176. 0	0. 00	698. 90	0. 00	100. 00
129. 0-130. 0	0. 00	698. 90	0. 00	100. 00	176. 0-177. 0	0. 00	698. 90	0. 00	100. 00
130. 0-131. 0	0. 00	698. 90	0. 00	100. 00	177. 0-178. 0	0. 00	698. 90	0. 00	100. 00
131. 0-132. 0	0. 00	698. 90	0. 00	100. 00	178. 0-179. 0	0. 00	698. 90	0. 00	100. 00
132. 0-133. 0	0. 00	698. 90	0. 00	100. 00	179. 0-180. 0	0. 00	698. 90	0. 00	100. 00
133. 0-134. 0	0. 00	698. 90	0. 00	100. 00					
134. 0-135. 0	0. 00	698. 90	0. 00	100. 00					
135. 0-136. 0	0. 00	698. 90	0. 00	100. 00					
136. 0-137. 0	0. 00	698. 90	0. 00	100. 00					
137. 0-138. 0	0. 00	698. 90	0. 00	100. 00					
138. 0-139. 0	0. 00	698. 90	0. 00	100. 00					
139. 0-140. 0	0. 00	698. 90	0. 00	100. 00					
140. 0-141. 0	0. 00	698. 90	0. 00	100. 00					

Rectangle ISO Lighting Intensity Diagram


Lum. Name: WL02-09-XX-01 2700K RA90 24D	Lum. Catalog:	Test ID: 01
Lamp Name:	Lamp Catalog: LED	Test Lab: Quality Department
Manufacture: Shenzhen Norming Lighting Co., Ltd	Test Machine:GON-2000	Test Date: 2021/10/22



Plane ISO-Illuminance Diagram

Lum. Name: WL02-09-XX-01 2700K RA90 24D	Lum. Catalog:	Test ID: 01
Lamp Name:	Lamp Catalog: LED	Test Lab: Quality Department
Manufacture: Shenzhen Norming Lighting Co., Ltd	Test Machine:GON-2000	Test Date: 2021/10/22

Plane ISO-Illuminance Curve




**Photometric Filename:WL02-09-XX-01 2700K RA90 24D.IES**

### 3D Plane ISO Illuminance Diagram

Lum. Name: WL02-09-XX-01 2700K RA90 24D	Lum. Catalog:	Test ID: 01
Lamp Name:	Lamp Catalog: LED	Test Lab: Quality Department
Manufacture: Shenzhen Norming Lighting Co., Ltd	Test Machine:GON-2000	Test Date: 2021/10/22

### 3D Plane Illuminance Modal




Curves: 3D Model 90% 80% 70% 60% 50% 40% 30% 20% 10%  
View Angles(deg): 0 Height(m): 3.0 Distance(m): 10.0



Space ISO Illuminance Diagram

Lum. Name: WL02-09-XX-01 2700K RA90 24D	Lum. Catelog:	Test ID: 01
Lamp Name:	Lamp Catelog: LED	Test Lab: Quality Department
Manufacture: Shenzhen Norming Lighting Co., Ltd	Test Machine:GON-2000	Test Date: 2021/10/22


Space ISO Illuminance Curve



Space Plane Maximum Illuminance and @Angle:4485.32lx,0.0deg  
Plane Maximum Lighting Intensity and @Angle:4485.324cd,0deg

Illuminance-Distance Diagram

Lum. Name: WL02-09-XX-01 2700K RA90 24D	Lum. Catelog:	Test ID: 01
Lamp Name:	Lamp Catelog: LED	Test Lab: Quality Department
Manufacture: Shenzhen Norming Lighting Co., Ltd	Test Machine:GON-2000	Test Date: 2021/10/22



Indoor Luminance Limiting Curves

Lum. Name: WL02-09-XX-01 2700K RA90 24D	Lum. Catalog:	Test ID: 01
Lamp Name:	Lamp Catalog: LED	Test Lab: Quality Department
Manufacture: Shenzhen Norming Lighting Co., Ltd	Test Machine:GON-2000	Test Date: 2021/10/22


Glare Grade Table

GI	Quality	Using Illuminance							
1.15	A	2000	1000	500	<=300				
1.5	B		2000	1000	500	<=300			
1.85	C			2000	1000	500	<=300		
2.2	D				2000	1000	500	<=300	
2.55	E	a				2000	1000	500	<=300
			b	c	d	e	f	g	h

Luminance Table

Gama(deg)	45	50	55	60	65	70	75	80	85
C0	4940	3033	1515	200	0	0	0	0	0
C90	2828	1332	63	0	0	0	0	0	0

Luminance Limiting Curve




Luminous Size: Length(m)=-0.076 Width(m)=-0.076 Height(m)=0.000 Area(m^2)=0.004536

Luminous Type: Without Luminous Side

Luminous Curves: C0-C180 Color: C90-C270 Color:

Indoor Budgetary Estimate Table

Lum. Name: WL02-09-XX-01 2700K RA90 24D	Lum. Catalog:	Test ID: 01
Lamp Name:	Lamp Catalog: LED	Test Lab: Quality Department
Manufacture: Shenzhen Norming Lighting Co., Ltd	Test Machine:GON-2000	Test Date: 2021/10/22



Indoor Coefficient of Utilization Table

Lum. Name: WL02-09-XX-01 2700K RA90 24D	Lum. Catelog:	Test ID: 01
Lamp Name:	Lamp Catelog: LED	Test Lab: Quality Department
Manufacture: Shenzhen Norming Lighting Co., Ltd	Test Machine:GON-2000	Test Date: 2021/10/22

Coefficients of Utilization - Zonal Cavity Method																		
Coef.	Effective Floor Cavity Reflectance RFC=0.20																	
RhoCC (%)	80				70				50			30			10			0
RhoW (%)	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR	Coefficient of Utilization(%)																	
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	115	113	111	110	113	111	109	108	107	106	105	103	102	102	100	99	99	97
2	112	108	105	103	110	106	104	102	103	101	100	101	99	97	98	97	95	94
3	108	104	100	98	106	102	99	97	100	97	95	98	96	94	96	94	93	91
4	105	100	96	93	104	99	95	93	97	94	92	95	93	91	93	91	90	89
5	102	97	93	90	101	96	92	89	94	91	89	93	90	88	91	89	87	86
6	100	94	90	87	98	93	89	87	92	88	86	90	88	86	89	87	85	84
7	97	91	87	84	96	90	87	84	89	86	84	88	85	83	87	85	83	82
8	95	88	85	82	94	88	84	82	87	84	81	86	83	81	85	83	81	80
9	92	86	82	80	92	86	82	80	85	82	79	84	81	79	84	81	79	78
10	90	84	80	78	90	84	80	78	83	80	78	83	80	78	82	79	77	76

Unified Glare Rating Table

Lum. Name: WL02-09-XX-01 2700K RA90 24D	Lum. Catelog:	Test ID: 01
Lamp Name:	Lamp Catalog: LED	Test Lab: Quality Department
Manufacture: Shenzhen Norming Lighting Co., Ltd	Test Machine:GON-2000	Test Date: 2021/10/22

Unified Glare Rating Table

Ceiling RCC	0.70	0.70	0.50	0.50	0.30	0.70	0.70	0.50	0.50	0.30
Wall RW	0.50	0.30	0.50	0.30	0.30	0.50	0.30	0.50	0.30	0.30
Floor RFC	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20
Room Size	Vewed crosswise					Vewed endwise				
X=2H    Y=2H	8.2	9.3	8.6	9.6	9.9	5.5	6.5	5.8	6.9	7.2
	8.0	8.9	8.4	9.3	9.6	5.3	6.2	5.6	6.6	6.9
	7.9	8.8	8.3	9.1	9.5	5.1	6.1	5.6	6.4	6.8
	7.7	8.6	8.2	9.0	9.4	5.0	5.9	5.5	6.2	6.6
	7.7	8.5	8.1	8.9	9.3	5.0	5.8	5.4	6.2	6.6
	7.6	8.4	8.1	8.8	9.2	4.9	5.7	5.4	6.1	6.5
X=4H    Y=2H	7.9	8.8	8.3	9.2	9.6	5.2	6.1	5.6	6.4	6.8
	7.7	8.5	8.1	8.9	9.3	5.0	5.7	5.4	6.1	6.5
	7.6	8.3	8.0	8.7	9.2	4.8	5.5	5.3	6.0	6.4
	7.5	8.1	7.9	8.5	9.0	4.7	5.3	5.2	5.8	6.2
	7.4	8.0	7.9	8.4	8.9	4.6	5.2	5.1	5.7	6.1
	7.3	7.9	7.8	8.3	8.8	4.6	5.1	5.1	5.6	6.1
X=8H    Y=4H	7.4	8.0	7.9	8.4	8.9	4.6	5.2	5.1	5.7	6.1
	7.2	7.8	7.8	8.3	8.8	4.5	5.0	5.0	5.5	6.0
	7.2	7.6	7.7	8.2	8.7	4.4	4.9	4.9	5.4	5.9
	7.1	7.5	7.6	8.0	8.6	4.4	4.8	4.9	5.3	5.9
X=12H    Y=4H	7.3	7.9	7.8	8.3	8.8	4.6	5.1	5.1	5.6	6.1
	7.2	7.7	7.7	8.1	8.7	4.4	4.9	5.0	5.4	5.9
	7.1	7.5	7.6	8.0	8.6	4.4	4.8	4.9	5.3	5.9
Variations with the objverver position at spacings										
S=1.0H	0.0/0.0					0.0/0.0				
S=1.5H	0.0/0.0					0.0/0.0				
S=2.0H	11.1/0.0					0.0/0.0				
Reduced UGR Table:										
Nordic Standard Table:	BK0					BK0				
Correction Value	0.0					0.0				

o the CIE Pub.117, data has been corrected, refers to the lamp's lumens 8.2flm.

Candela Tabulation

V/H	C0.0	C90.0	C180.0	C270.0
γ 0.0	4485.32	4485.32	4485.32	4485.32
γ 1.0	4481.26	4040.10	4603.88	4540.71
γ 2.0	4311.21	3695.95	4571.63	4731.64
γ 3.0	4102.48	3312.82	4500.00	4857.88
γ 4.0	3828.17	2874.75	4386.31	4920.83
γ 5.0	3512.48	2432.89	4211.72	4934.24
γ 6.0	3151.12	2007.06	3974.29	4889.37
γ 7.0	2770.75	1613.79	3666.64	4780.29
γ 8.0	2366.24	1262.02	3311.38	4623.18
γ 9.0	1958.69	978.50	2912.45	4412.47
γ 10.0	1576.18	761.24	2509.08	4146.50
γ 11.0	1235.35	600.40	2106.28	3808.65
γ 12.0	951.44	480.63	1729.55	3413.12
γ 13.0	735.71	392.38	1398.35	2973.96
γ 14.0	577.43	326.47	1118.91	2532.54
γ 15.0	461.07	275.71	891.55	2091.90
γ 16.0	377.82	236.52	712.60	1684.64
γ 17.0	315.55	204.63	574.61	1329.60
γ 18.0	269.01	178.95	467.79	1043.32
γ 19.0	232.14	156.85	384.82	817.82
γ 20.0	203.26	138.63	320.05	648.42
γ 21.0	178.65	122.97	268.06	519.57
γ 22.0	158.40	109.87	226.92	422.45
γ 23.0	141.02	98.50	193.27	347.93
γ 24.0	126.13	88.53	165.80	290.76
γ 25.0	113.31	79.94	143.13	246.05
γ 26.0	102.10	72.23	123.82	209.68
γ 27.0	92.26	65.23	107.93	180.36
γ 28.0	83.54	59.16	94.07	155.61
γ 29.0	75.85	53.55	82.43	134.67
γ 30.0	69.06	48.34	72.30	117.25
γ 31.0	62.72	43.81	63.96	102.61
γ 32.0	56.97	39.69	56.63	90.04
γ 33.0	51.87	35.73	50.35	79.45
γ 34.0	46.95	32.20	45.12	69.95
γ 35.0	42.88	29.03	40.75	62.32
γ 36.0	38.98	26.15	36.85	55.58
γ 37.0	35.38	23.50	33.41	49.90
γ 38.0	32.08	21.10	30.52	45.11
γ 39.0	29.27	18.99	27.97	41.22
γ 40.0	26.41	16.88	25.85	37.52
γ 41.0	23.95	15.07	23.71	34.37
γ 42.0	21.55	13.38	21.86	31.74
γ 43.0	19.61	11.81	20.19	29.28
γ 44.0	17.57	10.41	18.62	27.06
γ 45.0	15.85	9.07	17.10	25.11
γ 46.0	14.16	7.88	15.63	23.34

Candela Tabulation - (Cont.)

V/H	C0.0	C90.0	C180.0	C270.0
γ 47.0	12.69	6.79	14.16	21.70
γ 48.0	11.28	5.76	12.88	20.08
γ 49.0	10.03	4.80	11.65	18.46
γ 50.0	8.85	3.88	10.49	17.05
γ 51.0	7.72	3.02	9.23	15.62
γ 52.0	6.75	2.32	8.08	14.22
γ 53.0	5.76	1.65	7.16	12.84
γ 54.0	4.90	0.91	6.25	11.73
γ 55.0	3.94	0.17	5.30	10.50
γ 56.0	3.18	0.00	4.53	9.49
γ 57.0	2.46	0.00	3.70	8.37
γ 58.0	1.72	0.00	3.07	7.44
γ 59.0	1.00	0.00	2.28	6.59
γ 60.0	0.45	0.00	1.59	5.67
γ 61.0	0.00	0.00	0.87	4.97
γ 62.0	0.00	0.00	0.26	4.19
γ 63.0	0.00	0.00	0.00	3.44
γ 64.0	0.00	0.00	0.00	2.72
γ 65.0	0.00	0.00	0.00	2.09
γ 66.0	0.00	0.00	0.00	1.42
γ 67.0	0.00	0.00	0.00	0.73
γ 68.0	0.00	0.00	0.00	0.04
γ 69.0	0.00	0.00	0.00	0.00
γ 70.0	0.00	0.00	0.00	0.00
γ 71.0	0.00	0.00	0.00	0.00
γ 72.0	0.00	0.00	0.00	0.00
γ 73.0	0.00	0.00	0.00	0.00
γ 74.0	0.00	0.00	0.00	0.00
γ 75.0	0.00	0.00	0.00	0.00
γ 76.0	0.00	0.00	0.00	0.00
γ 77.0	0.00	0.00	0.00	0.00
γ 78.0	0.00	0.00	0.00	0.00
γ 79.0	0.00	0.00	0.00	0.00
γ 80.0	0.00	0.00	0.00	0.00
γ 81.0	0.00	0.00	0.00	0.00
γ 82.0	0.00	0.00	0.00	0.00
γ 83.0	0.00	0.00	0.00	0.00
γ 84.0	0.00	0.00	0.00	0.00
γ 85.0	0.00	0.00	0.00	0.00
γ 86.0	0.00	0.00	0.00	0.00
γ 87.0	0.00	0.00	0.00	0.00
γ 88.0	0.00	0.00	0.00	0.00
γ 89.0	0.00	0.00	0.00	0.00
γ 90.0	0.00	0.00	0.00	0.00
γ 91.0	0.00	0.00	0.00	0.00
γ 92.0	0.00	0.00	0.00	0.00
γ 93.0	0.00	0.00	0.00	0.00

---



Candela Tabulation - (Cont.)

V/H	C0.0	C90.0	C180.0	C270.0
γ 94.0	0.00	0.00	0.00	0.00
γ 95.0	0.00	0.00	0.00	0.00
γ 96.0	0.00	0.00	0.00	0.00
γ 97.0	0.00	0.00	0.00	0.00
γ 98.0	0.00	0.00	0.00	0.00
γ 99.0	0.00	0.00	0.00	0.00
γ 100.0	0.00	0.00	0.00	0.00
γ 101.0	0.00	0.00	0.00	0.00
γ 102.0	0.00	0.00	0.00	0.00
γ 103.0	0.00	0.00	0.00	0.00
γ 104.0	0.00	0.00	0.00	0.00
γ 105.0	0.00	0.00	0.00	0.00
γ 106.0	0.00	0.00	0.00	0.00
γ 107.0	0.00	0.00	0.00	0.00
γ 108.0	0.00	0.00	0.00	0.00
γ 109.0	0.00	0.00	0.00	0.00
γ 110.0	0.00	0.00	0.00	0.00
γ 111.0	0.00	0.00	0.00	0.00
γ 112.0	0.00	0.00	0.00	0.00
γ 113.0	0.00	0.00	0.00	0.00
γ 114.0	0.00	0.00	0.00	0.00
γ 115.0	0.00	0.00	0.00	0.00
γ 116.0	0.00	0.00	0.00	0.00
γ 117.0	0.00	0.00	0.00	0.00
γ 118.0	0.00	0.00	0.00	0.00
γ 119.0	0.00	0.00	0.00	0.00
γ 120.0	0.00	0.00	0.00	0.00
γ 121.0	0.00	0.00	0.00	0.00
γ 122.0	0.00	0.00	0.00	0.00
γ 123.0	0.00	0.00	0.00	0.00
γ 124.0	0.00	0.00	0.00	0.00
γ 125.0	0.00	0.00	0.00	0.00
γ 126.0	0.00	0.00	0.00	0.00
γ 127.0	0.00	0.00	0.00	0.00
γ 128.0	0.00	0.00	0.00	0.00
γ 129.0	0.00	0.00	0.00	0.00
γ 130.0	0.00	0.00	0.00	0.00
γ 131.0	0.00	0.00	0.00	0.00
γ 132.0	0.00	0.00	0.00	0.00
γ 133.0	0.00	0.00	0.00	0.00
γ 134.0	0.00	0.00	0.00	0.00
γ 135.0	0.00	0.00	0.00	0.00
γ 136.0	0.00	0.00	0.00	0.00
γ 137.0	0.00	0.00	0.00	0.00
γ 138.0	0.00	0.00	0.00	0.00
γ 139.0	0.00	0.00	0.00	0.00
γ 140.0	0.00	0.00	0.00	0.00

---

Candela Tabulation - (Cont.)

V/H	C0.0	C90.0	C180.0	C270.0
γ 141.0	0.00	0.00	0.00	0.00
γ 142.0	0.00	0.00	0.00	0.00
γ 143.0	0.00	0.00	0.00	0.00
γ 144.0	0.00	0.00	0.00	0.00
γ 145.0	0.00	0.00	0.00	0.00
γ 146.0	0.00	0.00	0.00	0.00
γ 147.0	0.00	0.00	0.00	0.00
γ 148.0	0.00	0.00	0.00	0.00
γ 149.0	0.00	0.00	0.00	0.00
γ 150.0	0.00	0.00	0.00	0.00
γ 151.0	0.00	0.00	0.00	0.00
γ 152.0	0.00	0.00	0.00	0.00
γ 153.0	0.00	0.00	0.00	0.00
γ 154.0	0.00	0.00	0.00	0.00
γ 155.0	0.00	0.00	0.00	0.00
γ 156.0	0.00	0.00	0.00	0.00
γ 157.0	0.00	0.00	0.00	0.00
γ 158.0	0.00	0.00	0.00	0.00
γ 159.0	0.00	0.00	0.00	0.00
γ 160.0	0.00	0.00	0.00	0.00
γ 161.0	0.00	0.00	0.00	0.00
γ 162.0	0.00	0.00	0.00	0.00
γ 163.0	0.00	0.00	0.00	0.00
γ 164.0	0.00	0.00	0.00	0.00
γ 165.0	0.00	0.00	0.00	0.00
γ 166.0	0.00	0.00	0.00	0.00
γ 167.0	0.00	0.00	0.00	0.00
γ 168.0	0.00	0.00	0.00	0.00
γ 169.0	0.00	0.00	0.00	0.00
γ 170.0	0.00	0.00	0.00	0.00
γ 171.0	0.00	0.00	0.00	0.00
γ 172.0	0.00	0.00	0.00	0.00
γ 173.0	0.00	0.00	0.00	0.00
γ 174.0	0.00	0.00	0.00	0.00
γ 175.0	0.00	0.00	0.00	0.00
γ 176.0	0.00	0.00	0.00	0.00
γ 177.0	0.00	0.00	0.00	0.00
γ 178.0	0.00	0.00	0.00	0.00
γ 179.0	0.00	0.00	0.00	0.00
γ 180.0	0.00	0.00	0.00	0.00