


6W 9W  
POWER



## Packaging

Box Dimensions	L150 x W150 x H165mm
Box Net Weight	0.538Kg
Box Gross Weight	0.642Kg
Carton Dimensions	L465 x W465 x H350 mm/18 PCS
Carton Net Weight	9.68Kg
Carton Gross Weight	12.37Kg

## FEATURES

- Maximum 45° vertical rotation can be created on the main body.
- Optic interchangeable.
- Power selectable.
- Flicker-free internal driver.
- Compatible with leading and trailing edge phase cut dimmers.
- 5-year guarantee.

## Technical Data

Input Voltage/Hz	AC200-240V 50/60Hz
Output Voltage/Current	DC34V/210mA(9W) DC33V/145mA(6W)
Power	9W 6W
Rated Input Current	0.045A
THD	<25%(9W)   <35%(6W)
PF value	>0.9(9W)   >0.8(6W)
Ingress Protection	IP20
Operating Temperature	-10—40℃
Dimmability	Triac dimmable with <b>DIMMATE</b> driver

## Optical Data

LED Brand	Bridgelux COB LED
CRI	Ra> 90
Beam Angle	150°
Colour temperatures	2700K/3000K/4000K
System luminous efficacy up to	82lm/W



Model	CCT		Beam Angle	Lumen	Efficacy		Beam Angle	Lumen	Efficacy
WL02-09-XX-03	2700K	6W	150°	462lm	74lm/W	9W	150°	692lm	78lm/W
WL02-09-XX-03	3000K		150°	479lm	76lm/W		150°	640lm	72lm/W
WL02-09-XX-03	4000K		150°	492lm	79lm/W		150°	726lm	82lm/W

## ECLIPSE CONSEIL

Siège : +33 (1) 79 30 48 19- Showroom Paris : +33 (1) 78 95 50 14 - Mob : +33 (6) 87 82 12 04  
Siège social : 7 rue Prudent Neel 92500 Rueil-Malmaison - Showroom : 1 rue Dulong 75017 PARIS