



FEATURES

- Power-selectable.
- Hassle-free maintenance with modular design.
- Interchangeable and functional lens available.
- Visual-comfort accessories available.
- 7-year guarantee.

Technical Data

Input Voltage/Hz	AC220-240V 50/60Hz
Output Voltage/Current	DC35.5V/480mA(20W) DC35V/365mA(15W)
Power	20W 15W
Rated Input Current	0.083A(20W) 0.063A(15W)
THD	<15%
PF value	>0.9
Ingress Protection	IP20
Operating Temperature	-10—40°C
Dimmability	Triac dimmable with DIMMATE driver
L70/B50 at 25°C	>160000H
L90/B10 at 25°C	>19000H

Packaging

Box Dimensions	L190 x W105 x H170 x T2mm
Box Net Weight	0.75Kg
Box Gross Weight	0.86Kg
Carton Dimensions	L545 x W395 x H360 mm/20 PCS
Carton Net Weight	15Kg
Carton Gross Weight	18.5Kg

LED and Optical Data

LED Brand	Bridgelux COB LED
CRI	>90
SDCM	<3
Beam Angle	15°/24°/36°/60°
Colour temperatures	2700K/3000K/4000K
System luminous efficacy up to	121lm/W

Accessories

	GTS-BD01	Barn door
	GTS-ST01	45° Snoot
	HC05	Honeycomb
	GTS-OL01	Linear spread lens
	GTS-TWW01	Wallwash lens



CCT		Power	Beam Angle	Lumen	Efficacy	Power	Beam Angle	Lumen	Efficacy
2700K	CRI 90+	15W	15°	1607lm	108lm/W	20W	15°	2101lm	105lm/W
			24°	1587lm	106lm/W		24°	2056lm	103lm/W
			36°	1545lm	104lm/W		36°	2002lm	101lm/W
			60°	1677lm	112lm/W		60°	2154lm	109lm/W
3000K			15°	1587lm	107lm/W		15°	2086lm	105lm/W
			24°	1623lm	109lm/W		24°	2097lm	106lm/W
			36°	1615lm	108lm/W		36°	2089lm	106lm/W
			60°	1723lm	116lm/W		60°	2213lm	112lm/W
4000K			15°	1660lm	112lm/W		15°	2128lm	108lm/W
			24°	1673lm	113lm/W		24°	2140lm	109lm/W
			36°	1624lm	110lm/W		36°	2082lm	106lm/W
			60°	1796lm	121lm/W		60°	2295lm	117lm/W

ECLIPSE CONSEIL

Siège : +33 (1) 79 30 48 19- Showroom Paris : +33 (1) 78 95 50 14 - Mob : +33 (6) 87 82 12 04
Siège social : 7 rue Prudent Neel 92500 Rueil-Malmaison - Showroom : 1 rue Dulong 75017 PARIS